SAFETY DATA SHEETS

This SDS packet was issued with item:

072759934

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

070425462 070441162 070639989 071486208 072759900 072760189 078562617 273044121 273045762

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

072760759 072760767 072760775 072760783 072760791 072760858 072760874 072760882 072760890

Dentsply Trubyte
Manufacturer MSDS Number: 151

terson Dental Supply Product Code: 72760189,72759934

SECTION 1 : Chemical Product and Company Identification

MSDS Name: Lucitone Liquid

Manufacturer Name: Dentsply Trubyte

Department: Dentsply Trubyte

Address:

570 W. College Ave. York, PA 17405-0872

"FOR CHEMICAL EMERGENCY"

SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT

CALL CHEMTREC - DAY OR NIGHT

Emergency Phone No.: 800-424-9300

Business Phone: 717-845-7511

Dentsply

Product Description:

Type/Grade/Class.: Not Applicable

For information in North America, call: 717-845-7511

Dentsply

Manufacturer MSDS Revision Date:

9/98

Supersedes: 8/15/98

Rev.: A

Trade Names:

Lucitone« Liquid

Chemical Family: Methacrylic ester Chemical Formula: CH2 (CH3) COOCH3

Chemical Name: Methyl Methacrylate Monomer

Dentsply Contact: Scott E. Shaffer

National Stock No.: Not Applicable

Specification No.: Not Applicable

NRC/EPA Number: Not Applicable

Product Codes:

684309 , 684315

SECTION 2 : Hazardous Ingredients/Identity Information

Chemical Name

Methyl Methacrylate CAS#

80-62-6 Percent

```
ACGIH TLV TWA: 100 ppm
Chemical Name
Ethylene Glycol Dimethacrylate CAS#
97-90-5 Percent
< 10%
*****************
SECTION 3 : Physical And Chemical Characteristics
***************
Physical State/Appearance:
Water clear liquid.
Odor:
 Characteristic acrylic odor.
Decomposition Temperature:
Not Established
Vapor Pressure:
 29 mmHg @68 deg F (20 deg C)
Vapor Density:
 3.45
Boiling Point:
 214 deg F/101 deg C
Freezing Point:
 -54 deg F (-48 deg C)
Melting Point:
 -54 deg F (-48 deg C)
Solubility:
 In Water: 1.5%
Specific Gravity:
 0.94
Evaporation Point:
 (BAC=1): > 1
Percent Volatile:
 By Vol.: 100%
Viscosity:
 Not Established
Molecular Weight:
 Not Applicable
FlashPoint:
 TOC: 55 deg F (13 deg C)
TCC: 55 deg F (13 deg C)
Auto Ignition Temp:
 815 deg F (435 deg C)
Upper Flammable Explosive Limit:
 12.5%
Lower Flammable Explosive Limit:
 2.12%
 Critical Temp: Not Applicable
Critical Pressure: Not Established
Perm. Exp. Limit: Not Applicable
Autoignition Temp.: 815 deg F (435 deg C)
```

Corrosion Rate: Not Applicable

Magnetism: Not Established ********************** SECTION 4 : Fire And Explosion Hazards ******************** Flash Point: TOC: 55 deg F (13 deg C) TCC: 55 deg F (13 deg C) Flash Point Method: TOC, TCC Upper Flammable or Explosive Limit: 12.5% Lower Flammable or Explosive Limit: 2.12% Auto Ignition Temperature: 815 deg F (435 deg C) Extinguishing Media: Alcohol Foam, CO2, Dry chemical, water spray Fire Fighting Instructions: Water may be ineffective unless used as a fine spray or fog. Explosion hazard. Use water spray to cool fire-exposed containers of methyl methacrylate. Unusual Fire Hazards: Vapors may travel to source of ignition and flash back. Avoid ignition sources or excessive temperatures. Heat can induce polymerization with rapid release of energy. Heated containers may rupture explosively. ************************ SECTION 5 : Health Hazards *********************** Applies to All Ingredients: Potential Health Effects: Acute and Chronic Exposure: Primary routes of exposure are inhalation and skin contact. High vapor concentration can induce headache, nausea, smarting of eyes and irritation of respiratory system. Liquid contact with eyes will cause irritation and possible corneal damage. Material may cause moderate skin irritation and is possibly harmful if swallowed. ******************* SECTION 6 : Emergency And First Aid Procedures ******************* Eye Contact: Flush eyes promptly with copious amounts of water for 15 minutes & consult physician if irritation is apparent. Skin Contact: Wash skin with soap and water. See a physician. Move subject to fresh air. Give artificial respiration if breathing has stopped.

Ingestion:

a physician immediately.

If swallowed and conscious, give 2 glasses of water to drink and consult

Chemical Stability:

Stable (When stored properly)

Conditions to Avoid:

Elevated temperatures and direct sunlight.

Incompatibilities with Other Materials:

Materials to Avoid: Acids, Bases, UV light, reducing or oxidizing materials.

Hazardous Polymerization:

May Occur

Conditions to Avoid: Elevated temperatures, excessive aging, O2-free atmosphere, inhibitor depletion, ultraviolet light, contamination with polymerization catalysts.

Hazardous Decomposition Products:

None known.

SECTION 8 : Precautions For Safe Handling

Spill Cleanup Measures:

Eliminate ignitions sources. Avoid breathing vapors. Dike & absorb spill with inert material (sand, soda, ash, vermiculite, etc.) and transfer to containers for disposal; use non-sparking tools. Contaminated monomer may be unstable; addition of inhibitor will prevent polymerization. Remove saturated clothing and wash affected skin areas with soap and water.

Storage:

Store at ambient temperatures out of direct sunlight/advisable to use oldest materials first. Use adequate ventilation. Do not store under 02-free environment.

Other Precautions: Avoid repeated breathing and contact with the skin. Keep containers closed and away from heat. Keep away from sparks and open flame.

Waste Disposal:

After addition of excess inhibitor, incinerate under controlled conditions in a safe open area, according to federal, state and local regulations.

Neutralizing Agent: Not Applicable

Transportation Information:

Applicable Regulations:

49 CFR: Yes

DOT Shipping Name:

Methyl Methacrylate Monomer Inhibited

DOT SPSC Container: Not Applicable

DOT Exempt/DOD/CCN: Not Applicable

Unit Container: Not Applicable

Limited Quantity: Yes DOT Hazard Class: 3

DOT Identification Number: UN1247

DOT Subpart E Labeling Requirement: No IATA:
Not Applicable
Reportable Quantity: Not Applicable

Aerosol Propellant(s): Not Applicable

Net Explosive Weight: Not Applicable

SECTION 9 : Control Measures

Ventilation System:

Local exhaust to keep vapor concentration below TLV. Mechanical ventilation should have explosion-proof motors.

Hand Protection Description:

Protective Gloves: Impervious gloves (butyl rubber preferred).

Eye/Face Protection:

Splash proof goggles (ANSI Z87.1 or approved equivalent).

Respiratory Protection:

None required if airborne concentrations are maintained below TLV listed in Section 2. For airborne concentrations up to 10 times the TLV (1000 ppm), wear a MSHA/NIOSH approved (or equivalent) half mask, air-purifying respirator. (Air-purifying respirators should be equipped with organic vapor cartridges and dust and mist fibers.) For airborne concentrations up to 100 times the TLV (10,000 ppm), wear a MSHA/NIOSH approved full facepiece airline respirator in the positive pressure mode with emergency escape provisions. For unknown concentrations or those above 10,000 ppm wear a self contained breathing apparatus in the positive pressure mode. Other Protective:

Use chemically resistant apron and overshoes to avoid prolonged or repeated skin contact.

SECTION 10 : Other Information

MSDS Revision Date:

9/98

Supersedes: 8/15/98

Rev.: A

MSDS Author:

Scott E. Shaffer

584897

DENTSPLY International

DENTSPLY PROSTHETICS

Safety Data Sheet

Date Issued: 5/28/04 Document Number: 151 Date Revised: 09/09/2011 Revision Number:4

1. PRODUCT IDENTIFICATION

Trade Name (as labeled): Lucitone Liquid

Product Identifier (Part/Item Number): 684309, 684315

U.N. Number: UN1247

U.N. Dangerous Goods Classification: 3, PG II

Recommended Use: Fabrication of Dentures

Restrictions on Use: For Professional Use Only

Manufacturer/Supplier Name: Dentsply Prosthetics

Manufacturer/Supplier Address: 570 West College Ave.

York, PA 17405-0872

Manufacturer/Supplier Telephone Number: 717-845-7511 (Product Information)

Emergency Contact Telephone Number: 800-424-9300 Chemtrec

Email address: Prosthetics_MSDS@Dentsply.com


2. HAZARD(s) IDENTIFICATION

EU Classification (1999/45/EC): Highly Flammable (F), Irritant (Xi) R11, R37/38, R43

Refer to Section 16 for the full text of the EU Classifications and R Phrases.

Labeling in accordance with 1999/45/EC







Irritant

Contains: Methyl Methacrylate R11 Highly flammable.

R37/38 Irritating to respiratory system and skin R43 May cause sensitization by skin contact.

S24/25 Avoid contact with skin and eyes.

S36/37 Wear suitable protective clothing and gloves.

US Hazard Classification: Hazardous.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Components	C.A.S. #	EINECS#	Substance Classification	WT %
Methyl Methacrylate	80-62-6	201-297-1	F, Xi, R11, R37/38, R43	90 - 99
Ethylene Glycol Dimethacrylate	97-90-5	202-617-2	Xi R36/37	1-10

Refer to Section 16 for the full text of the GHS and H phrases and EU Classifications and R Phrases.

4. FIRST-AID MEASURES

Routes of Exposure	First Aid Instructions
Eye	Flush eyes with water for at least 15 minutes, holding the eyelids apart. Get immediate medical attention.
Skin	Wash skin with soap and water. Get medical attention if irritation develops. Launder contaminated clothing before re-use.
Inhalation	Remove victim to fresh air. If breathing is difficult, have qualified personnel administer oxygen, and obtain immediate medical attention.
Ingestion	If small quantities are swallowed, rinse out mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Get immediate medical attention.
Most important symptoms of exposure	May cause respiratory tract, eye and skin irritation. Prolonged or repeated contact may cause allergic skin reaction (skin rash). Inhalation of vapors may cause dizziness, headache, and other central nervous system effects.
Note to Physicians	(Treatment, Testing, and Monitoring)
Treat symptomatica	ılly.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:	Use carbon dioxide, foam, water spray or water fog.	
Fire Fighting Procedures:	Fight fire from a safe distance of protected location. Water may be ineffective unless used as a fine spray or fog. Use water to cool fire-exposed containers.	
Specific Hazards Arising from the Chemical:	Vapors are heavier than air and may travel to ignition source and flash back. Heat of fire may cause an exothermic auto polymerization reaction. Emits toxic fumes under fire conditions. Closed containers may explode due to pressure build up when exposed to extreme heat.	
Precautions for Fire Fighters:	Do not enter fire area without proper protection. Firefighters should wear full emergency equipment and approved positive pressure self-containing breathing apparatus.	

THERMAL
3
400

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, PPE and Emergency Procedures: Avoid contact with skin, eyes or clothing. Avoid breathing vapors. Provide explosion-proof ventilation. Wear appropriate protective clothing.

Environmental Precautions: Do not allow spills to enter sewers, waterways or the environment.

Methods and Materials for Containment and Clean-up: Eliminate all ignition sources. Contain and absorb spills with inert material and transfer to a suitable container for disposal.

December ded Description Facilities for Containment and Classical

7. HANDLING AND STORAGE

Precautions for Safe Handing: Avoid contact with eyes, skin, and clothing. Avoid breathing vapors or mist. Wash thoroughly after handling. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation. Keep away from heat, sparks and flames. Ground container when pouring. Do not expose to direct sunlight.

Empty containers retain product residues can be hazardous. Follow all MSDS precautions when handling empty containers.

Conditions for Safe Storage: Store in a cool, dry, well ventilated area. Keep container tightly closed when not in use. Do not store in direct sunlight. Prevent moisture contact. Protect from physical damage. Keep away from oxidizers and other incompatible materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

Methyl Methacrylate

50 ppm TWA TLV 100 ppm STEL TLV 100 ppm PEL 50 ppm TWA DFG MAK 50 ppm TWA UK WEL 100 ppm STEL UK WEL

Ethylene Glycol Dimethacrylate:

None established

Biological Exposure Limits: None

Appropriate Engineering Controls: Use ventilation that is adequate to keep employee exposure to airborne concentrations below exposure limits. Use explosion-proof equipment where required.

Individual Protection Measures (PPE)

Specific Eye/face Protection: Wear safety glasses when the possibility exists for eye contact due to splashing or spraying material.

Specific Skin Protection: Wear nitrile rubber or other impervious gloves to prevent skin contact. Wear impervious clothing if needed to prevent any contact with this product, such as gloves, apron, boots, or whole body suit.

Specific Respiratory Protection: None required with adequate ventilation. An approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. Selection and use of respiratory equipment must be in accordance with appropriate regulations and good industrial hygiene practice.

Specific Thermal Hazards: None required.

EYES/FACE HANDS RESPRIATORY SKIN	YES/FACE HANDS RESPRIATORY SKIN		Recommended Person	al Protective Equipment	
		EYES/FACE	HANDS	RESPRIATORY	SKIN
			ommo		

Environmental Exposure Controls: Do not allow spills to enter sewers or waterways.

General Hygiene Considerations and Work Practices: Avoid contact with eyes, skin, and clothing. Avoid breathing vapors or mist. Wash thoroughly after handling.

Protective Measures During Repair and Maintenance of Contaminated Equipment: Wear appropriate protective clothing and equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear liquid	Explosive limits:	Not available
Odor:	Acrylic odor.	Vapor pressure:	29 mmHg @ 68°F
Odor threshold:	0.21 ppm (methyl methacrylate)	Vapor density:	3.45
pH:	Not available	Relative density:	0.94
Melting/freezing point:	-54°F (-48°C)/Not available	Solubility:	1.5%

Initial boiling point and range:	Not available	Partition coefficient: n- octanol/water:	Not available
Flash point:	55°F (13°C) TOC	Auto-ignition temperature:	815°F (435°C)
Evaporation rate:	3.1 (Bac = 1)	Decomposition temperature:	Not available
Flammability:	LEL:2.1% UEL: 12.5%	Viscosity:	Not available
Explosive Properties:	Vapors are explosive above the LEL	Oxidizing Properties:	None

10. STABILITY AND REACTIVITY

Reactivity:: May auto polymerize.

Chemical Stability: Unstable if heated.

Possibility of Hazardous Reactions: Polymerization can occur. Reaction with oxidizers may cause fire.

Conditions to Avoid: Conditions leading to polymerization are excessive heat, oxygen-free atmosphere inhibitor depletion (due to excessive aging), direct sunlight, and contamination with polymerization catalysts.

Incompatible materials: Avoid contact with oxidizing agents, reducing agents, acids, and bases.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, methyl methacrylate, and irritating smoke and fumes.

11. TOXICOLOGICAL INFORMATION

Potential Health Effects:

Eyes: Liquid and vapors can cause moderate irritation (tears, blurred vision and redness).

Skin: May cause skin irritation with allergic skin reaction (skin sensitization).

Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.

<u>Inhalation:</u> May cause respiratory tract irritation with coughing, mucous production and shortness of breath. High concentration is irritating to the respiratory tract and may cause dizziness, headache and anesthetic effects.

<u>Chronic Health Effects</u>: Prolonged or repeated overexposure may cause skin irritation or sensitization in some individuals, as well as kidney, lung, liver, and heart damage.

Carcinogenicity: The results of a 2-year inhalation studies conducted for NTP showed no evidence of carcinogenicity of methyl methacrylate for male rats exposed at 500 or 1,000 ppm and female rats exposed at 250, 500 or 1,000 ppm. In another study, no increase was seen in the number or type of tumors in either rats or hamsters from a chronic inhalation study. No carcinogenic activity was also reported in a chronic oral study. However, acute oral exposure studies and structure-activity relationship comparisons with other acrylates suggest that the introduction of a methyl group to the acrylate moiety (e.g., EC to MMA) negates carcinogenic activity. None of the components of this product are listed as

carcinogens by OSHA, IARC, NTP, ACGIH or the EU Substances Directive.

<u>Mutagenicity:</u> Methyl Methacrylate: Negative in AMES test, positive and negative in in-vitro studies. Negative in vivo studies.

Medical Conditions Aggravated by Exposure: Individuals with pre-existing skin conditions may be at increased risk from exposure.

Acute Toxicity Data:

Methyl Methacrylate: Oral rat LD50 7800 mg/kg; Inhalation rat LC50 7093 ppm/4 hr. Ethylene Glycol Methacrylate: Oral rat LD50: 3300 mg/kg; Oral mouse LD50: 2 g/kg.

Reproductive Toxicity Data: In a study in rats, there were no developmental effects, although there were decreases in maternal body weight following inhalation of concentrations up to 8,315 mg/m³. There was no reduction in fertility in a dominant lethal assay in mice exposed to this compound at concentrations up to 36,900 mg/m³ and no adverse effects on reproductive organs in repeated dose studies conducted to date.

Specific Target Organ Toxicity (STOT):

Single Exposure: In an inhalation study with dogs, a 2000 ppm dose showed a drop in arterial blood pressure and GI motor activities. The lethal oral dose for methyl methacrylate is 6 to 9 g/kg in lab animals. Poisoned animals exhibit respiratory depression, and coma; also irritation of skin, eyes and respiratory tract.

Repeated Exposure: Methyl Methacrylate: Impairment of locomotor activity and learning and behavioral effects on the brain were observed in rats exposed orally to 500 mg/kg bw/day for 21 days.

12. ECOLOGICAL INFORMATION

Toxicity: Methyl Methacrylate: Fathead minnow LC50 96h: 130 mg/L Algae EC50 48h: 170 mg/L Ethylene Glycol Dimethacrylate: No data available.

Persistence and Degradability: Methyl mathacrylate is readily biodegradable - 88% after 28 days.

Bio-accumulative Potential: The potential for bioaccumulate is expected to be low for methyl methacrylate.

Mobility in Soil: Methyl methacrylate is expected to have very high to high mobility in soil.

Other Adverse Effects: None known

Results of PBT/vPvB Assessment: Not required.

13. DISPOSAL CONSIDERATIONS

Regulations: Dispose in accordance with all national and local regulations.

Properties (Physical/Chemical) Affecting Disposal: This product will polymerize when exposed to sunlight. Empty containers retain product residues can be hazardous. Follow all MSDS precautions when handling empty containers.

Waste Treatment Recommendations: No discharge to wastewater anticipated.

14. TRANSPORT INFORMATION

UN Identification Number: UN1247

UN Proper Shipping Name: Methyl Methacrylate Monomer, Inhibited

Transport hazard class(es): 3

Packing Group: PG II

Special precautions for user: Take appropriate precautions to avoid release

15. REGULATORY INFORMATION

U.S. Federal Regulations

US OSHA Hazard Classification: Flammable Liquid, Irritant, Sensitizer, Target organ effects.

Comprehensive Environmental Response and Liability Act of 1980 (CERCLA): Releases above the RQ of 1,000 lbs (based on the RQ for methyl methacrylate of 1,000 lbs present at 100% max) must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Toxic Substances Control Act (TSCA): This product is a medical device and not subject to chemical notification

Clean Water Act (CWA): This material is not regulated under the Clean Water Act

Clean Air Act (CAA): This material is not regulated under the Clean Air Act

Superfund Amendments and Reauthorization Act (SARA) Title III Information:

SARA Section 311/312 (40 CFR 370) Hazard Categories:

Immediate Hazard:	Yes	Pressure Hazard:	No	
Delayed Hazard:	Yes	Reactivity Hazard:	Yes	
Fire Hazard:	Yes			

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372):

Components	C.A.S. #	WT %
Methyl Methacrylate	80-62-6	80-95%

State Regulations

California: This product contains the following substances known to the state of California to cause cancer and/or reproductive toxicity: None.

Components	C.A.S. #	WT %
None.	Not applicable	Not applicable

International Regulations

Canadian Environmental Protection Act: This product is a medical device and not subject to chemical notification requirements.

Canadian Workplace Hazardous Materials Information System (WHMIS): Medical devices are not covered by WHMIS.

European Inventory of Existing Chemicals (EINECS): This product is a medical device and not subject to chemical notification requirements.

EU REACH: All components requiring registration have been pre-registered.

Australian Inventory of Chemical Substances: This product is a medical device and not subject to chemical notification requirements.

China Inventory of Existing Chemicals and Chemical Substances: This product is a medical device and not subject to chemical notification requirements.

Korean Existing Chemicals List: This product is a medical device and not subject to chemical notification requirements.

Philippine Inventory of Chemicals and Chemical Substances: This product is a medical device and not subject to chemical notification requirements.

16. OTHER INFORMATION

HMIS Hazard Rating:

Health – 2 Flammability – 3 Physical Hazard – 2

Full text of Classification abbreviations used in Section 2 and 3;

F Flammable

Xi Irritant

R11 Highly flammable.

R36/37 Irritating to eyes and respiratory tract.

R37/38 Irritating to respiratory system and skin

R43 May cause sensitization by skin contact.

Supersedes: September 21, 2007

Revision Summary: Change in format. Comprehensive review. Changes to all sections.

Data Sources: US NLM ChemID Plus and HSDB, Substance SDS for components, IUCLID Dataset EU Chemical Bureau, ESIS, Country websites for occupational exposure limits.