SAFETY DATA SHEETS

This SDS packet was issued with item:

075896444

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

070473876 071462753 075896451 075896469 075896477 075896808 075896816 075896824 075896832 075896865 075897103 075897111 075897129 075897137 075897145 075897152 075897202 075897210 075897228 075897236 075897244 075914619

Trade Name: *EMBRACE™ Product Line*

| 1.0 | Commercial Product Name and Supplier | | | |
|----------------|---|--|--|------------------------------|
| 1.1 | Commercial product name | Code | | |
| | Embrace™ WetBond™ Class V Embrace™ WetBond™ First Coat Embrace™ Esthetic Opaquer Embrace™ WetBond™ Pit & Fissure Sealant Embrace™ WetBond™ Pit & Fissure Sealant Low Embrace™ WetBond™ Seal-n-Shine™ Embrace™ WetBond™ Resin Cement | EMFC EMOK, EI EMS, EM v Fill EMSWLF EMSNS, I | EMVA3.5, EMVB2, EMVD MO1, EMO2, EMO3, EMC S3, EMSB, EMSW, EMS3 ,EMSWLFB EMSNY MCAR, EMCAR2, EMCM, | 04, EMO5 BW, EMSWB |
| 1.2 | Application / Use | Dental m | naterial for use by dental p | professional only. |
| 1.2.2 1.2.3 | SIC Use Category | 851 Hun 55 | nan health activity | |
| 1.3 1.3.1 | Manufacturer, Importer Manufacturer Pulpdent Corporation 80 Oakland Street Watertown, MA 02472 USA | Telepho Fax: | ne: 1 617 926-6666 1 617 926-6262 ulpdent@pulpdent.com | |
| 1.4 | Emergency Telephone Number | 1-800-53 | 35-5053 (24 Hour / USA) | |
| 1.5 | Authorized European Representative | | | |
| | International Business Solutions Ltd. 54 Mayfield Ridge Hatch Warren, Basingstoke, RG22 4RS UK | Fax: 012 | 89 407479 256 350330 williams5@btconnect.co.u | <u>ık</u> |
| 2.0 | Hazards Identification | | | |
| 2.1 | Classification | | | |
| 2.1.1 | Classification according to Regulation (EC) | Hazard Class | Hazard Category | Hazard Statement |
| | No 1272/2008 [CLP] | Eye irritation STOT SE Skin irritation Skin sensitization | 2 3 2 1 | H319 H335 H315 H317 |
| 2.1.2 | Classification according to Directive 67/548/EEC (See SECTION 16 for full text of risk phrases) | Irritant; Xi; F | R 36/37/38 - 43 | |

2.2 GHS Label Elements

Hazard Pictograms



Signal Word: WARNING

Trade Name: *EMBRACE™ Product Line*

Restricted to use by dental professional only.

Hazard Statements

H319: Eye irritation. 2. May cause eye irritation.

H335: STOT SE. 3. May cause respiratory irritation.

H315: Skin irritation. 2. May cause skin irritation.

H317: Sensitization. 1. May cause an allergic skin reaction.

Precautionary Statements

P261: Avoid breathing vapor.

P280: Wear protective gloves and eye protection

P305+P351: If in eyes, rinse cautiously with water for several minutes.

P337+P313: If eye irritation persists, get medical advice/attention.

P302+P352: If on skin, wash with plenty of soap and water.

P333+P313: If irritation or rash occurs, get medical advice/attention.

P410+P411: Protect from sunlight. Store at temperature not exceeding 27°C / 80°F.

| 3.0 | Composition | | | | |
|-----|-----------------------|---------------------------------|---|--|---|
| 3.1 | Chemical character | rization of the preparation: | Acrylate ester monomers in two-part, glass-filled, dual-cure paste. | | |
| 3.2 | Hazardous ingredients | | | | |
| | CAS Number | Name of the Ingredient | Concentration | Classification per 67/548/EEC | Classification per Regulation (EC) No.1278/2008 (CLP). |
| | Proprietary | Uncured acrylate ester monomers | 55-60% | Irritant; Xi R 3637//38 - 43 | Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315 Skin sensitization, 1, H317 |
| | 112945-52-5 | Silica, amorphous | 5 % | Irritant; Xi, R 36/37/38 | Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315 |
| 4.0 | First Aid Measure | s | | | , |
| 4.1 | General Information | | eyes and skin. I | Do not inhale vapo nis safety data shee | system and skin. Avoid contact with rs. May cause sensitization by skin to medical personnel. Get medical |
| 4.2 | Inhalation | | | air. If necessary, medical attention. | administer oxygen and/or artificial |
| 4.3 | Skin Contact | | Take off contami | nated clothing. Was | sh thoroughly with soap and water. |
| 4.4 | Eye Contact | | Keep eyelids ap | | running water for 15+ minutes. Get |
| 4.5 | Ingestion | | | | ice vomiting. Get immediate medical us membranes. Never give anything |

| | | by mouth to an unconscious person. |
|-----|--|---|
| 4.6 | Precautions for first responders | Ventilate the area. Wear eye and skin protection. |
| 4.7 | Information for physicians | |
| | Symptoms | Irritation or redness in eyes, throat or on skin. |
| | Hazards | May be irritating to eyes, respiratory system and skin. May cause sensitization by skin contact. |
| | Treatment | As above under First Aid. |
| 5.0 | Fire Fighting Measures | |
| 5.1 | Suitable extinguishing media | Carbon dioxide, dry chemical, alcohol foam, or water fog. Water spray may be used to keep fire exposed containers cool. |
| 5.2 | Extinguishing media to avoid | Do not use direct water stream |
| 5.3 | Special exposure hazards in a fire | Heat may cause polymerization with rapid release of energy. |
| 5.4 | Special protective equipment for fire-fighters | A self-contained breathing apparatus should be worn by fire fighting personnel. Cool exposed containers with water spray to prevent polymerization under fire conditions. |
| 6.0 | Accidental Release Measures | |
| 6.1 | Personal precautions. | Wear safety glasses, gloves and lab coat. |
| 6.2 | Environmental precautions | Avoid releasing large amounts of uncured material into the environment. Cured / set-up material is, to our knowledge, inert. |
| 6.3 | Method for clean up | Contain spilled material. Absorb or wipe up spill with suitable material (paper towels or cloths). Collect for disposal in a covered container. Wash area of spill with alcohol or soap and water. |
| 7.0 | Handling and Storage | |
| 7.1 | Handling | For use only by dental professionals. Follow good hygiene practices. Do not smoke, eat or drink while using. Avoid direct / strong light sources, extremes of temperature (>27°C/80°F, <5°C/40°F), contamination, and cross contamination of two-part materials. Recap immediately after use. |
| 7.2 | Storage | Keep containers tightly closed. Store product in original container at cool room temperature (<25°C) and in a dry, well ventilated area. Avoid direct, strong light, sources of ignition and extremes of temperature. Shelf life for unopened product is two years from date of manufacture, provided that the material has been stored properly. |
| 7.3 | Specific uses | Dental restorative materials |

| 8.0 | Exposure Controls / Personal Protecti | on | |
|---------|--|--|--|
| 8.1 | Exposure limit values | PEL: Not established. TLV: Not es | stablished. |
| 8.2 | Exposure controls | | |
| 8.2.1 | Occupational exposure controls | No special equipment required ur product in the quantity provided. | nder normal conditions of use of thi |
| 8.2.1.1 | Respiratory protection | None required. Good general ve airborne vapors from uncured mate | entilation is sufficient to control an erial. |
| 8.2.1.2 | Hand protection | No special requirements. The usua will limit contact with uncured mate | al surgical gloves worn by dental sta rial. |
| 8.2.1.3 | Eye protection | No special requirements other that dental staff. | an the usual safety glasses worn b |
| 8.2.1.4 | Skin protection | | ersonal hygiene and safety practice rotect dental staff from unnecessar |
| 8.2.1.5 | Other controls | Emergency eye wash fountain sh use. | ould be available. Wash hands after |
| 8.2.2 | Environmental exposure controls | Cure material before disposing. | |
| 9.0 | Physical and Chemical Properties | | |
| 9.1 | Appearance | | |
| 9.1.1 | Color / Physical state | Embrace Product | <u>Description</u> |
| | | First Coat, Seal-n-Shine | Thin, clear liquid |
| | | Esthetic Opaquer | Opaque, thick paste Bleach White, Off-White, Light Yellow, Pink or Dark Yellow |
| | | Pit and Fissure Sealant | Natural tooth shade or off-white thin paste. |
| | | Pit and Fissure Sealant, Low Fill | Off-white thin paste |
| | | Class V | Tooth-colored paste. |
| | | Resin Cement. | Two thin pastes: one white, one yellow. |
| 9.1.2 | Odor | Faint, characteristic | |
| 9.2 | Important health, safety and environmental information | | |
| 9.2.1 | pH Not determined | | |
| 9.2.2 | Boiling point Not determined | | |
| 9.2.3 | Flash point | Not determined | |
| 9.2.4 | Flammability (solid, gas) | Not applicable | |
| 9.2.5 | Explosive properties | Not applicable | |
| 9.2.6 | Oxidizing properties | Not determined | |

Pulpdent Corporation Revision Date: July 1, 2013

Safety Data Sheet

| 9.2.7 | Vapor pressure | < 1 mm Hg |
|--------------------------------------|---|--|
| 9.2.8 | Specific gravity | Embrace First Coat: 1.420 Embrace Seal-n-Shine: 1.240 Embrace Opaquer: 1.780 Embrace Pit & Fissure Sealant: 1.575 Embrace Pit & Fissure Sealant, Low Fill: 1.160 Embrace Class V: 2.030 Embrace Resin Cement: Low Viscosity: 1.660 Embrace Resin Cement: Medium Viscosity: 1.400 |
| 9.2.9 | Solubility in water | Nil |
| 9.2.10 | Partition coefficient | Not determined |
| 9.2.11 | Viscosity | Not determined |
| 9.2.12 | Vapor density | Not determined |
| 9.2.13 | Evaporation rate | Not determined |
| 10.0 | Stability and reactivity | |
| 10.1 | Conditions to avoid | Temperature > 38°C, intense light, cross-contamination. |
| 10.2 | Materials to avoid | Reducing and oxidizing agents, peroxides, amines. |
| | | |
| 10.3 | Hazardous decomposition products | Under fire conditions and with amounts greater than that supplied in this product, hazardous polymerization may occur with heat build-up release of carbon monoxide, carbon dioxide, and oxides of nitrogen. |
| 10.3 | Hazardous decomposition products Further information | this product, hazardous polymerization may occur with heat build-up |
| | | this product, hazardous polymerization may occur with heat build-up release of carbon monoxide, carbon dioxide, and oxides of nitrogen. Stable material if stored and used as directed. Polymerization will |
| 10.4 | Further information | this product, hazardous polymerization may occur with heat build-up release of carbon monoxide, carbon dioxide, and oxides of nitrogen. Stable material if stored and used as directed. Polymerization will |
| 10.4 | Further information Toxicological information | this product, hazardous polymerization may occur with heat build-up release of carbon monoxide, carbon dioxide, and oxides of nitrogen. Stable material if stored and used as directed. Polymerization will occur when light-cured material is exposed to direct light. Not toxic. Minimal health hazard in the quantity present in this |
| 10.4 11.0 11.1 | Further information Toxicological information Acute toxicity | this product, hazardous polymerization may occur with heat build-up release of carbon monoxide, carbon dioxide, and oxides of nitrogen. Stable material if stored and used as directed. Polymerization will occur when light-cured material is exposed to direct light. Not toxic. Minimal health hazard in the quantity present in this product and under normal conditions of use. May be irritating to eyes, respiratory tract, mucous membranes or |
| 10.4 11.0 11.1 11.2 | Further information Toxicological information Acute toxicity Irritation and corrosiveness | this product, hazardous polymerization may occur with heat build-up release of carbon monoxide, carbon dioxide, and oxides of nitrogen. Stable material if stored and used as directed. Polymerization will occur when light-cured material is exposed to direct light. Not toxic. Minimal health hazard in the quantity present in this product and under normal conditions of use. May be irritating to eyes, respiratory tract, mucous membranes or skin on contact or with prolonged exposure. May be sensitizing. Prolonged or frequent skin contact may cause |
| 10.4 11.0 11.1 11.2 11.3 | Further information Toxicological information Acute toxicity Irritation and corrosiveness Sensitization | this product, hazardous polymerization may occur with heat build-up release of carbon monoxide, carbon dioxide, and oxides of nitrogen. Stable material if stored and used as directed. Polymerization will occur when light-cured material is exposed to direct light. Not toxic. Minimal health hazard in the quantity present in this product and under normal conditions of use. May be irritating to eyes, respiratory tract, mucous membranes or skin on contact or with prolonged exposure. May be sensitizing. Prolonged or frequent skin contact may cause allergic skin reactions in some susceptible individuals. Prolonged and/or frequent skin contact may cause allergic skin reactions in susceptible individuals. Prolonged exposure to large amounts (more than in this product) of Embrace resins may cause |

| 11.7 | Clinical experience | Embrace products have been on the market in the US and internationally for more than 10 years. There have been no reports of adverse events. |
|------|----------------------------|---|
| 12.0 | Ecological Information | |
| 12.1 | Ecotoxicity | Avoid release of uncured material into the environment. To the best of our knowledge, polymerized material is inert. No other information is available. Follow all government regulations. |
| 13.0 | Disposal Considerations | |
| 13.1 | Regulations | Follow all local and national government regulations in disposing material or contaminated packaging. |
| 14.0 | Transport Information | |
| 14.1 | Restrictions | None. Not regulated. |
| 15.0 | Regulatory Information | |
| 15.1 | EU | Class IIA medical devices under MDD 93/42/EEC. |
| 15.2 | US FDA | Class II medical devices. |
| 15.3 | Health Canada | Class III medical devices |
| 16.0 | Other information | |
| 16.1 | List of relevant R phrases | R 36 / 3 7/ 38: Irritating to eyes, respiratory system and skin. R 43: Sensitizing by skin contact. |
| 16.2 | Hazard Statements | H319: Eye irritation. Hazard category 2. H335: Specific Target Organ Toxicity - Single exposure; hazard category. 3. Respiratory tract irritation. H315: Skin irritation. Hazard category 2. H317: Skin Sensitization. Hazard category 1. |
| 16.3 | Precautionary Statements | P261: Avoid breathing vapor. P280: Wear protective gloves and eye protection P305 + P351: If in eyes, rinse cautiously with water for several minutes. P337 + P313: If eye irritation persists, get medical advice/attention. P302 + P352: If on skin, wash with plenty of soap and water. P333 + P313: If irritation or rash occurs, get medical advice / attention. P410 + P411: Protect from sunlight. Store at temperature not exceeding 27°C / 80°F. |

Pulpdent Corporation Revision Date: July 1, 2013

Safety Data Sheet

| 16.4 | Restrictions on use | Embrace Products are to be sold to and used by dental professionals only. |
|------|---|--|
| 16.5 | Further information | The information presented herein is believed to be factual as it has been derived from the works of persons believed to be qualified experts. However, nothing contained in this information is to be taken as a warranty or representation for which Pulpdent Corporation bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate. |
| 16.6 | Sources of key data | National Institute for Occupational Safety (NIOSH) |
| | | US Occupational Safety and Health Administration (OSHA) |
| | | Eur-Lex European Union Law: Regulation (EC) No. 1272/2008 (CLP) and Regulation (EC) No. 1907/2006 (REACH). |
| | | Guidance on the compilation of safety data sheets. Version 1.1; December 2011. European Chemicals Agency |
| 16.7 | Information which has been added, deleted or revised. | This Safety Data Sheet has been revised to meet the GHS SDS format and the requirements of Regulation (EC) No. 1272/2008 (CLP) and Regulation (EC) No. 1907/2006 (REACH). Specifically Sections 2.1, 2.2, 3.2, 16.2, 16.3 have been modified. |