

SAFETY DATA SHEETS

This SDS packet was issued with item:

075896477

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

070473876 071462753 075896444 075896451 075896469 075896808 075896816 075896824 075896832 075896865
075897103 075897111 075897129 075897137 075897145 075897152 075897202 075897210 075897228 075897236
075897244 075914619

Safety Data SheetTrade Name: **EMBRACE™ WetBond™ Pit and Fissure Sealant, Natural and Off-White Shades****1.0 Commercial Product Name and Supplier**

1.1	Commercial product name	Embrace™ WetBond™ Pit and Fissure Sealant, Natural Shade Embrace™ WetBond™ Pit and Fissure Sealant, Off-White Shade
1.2	Application / Use	Dental material for use by dental professional only.
1.2.2	SIC	851 Human health activity
1.2.3	Use Category	55
1.3	Manufacturer, Importer	
1.3.1	Manufacturer	Pulpdent Corporation 80 Oakland Street P.O. Box 780 Watertown, MA 02472 USA Telephone: 1 617 926-6666 Fax: 1 617 926-6262 Email: Pulpdent@pulpdent.com
1.4	Emergency Telephone Number	1-800-535-5053 (24 Hour / USA)
1.5	Authorized European Representative	Tel: 07989 407479 International Business Solutions Ltd. 54 Mayfield Ridge Hatch Warren, Basingstoke, RG22 4RS UK Fax: 01256 350330 Email: s.williams5@btconnect.co.uk

2.0 Hazards Identification**2.1 Classification**

2.1.1	Classification according to Regulation (EC) No 1272/2008 [CLP]	<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Hazard Statement</u>
		Eye irritation	2	H319
		STOT SE	3	H335
		Skin irritation	2	H315
		Skin sensitization	1	H317
2.1.2	Classification according to Directive 67/548/EEC (See SECTION 16 for full text of risk phrases)	Irritant; Xi; R 36/37/38 - 43		

2.2 Label Elements

Labeling according to Regulation (EC) No 1272/2008 [CLP]

Hazard Pictograms

Signal Word: **WARNING****Restricted to use by dental professional only.****Hazard Statements**

H319: Eye irritation. 2. May cause eye irritation.

H335: STOT SE. 3. May cause respiratory irritation.

H315: Skin irritation. 2. May cause skin irritation.

H317: Sensitization. 1. May cause an allergic skin reaction.

Trade Name: **EMBRACE™ WetBond™ Pit and Fissure Sealant, Natural and Off-White Shades**

Precautionary Statements

P261: Avoid breathing vapor.

P280: Wear protective gloves and eye protection

P305+P351: If in eyes, rinse cautiously with water for several minutes.

P337+P313: If eye irritation persists, get medical advice/attention.

P302+P352: If on skin, wash with plenty of soap and water.

P333+P313: If irritation or rash occurs, get medical advice/attention.

P410+P411: Protect from sunlight. Store at temperature not exceeding 27°C / 80°F.

3.0 Composition

3.1 Chemical characterization of the preparation: Acrylate ester monomers in two-part, glass-filled, dual-cure paste.

3.2 Hazardous ingredients

CAS Number	Name of the Ingredient	Concentration	Classification per 67/548/EEC	Classification per Regulation (EC) No.1278/2008 (CLP).
Proprietary	Uncured acrylate ester monomers	55-60%	Irritant; Xi R 3637//38 - 43	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315 Skin sensitization, 1, H317
112945-52-5	Silica, amorphous	5 %	Irritant; Xi, R 36/37/38	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315

4.0 First Aid Measures

4.1	General Information	May be irritating to eyes, respiratory system and skin. Avoid contact with eyes and skin. Do not inhale vapors. May cause sensitization by skin contact. Show this safety data sheet to medical personnel. Get medical attention in case of uncertainty.
4.2	Inhalation	Move to fresh air. If necessary, administer oxygen and/or artificial respiration. Seek medical attention.
4.3	Skin Contact	Take off contaminated clothing. Wash skin thoroughly with soap and water.
4.4	Eye Contact	Keep eyelids apart and flush with running water for 15+ minutes. Get medical attention.
4.5	Ingestion	Rinse mouth with water. Do not induce vomiting. Get immediate medical attention. May be irritating to mucous membranes. Never give anything by mouth to an unconscious person.
4.6	Precautions for first responders	Ventilate the area. Wear eye and skin protection.
4.7	Information for physicians	
	Symptoms	Irritation or redness in eyes, throat or on skin.
	Hazards	May be irritating to eyes, respiratory system and skin. May cause sensitization by skin contact.
	Treatment	As above under First Aid.

Pulpdent Corporation
Safety Data Sheet

Revision Date: August 1, 2013

Trade Name: **EMBRACE™ WetBond™ Pit and Fissure Sealant, Natural and Off-White Shades**

5.0 Fire Fighting Measures

- | | | |
|-----|--|---|
| 5.1 | Suitable extinguishing media | Carbon dioxide, dry chemical, alcohol foam, or water fog. Water spray may be used to keep fire exposed containers cool. |
| 5.2 | Extinguishing media to avoid | Do not use direct water stream |
| 5.3 | Special exposure hazards in a fire | Heat may cause polymerization with rapid release of energy. |
| 5.4 | Special protective equipment for fire-fighters | A self-contained breathing apparatus should be worn by fire fighting personnel. Cool exposed containers with water spray to prevent polymerization under fire conditions. |

6.0 Accidental Release Measures

- | | | |
|-----|---------------------------|--|
| 6.1 | Personal precautions. | Wear safety glasses, gloves and lab coat. |
| 6.2 | Environmental precautions | Avoid releasing large amounts of uncured material into the environment. Cured / set-up material is, to our knowledge, inert. |
| 6.3 | Method for clean up | Contain spilled material. Absorb or wipe up spill with suitable material (paper towels or cloths). Collect for disposal in a covered container. Wash area of spill with alcohol or soap and water. |

7.0 Handling and Storage

- | | | |
|-----|---------------|---|
| 7.1 | Handling | For use only by dental professionals. Follow good hygiene practices. Do not smoke, eat or drink while using. Avoid direct / strong light sources, extremes of temperature (>27°C/80°F, <5°C/40°F), contamination, and cross contamination of two-part materials. Recap immediately after use. |
| 7.2 | Storage | Keep containers tightly closed. Store product in original container at cool room temperature (<25°C) and in a dry, well ventilated area. Avoid direct, strong light, sources of ignition and extremes of temperature. Shelf life for unopened product is two years from date of manufacture, provided that the material has been stored properly. |
| 7.3 | Specific uses | Dental restorative materials |

8.0 Exposure Controls / Personal Protection

- | | | |
|---------|--------------------------------|---|
| 8.1 | Exposure limit values | PEL: Not established. TLV: Not established. |
| 8.2 | Exposure controls | |
| 8.2.1 | Occupational exposure controls | No special equipment required under normal conditions of use of this product in the quantity provided. |
| 8.2.1.1 | Respiratory protection | None required. Good general ventilation is sufficient to control any airborne vapors from uncured material. |
| 8.2.1.2 | Hand protection | No special requirements. The usual surgical gloves worn by dental staff will limit contact with uncured material. |
| 8.2.1.3 | Eye protection | No special requirements other than the usual safety glasses worn by dental staff. |
| 8.2.1.4 | Skin protection | No special requirements. Good personal hygiene and safety practices and wearing a lab coat should protect dental staff from unnecessary exposure to uncured material. |

Pulpdent Corporation
Safety Data Sheet

Revision Date: August 1, 2013

Trade Name: **EMBRACE™ WetBond™ Pit and Fissure Sealant, Natural and Off-White Shades**

8.2.1.5	Other controls	Emergency eye wash fountain should be available. Wash hands after use.
8.2.2	Environmental exposure controls	Cure material before disposing.

9.0 Physical and Chemical Properties

9.1	Appearance	
9.1.1	Color / Physical state	Natural tooth shade or off-white thin paste.
9.1.2	Odor	Faint, characteristic
9.2	Important health, safety and environmental information	
9.2.1	pH	Not determined
9.2.2	Boiling point	Not determined
9.2.3	Flash point	Not determined
9.2.4	Flammability (solid, gas)	Not applicable
9.2.5	Explosive properties	Not applicable
9.2.6	Oxidizing properties	Not determined
9.2.7	Vapor pressure	< 1 mm Hg
9.2.8	Specific gravity	1.575
9.2.9	Solubility in water	Nil
9.2.10	Partition coefficient	Not determined
9.2.11	Viscosity	Not determined
9.2.12	Vapor density	Not determined
9.2.13	Evaporation rate	Not determined

10.0 Stability and reactivity

10.1	Conditions to avoid	Temperature > 38°C, intense light.
10.2	Materials to avoid	Reducing and oxidizing agents, peroxides, amines.
10.3	Hazardous decomposition products	Under fire conditions and with amounts greater than that supplied in this product, hazardous polymerization may occur with heat build up and release of carbon monoxide, carbon dioxide, and oxides of nitrogen.
10.4	Further information	Stable material if stored and used as directed. Polymerization will occur when light-cured material is exposed to direct light.

11.0 Toxicological information

11.1	Acute toxicity	Not toxic. Minimal health hazard in the quantity present in this product and under normal conditions of use.
11.2	Irritation and corrosiveness	May be irritating to eyes, respiratory tract, mucous membranes or skin on contact or with prolonged exposure.
11.3	Sensitization	May be sensitizing. Prolonged or frequent skin contact may cause allergic skin reactions in some susceptible individuals.

Safety Data SheetTrade Name: **EMBRACE™ WetBond™ Pit and Fissure Sealant, Natural and Off-White Shades**

11.4	Sub-acute, sub-chronic and prolonged toxicity	Prolonged and/or frequent skin contact may cause allergic skin reactions in susceptible individuals. Prolonged exposure to large amounts (more than in this product) of Embrace resins may cause eye and respiratory irritation.
11.5	Carcinogenicity, Mutagenicity, Reproductive Toxicity	None known
11.6	Empirical data	Not available
11.7	Clinical experience	Embrace Pit and Fissure Sealants have been on the market in the US and internationally for more than 10 years. There have been no reports of adverse events.
12.0 Ecological Information		
12.1	Ecotoxicity	Avoid release of uncured material into the environment. To the best of our knowledge, polymerized material is inert. No other information is available. Follow all government regulations.
13.0 Disposal Considerations		
13.1	Regulations	Follow all local and national government regulations in disposing material or contaminated packaging.
14.0 Transport Information		
14.1	Restrictions	None. Not regulated.
15.0 Regulatory Information		
15.1	EU	Class IIA medical devices under MDD 93/42/EEC.
15.2	US FDA	Class II medical devices.
15.3	Health Canada	Class III medical devices
16.0 Other Information		
16.1	List of relevant R phrases	R 36 / 3 7 / 38: Irritating to eyes, respiratory system and skin. R 43: Sensitizing by skin contact.
16.2	Hazard Statements	H319: Eye irritation. Hazard category 2. H335: Specific Target Organ Toxicity - Single exposure; hazard category. 3. Respiratory tract irritation. H315: Skin irritation. Hazard category 2. H317: Skin Sensitization. Hazard category 1.
16.3	Precautionary Statements	P261: Avoid breathing vapor. P280: Wear protective gloves and eye protection P305 + P351: If in eyes, rinse cautiously with water for several minutes. P337 + P313: If eye irritation persists, get medical advice/attention. P302 + P352: If on skin, wash with plenty of soap and water. P333 + P313: If irritation or rash occurs, get medical advice / attention. P410 + P411: Protect from sunlight. Store at temperature not exceeding 27°C / 80°F.

Safety Data SheetTrade Name: **EMBRACE™ WetBond™ Pit and Fissure Sealant, Natural and Off-White Shades**

16.4	Restrictions on use	Embrace Pit and Fissure Sealants are to be sold to and used by dental professionals only.
16.5	Further information	The information presented herein is believed to be factual as it has been derived from the works of persons believed to be qualified experts. However, nothing contained in this information is to be taken as a warranty or representation for which Pulpdent Corporation bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.
16.6	Sources of key data	National Institute for Occupational Safety (NIOSH) US Occupational Safety and Health Administration (OSHA) Eur-Lex European Union Law: Regulation (EC) No. 1272/2008 (CLP) and Regulation (EC) No. 1907/2006 (REACH). Guidance on the compilation of safety data sheets. Version 1.1; December 2011. European Chemicals Agency
16.7	Information which has been added, deleted or revised.	This Safety Data Sheet has been revised to meet the requirements of GHS SDS format and Regulations (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH). Specifically Sections 2.1, 2.2, 3.2, 16.2, 16.3 have been modified.
