## **SAFETY DATA SHEETS**

# This SDS packet was issued with item:

073241304

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071691005 072557858 072557890 072557908 072557916 072557924 072557932 072557940 072557965 072557973 072558021 072558039 073239100 073239118 073239126 073239134 073239142 073239159 073239167 073239209 073239217 073239225 073239233 073239449 073239456 073239464 073239472 073239480 073239498 073239506 073239563 073239571 073239589 073241338 073241346 073241353 073241361 073241379 073241387 073241403 073241411 073241429 073241437 073242443 073242476 073242682 078634810 078634813 078634816 078634819 078634822 078634955

according to Regulation (EC) No 1907/2006

## **Luxatemp Ultra**

Print date: 03.07.2014 Product code: 1300\_GHS Page 1 of 4

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Luxatemp Ultra

Product group: Endprodukt

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Company name: DMG Chemisch-Pharmazeutische Fabrik GmbH

Street: Elbgaustraße 248
Place: D-22547 Hamburg
Telephone: +49. (0) 40. 84006-0

+49. (0) 40. 84006-0 Telefax: +49. (0) 40. 84006-222

e-mail: info@dmg-dental.com Internet: www.dmg-dental.com

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant

R phrases:

Irritating to eyes, respiratory system and skin. May cause sensitisation by skin contact.

## **GHS** classification

Hazard Statements:

May cause respiratory irritation. Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

#### 2.2. Label elements

Signal word: Warning Pictograms: GHS07



## **Hazard statements**

H335 May cause respiratory irritation.
H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

## **Precautionary statements**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

#### 2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

according to Regulation (EC) No 1907/2006

## **Luxatemp Ultra**

Print date: 03.07.2014 Product code: 1300\_GHS Page 2 of 4

#### **Chemical characterization**

chemical characterization (preparation): Acrylate.-resin.

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### After inhalation

Exposition vermeiden. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

#### After contact with skin

After contact with skin, wash immediately with: Water and soap.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### After ingestion

Consult physician.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO2).

#### Extinguishing media which must not be used for safety reasons

High power water jet.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

#### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

#### 6.3. Methods and material for containment and cleaning up

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

#### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store only in original container.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### 8.2. Exposure controls



according to Regulation (EC) No 1907/2006

## **Luxatemp Ultra**

Print date: 03.07.2014 Product code: 1300\_GHS Page 3 of 4

#### Protective and hygiene measures

When using do not eat or drink.

## **Respiratory protection**

The following must be prevented: inhalation.

## **Hand protection**

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

#### Eye protection

Tightly sealed safety glasses.

### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Paste

Colour: characteristic

Odour: ester

Test method

pH-Value (at 20 °C): ca. 7

Changes in the physical state

Boiling point: >250 °C
point of decomposition: 200 °C
Flash point: >150 °C
Ignition temperature: >380 °C
Vapour pressure: 1 hPa
(at 20 °C)
Density: 15 g/cm³

Density: 1,5 g/cm³
Water solubility: 10 g/L
Vapour density: 1

## **SECTION 10: Stability and reactivity**

## 10.4. Conditions to avoid

heat. Light.

Decompostion takes place from temperatures above: 200 °C

Decomposition under formation of: Acrylate.

## 10.5. Incompatible materials

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

### 10.6. Hazardous decomposition products

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent). nitrogen oxides (NOx).

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

#### **Acute toxicity**

LD50: Rat. 5000 mg/kg

## Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye:

### Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

according to Regulation (EC) No 1907/2006

## **Luxatemp Ultra**

Print date: 03.07.2014 Product code: 1300\_GHS Page 4 of 4

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Acute fish toxicity LC50: >360 mg/l/48h

#### 12.2. Persistence and degradability

Preparation not tested.

#### **Further information**

Do not empty into drains or the aquatic environment.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of harzardous waste according to official regulations.

#### Waste disposal number of waste from residues/unused products

180106

WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances

Classified as hazardous waste.

## **SECTION 14: Transport information**

## Other applicable information

Not a hazardous material with respect to these transportation regulations.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

#### **SECTION 16: Other information**

## Full text of R phrases referred to under Sections 2 and 3

36/37/38 Irritating to eyes, respiratory system and skin.43 May cause sensitisation by skin contact.

#### Full text of H statements referred to under Sections 2 and 3

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)