SAFETY DATA SHEETS

This SDS packet was issued with item:

071225960

N/A

Distributor:

SAFETY DATA SHEET

SECTION 1 - Identification Common Name: BlissEtch® Universal Etchant with 5% Glutaraldehyde CAO (China) Medical Equipment Co., Ltd. Manufacturer: No. 19 Baihe Road, Langfang EDTZ Hebei Province, China P.C: 065001 Tel: 86.316.6083456

> CAO Group, Inc. 4628 West Skyhawk Drive West Jordan, UT 84084-4501 U.S.A. Phone 877.236.4408 (M-F 8-5, GMT-7)

Email: info@caogroup.com

Recommended Use: Tooth etchant

Restrictions on Use: Not for use on skin or oral soft tissues. Chemical Name: Mixture

Chemical Family: Not applicable Chemical Formula: Mixture CAS#: Mixture

TSCA 8(b): Glutaraldehyde, water

Physical Hazard:

MSD-000003_12-14-01_BlissEtch SDS.indd 1-4



PRINT READY

Eye Contact:

Substances:

Acute Toxicity: Category 2 Skin Corrosion: Category 1C

Eye Corrosion: Category 1 DANGER: May be fatal if swallowed. Causes severe skin burns and eve damage.

Environment Hazard: Acute Aquatic Hazard: Category 2

Chronic Aquatic Hazard: Category 2 Toxic to aquatic life with long lasting effects.

Potential Acute Health Effects:

Health Hazard:

Irritating to eyes and skin. Hazardous if ingested. Residual contamination if not cleansed may cause

Hazard Statements: H300: Fatal if swallowed

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage. H401+H411: Toxic to aquatic life with long lasting

Precautionary P260: Do not breathe mist or spray. P264: Wash hands thoroughly after handling

P270: do not eat, drink, or smoke when using this product.

P280: Wear protective gloves, clothing, and eye protection

P301+P303+P304+P305+P310: If swallowed, inhaled, or on skin or in eyes: Contact a poison control center or physician immediately. P321+P330+P331+P338+P340+P351: If not breathing,

remove to fresh air and give artificial respiration. If ingested, rinse mouth, do not induce vomiting unless directed by medical personnel. If on skin, cautiously flush with water for 15 minutes. If in eyes, remove contacts if safe to do so, then cautiously flush with water for 15 minutes.

P361+P363: Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. P405: Store locked up.

P501: Dispose of contents/container consistent with national, regional, and municipal regulations.

Common Names

Large Spill:

Storage

HMIS Flammability Physical

SECTION 3 - Composition and Information on

Component Name CAS# wt% Synonyms Glutaraldehyde 5 111-30-8 Glutaral Water 7732-18-5 90-95 Proprietary organic 1-5

SECTION 4 - First Aid Measures

Check for and remove contact lenses immediately. Cautiously flush with water for 15 minutes. Contact a

Skin Contact: Flush with plenty of water for 15 minutes. Contact a physician if redness or irritation persists for more than

Inhalation: If inhaled, remove to fresh air. If not breathing, give

artificial breathing. Seek medical help immediately Rinse mouth. Do not induce vomiting. Seek medical Inaestion: attention immediately.

SECTION 5 - Fire and Explosion

Flammability: Not Flammable Special Protective Self-contained breathing apparatus. Protective clothing. Equipment for

Firefighting: Products of Carbon monoxide, carbon dioxide, nitrogen oxides, Combustion: oxygen, chlorine oxides.

Hazards in Not Available Presence of Various

Fire Fighting Media Water spray or Class A extinguisher.

SECTION 6 - Accidental Release Measures

Personal Wear protective gloves and protective eyewear. Wear a Precautions protective apron or smock

Environmental If safe to do so, establish containment to prevent Precautions: material from entering drains.

Small Spill: Wipe up excess with wet cloth. Use wet cloth or mop to remove residual material. Dispose of rinse water

consistent with national, regional, and municipal

Keep away from heat or ignition sources. Contain spill if without risk. Prevent the material from entering drains or sewage systems. Use absorbent earth or similar material. Remove residual material with a wet cloth or mop. Dispose of rinse water consistent with national,

regional, and municipal regulations SECTION 7 - Handling and Storage

Precautions Do not expose to excessive temperatures. Avoid contacting the material with skin or clothing. Store away from incompatible materials such as strong bases.

Store material at room temperature in a dry, well ventilated environment. Do not heat above 100°F/38°C, or cool below 32°F/0°C. Keep container tightly closed

when not in use.

SECTION 8 - Exposure Controls / Personal Protection

Engineering Ensure adequate ventilation in the working area to Controls prevent build-up of vapors. General Hygiene Avoid contacting the material with skin. Avoid contact

with eyes, Avoid ingesting. Wash hands after handling. Measures Respiratory Not Applicable

Protection: Hand Protection: Protective gloves (nitrile)

Eye Protection: Protective glasses.

12/1/2014 2:22:15 PM

PRINT SPECS


Project: BlissEtch SDS, Cover

Finished Size: 17" wide x 6" high, folds to 4.25" wide x 6" high

Ink Colors: black DO NOT PRINT THESE MARKS - FOR REFERENCE ONLY

Red dotted line indicates SCORE/FOLD - - -Paper Stock: 75 grams white non-glossy - - - Green dotted line indicates CUT - - -Finishing: accordion fold, 4-panels

MSD-000003 v.12.14.01





PRINT SPECS

Project: BlissEtch SDS, Inside

Finished Size: 17" wide x 6" high, folds to 4.25" wide x 6" high

Ink Colors: black DO NOT PRINT THESE MARKS - FOR REFERENCE ONLY

Red dotted line indicates SCORE/FOLD

Paper Stock: 75 grams white non-glossy

- Green dotted line indicates CUT Finishing: accordion fold, 4-panels

MSD-000003 v. 12.14.01

Obtained by Global Safety Management, www.globalsafetynet.com, (877) 683-7460