

SAFETY DATA SHEETS

This SDS packet was issued with item:

075773833

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

075015623 075015649 075773411 075773601 075773791 075793914 075793955 075794037 079563330 273014404

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

075015656 075769542 075793922



Material Safety Data Sheet

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

PRODUCT NAME: 3M™ ESPE™ IMPREGUM PENTA SOFT/ IMPREGUM PENTA SOFT MB/
IMPREGUM PENTA SOFT HB/ IMPREGUM GARANT L DUOSOFT/
IMPREGUM GARANT SOFT LB PLUS ADHESIVE

MANUFACTURER: 3M

DIVISION: 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 02/10/12

Supersedes Date: 02/10/12

Document Group: 16-5656-0

ID Number(s):

70-2011-3279-5, 70-2011-3411-4, 70-2011-3797-6

This product is a kit or a multipart product which consists of multiple, independently packaged components. An MSDS for each of these components is included. Please do not separate the component MSDSs from this cover page. The document numbers of the MSDSs for components of this product are:

16-4015-0, 16-2742-1, 16-2740-5, 16-5565-3, 16-5566-1

Revision Changes:

Kit: ID Number(s) was modified.

Kit: Component document group number(s) was modified.

Page Heading: Product name was modified.

Kit: Product name was modified.

Copyright was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY

OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



Material Safety Data Sheet

Copyright, 2011, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M™ ESPE™ Impregum™ Penta™ HB Soft Base Paste

MANUFACTURER: 3M

DIVISION: 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 12/08/11

Supersedes Date: 08/30/10

Document Group: 16-2740-5

Product Use:

Intended Use: Dental Product
Limitations on Use: For use only by dental professionals
Specific Use: Impressions

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
POLYETHER	110531-92-5	50 - 60
FATTY ACID TRIGLYCERIDES	67701-27-3	15 - 25
POLYMERIC ACETATE	91825-26-2	10 - 20
DIBENZYL TOLUENE	26898-17-9	5 - 10
DIATOMACEOUS EARTH	68855-54-9	1 - 5
CRISTOBALITE	14464-46-1	1 - 5
1-DODECYLIMIDAZOLE	4303-67-7	< 1

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Different colors, characteristic odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: May cause allergic skin reaction.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Target Organ Effects:

This product contains Cristobalite (CASRN 14464-46-1). Cancer of the lungs and silicosis has been associated with cristobalite. No exposure to cristobalite is anticipated during normal intended handling of the paste or cured material and therefore, the health effects associated with cristobalite are not expected during the foreseeable use of this product.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: No need for first aid is anticipated.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature

No Data Available

Flash Point

No flash point

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)

Not Applicable

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air.

6.2. Environmental precautions

Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Collect as much of the spilled material as possible. Clean up residue.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid skin contact. Wash hands after handling and before eating. Avoid eye contact with dust or airborne particles.

7.2 STORAGE

Store away from heat. Store out of direct sunlight. Store away from areas where product may come into contact with food or pharmaceuticals.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Not applicable.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields

.

8.2.2 Skin Protection

Avoid skin contact. Avoid prolonged or repeated skin contact. Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Not applicable. Do not ingest.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
CRISTOBALITE	ACGIH	TWA, respirable fraction	0.025 mg/m ³	
CRISTOBALITE	OSHA	TWA concentration, respirable	0.05 mg/m ³	
CRISTOBALITE	OSHA	TWA concentration, as total dust	0.15 mg/m ³	
SILICA, AMORPHOUS	OSHA	TWA concentration	0.8 mg/m ³	
SILICA, AMORPHOUS	OSHA	TWA	20 millions of particles/cu. ft.	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Paste
Odor, Color, Grade:	Different colors, characteristic odor
General Physical Form:	Solid
Autoignition temperature	<i>No Data Available</i>
Flash Point	No flash point
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Boiling Point	<i>Not Applicable</i>
Vapor Density	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Specific Gravity	1.0 - 1.2 [Ref Std: WATER=1]
pH	<i>No Data Available</i>
Melting point	<i>No Data Available</i>
Solubility in Water	Nil
Evaporation rate	<i>Not Applicable</i>
Volatile Organic Compounds	<i>Not Applicable</i>
Kow - Oct/Water partition coef	<i>No Data Available</i>
Percent volatile	<i>Not Applicable</i>
VOC Less H₂O & Exempt Solvents	<i>Not Applicable</i>
Viscosity	40000 - 150000 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of waste product in a sanitary landfill. As a disposal alternative, incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, incinerate in an industrial or commercial facility.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

BA-ESPE-3173-1, LE-FSFD-3173-1

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 1: Product name was modified.

Section 1: Product use information was modified.

Section 16: Disclaimer (second paragraph) was modified.

Section 7: Handling information was modified.

Section 7: Storage information was modified.

Section 8: Skin protection phrase was modified.

Section 8: Prevention of swallowing information was modified.

Section 10: Hazardous decomposition or by-products table was modified.

Page Heading: Product name was modified.

Section 9: Vapor density value was modified.

Section 9: Vapor pressure value was modified.

Section 9: Boiling point information was modified.

Section 5: Flammable limits (UE) information was modified.

Section 5: Flammable limits (LEL) information was modified.

Section 5: Autoignition temperature information was modified.

Section 5: Flash point information was modified.

Section 9: Property description for optional properties was modified.

Section 9: Specific gravity information was modified.
Section 9: pH information was modified.
Section 9: Melting point information was modified.
Section 9: Solubility in water text was modified.
Section 9: Flash point information was modified.
Section 9: Flammable limits (LEL) information was modified.
Section 9: Flammable limits (UEL) information was modified.
Section 9: Autoignition temperature information was modified.
Section 2: Ingredient table was modified.
Section 6: 6.2. Environmental precautions heading was modified.
Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was modified.
Section 3: Other potential health effects heading was added.
Section 3: Other potential health effects was added.
Section 8: Exposure guidelines ingredient information was added.
Section 8: Exposure guidelines data source legend was added.
Section 16: Web address was added.
Section 8: Hand protection information was added.
Section 1: Address was added.
Copyright was added.
Company logo was added.
Telephone header was added.
Company Telephone was added.
Section 1: Emergency phone information was added.
Section 1: Emergency phone information was deleted.
Company Logo was deleted.
Copyright was deleted.
Section 16: Web address heading was deleted.
Section 1: Address line 1 was deleted.
Section 1: Address line 2 was deleted.
Section 8: Exposure guidelines information - none - was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



Material Safety Data Sheet

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M™ ESPE™ Impregum™ Penta™ Soft Catalyst

MANUFACTURER: 3M

DIVISION: 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 02/08/12

Supersedes Date: 05/16/08

Document Group: 16-2742-1

Product Use:

Intended Use: Dental Product
Limitations on Use: For use only by dental professionals
Specific Use: Impressions

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
CITRIC ESTER	77-90-7	35 - 50
SULFONIUM SALT	72140-65-9	15 - 30
SILANE TREATED SILICA	68909-20-6	20 - 30
DIATOMACEOUS EARTH	68855-54-9	10 - 20
CRISTOBALITE	14464-46-1	1 - 10
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 5

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Dark red color, slightly acrid odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: May cause target organ effects. This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or

ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Inhalation:

No health effects are expected. This product may have a characteristic odor; however, no adverse health effects are anticipated.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

This product contains Cristobalite (CASRN 14464-46-1). Cancer of the lungs and silicosis has been associated with cristobalite. No exposure to cristobalite is anticipated during normal intended handling of the paste or cured material and therefore, the health effects associated with cristobalite are not expected during the foreseeable use of this product.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: No need for first aid is anticipated.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature

No Data Available

Flash Point

No flash point

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)

Not Applicable

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

6.2. Environmental precautions

Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid eye contact with dust or airborne particles.

7.2 STORAGE

Store away from heat. Store out of direct sunlight.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Not applicable.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields

8.2.2 Skin Protection

Avoid skin contact. Avoid prolonged or repeated skin contact. Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Do not ingest.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
Borates	ACGIH	TWA, inhalable fraction	2 mg/m ³	
Borates	ACGIH	STEL, inhalable fraction	6 mg/m ³	
CRISTOBALITE	ACGIH	TWA, respirable fraction	0.025 mg/m ³	
CRISTOBALITE	OSHA	TWA concentration, respirable	0.05 mg/m ³	
CRISTOBALITE	OSHA	TWA concentration, as total dust	0.15 mg/m ³	
SILICA, AMORPHOUS	OSHA	TWA concentration	0.8 mg/m ³	
SILICA, AMORPHOUS	OSHA	TWA	20 millions of particles/cu. ft.	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Paste
Odor, Color, Grade:	Dark red color, slightly acrid odor
General Physical Form:	Solid
Autoignition temperature	<i>No Data Available</i>
Flash Point	No flash point
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Boiling Point	<i>Not Applicable</i>
Vapor Density	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Specific Gravity	1.1 - 1.4 [Ref Std: WATER=1]
pH	<i>No Data Available</i>
Melting point	<i>No Data Available</i>

Solubility in Water	Nil
Evaporation rate	Not Applicable
Volatile Organic Compounds	Not Applicable
Kow - Oct/Water partition coef	No Data Available
Percent volatile	Not Applicable
VOC Less H2O & Exempt Solvents	Not Applicable
Viscosity	No Data Available

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance

Irritant Vapors or Gases

Condition

During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of completely cured (or polymerized) wastes in a sanitary landfill.

Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

CA-ESPE-3173-1, LE-FSFD-3173-8

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 1: Product name was modified.

Section 1: Product use information was modified.

Section 16: Disclaimer (second paragraph) was modified.

Section 3: Potential effects from eye contact was modified.

Section 3: Potential effects from skin contact information was modified.

Section 3: Potential effects from inhalation information was modified.

Section 3: Potential effects from ingestion information was modified.

Section 7: Handling information was modified.

Section 8: Engineering controls information was modified.
Section 8: Skin protection phrase was modified.
Section 8: Prevention of swallowing information was modified.
Section 10: Hazardous decomposition or by-products table was modified.
Section 13: Waste disposal method information was modified.
Section 8: Eye/face protection information was modified.
Section 4: First aid for skin contact - decontamination - was modified.
Section 4: First aid for skin contact - medical assistance - was modified.
Section 14: Transportation legal text was modified.
Page Heading: Product name was modified.
Section 9: Vapor density value was modified.
Section 9: Vapor pressure value was modified.
Section 9: Boiling point information was modified.
Section 5: Flammable limits (UE) information was modified.
Section 5: Flammable limits (LEL) information was modified.
Section 5: Autoignition temperature information was modified.
Section 5: Flash point information was modified.
Section 9: Property description for optional properties was modified.
Section 9: Specific gravity information was modified.
Section 9: pH information was modified.
Section 9: Melting point information was modified.
Section 9: Solubility in water text was modified.
Section 9: Flash point information was modified.
Section 9: Flammable limits (LEL) information was modified.
Section 9: Flammable limits (UEL) information was modified.
Section 9: Autoignition temperature information was modified.
Section 2: Ingredient table was modified.
Section 8: Exposure guidelines ingredient information was modified.
Section 3: Other potential health effects heading was added.
Section 4: First aid for skin contact - termination of exposure - was added.
Section 4: First aid for skin contact - handling - was added.
Section 4: First aid for ingestion (swallowing) - decontamination - was added.
Section 4: First aid for ingestion (swallowing) - intervention - was added.
Section 4: First aid for ingestion (swallowing) - medical assistance - was added.
Section 3: Immediate other hazard(s) was added.
Section 3: Other health effects information was added.
Section 3: Other potential health effects was added.
Section 6: 6.2. Environmental precautions heading was added.
Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was added.
Section 10.1 Conditions to avoid heading was added.
Section 10.2 Materials to avoid heading was added.
Section 16: Web address was added.
Section 6: Personal precautions information was added.
Section 6: Environmental procedures information was added.
Section 6: Methods for cleaning up information was added.
Section 10: Materials to avoid physical property was added.
Section 10: Conditions to avoid physical property was added.
Section 8: Hand protection information was added.
Section 1: Address was added.
Copyright was added.
Company logo was added.
Section 6: Clean-up methods heading was added.
Telephone header was added.
Company Telephone was added.
Section 1: Emergency phone information was added.
Section 1: Emergency phone information was deleted.

Company Logo was deleted.

Copyright was deleted.

Section 16: Web address heading was deleted.

Section 3: Immediate physical hazard(s) comment was deleted.

Section 6: Release measures information was deleted.

Section 6: Release measures heading was deleted.

Section 10: Materials and conditions to avoid physical property was deleted.

Section 1: Address line 1 was deleted.

Section 1: Address line 2 was deleted.

Section 4: First aid for ingestion (swallowing) - none - was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



Material Safety Data Sheet

Copyright, 2011, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 30601 POLYETHER ADHESIVE - 17 ML BOTTLE (NA)
MANUFACTURER: 3M
DIVISION: 3M ESPE Dental Products

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 03/02/11
Supersedes Date: 04/09/10

Document Group: 16-4015-0

Product Use:

Intended Use: Dental Product
Limitations on Use: For use only by dental professionals.
Specific Use: Used in impressioning systems.

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
ETHYL ACETATE	141-78-6	25 - 50
HEPTANE	142-82-5	25 - 35
ACETONE	67-64-1	5 - 15
METHYLCYCLOHEXANE	108-87-2	5 - 10
FORMALDEHYDE, POLYMER WITH 1,3-BENZENEDIOL AND 4-(1,1-DIMETHYLETHYL)PHENOL	59633-97-5	0 - 5
POLYCHLOROPRENE	9010-98-4	0 - 5

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Liquid

Odor, Color, Grade: Blue in color, characteristic solvent odor.

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause target organ effects. This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature	No Data Available
Flash Point	30 °F [Test Method: Closed Cup]
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard.

6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with detergent and water. Seal the container.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact. Contents may be under pressure, open carefully. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid skin contact.

7.2 STORAGE

Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Keep container tightly closed.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use in an enclosed process area is recommended. Use in a well-ventilated area. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

The following eye protection(s) are recommended: Safety Glasses with side shields

.

8.2.2 Skin Protection

Avoid skin contact.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Not applicable. Do not ingest.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
ACETONE	ACGIH	TWA	500 ppm	
ACETONE	ACGIH	STEL	750 ppm	
ACETONE	OSHA	TWA	2400 mg/m3	
ETHYL ACETATE	ACGIH	TWA	400 ppm	
ETHYL ACETATE	OSHA	TWA	1400 mg/m3	
HEPTANE	OSHA	TWA	2000 mg/m3	
Heptane, all isomers	ACGIH	TWA	400 ppm	
Heptane, all isomers	ACGIH	STEL	500 ppm	
METHYLCYCLOHEXANE	ACGIH	TWA	400 ppm	

METHYLCYCLOHEXANE

OSHA

TWA

2000 mg/m3

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Liquid
Odor, Color, Grade:	Blue in color, characteristic solvent odor.
General Physical Form:	Liquid
Autoignition temperature	No Data Available
Flash Point	30 °F [Test Method: Closed Cup]
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Boiling Point	133 °F
Density	No Data Available
Vapor Density	2 - 4 [Ref Std: AIR=1]
Vapor Pressure	180 mmHg
Specific Gravity	0.8 - 0.9 [Ref Std: WATER=1]
pH	No Data Available
Melting point	No Data Available
Solubility in Water	Moderate
Evaporation rate	Approximately 1 [Ref Std: BUOAC=1]
Volatile Organic Compounds	No Data Available
Kow - Oct/Water partition coef	No Data Available
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	No Data Available
Viscosity	40000 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat

Sparks and/or flames

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number(s):

70-2011-0648-4, 70-2011-0895-1, 70-2011-0997-5

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
HEPTANE (Heptane)	142-82-5	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable
HEPTANE	142-82-5	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 1 **Flammability:** 3 **Reactivity:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Copyright was modified.

Section 3: Potential effects from inhalation information was modified.

Section 3: Potential effects from ingestion information was modified.

Section 14: Transportation legal text was modified.

Section 9: Boiling point information was modified.

Section 5: Flammable limits (UE) information was modified.

Section 5: Flammable limits (LEL) information was modified.

Section 9: Flammable limits (LEL) information was modified.

Section 9: Flammable limits (UEL) information was modified.

Section 2: Ingredient table was modified.

Section 8: Exposure guidelines ingredient information was modified.

Section 15: TSCA section 12[b] information was modified.

Section 6: Methods for cleaning up information was modified.

Section 3: Immediate other hazard(s) was added.

Section 6: 6.2. Environmental precautions heading was added.

Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was added.

Section 6: Clean-up methods heading was added.

Section 6: Release measures heading was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com



Material Safety Data Sheet

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB BASE

MANUFACTURER: 3M

DIVISION: 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 12/10/12

Supersedes Date: 02/07/12

Document Group: 16-5565-3

Product Use:

Intended Use: Dental Product
Limitations on Use: For use only by dental professionals
Specific Use: Impression

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
POLYETHER	110531-92-5	75 - 85
FATTY ACIDS TRIGLYCERIDES	67701-27-3	1 - 10
DIATOMACEOUS EARTH	68855-54-9	1 - 10
DIBENZYL TOLUENE	26898-17-9	1 - 10
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 5
C.I. PIGMENT WHITE 5	1345-05-7	1 - 5
1-DODECYLIMIDAZOLE	4303-67-7	< 1

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Orange colored pastes, characteristic odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: No immediate health, physical, or environmental hazards are anticipated.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: No need for first aid is anticipated.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature

Not Applicable

Flash Point

No flash point

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)

Not Applicable

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: During a fire irritating gases may develop.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air.

6.2. Environmental precautions

Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities.

Dispose of collected material as soon as possible.

Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Collect as much of the spilled material as possible. Clean up residue with detergent and water.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE**7.1 HANDLING**

Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid prolonged or repeated skin contact.

7.2 STORAGE

Store away from heat.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 ENGINEERING CONTROLS**

Use with appropriate local exhaust ventilation. Not applicable.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**8.2.1 Eye/Face Protection**

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields

.

8.2.2 Skin Protection

Avoid prolonged or repeated skin contact. Gloves not normally required.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Do not ingest.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
BARIUM, SOLUBLE COMPOUNDS	ACGIH	TWA, as Ba	0.5 mg/m3	
BARIUM, SOLUBLE COMPOUNDS	OSHA	TWA, as Ba	0.5 mg/m3	
SILICA, AMORPHOUS	OSHA	TWA concentration	0.8 mg/m3	
SILICA, AMORPHOUS	OSHA	TWA	20 millions of	

particles/cu. ft.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Paste
Odor, Color, Grade:	Orange colored pastes, characteristic odor
General Physical Form:	Solid
Autoignition temperature	<i>Not Applicable</i>
Flash Point	No flash point
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Boiling Point	<i>Not Applicable</i>
Density	1 g/cm ³ - 1.2 g/cm ³
Vapor Density	<i>Not Applicable</i>
Vapor Pressure	<i>No Data Available</i>
Specific Gravity	1 - 1.2 [<i>Ref Std: WATER=1</i>]
pH	<i>Not Applicable</i>
Melting point	<i>Not Applicable</i>
Solubility in Water	Negligible
Evaporation rate	<i>Not Applicable</i>
Volatile Organic Compounds	<i>No Data Available</i>
Kow - Oct/Water partition coef	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H₂O & Exempt Solvents	<i>No Data Available</i>
Viscosity	40 Pa-s - 150 Pa-s

SECTION 10: STABILITY AND REACTIVITY**Stability:** Stable.**Materials and Conditions to Avoid:****10.1 Conditions to avoid**

Heat

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Cure (harden, set, or react) the product according to product instructions.

Dispose of completely cured (or polymerized) wastes in a sanitary landfill.

As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator in the presence of a combustible material.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

LE-FSFD-3061-2

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
C.I. PIGMENT WHITE 5 (Barium compounds, except barium sulfate)	1345-05-7	1 - 5
C.I. PIGMENT WHITE 5 (ZINC COMPOUNDS)	1345-05-7	1 - 5

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 2: Ingredient table was modified.

Section 15: EPCRA 313 information was added.

Section 15: EPCRA 313 text was added.

Section 8: Exposure guidelines ingredient information was added.

Section 8: Exposure guidelines information - none - was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



Material Safety Data Sheet

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB CATALYST

MANUFACTURER: 3M

DIVISION: 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 02/07/12

Supersedes Date: 02/10/10

Document Group: 16-5566-1

Product Use:

Intended Use: Dental Product
Limitations on Use: For use only by dental professionals
Specific Use: Impression

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
POLYMERIC ACETATE	91825-26-2	25 - 35
DIATOMACEOUS EARTH	68855-54-9	20 - 30
CITRIC ESTER	77-90-7	10 - 20
SULFONIUM SALT	72140-65-9	10 - 20
DIBENZYL TOLUENE	26898-17-9	1 - 10
SILANE TREATAD SILICA	68909-20-6	1 - 10
FATTY ACIDS TRIGLYCERIDES	67701-27-3	1 - 5
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 5

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Red colored pastes, slightly acrid odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: May cause target organ effects.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention. No need for first aid is anticipated.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature

Not Applicable

Flash Point

No flash point

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)

Not Applicable

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: No unusual fire or explosion hazards are anticipated.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air.

6.2. Environmental precautions

Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Collect as much of the spilled material as possible. Clean up residue.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid prolonged or repeated skin contact.

7.2 STORAGE

Store away from heat.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Not applicable.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields

.

8.2.2 Skin Protection

Avoid prolonged or repeated skin contact. Gloves not normally required.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Do not ingest.

8.3 EXPOSURE GUIDELINES

None Established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Paste
Odor, Color, Grade:	Red colored pastes, slightly acrid odor
General Physical Form:	Solid
Autoignition temperature	<i>Not Applicable</i>
Flash Point	No flash point
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Boiling Point	<i>Not Applicable</i>
Density	1.1 g/cm ³ - 1.2 g/cm ³
Vapor Density	<i>No Data Available</i>
Vapor Pressure	<i>No Data Available</i>
Specific Gravity	1.1 - 1.2 [Ref Std: WATER=1]
pH	<i>Not Applicable</i>
Melting point	<i>No Data Available</i>
Solubility in Water	Negligible
Evaporation rate	<i>Not Applicable</i>
Volatile Organic Compounds	<i>Not Applicable</i>
Kow - Oct/Water partition coef	<i>No Data Available</i>
Percent volatile	<i>Not Applicable</i>
VOC Less H₂O & Exempt Solvents	<i>Not Applicable</i>
Viscosity	<i>No Data Available</i>

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:**10.1 Conditions to avoid**

Heat

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion

Irritant Vapors or Gases

During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Cure (harden, set, or react) the product according to product instructions.

Dispose of completely absorbed waste product in a sanitary landfill. As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator in the presence of a combustible material.

Combustion products will include HF. Facility must be capable of handling halogenated materials.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

LE-FSFD-6306-1

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the

FDA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 1: Product use information was modified.
Section 16: Disclaimer (second paragraph) was modified.
Section 10: Hazardous decomposition or by-products table was modified.
Section 8: Eye/face protection information was modified.
Section 14: Transportation legal text was modified.
Section 9: Vapor density value was modified.
Section 9: Vapor pressure value was modified.
Section 9: Boiling point information was modified.
Section 5: Flammable limits (UE) information was modified.
Section 5: Flammable limits (LEL) information was modified.
Section 5: Autoignition temperature information was modified.
Section 5: Flash point information was modified.
Section 9: Property description for optional properties was modified.
Section 9: Specific gravity information was modified.
Section 9: pH information was modified.
Section 9: Melting point information was modified.
Section 9: Solubility in water text was modified.
Section 9: Flash point information was modified.
Section 9: Flammable limits (LEL) information was modified.
Section 9: Flammable limits (UEL) information was modified.
Section 9: Autoignition temperature information was modified.
Section 2: Ingredient table was modified.
Section 10: Materials to avoid physical property was modified.
Section 10: Conditions to avoid physical property was modified.
Section 9: Density information was added.
Section 6: 6.2. Environmental precautions heading was added.
Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was added.
Section 16: Web address was added.
Section 1: Address was added.
Copyright was added.
Company logo was added.
Section 6: Clean-up methods heading was added.
Telephone header was added.

Company Telephone was added.

Section 1: Emergency phone information was added.

Section 1: Emergency phone information was deleted.

Company Logo was deleted.

Copyright was deleted.

Section 16: Web address heading was deleted.

Section 6: Release measures heading was deleted.

Section 1: Address line 1 was deleted.

Section 1: Address line 2 was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	16-5656-0	Version Number:	8.01
Issue Date:	02/24/15	Supersedes Date:	02/10/12

Product identifier

3M™ ESPE™ IMPREGUM PENTA SOFT/ IMPREGUM PENTA SOFT MB/ IMPREGUM PENTA SOFT HB/ IMPREGUM GARANT L DUOSOFT/ IMPREGUM GRARANT SOFT LB PLUS ADHESIVE

ID Number(s):

70-2011-3411-4, 70-2011-3797-6

Recommended use

Dental Material, IMPRESSIONS

Restrictions on use

For use only by dental professionals

Supplier's details

MANUFACTURER:	3M
DIVISION:	3M ESPE Dental Products
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

16-4015-0, 16-2742-1, 16-5565-3, 16-5566-1, 16-2740-5

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 16-5565-3
Issue Date: 11/02/16

Version Number: 5.00
Supersedes Date: 02/25/16

SECTION 1: Identification

1.1. Product identifier

IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB BASE Paste

Product Identification Numbers

LE-FSFD-3061-2

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression material

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Oral Care Solutions Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1A.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms**Hazard Statements**

Causes eye irritation.

May cause an allergic skin reaction.

Precautionary Statements**Prevention:**

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
ETHYLENE OXIDE TETRAMETHYLENE OXIDE COPOLYMER	110531-92-5	70 - 90 Trade Secret *
DIATOMACEOUS EARTH	68855-54-9	1 - 10 Trade Secret *
DIBENZYL TOLUENE	26898-17-9	1 - 10 Trade Secret *
FATTY ACIDS TRIGLYCERIDES	67701-27-3	1 - 10 Trade Secret *
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 10 Trade Secret *
ACETYL TRIBUTYL CITRATE	77-90-7	1 - 5 Trade Secret *
C.I. PIGMENT WHITE 5	1345-05-7	1 - 5 Trade Secret *
CRISTOBALITE	14464-46-1	1 - 5 Trade Secret *
1-DODECYLIMIDAZOLE	4303-67-7	< 1
Mentha arvensis, ext.	90063-97-1	< 0.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
BARIUM, SOLUBLE COMPOUNDS	1345-05-7	OSHA	TWA(as Ba):0.5 mg/m ³	
BARIUM, SOLUBLE COMPOUNDS	1345-05-7	ACGIH	TWA(as Ba):0.5 mg/m ³	A4: Not class. as human carcin
CRISTOBALITE	14464-46-1	OSHA	TWA concentration(respirable):0.05 mg/m ³ (1.2 millions of particles/cu. ft.);TWA:0.05 mg/m ³	
CRISTOBALITE	14464-46-1	ACGIH	TWA(respirable fraction):0.025 mg/m ³	A2: Suspected human carcin.
SILICA, AMORPHOUS	68855-54-9	OSHA	TWA concentration:0.8 mg/m ³ ;TWA:20 millions of particles/cu. ft.	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	characteristic odor, Orange colored pastes
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>Not Applicable</i>
Boiling Point	<i>Not Applicable</i>
Flash Point	No flash point
Evaporation rate	<i>Not Applicable</i>
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>No Data Available</i>
Vapor Density	<i>Not Applicable</i>
Density	1 g/cm ³ - 1.2 g/cm ³
Specific Gravity	1 - 1.2 [Ref Std: WATER=1]
Solubility in Water	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H₂O & Exempt Solvents	<i>No Data Available</i>

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

May be harmful in contact with skin.

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>CAS No.</u>	<u>Class Description</u>	<u>Regulation</u>
SILICA, CRYSTALLINE	14464-46-1	Known human carcinogen	National Toxicology Program Carcinogens
SILICA, CRYSTALLINE	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYSTALLINE	68855-54-9	Known human carcinogen	National Toxicology Program Carcinogens
CRISTOBALITE	14464-46-1	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
ETHYLENE OXIDE TETRAMETHYLENE OXIDE COPOLYMER	Dermal	Professional judgement	LD50 Not applicable
ETHYLENE OXIDE TETRAMETHYLENE OXIDE COPOLYMER	Ingestion	Rat	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Dermal	Rabbit	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Ingestion	Rat	LD50 > 10,360 mg/kg
FATTY ACIDS TRIGLYCERIDES	Dermal	Rabbit	LD50 > 2,000 mg/kg
FATTY ACIDS TRIGLYCERIDES	Ingestion	Rat	LD50 > 2,000 mg/kg
CRISTOBALITE	Dermal		LD50 estimated to be > 5,000 mg/kg
CRISTOBALITE	Ingestion		LD50 estimated to be > 5,000 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Ingestion	Rat	LD50 5,700 mg/kg
DIATOMACEOUS EARTH	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
DIATOMACEOUS EARTH	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.7 mg/l
DIATOMACEOUS EARTH	Ingestion	Rat	LD50 > 2,000 mg/kg
C.I. PIGMENT WHITE 5	Ingestion	Rat	LD50 > 15,000 mg/kg
C.I. PIGMENT WHITE 5	Dermal	similar compounds	LD50 > 1,000 mg/kg
C.I. PIGMENT WHITE 5	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 2.52 mg/l
ACETYL TRIBUTYL CITRATE	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
ACETYL TRIBUTYL CITRATE	Ingestion	Rat	LD50 > 25,000 mg/kg
1-DODECYLIMIDAZOLE	Ingestion	Rat	LD50 641 mg/kg
Mentha arvensis, ext.	Dermal	Rabbit	LD50 > 5,000 mg/kg
Mentha arvensis, ext.	Ingestion	Rat	LD50 1,240 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
ETHYLENE OXIDE TETRAMETHYLENE OXIDE COPOLYMER	Rabbit	No significant irritation
CRISTOBALITE	Professional judgement	No significant irritation
DIATOMACEOUS EARTH	In vitro data	No significant irritation
1-DODECYLIMIDAZOLE	Rabbit	Mild irritant
Mentha arvensis, ext.	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
ETHYLENE OXIDE TETRAMETHYLENE OXIDE COPOLYMER	Rabbit	Moderate irritant
DIATOMACEOUS EARTH	Rabbit	Mild irritant
1-DODECYLIMIDAZOLE	In vitro data	Severe irritant
Mentha arvensis, ext.	In vitro data	Severe irritant

Skin Sensitization

Name	Species	Value
ETHYLENE OXIDE TETRAMETHYLENE OXIDE COPOLYMER	Guinea pig	Not sensitizing
DIATOMACEOUS EARTH	Mouse	Not sensitizing
1-DODECYLIMIDAZOLE	Mouse	Sensitizing
Mentha arvensis, ext.	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
ETHYLENE OXIDE TETRAMETHYLENE OXIDE COPOLYMER	In Vitro	Not mutagenic
CRISTOBALITE	In Vitro	Some positive data exist, but the data are not sufficient for classification
CRISTOBALITE	In vivo	Some positive data exist, but the data are not sufficient for classification
DIATOMACEOUS EARTH	In Vitro	Some positive data exist, but the data are not sufficient for classification
1-DODECYLIMIDAZOLE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
CRISTOBALITE	Inhalation	Human and animal	Carcinogenic
DIATOMACEOUS EARTH	Inhalation	Human and animal	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
CRISTOBALITE	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
DIATOMACEOUS EARTH	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

DIATOMACEOUS EARTH	Ingestion	hematopoietic system eyes kidney and/or bladder	All data are negative	Rat	NOAEL 3,738 mg/kg/day	90 days
--------------------	-----------	---	-----------------------	-----	-----------------------------	---------

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
C.I. PIGMENT WHITE 5 (Barium compounds, except barium sulfate)	1345-05-7	1 - 5
C.I. PIGMENT WHITE 5 (ZINC COMPOUNDS)	1345-05-7	1 - 5

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 16-5565-3
Issue Date: 11/02/16

Version Number: 5.00
Supersedes Date: 02/25/16

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	16-5566-1	Version Number:	6.00
Issue Date:	02/25/16	Supersedes Date:	12/16/14

SECTION 1: Identification

1.1. Product identifier

IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB CATALYST

Product Identification Numbers

LE-FSFD-6306-1

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Oral Care Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

2.2. Label elements

Signal word

Warning

Symbols

Not applicable

Pictograms

Not applicable

Hazard Statements

Causes eye irritation.

Precautionary Statements**Prevention:**

Wash thoroughly after handling.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
POLYMERIC ACETATE	91825-26-2	25 - 35 Trade Secret *
DIATOMACEOUS EARTH	68855-54-9	20 - 30 Trade Secret *
CITRIC ESTER	77-90-7	10 - 20 Trade Secret *
SULFONIUM SALT	72140-65-9	10 - 20 Trade Secret *
DIBENZYL TOLUENE	26898-17-9	1 - 10 Trade Secret *
SILANE TREATAD SILICA	68909-20-6	1 - 10 Trade Secret *
FATTY ACIDS TRIGLYCERIDES	67701-27-3	1 - 5 Trade Secret *
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

No need for first aid is anticipated.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

No need for first aid is anticipated.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide

Carbon dioxide

Irritant Vapors or Gases

Condition

During Combustion

During Combustion

During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid eye contact. Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

Respiratory protection is not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	slightly characteristic odor, red colored pastes
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>No Data Available</i>
Boiling Point	<i>Not Applicable</i>
Flash Point	Flash point > 93 °C (200 °F)
Evaporation rate	<i>Not Applicable</i>
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>No Data Available</i>
Vapor Density	<i>No Data Available</i>
Density	1.1 g/cm ³ - 1.2 g/cm ³
Specific Gravity	1.1 - 1.2 [Ref Std: WATER=1]
Solubility in Water	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	<i>Not Applicable</i>
Percent volatile	<i>Not Applicable</i>
VOC Less H ₂ O & Exempt Solvents	<i>Not Applicable</i>

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Amines

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

No known health effects.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTAL AIRRESP	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYSTAL AIRRESP	68855-54-9	Known human carcinogen	National Toxicology Program Carcinogens

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
POLYMERIC ACETATE	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
POLYMERIC ACETATE	Ingestion	Rat	LD50 > 2,000 mg/kg
DIATOMACEOUS EARTH	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
DIATOMACEOUS EARTH	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.7 mg/l
DIATOMACEOUS EARTH	Ingestion	Rat	LD50 > 2,000 mg/kg
CITRIC ESTER	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
CITRIC ESTER	Ingestion	Rat	LD50 > 25,000 mg/kg
SULFONIUM SALT	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
SULFONIUM SALT	Ingestion	Rat	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Dermal	Rabbit	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Ingestion	Rat	LD50 > 10,360 mg/kg
SILANE TREATMENT SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATMENT SILICA	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
SILANE TREATMENT SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Ingestion	Rat	LD50 5,700 mg/kg
FATTY ACIDS TRIGLYCERIDES	Dermal	Rabbit	LD50 > 2,000 mg/kg
FATTY ACIDS TRIGLYCERIDES	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
DIATOMACEOUS EARTH	In vitro data	No significant irritation
SULFONIUM SALT	Rabbit	Mild irritant
SILANE TREATMENT SILICA	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
-------------	----------------	--------------

DIATOMACEOUS EARTH	Rabbit	Mild irritant
SULFONIUM SALT	similar health hazards	Moderate irritant
SILANE TREATAD SILICA	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
DIATOMACEOUS EARTH	Mouse	Not sensitizing
SILANE TREATAD SILICA	Human and animal	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
POLYMERIC ACETATE	In Vitro	Not mutagenic
DIATOMACEOUS EARTH	In Vitro	Some positive data exist, but the data are not sufficient for classification
SULFONIUM SALT	In Vitro	Not mutagenic
SILANE TREATAD SILICA	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
DIATOMACEOUS EARTH	Inhalation	Human and animal	Carcinogenic
SILANE TREATAD SILICA	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
SILANE TREATAD SILICA	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATAD SILICA	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SILANE TREATAD SILICA	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SULFONIUM SALT	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 2,000 mg/kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
DIATOMACEOUS EARTH	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
DIATOMACEOUS EARTH	Ingestion	hematopoietic system eyes	All data are negative	Rat	NOAEL 3,738	90 days

		kidney and/or bladder			mg/kg/day	
SILANE TREATMENT SILICA	Inhalation	respiratory system silicosis	All data are negative	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

California Proposition 65**Ingredient**

SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)

C.A.S. No.

None

Classification

Carcinogen

WARNING: This product contains a chemical known to the State of California to cause cancer.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	16-5566-1	Version Number:	6.00
Issue Date:	02/25/16	Supersedes Date:	12/16/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 16-2740-5
Issue Date: 01/21/16

Version Number: 12.00
Supersedes Date: 01/21/16

SECTION 1: Identification

1.1. Product identifier

3M™ ESPE™ Impregum™ Penta™ Soft Base Paste

Product Identification Numbers

BA-ESPE-3173-1, LE-FSFD-3173-1

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression material

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Oral Care Solutions Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1A.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements

Causes eye irritation.

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
POLYETHER	110531-92-5	40 - 60 Trade Secret *
FATTY ACID TRIGLYCERIDES	67701-27-3	10 - 30 Trade Secret *
POLYMERIC ACETATE	91825-26-2	1 - 20 Trade Secret *
DIBENZYL TOLUENE	26898-17-9	1 - 10 Trade Secret *
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	68855-54-9	1 - 10 Trade Secret *
1-DODECYLIMIDAZOLE	4303-67-7	< 0.7
Mentha arvensis, ext.	90063-97-1	< 0.2

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid

contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Cristobalite	68855-54-9	ACGIH	TWA(respirable fraction):0.025 mg/m ³	A2: Suspected human carcin.
Cristobalite	68855-54-9	OSHA	TWA concentration(as total dust):0.15 mg/m ³ ;TWA concentration(respirable):0.05 mg/m ³ (1.2 millions of particles/cu. ft.)	
SILICA, AMORPHOUS	68855-54-9	OSHA	TWA concentration:0.8 mg/m ³ ;TWA:20 millions of particles/cu. ft.	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	paste with different colors and mint odor
Odor threshold	<i>No Data Available</i>
pH	<i>No Data Available</i>
Melting point	<i>No Data Available</i>
Boiling Point	<i>Not Applicable</i>
Flash Point	No flash point
Evaporation rate	<i>Not Applicable</i>
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Vapor Density	<i>Not Applicable</i>
Specific Gravity	1.0 - 1.2 [Ref Std: WATER=1]
Solubility in Water	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Volatile Organic Compounds	<i>Not Applicable</i>
Percent volatile	<i>Not Applicable</i>
VOC Less H2O & Exempt Solvents	<i>Not Applicable</i>

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient

classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

May be harmful in contact with skin.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>CAS No.</u>	<u>Class Description</u>	<u>Regulation</u>
SILICA, CRYSTAL AIRRESP	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYSTAL AIRRESP	68855-54-9	Known human carcinogen	National Toxicology Program Carcinogens
Generic: Cristobalite	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

<u>Name</u>	<u>Route</u>	<u>Species</u>	<u>Value</u>
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
POLYETHER	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
POLYETHER	Ingestion	Rat	LD50 > 2,000 mg/kg
FATTY ACID TRIGLYCERIDES	Dermal	Rabbit	LD50 > 2,000 mg/kg

FATTY ACID TRIGLYCERIDES	Ingestion	Rat	LD50 > 2,000 mg/kg
POLYMERIC ACETATE	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
POLYMERIC ACETATE	Ingestion	Rat	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Dermal	Rabbit	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Ingestion	Rat	LD50 > 10,360 mg/kg
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.7 mg/l
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Ingestion	Rat	LD50 > 2,000 mg/kg
1-DODECYLIMIDAZOLE	Ingestion	Rat	LD50 641 mg/kg
Mentha arvensis, ext.	Dermal	Rabbit	LD50 > 5,000 mg/kg
Mentha arvensis, ext.	Ingestion	Rat	LD50 1,240 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
POLYETHER	Rabbit	No significant irritation
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	In vitro data	No significant irritation
1-DODECYLIMIDAZOLE	Rabbit	Mild irritant
Mentha arvensis, ext.	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
POLYETHER	Rabbit	Moderate irritant
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Rabbit	Mild irritant
1-DODECYLIMIDAZOLE	In vitro data	Severe irritant
Mentha arvensis, ext.	In vitro data	Severe irritant

Skin Sensitization

Name	Species	Value
POLYETHER	Guinea pig	Not sensitizing
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Mouse	Not sensitizing
1-DODECYLIMIDAZOLE	Mouse	Sensitizing
Mentha arvensis, ext.	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
POLYETHER	In Vitro	Not mutagenic
POLYMERIC ACETATE	In Vitro	Not mutagenic
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	In Vitro	Some positive data exist, but the data are not sufficient for classification
1-DODECYLIMIDAZOLE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
------	-------	---------	-------

Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation	Human and animal	Carcinogenic
--	------------	------------------	--------------

Reproductive Toxicity

Reproductive and/or Developmental Effects

For the component/components, either no data are currently available or the data are not sufficient for classification.

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Ingestion	hematopoietic system eyes kidney and/or bladder	All data are negative	Rat	NOAEL 3,738 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	16-2740-5	Version Number:	12.00
Issue Date:	01/21/16	Supersedes Date:	01/21/16

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 16-2742-1
Issue Date: 01/22/16

Version Number: 9.01
Supersedes Date: 06/19/15

SECTION 1: Identification

1.1. Product identifier

3M™ ESPE™ Impregum™ Penta™ Soft Catalyst

Product Identification Numbers

CA-ESPE-3173-1, LE-FSFD-3173-8

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impressions

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Oral Care Solutions Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

2.2. Label elements

Signal word

Warning

Symbols

Not applicable

Pictograms

Not applicable

Hazard Statements

Causes eye irritation.

Precautionary Statements**Prevention:**

Wash thoroughly after handling.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
CITRIC ESTER	77-90-7	30 - 50 Trade Secret *
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	68855-54-9	10 - 30 Trade Secret *
SILANE TREATED SILICA	68909-20-6	10 - 30 Trade Secret *
SULFONIUM SALT	72140-65-9	10 - 30 Trade Secret *
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 10 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

No need for first aid is anticipated.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Carbon dioxide

Irritant Vapors or Gases

Condition

During Combustion

During Combustion

During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid eye contact. Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Cristobalite	68855-54-9	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Cristobalite	68855-54-9	OSHA	TWA concentration(as total	

			dust):0.15 mg/m ³ ;TWA concentration(respirable):0.05 mg/m ³ (1.2 millions of particles/cu. ft.)	
SILICA, AMORPHOUS	68855-54-9	OSHA	TWA concentration:0.8 mg/m ³ ;TWA:20 millions of particles/cu. ft.	
SILICA, AMORPHOUS	68909-20-6	OSHA	TWA concentration:0.8 mg/m ³ ;TWA:20 millions of particles/cu. ft.	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	Dark red color, slightly acrid odor
Odor threshold	<i>No Data Available</i>
pH	<i>No Data Available</i>
Melting point	<i>No Data Available</i>
Boiling Point	<i>Not Applicable</i>
Flash Point	No flash point
Evaporation rate	<i>Not Applicable</i>
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Vapor Density	<i>Not Applicable</i>
Specific Gravity	1.1 - 1.4 [Ref Std: WATER=1]
Solubility in Water	Negligible

Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	No Data Available
Volatile Organic Compounds	Not Applicable
Percent volatile	Not Applicable
VOC Less H2O & Exempt Solvents	Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:**Carcinogenicity:**

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTALLINE	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYSTALLINE	68855-54-9	Known human carcinogen	National Toxicology Program Carcinogens
Generic: Cristobalite	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
CITRIC ESTER	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
CITRIC ESTER	Ingestion	Rat	LD50 > 25,000 mg/kg
SILANE TREATED SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATED SILICA	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
SILANE TREATED SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
SULFONIUM SALT	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
SULFONIUM SALT	Ingestion	Rat	LD50 > 2,000 mg/kg
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.7 mg/l
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Ingestion	Rat	LD50 > 2,000 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Ingestion	Rat	LD50 5,700 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
SILANE TREATED SILICA	Rabbit	No significant irritation
SULFONIUM SALT	Rabbit	Mild irritant
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	In vitro data	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
SILANE TREATED SILICA	Rabbit	No significant irritation
SULFONIUM SALT	similar health hazards	Moderate irritant
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
SILANE TREATED SILICA	Human and animal	Not sensitizing
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Mouse	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
SILANE TREATED SILICA	In Vitro	Not mutagenic
SULFONIUM SALT	In Vitro	Not mutagenic
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
SILANE TREATED SILICA	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation	Human and animal	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

SULFONIUM SALT	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 2,000 mg/kg	not applicable
----------------	-----------	-----------------------------------	-----------------------------------	-----	----------------------	----------------

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA	Inhalation	respiratory system silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Ingestion	hematopoietic system eyes kidney and/or bladder	All data are negative	Rat	NOAEL 3,738 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	16-2742-1	Version Number:	9.01
Issue Date:	01/22/16	Supersedes Date:	06/19/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	16-4015-0	Version Number:	16.00
Issue Date:	02/25/16	Supersedes Date:	10/09/14

SECTION 1: Identification

1.1. Product identifier

30601 POLYETHER ADHESIVE - 17 ML BOTTLE (NA)

Product Identification Numbers

70-2011-0895-1, 70-2011-0997-5

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Used in impressioning systems.

Restrictions on use

For use only by dental professionals.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Oral Care Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2A.

Specific Target Organ Toxicity (central nervous system): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark |

Pictograms**Hazard Statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Precautionary Statements**Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Keep container tightly closed.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
ETHYL ACETATE	141-78-6	25 - 50 Trade Secret *
HEPTANE	142-82-5	25 - 35 Trade Secret *
ACETONE	67-64-1	5 - 15 Trade Secret *
METHYLCYCLOHEXANE	108-87-2	5 - 10 Trade Secret *
FORMALDEHYDE, POLYMER WITH 1,3-BENZENEDIOL AND 4-(1,1-	59633-97-5	0 - 5 Trade Secret *

DIMETHYLETHYLPHENOL		
POLYCHLOROPRENE	9010-98-4	0 - 5 Trade Secret *
CYCLOHEXANE	110-82-7	0 - 0.5 Trade Secret *
ZINC OXIDE	1314-13-2	0 - 0.2 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
METHYLCYCLOHEXANE	108-87-2	ACGIH	TWA:400 ppm	
METHYLCYCLOHEXANE	108-87-2	OSHA	TWA:2000 mg/m3(500 ppm)	
CYCLOHEXANE	110-82-7	ACGIH	TWA:100 ppm	
CYCLOHEXANE	110-82-7	OSHA	TWA:1050 mg/m3(300 ppm)	
ZINC OXIDE	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m3;STEL(respirable fraction):10 mg/m3	
ZINC OXIDE	1314-13-2	OSHA	TWA(as fume):5 mg/m3;TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
ETHYL ACETATE	141-78-6	ACGIH	TWA:400 ppm	
ETHYL ACETATE	141-78-6	OSHA	TWA:1400 mg/m3(400 ppm)	
HEPTANE	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
HEPTANE	142-82-5	OSHA	TWA:2000 mg/m3(500 ppm)	
ACETONE	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human carcin
ACETONE	67-64-1	OSHA	TWA:2400 mg/m3(1000 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Liquid
Odor, Color, Grade:	Blue in color, characteristic solvent odor.
Odor threshold	<i>No Data Available</i>
pH	<i>No Data Available</i>
Melting point	<i>No Data Available</i>
Boiling Point	133 °F
Flash Point	30 °F [<i>Test Method:</i> Closed Cup]
Evaporation rate	Approximately 1 [<i>Ref Std:</i> BUOAC=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	180 mmHg
Vapor Density	2 - 4 [<i>Ref Std:</i> AIR=1]
Density	<i>No Data Available</i>
Specific Gravity	0.8 - 0.9 [<i>Ref Std:</i> WATER=1]
Solubility in Water	Moderate
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	40,000 centipoise
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H2O & Exempt Solvents	<i>No Data Available</i>

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
HEPTANE	Dermal	Rabbit	LD50 3,000 mg/kg
HEPTANE	Inhalation-Vapor (4 hours)	Rat	LC50 103 mg/l
HEPTANE	Ingestion	Rat	LD50 > 15,000 mg/kg
ETHYL ACETATE	Dermal	Rabbit	LD50 > 18,000 mg/kg
ETHYL ACETATE	Inhalation-Vapor (4 hours)	Rat	LC50 70.5 mg/l
ETHYL ACETATE	Ingestion	Rat	LD50 5,620 mg/kg
ACETONE	Dermal	Rabbit	LD50 > 15,688 mg/kg
ACETONE	Inhalation-Vapor (4 hours)	Rat	LC50 76 mg/l
ACETONE	Ingestion	Rat	LD50 5,800 mg/kg
METHYLCYCLOHEXANE	Inhalation-Vapor (4 hours)	Mouse	LC50 26 mg/l
METHYLCYCLOHEXANE	Dermal	Rabbit	LD50 > 86,700 mg/kg
METHYLCYCLOHEXANE	Ingestion	Rat	LD50 > 3,200 mg/kg
POLYCHLOROPRENE	Dermal		LD50 estimated to be > 5,000 mg/kg
POLYCHLOROPRENE	Ingestion	Rat	LD50 > 20,000 mg/kg
CYCLOHEXANE	Dermal	Rat	LD50 > 2,000 mg/kg
CYCLOHEXANE	Inhalation-Vapor (4 hours)	Rat	LC50 > 32.9 mg/l
CYCLOHEXANE	Ingestion	Rat	LD50 6,200 mg/kg
ZINC OXIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
ZINC OXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
ZINC OXIDE	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HEPTANE	Human	Mild irritant
ETHYL ACETATE	Rabbit	Minimal irritation
ACETONE	Mouse	Minimal irritation
METHYLCYCLOHEXANE	Rabbit	Minimal irritation
POLYCHLOROPRENE	Human	No significant irritation

CYCLOHEXANE	Rabbit	Mild irritant
ZINC OXIDE	Human and animal	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
HEPTANE	Professional judgement	Moderate irritant
ETHYL ACETATE	Rabbit	Mild irritant
ACETONE	Rabbit	Severe irritant
METHYLCYCLOHEXANE	Rabbit	Mild irritant
POLYCHLOROPRENE	Professional judgement	No significant irritation
CYCLOHEXANE	Rabbit	Mild irritant
ZINC OXIDE	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
ETHYL ACETATE	Guinea pig	Not sensitizing
ZINC OXIDE	Guinea pig	Some positive data exist, but the data are not sufficient for classification

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
HEPTANE	In Vitro	Not mutagenic
ETHYL ACETATE	In Vitro	Not mutagenic
ETHYL ACETATE	In vivo	Not mutagenic
ACETONE	In vivo	Not mutagenic
ACETONE	In Vitro	Some positive data exist, but the data are not sufficient for classification
CYCLOHEXANE	In Vitro	Not mutagenic
CYCLOHEXANE	In vivo	Some positive data exist, but the data are not sufficient for classification
ZINC OXIDE	In Vitro	Some positive data exist, but the data are not sufficient for classification
ZINC OXIDE	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
ACETONE	Not Specified	Multiple animal species	Not carcinogenic
METHYLCYCLOHEXANE	Inhalation	Multiple animal species	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
------	-------	-------	---------	-------------	-------------------

ACETONE	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,700 mg/kg/day	13 weeks
ACETONE	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 5.2 mg/l	during organogenesis
CYCLOHEXANE	Inhalation	Not toxic to female reproduction	Rat	NOAEL 24 mg/l	2 generation
CYCLOHEXANE	Inhalation	Not toxic to male reproduction	Rat	NOAEL 24 mg/l	2 generation
CYCLOHEXANE	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 6.9 mg/l	2 generation
ZINC OXIDE	Ingestion	Some positive reproductive/developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 125 mg/kg/day	prematuring & during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HEPTANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
HEPTANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
HEPTANE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ETHYL ACETATE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ETHYL ACETATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
ETHYL ACETATE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ACETONE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ACETONE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
ACETONE	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL 1.19 mg/l	6 hours
ACETONE	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Guinea pig	NOAEL Not available	
ACETONE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
METHYLCYCLOHEXANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
METHYLCYCLOHEXANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
METHYLCYCLOHEXANE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgment	NOAEL Not available	
CYCLOHEXANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
CYCLOHEXANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
CYCLOHEXANE	Ingestion	central nervous	May cause drowsiness or	Professional	NOAEL Not	

		system depression	dizziness	nal judgeme nt	available	
--	--	-------------------	-----------	----------------------	-----------	--

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HEPTANE	Inhalation	liver nervous system kidney and/or bladder	All data are negative	Rat	NOAEL 12 mg/l	26 weeks
ETHYL ACETATE	Inhalation	endocrine system liver nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.043 mg/l	90 days
ETHYL ACETATE	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 16 mg/l	40 days
ETHYL ACETATE	Ingestion	hematopoietic system liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3,600 mg/kg/day	90 days
ACETONE	Dermal	eyes	Some positive data exist, but the data are not sufficient for classification	Guinea pig	NOAEL Not available	3 weeks
ACETONE	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL 3 mg/l	6 weeks
ACETONE	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL 1.19 mg/l	6 days
ACETONE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Guinea pig	NOAEL 119 mg/l	not available
ACETONE	Inhalation	heart liver	All data are negative	Rat	NOAEL 45 mg/l	8 weeks
ACETONE	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 900 mg/kg/day	13 weeks
ACETONE	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	13 weeks
ACETONE	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 200 mg/kg/day	13 weeks
ACETONE	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 3,896 mg/kg/day	14 days
ACETONE	Ingestion	eyes	All data are negative	Rat	NOAEL 3,400 mg/kg/day	13 weeks
ACETONE	Ingestion	respiratory system	All data are negative	Rat	NOAEL 2,500 mg/kg/day	13 weeks
ACETONE	Ingestion	muscles	All data are negative	Rat	NOAEL 2,500 mg/kg	13 weeks
ACETONE	Ingestion	skin bone, teeth, nails, and/or hair	All data are negative	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
METHYLCYCLOHEXANE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.6 mg/l	12 months
METHYLCYCLOHEXANE	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 12 mg/l	10 weeks
CYCLOHEXANE	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 24 mg/l	90 days
CYCLOHEXANE	Inhalation	auditory system	Some positive data exist, but the	Rat	NOAEL 1.7	90 days

			data are not sufficient for classification		mg/l	
CYCLOHEXANE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 2.7 mg/l	10 weeks
CYCLOHEXANE	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 24 mg/l	14 weeks
CYCLOHEXANE	Inhalation	peripheral nervous system	All data are negative	Rat	NOAEL 8.6 mg/l	30 weeks
ZINC OXIDE	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	10 days
ZINC OXIDE	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Other	NOAEL 500 mg/kg/day	6 months

Aspiration Hazard

Name	Value
HEPTANE	Aspiration hazard
METHYLCYCLOHEXANE	Aspiration hazard
CYCLOHEXANE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 16-4015-0
Issue Date: 02/25/16

Version Number: 16.00
Supersedes Date: 10/09/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com