## This SDS packet was issued with item:

073233509

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

073233004 073233525

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

073233608

Issued Date: June 1, 2015

Revision Date: June 1, 2015

DirectCrown® Products 817 N. Central Ave., Ste. B Medford, OR 97501 888-910-4490/541-622-6115

## **SECTION I PRODUCT AND COMPANY IDENTIFICATION**

#### **Product Identifiers**

Product Name:

Coldpac Ultra-Fast Set Tooth Acrylic Powder

Product Code:

TP0165UFS

Synonyms:

Self Cure Acrylic Powder

## Recommended Use of the substance or mixture and Restrictions on Use

Cosmetic Use Only

## Details of the Supplier of the Safety Data Sheet

Supplier Name:

Yates Motloid

Supplier Address

300 N. Oakley Blvd.

Obi---- II cocao

Chicago, IL 60612

Website: www.yates-motloid.com E-mail: sales@yates-motloid.com

## **Emergency Telephone Numbers**

Company Phone Number:

(312) 226-2473 (During Business Hours, 8:00am - 4:00pm CST)

**Emergency Telephone:** 

INFOTRAC: 1-800-535-5053 (Outside U.S. 1-352-323-3500)

## **SECTION II HAZARDS IDENTIFICATION**

## Classification of the substance or mixture

Hazard Class - Physical, Health, Environmental

Category

Eye Damage/Irritation

Skin Sensitizer

2B 1

## **OSHA Defined Hazards**

Combustible dust, may form combustible dust concentrations in air, explosion hazard

Label Elements - Pictograms, Signal Word, Hazard Statements, Precautionary Statements, & Supplemental Information



Signal Word Warning

Issued Date: June 1, 2015 Hazards Statements		Precautionary Statements - Prevention, Response, & Disposal		
H317	May cause an allergic skin reaction	P240	Ground and bond container and receiving equipment	
H320 Causes	Causes eye irritation	P261	Avoid breathing dust/fume/gas/mist/vapours/spray	
		P264	Wash hands and exposed skin thoroughly after handling	
		P272	Contaminated work clothing should not be allowed out of the workplace	
		P280	Wear protective gloves/protective clothing/eye protection/face protection	
		P321	Specific treatment (see on this label)	
		P363	Wash contaminated clothing before	
			reuse	
		4		

Issued Date: June 1, 2015	Revision Date	e: June 1, 2015
	P302+P352 P305+P351 +P338	IF ON SKIN: Wash with soap and water IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
	P333+P313 P337+P313 P501	If skin irritation or a rash occurs: Get medical advice/attention Get medical advice/attention Dispose of contents/container to an authorized disposal facility

#### **SECTION III COMPOSITION ON INGREDIENTS**

Chemical Name	Cas No.	Weight-%	GHS Ratings
Polymer	9011-14-7		Eye Damage/Irritation 2B (H320)
Diethyl Phthalate	84-66-2		
Benzoyl Peroxide	94-36-0	•	Eye Damage/Irritation 2A (H319) Skin Sensitizer 1 (H317)
Polymer	9003-42-3	-	Eye Damage/Irritation 2B (H320)

## **SECTION IV FIRST AID MEASURES**

#### General Advice

Provide the SDS to medical personnel for treatment.

#### Inhalation:

Remove victim to fresh air. Seek immediate medical attention.

#### Eye Contact:

If product gets in the eyes, flush with lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.

#### Skin Contact:

Rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.

#### Clothing:

Remove contaminated clothing, wash thoroughly before reuse.

#### Ingestion:

If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Get medical attention immediately.

## **SECTION V FIRE-FIGHTING MEASURE**

## Suitable Extinguishing Media

Water, Chemical (alcohol-resistant) foam, dry chemical, or carbon dioxide.

## Unsuitable Extinguishing Media

Water may not be effective in extinguishing this fire.

## Specific Hazards Arising from the Chemical

Polymers are combustible dusts; care should be taken to avoid creating explosive concentrations in the air. Follow grounding and bonding procedures.

#### Special Fire Fighting Procedures:

Avoid extinguishing methods, which may generate dust clouds. Water stream can disperse dust into air producing a fire hazard and possible explosion hazard if exposed to ignition source. Firefighters should wear self-contained breathing apparatus.

## Protective Equipment and Precautions for Firefighters

Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust. Polymers are sensitive to static discharge, follow grounding and bounding procedures. Polymers are not sensitive to mechanical impacts.

Issued Date: June 1, 2015

Revision Date: June 1, 2015

## **SECTION VI ACCIDENTAL RELEASE MEASURES**

## Personal Precautions, Protective Equipment and Emergency Procedures

**Personal Precautions** 

Before cleaning any spill or leak, individuals must wear appropriate Personal Protective Equipment that is specified in section 8. Keep airborne particulates at a minimum when cleaning up spills. Deny entry to all unprotected individuals. Remove any contaminated clothing and wash thoroughly before reuse.

## **Environmental Precautions**

Extinguish all ignition sources. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802

## Methods and Material for Containment and Cleaning Up

#### Methods for Containment

Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material (e.g. sand or earth). May contaminate water supply.

#### Methods for Cleaning Up

Maximize ventilation (open doors and windows) and secure all sources of ignition. Use good, local ventilation with a minimum capture velocity of 100 ft/min (30m/min) at point of product release. Place into appropriate closed container(s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap. Not a RCRA Hazardous waste.

#### SECTION VII HANDLING AND STORAGE

#### Precautions for Safe Handling

## Advice on Safe Handling

Use in well ventilated areas. Avoid contact with skin, eyes and clothing. Avoid breathing dust. Use good personal hygiene and housekeeping. Avoid prolonged contact with the product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

## Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions

Store containers in a cool, dry location, away from direct sunlight, heat, sparks, flame, other light sources, or sources of intense heat. The temperature should remain at or under 72°F (22°C) at all times. Storing at above recommended temperature will cause product performance issues. Store in accordance with National Fire Protection Association recommendations. Observe all label precautions until the container is cleaned, reconditioned, or destroyed.

#### Incompatible Materials

Strong oxidizers, strong oxidizing agents.

## SECTION VIII EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Polymer 9011-14-			
Diethyl Phthalate 84-66-2		5 mg/m3 TWA	NIOSH: 5 mg/m3 TWA
Benzoyl Peroxide 94-36-0	5 mg/m3 TWA	5 mg/m3 TWA	NIOSH: 5 mg/m3 TWA
Polymer 9003-42-			

#### Engineering Controls

Use local explosion-proof ventilation that is adequate to keep employee exposure to airborne concentrations below exposure limits. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition for details.

## Personal Protective Equipment (PPE)

Respiratory Protection

A respirator should be worn whenever workplace conditions warrant use of a respirator. If dust conditions are present, a N95 respirator dust mask is required. None required if airborne concentrations are maintained below any exposure limit that may be

Issued Date: June 1, 2015

Revision Date: June 1, 2015

listed above. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134 or other appropriate governing standard.

Eye/Face Protection

Wear safety glasses, chemical goggles when splashing is possible, when dealing with this material. If necessary, refer to U.S. OSHA 29 CFR §1910.133 or other appropriate governing standard. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Skin and Body Protection

Complete suit protecting against chemicals, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full Contact:

Material: Nitrile Rubber

Minimum Layer Thickness: 0.4 mm Break Through Time: 480 min. Splash Contact: Material: Nitrile Rubber

Minimum Layer Thickness: 0.11 mm Break Through Time: 120 min.

**General Hygiene Considerations** 

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. An eyewash station and a safety shower are recommended. Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Wash hands thoroughly before eating, drinking, orsmoking.

#### **SECTION IX PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: Clear

Odor: Faint

Flammable Limit (Air Volume%, 0% Lower/Upper)

Evaporation Rate: No Data Available

Specific Gravity: 0

Physical State: Powder Flash Point: 577° F 303° C Autoignition Temperature: 80°C Boiling Range (low-high): 295°C

#### **SECTION X STABILITY AND REACTIVITY**

#### **Material Stability**

Stable

## Incompatible Materials

Strong Oxidizers

## **Hazardous Decomposition Products**

Methacrylate Monomer and Oxides of Carbon when burned

#### Possibility of Hazardous Reactions

Hazardous polymerization will not occur

## SECTION XI TOXICOLOGICAL INFORMATION

Mixture Toxicity
Component Toxicity

## Routes of Exposure

Inhalation

**Eye Contact** 

Inhalation Eye Contact

#### **Target Organs**

Eyes

Central Nervous System

Reproductive System

Skin

Peripheral Nervous System

Respiratory System

### **Effects of Overexposure**

Inhalation

Overexposure by inhalation of titanium dioxide may include mild and temporary upper respiratory irritation

with cough and shortness of breath

Skin Contact

No data found.

Issued Date: June 1, 2015

**Eye Contact** Ingestion

No data found. No data found. Revision Date: June 1, 2015

Product Components Listed as Carcinogenic

CAS Number None

Description

%Weight

Carcinogen Rating No data available

## **SECTION XII ECOLOGICAL INFORMATION**

## **Component Ecotoxicity**

Diethyl Phthalate

96 Hr LC50 Pimephales promelas: 17 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 16.8 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 22 mg/L [flow-through]: 96 Hr LC50 Lepomis macrochirus: 16.7 mg/L [static]: 96 Hr LC50 Oncorhynchus mykiss: 12 mg/L [flow-through] 48 Hr EC50 Daphnia magna: 36 - 74 mg/L; 48 Hr EC50 Daphnia magna: 86 mg/L [Static] 72 Hr EC50 Desmodesmus subspicatus: 23 mg/L; 72 Hr EC50 Desmodesmus subspicatus: 23 mg/L [static]; 96 Hr EC50 Desmodesmus subspicatus: 21 mg/L; 96 Hr EC50 Desmodesmus subspicatus: 21 mg/L [static]; 72 Hr EC50 Pseudokirchneriella subcapitata: 42 - 255 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: 2.11 -4.29 mg/L [static]

## **SECTION XIII DISPOSAL CONSIDERATIONS**

## Waste Treatment Methods

**Disposal of Wastes** 

Dispose waste material in accordance with Federal, State, and Local regulations. It is the responsibility of the generator to determine at the time of disposal whether the product meets the criteria of a hazardous waste. Comply with all applicable federal, state and local regulations. Waste disposal options include landfilling solids at permitted sites. Incinerate in a chemical incinerator equipped with an afterburner and scrubber. Use registered transporters.

Contaminated Packaging

Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards, due to residual flammable material, associated with empty containers. Dispose of all empty containers properly, in accordance with Federal, State and Local regulations.

#### SECTION XIV TRANSPORT INFORMATION

Agency

Proper Shipping Name

**UN Number** 

**Packing Group** 

**Hazard Class** 

DOT Not Regulated, Polymer, NOS Not Regulated, Polymer, NOS IATA IMDG

Not Regulated, Polymer, NOS

#### **SECTION XV REGULATORY INFORMATION**

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

13463-67-7 Titanium Dioxide (CI 77891) 0% Carcinogen

## **SARA 313**

Benzoyl Peroxide 94-36-0

## **US State Right-to-Know Regulations**

-None

Country

Regulation

All Components Listed

Canada DSL **EINECS** 

Yes No

SARA Hazard Categories TSCA Inventory

No Yes

## **SECTION XVI OTHER INFORMATION**

Hazardous Material Information System (HMIS)

National Fire Protection Association (NFPA)

SDS for Coldpac Ultra-Fast Set Tooth Acrylic Powder


Page 6 of 6

Issued Date: June 1, 2015

Revision Date: June 1, 2015



HMIS & NFPA Hazard Rating Legend
\* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH



The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not considered a warranty or quality specification. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.