

SAFETY DATA SHEETS

This SDS packet was issued with item:

076705164

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

076704183 076704670

Material Safety Data Sheet**U.S. Department of Labor**

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved
OMB No. 1218-0072

Hazard Rating

4= Extreme
3= High
2= Moderate
1= Slight
0= Insignificant
** See Sect IV

Toxicity = 2
Fire = 3
Reactivity = 0

Personal Protection = C



IDENTITY (As Used on Label and List) HYDROXYLINE, HYDROXYLINE-TC HYDROXYLINE THINNER	DOT Hazard Class UN 1993, Flammable liquid, nos, OSHA Haz. Class: Fl. Liq. C1 IB, ORM-D Consumer Commodity	Item Code: 05-xxxx
---	---	------------------------------

Section I - Contact

Manufacturer's Name: George Taub Products & Fusion Co., Inc.	Emergency Telephone Number: Chemtrec: 800-424-9300, 703-527-3887
Address (Number, Street, City, State, and ZIP Code): 277 New York Ave Jersey City, N.J. 07307	Telephone Number for Information: 201-798-5353
	Date Prepared: 06/13/11
	Signature of Preparer (optional):

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)):	CAS REG. NO.:	OSHA PEL:	ACGIH TLV:	% (optional):
Methyl Ethyl Ketone	78-93-3	200 ppm	200 ppm	> 80
Calcium Hydroxide	1305-62-0			< 3
Titanium Dioxide	13463-67-7			< 4

Section III - Physical/Chemical Characteristics

Boiling Point: 80C/176F initial	Melting Point: -86C/-123F initial	Evaporation Rate (Butyl Acetate = 1): > 1	Viscosity: 0.8 cps max @ pH 9.0
Vapor Pressure (mm Hg): 70 est. @ 20C/68F	Vapor Density (AIR = 1): > 1	Specific Gravity (H ₂ O = 1): 0.95	% Volatile (by weight): > 80
Solubility in Water: Slightly as a dry film, Moderate in liquid form			
Appearance and Odor: Low viscosity liquid, sweet, sharp odor. Hydroxyline - milky white; Hydroxyline TC - dentin color; Thinner - clear			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used): -4C/25F SFCC	Auto Ignition Temp: 516C/961F est.	Flammable Limits:	LEL: 2.0 est.	UEL: 12.0 est
Extinguishing Media: <input type="checkbox"/> Foam <input checked="" type="checkbox"/> "Alcohol" Foam <input checked="" type="checkbox"/> CO ₂ <input checked="" type="checkbox"/> Dry Chemical <input checked="" type="checkbox"/> Water Spray <input type="checkbox"/> Other				
Special Fire Fighting Procedures: Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH-approved or equivalent) and full protective gear. Use water spray to cool containers. Do not use water on open flame. Dike fire area gently with fine, dry sand to extinguish fire.				
Unusual Fire and Explosion Hazards: Vapors can travel to a source of ignition and flash back. Material can form explosive vapors with air. Avoid contact with water.				

Section V - Reactivity Data

Stability: <input checked="" type="checkbox"/> Stable <input type="checkbox"/> Unstable	Conditions to Avoid: N.A.
Incompatibility (Materials to Avoid): Strong oxidizers	
Hazardous Decomposition or Byproducts: N.A.	
Hazardous Polymerization: <input type="checkbox"/> May Occur <input checked="" type="checkbox"/> Will Not Occur	Conditions to Avoid: N.A.

Section VI - Health Hazard Data

Route(s) of Entry: ☒ Inhalation ☒ Skin ☒ Ingestion **Workplace Exposure Limits:** STEL= 125 ppm Methyl Ethyl Ketone

Health Hazards (Acute and Chronic): May cause nervous system depression (fatigue, drowsiness, dizziness), headache, nausea, stupor, Burning, tearing, redness and swelling of eyes, drying and cracking of skin.

Carcinogenicity: ☐ NTP ☐ IARC Monographs ☐ OSHA Regulated

No, but Proposition 65 (CA)-Warning - This product (may) contains trace amounts of heavy metals which the State of Calif. has determined are carcinogens or cause reproductive toxicity.

Signs and Symptoms of Exposure:

INHALATION/INGESTION: Solvent vapor or mist can cause headache, nausea, dizziness, incoordination, stupor, irritation of nose, throat, lungs. Irritation of digestive tract. Nervous system depression (fatigue, drowsiness, dizziness)

SKIN/EYES: Burning, tearing, redness and swelling of eyes, transient corneal injury, drying and cracking of skin.

Medical Conditions - Generally Aggravated by Exposure: None known

Emergency and First Aid Procedures: INHALATION: Move subject to fresh air. Give artificial respiration if breathing has stopped. See a physician. EYE/SKIN CONTACT: Flush eyes with large amount of water for at least 15 min. Wash affected skin with soap and water. Remove and clean contaminated clothing. See Physician if irritation persists. INGESTION: Seek medical attention. If victim is drowsy/unconscious, place on the left side with head down. Do not give anything by mouth. If victim is conscious/alert, DO NOT induce vomiting. Neutralize by giving egg whites or milk. Otherwise wash out mouth with water and dilute by drinking large quantities of water.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled: Personal Precautions: Appropriate protective equipment must be worn for handling spill, see Section 8. If exposed to material, see Section 6. Environmental Precautions: Warning - Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

Waste Disposal Method:

Spill Clean up: Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery, use caution. Soak up with inert absorbent material (Paper towel, sand, silica gel, sawdust). Avoid breathing vapor. Wear MSHA/NIOSH approved respirator. Note: Spills on porous surfaces can contaminate ground water. NORMAL DISPOSAL: Waste Classification: Methyl Ethyl Ketone (78-93-3), 40 CFR 261.20-.24. For discard, this is classified as a hazardous waste with the characteristic of ignitability and toxicity. RCRA #D001. Reportable quantity is 100 lbs.(40 CFR 302) Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations. (See 40 CFR 268). For small quantity spills, allow solvent in paper towel to evaporate in well ventilated areas or outdoors (preferred). CONTAMINATED PACKAGING: Empty containers should be taken for local recycling or waste disposal.

Precautions to Be taken in Handling and Storing:

Limit storage of flammable material to approved areas. Keep properly ventilated. Ground all containers when transferring material. Store bottles away from heat. Keep away from open flame of bunsen burner or furnace. Keep containers tightly sealed. Periodically clean neck of bottle of resinous build up (clean inside of cap) to maintain proper seal. Do not smoke when using. Avoid storing near acids, chlorinated solvents. Add thinner as needed, to keep proper thinness of material.

Other Precautions: Storage Temp: 60C/140F min. STEL: 125 ppm MEK. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Emptied containers contain residue. Follow all MSDS and labels. Keep away from spark.

Section VIII - Control Measures

Respiratory Protection (Specify Type):

None required if good ventilation is maintained. Otherwise self-contained breathing apparatus (pressure-demand, MSHA/NIOSH - approved or equivalent.)

Ventilation: ☒ Local Exhaust ☐ Mechanical (General) ☐ Special ☐ Other

Use explosion proof local exhaust ventilation with min. capture velocity of 100 ft/min at point of vapor evolution.

Protective Gloves: Chemical-resistant only

Eye Protection: Chemical-resistant goggles

Other Protective Clothing or Equipment: Chemical-resistant apron or other impervious cloth

Work/Hygienic Practices: Eyewash, shower

Section IX - Toxicity Information

Data for MEK: Rat - Oral LD50: 3.3 g/kg, Rabbit - Dermal LD50: >8 ml/kg, Rat - Inhalation LC50: >2000 ppm / 2hrs

Section X - Regulatory Information

This product is considered hazardous under OSHA Hazard Communication. Standard (29CFR 1910.1200).

This product is a 'controlled product' under Canadian Workplace Hazardous Materials Information System (WHMIS)

SARA TITLE III: Sect 313 (40CFR372) above de minimus concentrations Methyl Ethyl Ketone (78-93-3), Titanium Dioxide. CERCLA (40CFR302.4) regulated components: MMA (RQ 1000 lbs), MEK (RQ 5000 lbs)

Disclaimer: While the information and recommendations set forth herein are believed to be accurate as of the date hereof, George Taub Products makes no warranty with respect thereto and disclaims all liability from reliance thereon.

* U.S.G.P.O.: 1986 - 491 - 529/45775

Safety Data Sheet

Hydroxyline Thinner

SDS Revision Date:

09/10/2015

1. Identification

1.1. Product identifier

Product Identity Hydroxyline Thinner

Alternate Names Hydroxyline Thinner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name George Taub Products & Fusion Co., Inc.
277 New York Ave
Jersey City, NJ 07307

Emergency

CHEMTREC (USA) (800) 424-9300

24 hour Emergency Telephone No. 201-798-5353

Customer Service: George Taub Products & Fusion Co., Inc. Chemtrec: 800-424-9300, 703-527-3887

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225 Highly Flammable liquid and vapor.
Eye Irrit. 2;H319 Causes serious eye irritation.
STOT SE 3;H336 May cause drowsiness or dizziness.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

Safety Data Sheet

Hydroxyline Thinner

SDS Revision Date:

09/10/2015

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P337+313 If eye irritation persists: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Butanone CAS Number: 0000078-93-3	50 - 75	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

Safety Data Sheet

Hydroxyline Thinner

SDS Revision Date:

09/10/2015

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	<p>INHALATION/INGESTION: Solvent vapor or mist can cause headache, nausea, dizziness, incoordination, stupor, irritation of nose, throat, lungs. Irritation of digestive tract. Nervous system depression (fatigue, drowsiness, dizziness)</p> <p>SKIN/EYES: Burning, tearing, redness and swelling of eyes, transient corneal injury, drying and cracking of skin.</p> <p>Medical Conditions - Generally Aggravated by Exposure: pre-existing skin disorders, respiration, liver, kidney & Wilson's disease.</p> <p>Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.</p> <p>Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.</p>
Inhalation	May cause drowsiness or dizziness.
Eyes	Causes serious eye irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Do not use: water jet.

5.2. Special hazards arising from the substance or mixture

Safety Data Sheet

Hydroxyline Thinner

SDS Revision Date:

09/10/2015

Hazardous decomposition: None at ambient temperature.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Special Fire Fighting Procedures: Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH-approved or equivalent) and full protective gear. Use water spray to cool containers. Do not use water on open flame. Dike fire area gently with fine, dry sand to extinguish fire. Do not use halogenated hydrocarbon extinguishing agents.

Unusual Fire and Explosion Hazards: Vapors can travel to a source of ignition and flash back. Material can form explosive vapors with air. Avoid contact with water.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Personal Precautions: Appropriate protective equipment must be worn for handling spill, see Section 8. If exposed to material, see Section 6.

Environmental Precautions: Warning - Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

Waste Disposal Method:

Spill Clean up: Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery, use caution. Soak up with inert absorbent material (Paper towel, sand, silica gel, sawdust). Avoid breathing vapor. Wear MSHA/NIOSH approved respirator. Note: Spills on porous surfaces can contaminate ground water.

NORMAL DISPOSAL:

Waste Classification: Methyl Ethyl Ketone (78-93-3), 40 CFR 261.20-.24. For discard, this is classified as a hazardous waste with the characteristic of ignitability and toxicity. RCRA #D001. Reportable quantity is 100 lbs.(40 CFR 302) Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations. (See 40 CFR 268). For small quantity spills, allow solvent in paper towel to evaporate in well ventilated areas or outdoors (preferred).

CONTAMINATED PACKAGING: Empty containers should be taken for local recycling or waste disposal.

7. Handling and storage

Safety Data Sheet

Hydroxyline Thinner

SDS Revision Date:

09/10/2015

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Water, acids, alkalis, chlorinated solvents

Precautions to Be Taken in Handling and Storing: Limit storage of flammable material to approved areas. Keep properly ventilated. Ground all containers when transferring material. Store bottles away from heat. Keep away from open flame of bunsen burner or furnace. Keep containers tightly sealed. Periodically clean neck of bottle of resinous build up (clean inside of cap) to maintain proper seal. Do not smoke when using. Avoid storing near acids, chlorinated solvents. Add thinner as needed, to keep proper thinness of material.

Other Precautions: Storage Temp: 60C/140F min. STEL: 125 ppm MEK. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Emptied containers contain residue. Follow all MSDS and labels. Keep away from spark.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000078-93-3	Butanone	OSHA	TWA 200 ppm (590 mg/m3)
		ACGIH	TWA: 50 ppm STEL: 100 ppm
		NIOSH	TWA 200 ppm (590 mg/m3) ST 300 ppm (885 mg/m3)
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000078-93-3	Butanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes

Chemical-resistant goggles

Skin

Use chemical-resistant apron or other impervious clothing, and rubber boots if necessary, to avoid contaminating regular clothing and shoes and to prevent skin contact. Chemical resistant gloves.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the

Safety Data Sheet

Hydroxyline Thinner

SDS Revision Date:

09/10/2015

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Clear, Colorless Liquid
Odor	sweet/sharp odor
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	-86 C/-123 F initial
Initial boiling point and boiling range	80 C/176 F initial
Flash Point	-4 C/25 F (SFCC)
Evaporation rate (Ether = 1)	> 1 (Butyl Acetate = 1)
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1.8 est Upper Explosive Limit: 11.5 est
Vapor pressure (Pa)	70 mmHg est. 20 C/68 F
Vapor Density	> 1
Specific Gravity	0.95 (H ₂ O = 1)
Solubility in Water	Slight
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	516 C/961 F
Decomposition temperature	Not Measured
Viscosity (cSt)	400 cPs max

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Safety Data Sheet

Hydroxyline Thinner

SDS Revision Date:

09/10/2015

Avoid contact with water, mineral acids, chlorinated solvents.

10.5. Incompatible materials

Water, acids, alkalis, chlorinated solvents.

10.6. Hazardous decomposition products

None at ambient temperature.

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Butanone - (78-93-3)	2,737.00, Rat - Category: 5	6,480.00, Rabbit - Category: NA	32.00, Mouse - Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable

Safety Data Sheet

Hydroxyline Thinner

SDS Revision Date:

09/10/2015

STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Butanone - (78-93-3)	400.00, Cyprinodon variegatus	520.00, Daphnia magna	500.00 (96 hr), Skeletonema costatum

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1993	UN1993	UN1993
14.2. UN proper shipping name	Flammable liquids, n.o.s., (Ethyl Methyl Ketone)	Flammable liquids, n.o.s., (Ethyl Methyl Ketone)	Flammable liquids, n.o.s., (Ethyl Methyl Ketone)
14.3. Transport hazard class(es)	DOT Hazard Class: 3	IMDG: 3 Sub Class: Not Applicable	Air Class: 3
14.4. Packing group	II	II	II
14.5. Environmental hazards			

Safety Data Sheet

Hydroxyline Thinner

SDS Revision Date:

09/10/2015

IMDG

Marine Pollutant: No

14.6. Special precautions for user

No further information

15. Regulatory information

Regulatory Overview

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA)

All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification

B2 D2B

US EPA Tier II Hazards

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes

Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs (lbs):

Butanone (5,000.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Butanone

Pennsylvania RTK Substances (>1%):

Butanone

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

Safety Data Sheet

Hydroxyline Thinner

SDS Revision Date:

09/10/2015

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

End of Document