SAFETY DATA SHEETS

This SDS packet was issued with item:

074486858

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

074486353 074486809



Page 1/9

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Tel.: +49 (0)800 4372522

1 Identification

- · Product identifier
 - · Trade name: iBOND Etch 35 Fluid
 - · Application of the substance / the mixture dental etching agent
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

· Information department:

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545 e-mail: customer.servicehkna@kulzer-dental.com

· Emergency telephone number:

Emergency CONTACT (24-Hour-Number)

GBK/Infotrac ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
 - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS05

- · Signal word Danger
- Hazard-determining components of labeling:

orthophosphoric acid

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Store locked up.

(Contd. on page 2)

USA -



Page 2/9

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017 Reviewed on 06/03/2017

Trade name: iBOND Etch 35 Fluid

(Contd. of page 1)

· Classification system

NFPA ratings for USA (scale 0-4)



Health = 3 Fire = 0 Reactivity = 0

· HMIS-Ratings (Scale 0-4)



Health = 3 Fire = 0 Reactivity = 0

- · Results of PBT and vPvB assessment
 - PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
 - · Description: -
 - · Dangerous components:

7664-38-2 orthophosphoric acid

Skin Corr. 1B, H314 25-50%

· Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
 - · General information Immediately remove any clothing soiled by the product.
 - · After skin contact Immediately wash with water and soap and rinse thoroughly.
 - · After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

- Information for doctor
 - · Most important symptoms and effects, both acute and delayed

No further relevant information available.

 Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - Suitable extinguishing agents

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam

· Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)



Page 3/9

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017 Reviewed on 06/03/2017

Trade name: iBOND Etch 35 Fluid

(Contd. of page 2)

- · Advice for firefighters
 - Protective equipment: No special measures required.
- · Additional information -

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Dilute with plenty of water.
- Methods and material for containment and cleaning up:

Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues). Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 13 for disposal information.

See Section 8 for information on personal protection equipment.

-

7 Handling and storage

- · Handling
 - Precautions for safe handling

Keep receptacles tightly sealed.

Please observe the additional instructions in the product's instructions for use.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
 - · Storage
 - · Requirements to be met by storerooms and receptacles: No special requirements.
 - · Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: None.
- · **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
 - · Components with limit values that require monitoring at the workplace:

7664-38-2 orthophosphoric acid

PEL 1 mg/m³

REL Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ TLV Short-term value: 3 mg/m³ Long-term value: 1 mg/m³

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 4)

USA



Page 4/9

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017 Reviewed on 06/03/2017

Trade name: iBOND Etch 35 Fluid

(Contd. of page 3)

- · Exposure controls
 - Personal protective equipment
 - General protective and hygienic measures
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Natural rubber, NR

- · Eye protection: Tightly sealed goggles.
- · Body protection: Light weight protective clothing

Information on basic physical at General Information	nd chemical properties	
· Appearance: · Form:	Fluid	
· Form: · Color:	Red	
Odor:	Odorless	
· pH-value at 20 °C (68 °F):	0.3	
· Change in condition · Melting point/Melting rang · Boiling point/Boiling rang		
· Flash point:	Not applicable	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Vapor pressure at 20 °C (68 °	F): 23 hPa (17 mm Hg)	
· Density at 20 °C (68 °F):	1.23 g/cm³ (10.264 lbs/gal)	



Page 5/9

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017 Reviewed on 06/03/2017

Trade name: iBOND Etch 35 Fluid

		(Contd. of page 4)
Solubility in / Miscibility Water:	with Fully miscible	
Solvent content: Water:	56.5 %	
Solids content: Other information	4.1 % No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: none

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
7664-38-2 orthophosphoric acid			
Oral	LD50	1530 mg/kg (rat)	
Dermal	LD50	2740 mg/kg (can)	
Inhalative	LC50/4 h	>850 mg/l (rat)	

- · Primary irritant effect:
 - · on the skin: Caustic effect on skin and mucous membranes.
 - · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

9002-89-5 Polyvinylalkohol (vollverseift) • NTP (National Toxicology Program) None of the ingredients is listed.	3			
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \				
None of the ingredients is listed	· NTP (National Toxicology Program)			
None of the ingredients is listed.				
· OSHA-Ca (Occupational Safety & Health Administration)				
None of the ingredients is listed.				

(Contd. on page 6)



Page 6/9

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017 Reviewed on 06/03/2017

Trade name: iBOND Etch 35 Fluid

(Contd. of page 5)

12 Ecological information

- · Toxicity
 - · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- · Additional ecological information:
 - · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.
 - Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	
· DOT	UN1805
· ADR, IMDG, IATA	1805

· UN proper shipping name

· DOT PHOSPHORIC ACID, SOLUTION
· ADR 1805 PHOSPHORIC ACID, SOLUTION
· IMDG, IATA PHOSPHORIC ACID SOLUTION

(Contd. on page 7)

USA



Page 7/9

Safety Data Sheet acc. to OSHA HCS

Printing date 06/03/2017 Reviewed on 06/03/2017

Trade name: iBOND Etch 35 Fluid

(Contd. of page 6) · Transport hazard class(es) · DOT · Class 8 Corrosive substances · Label · ADR · Class 8 (C1) Corrosive substances · Label · IMDG, IATA 8 Corrosive substances · Class · Label · Packing group · DOŤ, ĂDR, IMDG, IATA Ш · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Corrosive substances · Danger code (Kemler): · EMS Number: F-A,S-B · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · UN "Model Regulation": UN1805, Phosphoric acid solution, 8, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

(Contd. on page 8)



Page 8/9

Safety Data Sheet acc. to OSHA HCS

Reviewed on 06/03/2017 Printing date 06/03/2017

Trade name: iBOND Etch 35 Fluid

(Contd. of page 7)

- TSCA (Toxic Substances Control Act) Medical devices are exempted from TSCA.
- Cancerogenity categories
 - · TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

orthophosphoric acid

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Store locked up.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H314 Causes severe skin burns and eye damage.

- · Date of preparation / last revision 06/03/2017 / 1
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 9)



Safety Data Sheet acc. to OSHA HCS

Page 9/9

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: iBOND Etch 35 Fluid

OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

* Data compared to the previous version altered.

(Contd. of page 8)