SAFETY DATA SHEETS

This SDS packet was issued with item:

075825567

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

075825500 075825526 075825534 075825542 075825559 075825575 075825583



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 24-8564-7
 Version Number:
 5.00

 Issue Date:
 02/25/16
 Supercedes Date:
 03/05/15

SECTION 1: Identification

1.1. Product identifier

3MTM ESPETM PROTEMPTM PLUS BASE PASTE

Product Identification Numbers

LE-F100-0544-1, LE-F100-0714-9

1.2. Recommended use and restrictions on use

Recommended use

Dental Material, Temporary crown and bridge material

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Page 1 of 8

Pictograms

Not applicable.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
DIMETHACRYLATE (BISEMA6)	41637-38-1	50 - 60 Trade Secret *
SILANE TREATED AMORPHOUS SILICA	None	20 - 30 Trade Secret *
REACTION PRODUCTS OF 1,6-	1101874-33-2	10 - 15 Trade Secret *
DIISOCYANATOHEXANE WITH 2-[(2-		
METHACRYLOYL)ETHYL]6-		
HYDROXYHEXANOATE AND 2-HYDROXYETHYL		
METHACRYLATE (DESMA)		
SILANE TREATED SILICA	68909-20-6	5 - 10 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Material will not burn. Non-combustible. Use a fire fighting agent suitable for surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Page 2 of 8

Substance

Carbon monoxide Carbon dioxide Irritant Vapors or Gases **Condition**

During Combustion During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Observe precautions from other sections.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use with appropriate local exhaust ventilation.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Page 3 of 8

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:
Specific Physical Form:
Paste

Odor, Color, Grade: tooth colored paste, slight acrylic odor

Odor threshold No Data Available Not Applicable pН No Data Available **Melting point Boiling Point** No Data Available **Flash Point** Not Applicable **Evaporation rate** No Data Available Flammability (solid, gas) Not Classified Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Not Applicable **Vapor Pressure** No Data Available **Vapor Density** No Data Available **Density** 1.3 - 1.4 g/cm3

Specific Gravity 1.3 - 1.4 [Ref Std: WATER=1]

Solubility in Water Negligible Solubility- non-water No Data Available Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available No Data Available Viscosity Molecular weight No Data Available Not Applicable **Volatile Organic Compounds**

Percent volatile

VOC Less H2O & Exempt Solvents

Not Applicable
Not Applicable
Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Page 4 of 8

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation. Vapors released during curing may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
DIMETHACRYLATE (BISEMA6)	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
DIMETHACRYLATE (BISEMA6)	Ingestion	Rat	LD50 > 2,000 mg/kg
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2-METHACRYLOYL)ETHYL]6- HYDROXYHEXANOATE AND 2-HYDROXYETHYL METHACRYLATE (DESMA)	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2-METHACRYLOYL)ETHYL]6-	Ingestion	Rat	LD50 > 2,000 mg/kg

Page 5 of 8

HYDROXYHEXANOATE AND 2-HYDROXYETHYL			
METHACRYLATE (DESMA)			
SILANE TREATED SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATED SILICA	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
SILANE TREATED SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2-METHACRYLOYL)ETHYL]6-HYDROXYHEXANOATE AND 2-HYDROXYETHYL METHACRYLATE (DESMA)	Rabbit	Minimal irritation
SILANE TREATED SILICA	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name		Value
Overall product	Rabbit	Mild irritant
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2-	In vitro	No significant irritation
METHACRYLOYL)ETHYL]6-HYDROXYHEXANOATE AND 2-	data	
HYDROXYETHYL METHACRYLATE (DESMA)		
SILANE TREATED SILICA	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
DIMETHACRYLATE (BISEMA6)	Guinea	Not sensitizing
	pig	
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2-	Mouse	Not sensitizing
METHACRYLOYL)ETHYL]6-HYDROXYHEXANOATE AND 2-		
HYDROXYETHYL METHACRYLATE (DESMA)		
SILANE TREATED SILICA	Human	Not sensitizing
	and	
	animal	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
DIMETHACRYLATE (BISEMA6)	In Vitro	Not mutagenic
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2- METHACRYLOYL)ETHYL]6-HYDROXYHEXANOATE AND 2- HYDROXYETHYL METHACRYLATE (DESMA)	In Vitro	Not mutagenic
SILANE TREATED SILICA	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
SILANE TREATED SILICA	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

reproductive and/or Developmental Effects						
Name	Route	Value	Species	Test Result	Exposure Duration	
SILANE TREATED SILICA	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation	
SILANE TREATED SILICA	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497	1 generation	

				mg/kg/day	
SILANE TREATED SILICA	Ingestion	Not toxic to development	Rat	NOAEL 1,350	during
				mg/kg/day	organogenesi
					S

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SILANE TREATED	Inhalation	respiratory system	All data are negative	Human	NOAEL Not	occupational
SILICA		silicosis			available	exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Page 7 of 8

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 24-8564-7
 Version Number:
 5.00

 Issue Date:
 02/25/16
 Supercedes Date:
 03/05/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 8 of 8



Material Safety Data Sheet

Copyright, 2013, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3MTM ESPETM PROTEMPTM PLUS CATALYST PASTE

MANUFACTURER: 3M

DIVISION: 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 03/18/13 **Supercedes Date:** 08/25/11

Document Group: 24-8557-1

Product Use:

Intended Use: Dental Material

Limitations on Use: For use only by dental professionals
Specific Use: Dental temporary crown and bridge material

SECTION 2: INGREDIENTS

<u>Ingredient</u>	C.A.S. No.	<u>% by Wt</u>
ETHANOL, 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXY)]BIS-,	19224-29-4	70 - 80
DIACETATE		
BENZYL-PHENYL-BARBITURIC ACID	72846-00-5	5 - 15
SILANE TREATED SILICA	68909-20-6	5 - 15
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	13122-18-4	< 0.4

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: white, paste, slight acridic odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: No immediate health, physical or environmental hazards are anticipated. May cause allergic skin reaction. May cause target organ effects. This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of

Page 1 of 6

the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

3.2 POTENTIAL HEALTH EFFECTS

Eve Contact:

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNo Data AvailableFlash PointNo flash pointFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data Available

5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

5.3 PROTECTION OF FIRE FIGHTERS

Page 2 of 6

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

6.2. Environmental precautions

Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid skin contact. Wash hands after handling and before eating.

7.2 STORAGE

Store away from heat. Store out of direct sunlight.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields

8.2.2 Skin Protection

Page 3 of 6

Avoid skin contact. Gloves not normally required.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Do not ingest. Wash hands after handling and before eating.

8.3 EXPOSURE GUIDELINES

None Established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form: Paste

Odor, Color, Grade: white, paste, slight acridic odor

General Physical Form: Solid

Autoignition temperatureNo Data AvailableFlash PointNo flash pointFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableBoiling PointNo Data AvailableDensity1.2 - 1.3 g/cm3Vapor DensityNo Data Available

Vapor Pressure No Data Available

Specific Gravity 1.2 - 1.3 [*Ref Std:* WATER=1]

pH Not ApplicableMelting point No Data Available

Solubility in Water Negligible

Evaporation rateNo Data AvailableKow - Oct/Water partition coefNo Data AvailableViscosityNo Data Available

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide Carbon dioxide Irritant Vapors or Gases **Condition**

During Combustion During Combustion During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

LE-F100-0543-9, LE-F100-0714-8

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

Page 5 of 6

CHEMICAL INVENTORIES

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 0 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 13: Waste disposal method information was modified.

Section 2: Ingredient table was modified.

Section 6: Personal precautions information was modified.

Section 6: Methods for cleaning up information was modified.

Copyright was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 24-8557-1
 Version Number:
 4.00

 Issue Date:
 02/25/16
 Supercedes Date:
 05/18/15

SECTION 1: Identification

1.1. Product identifier

3MTM ESPETM PROTEMPTM PLUS CATALYST PASTE

Product Identification Numbers

LE-F100-0543-9, LE-F100-0714-8

1.2. Recommended use and restrictions on use

Recommended use

Dental Material, Temporary crown and bridge material

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Page 1 of 9

Pictograms



Hazard Statements

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
ETHANOL, 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-	19224-29-4	70 - 80 Trade Secret *
PHENYLENEOXY)]BIS-, DIACETATE		
BENZYL-PHENYL-BARBITURIC ACID	72846-00-5	5 - 15 Trade Secret *
SILANE TREATED SILICA	68909-20-6	5 - 15 Trade Secret *
TERT-BUTYL PEROXY-3,5,5-	13122-18-4	< 0.4 Trade Secret *
TRIMETHYLHEXANOATE		

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

3MTM ESPETM PROTEMPTM PLUS CATALYST PASTE 02/25/16

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide Carbon dioxide Irritant Vapors or Gases

Condition

During Combustion During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

7.2. Conditions for safe storage including any incompatibilities

Page 3 of 9

3MTM ESPETM PROTEMPTM PLUS CATALYST PASTE 02/25/16

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Solid **Specific Physical Form:** Paste

Odor, Color, Grade: white, paste, slight acridic odor

Odor threshold No Data Available Not Applicable pН **Melting point** No Data Available **Boiling Point** No Data Available **Flash Point** No flash point **Evaporation rate** No Data Available Flammability (solid, gas) Not Classified Flammable Limits(LEL) No Data Available Flammable Limits(UEL) No Data Available **Vapor Pressure** No Data Available **Vapor Density** No Data Available **Density** 1.2 - 1.3 g/cm3

Specific Gravity 1.2 - 1.3 [*Ref Std:* WATER=1]

Solubility in Water Negligible

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data AvailableViscosityNo Data Available

Page 4 of 9

3MTM ESPETM PROTEMPTM PLUS CATALYST PASTE 02/25/16

Molecular weightNo Data AvailablePercent volatileNo Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

May be harmful in contact with skin.

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Page 5 of 9

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000
•			mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000
•			mg/kg
ETHANOL, 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-	Dermal	Professio	LD50 estimated to be 2,000 - 5,000 mg/kg
PHENYLENEOXY)]BIS-, DIACETATE		nal	
·-		judgeme	
		nt	
ETHANOL, 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-	Ingestion	Rat	LD50 > 2,000 mg/kg
PHENYLENEOXY)]BIS-, DIACETATE			
BENZYL-PHENYL-BARBITURIC ACID	Dermal	Professio	LD50 estimated to be 2,000 - 5,000 mg/kg
		nal	
		judgeme	
		nt	
BENZYL-PHENYL-BARBITURIC ACID	Ingestion	Rat	LD50 > 2,000 mg/kg
SILANE TREATED SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATED SILICA	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
SILANE TREATED SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Dermal	Rat	LD50 > 2,000 mg/kg
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Inhalation-	Rat	LC50 > 0.8 mg/l
	Dust/Mist		
	(4 hours)		
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Ingestion	Rat	LD50 12,905 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
ETHANOL, 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-	In vitro	No significant irritation
PHENYLENEOXY)]BIS-, DIACETATE	data	
SILANE TREATED SILICA	Rabbit	No significant irritation
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name		Value
ETHANOL, 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-	In vitro	No significant irritation
PHENYLENEOXY)]BIS-, DIACETATE	data	
SILANE TREATED SILICA	Rabbit	No significant irritation
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
ETHANOL, 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-	Mouse	Not sensitizing
PHENYLENEOXY)]BIS-, DIACETATE		_
BENZYL-PHENYL-BARBITURIC ACID	Mouse	Not sensitizing

SILANE TREATED SILICA	Human	Not sensitizing
	and	
	animal	
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Guinea	Sensitizing
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

or in contratagometry							
Name	Route	Value					
ETHANOL, 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1- PHENYLENEOXY)]BIS-, DIACETATE	In Vitro	Not mutagenic					
BENZYL-PHENYL-BARBITURIC ACID	In Vitro	Not mutagenic					
SILANE TREATED SILICA	In Vitro	Not mutagenic					

Carcinogenicity

Name	Route	Species	Value
SILANE TREATED SILICA	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

specific ranger organi romenty single exposure						
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BENZYL-PHENYL- BARBITURIC ACID	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,000 mg/kg	

Specific Target Organ Toxicity - repeated exposure

Specific Target Organ Toxicity - repeated exposure						
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA	Inhalation	respiratory system silicosis	All data are negative	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Page 7 of 9

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

Page 8 of 9

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 24-8557-1
 Version Number:
 4.00

 Issue Date:
 02/25/16
 Supercedes Date:
 05/18/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 9 of 9



Safety Data Sheet

Copyright, 2017, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 24-8564-7
 Version Number:
 6.00

 Issue Date:
 08/10/17
 Supercedes Date:
 02/25/16

SECTION 1: Identification

1.1. Product identifier

3MTM ESPETM PROTEMPTM PLUS BASE PASTE

Product Identification Numbers

LE-F100-0544-1, LE-F100-0714-9

1.2. Recommended use and restrictions on use

Recommended use

Dental Material, Temporary crown and bridge material

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Page 1 **of** 10

Not applicable.

Pictograms

Not applicable.

2.3. Hazards not otherwise classified

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
DIMETHACRYLATE (BISEMA6)	41637-38-1	45 - 55 Trade Secret *
Amorphous silica (7631-86-9), surface modified with 2-	None	20 - 30 Trade Secret *
propenoic acid, methyl-, 3-(trimethoxysilyl)propyl ester		
(2530-80-0) and phenyltrimethoxy silane (2996-92-1)		
REACTION PRODUCTS OF 1,6-	1101874-33-2	10 - 15 Trade Secret *
DIISOCYANATOHEXANE WITH 2-[(2-		
METHACRYLOYL)ETHYL]6-		
HYDROXYHEXANOATE AND 2-HYDROXYETHYL		
METHACRYLATE (DESMA)		
SILANE TREATED SILICA	68909-20-6	5 - 10 Trade Secret *
Ethyl Acetate	141-78-6	< 2 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

No need for first aid is anticipated.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

Page 2 **of** 10

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide Carbon dioxide Irritant Vapors or Gases

Condition

During Combustion During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Tot the component				
Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethyl Acetate	141-78-6	OSHA	TWA:1400 mg/m3(400 ppm)	
Ethyl Acetate	141-78-6	ACGIH	TWA:400 ppm	
SILICA, AMORPHOUS	68909-20-6	OSHA	TWA concentration:0.8	
			mg/m3;TWA:20 millions of	
			particles/cu. ft.	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

Page 3 **of** 10

STEL: Short Term Exposure Limit CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:Solid Paste **Specific Physical Form:**Paste

Odor, Color, Grade: tooth colored paste, slight acrylic odor

Odor threshold No Data Available Not Applicable pН **Melting point** No Data Available **Boiling Point** No Data Available **Flash Point** No flash point **Evaporation rate** No Data Available Flammability (solid, gas) Not Classified Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Not Applicable Vapor Pressure No Data Available **Vapor Density** No Data Available **Density** 1.3 - 1.4 g/cm3

Specific Gravity 1.3 - 1.4 [*Ref Std*:WATER=1]

Solubility in Water Negligible Solubility- non-water No Data Available Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available Viscosity No Data Available Molecular weight No Data Available **Volatile Organic Compounds** Not Applicable Percent volatile Not Applicable **VOC Less H2O & Exempt Solvents** Not Applicable

SECTION 10: Stability and reactivity

Page 4 of 10

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Page 5 **of** 10

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
DIMETHACRYLATE (BISEMA6)	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
DIMETHACRYLATE (BISEMA6)	Ingestion	Rat	LD50 > 2,000 mg/kg
Amorphous silica (7631-86-9), surface modified with 2-propenoic acid, methyl-, 3-(trimethoxysilyl)propyl ester (2530-80-0) and phenyltrimethoxy silane (2996-92-1)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous silica (7631-86-9), surface modified with 2-propenoic acid, methyl-, 3-(trimethoxysilyl)propyl ester (2530-80-0) and phenyltrimethoxy silane (2996-92-1)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous silica (7631-86-9), surface modified with 2-propenoic acid, methyl-, 3-(trimethoxysilyl)propyl ester (2530-80-0) and phenyltrimethoxy silane (2996-92-1)	Ingestion	Rat	LD50 > 5,110 mg/kg
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2-METHACRYLOYL)ETHYL]6- HYDROXYHEXANOATE AND 2-HYDROXYETHYL METHACRYLATE (DESMA)	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2-METHACRYLOYL)ETHYL]6- HYDROXYHEXANOATE AND 2-HYDROXYETHYL METHACRYLATE (DESMA)	Ingestion	Rat	LD50 > 2,000 mg/kg
SILANE TREATED SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATED SILICA	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
SILANE TREATED SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
Ethyl Acetate	Dermal	Rabbit	LD50 > 18,000 mg/kg
Ethyl Acetate	Inhalation- Vapor (4 hours)	Rat	LC50 70.5 mg/l
Ethyl Acetate	Ingestion	Rat	LD50 5,620 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Amorphous silica (7631-86-9), surface modified with 2-propenoic acid, methyl-,	Rabbit	No significant irritation
3-(trimethoxysilyl)propyl ester (2530-80-0) and phenyltrimethoxy silane (2996-		
92-1)		
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2-	Rabbit	Minimal irritation
METHACRYLOYL)ETHYL]6-HYDROXYHEXANOATE AND 2-		
HYDROXYETHYL METHACRYLATE (DESMA)		
SILANE TREATED SILICA	Rabbit	No significant irritation
Ethyl Acetate	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Serious Lye Damage/II Itation		
Name	Species	Value
Overall product	Rabbit	Mild irritant
Amorphous silica (7631-86-9), surface modified with 2-propenoic acid, methyl-,	Rabbit	No significant irritation
3-(trimethoxysilyl)propyl ester (2530-80-0) and phenyltrimethoxy silane (2996-		
92-1)		
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2-	In vitro	No significant irritation
METHACRYLOYL)ETHYL]6-HYDROXYHEXANOATE AND 2-	data	
HYDROXYETHYL METHACRYLATE (DESMA)		

Page 6 **of** 10

3M TM ESPE TM PROTEMP TM PLUS BASE PASTE 08/10/17	3MTM ESPETM	PROTEMPTM	M PLUS BASE PASTE	08/10/17
--	-------------	-----------	-------------------	----------

SILANE TREATED SILICA	Rabbit	No significant irritation
Ethyl Acetate	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
DIMETHACRYLATE (BISEMA6)	Guinea	Not classified
	pig	
Amorphous silica (7631-86-9), surface modified with 2-propenoic acid, methyl-,	Human	Not classified
3-(trimethoxysilyl)propyl ester (2530-80-0) and phenyltrimethoxy silane (2996-	and	
92-1)	animal	
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2-	Mouse	Not classified
METHACRYLOYL)ETHYL]6-HYDROXYHEXANOATE AND 2-		
HYDROXYETHYL METHACRYLATE (DESMA)		
SILANE TREATED SILICA	Human	Not classified
	and	
	animal	
Ethyl Acetate	Guinea	Not classified
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
DIMETHACRYLATE (BISEMA6)	In Vitro	Not mutagenic
Amorphous silica (7631-86-9), surface modified with 2-propenoic acid, methyl-, 3-(trimethoxysilyl)propyl ester (2530-80-0) and phenyltrimethoxy silane (2996-92-1)	In Vitro	Not mutagenic
REACTION PRODUCTS OF 1,6-DIISOCYANATOHEXANE WITH 2-[(2-METHACRYLOYL)ETHYL]6-HYDROXYHEXANOATE AND 2-HYDROXYETHYL METHACRYLATE (DESMA)	In Vitro	Not mutagenic
SILANE TREATED SILICA	In Vitro	Not mutagenic
Ethyl Acetate	In Vitro	Not mutagenic
Ethyl Acetate	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Amorphous silica (7631-86-9), surface modified with 2-propenoic	Not	Mouse	Some positive data exist, but the data are not
acid, methyl-, 3-(trimethoxysilyl)propyl ester (2530-80-0) and	Specified		sufficient for classification
phenyltrimethoxy silane (2996-92-1)			
SILANE TREATED SILICA	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Amorphous silica (7631-86-9), surface modified with 2-propenoic acid, methyl-, 3- (trimethoxysilyl)propyl ester (2530-80-0) and phenyltrimethoxy silane (2996-92-1)	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous silica (7631-86-9), surface modified with 2-propenoic acid, methyl-, 3- (trimethoxysilyl)propyl ester (2530-80-0) and phenyltrimethoxy silane (2996-92-1)	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous silica (7631-86-9), surface modified with 2-propenoic acid, methyl-, 3- (trimethoxysilyl)propyl ester (2530-80-0) and phenyltrimethoxy silane (2996-92-1)	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
SILANE TREATED SILICA	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not classified for male reproduction	Rat	NOAEL 497	1 generation

Page 7 **of** 10

				mg/kg/day	
SILANE TREATED SILICA	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ethyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethyl Acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Ethyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Amorphous silica (7631-86-9), surface modified with 2-propenoic acid, methyl-, 3- (trimethoxysilyl)propyl ester (2530-80-0) and phenyltrimethoxy silane (2996-92-1)	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
SILANE TREATED SILICA	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Ethyl Acetate	Inhalation	endocrine system liver nervous system	Not classified	Rat	NOAEL 0.043 mg/l	90 days
Ethyl Acetate	Inhalation	hematopoietic system	Not classified	Rabbit	LOAEL 16 mg/l	40 days
Ethyl Acetate	Ingestion	hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 3,600 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Page 8 **of** 10

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

EPCRA 311/312 Hazard Classifications (effective January 1, 2018):

Physical	Hazards
----------	---------

Not applicable

Health Hazards

Not applicable

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

Ingredient

C.A.S. No.

Classification

Toluene

108-88-3

Developmental Toxin

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Page 9 **of** 10

SECTION 16: Other information

NFPA Hazard Classification

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 24-8564-7
 Version Number:
 6.00

 Issue Date:
 08/10/17
 Supercedes Date:
 02/25/16

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com

Page 10 **of** 10