

SAFETY DATA SHEETS

This SDS packet was issued with item:

074596227

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

070753517 070884213 070951293 071038520 071043686 071095546 071106863 074595674 074596169 074596193
074596250 074596284 074596318 074596342 074596375 074596409 074596433 074596466 074596474 074596490
074596524 074596532 074596540 074596557 074596987 074596995 074597019 074597043 074597076 074597100
074597134 074597167 074597191 074597225 074597258 074597282 074597316 074597332 074597340 074597357
074597365 074597373 074597381 074597399 074597407 074597415 074597423 074597431 074597449 074597456
074597464 074597472 074597480 074597498 074597506 074598371

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

071365485 074597944 074598058



SAFETY DATA SHEET

Effective Date 28-Sep-2018

Version 4

1. IDENTIFICATION

Product Identifier

Product Name JET TOOTH SHADE POWDER

Other means of identification

SDS# 018

Product Code 1410, 1412, 1420, 1430, 1450, 1470, 1480, 1484, 1493

Recommended use of the chemical and restrictions on use

Recommended Use Fabrication of provisional crowns and bridges

Details of the supplier of the safety data sheet

Supplier Address Lang Dental Mfg. Co., Inc.
175 Messner Dr.
Wheeling, IL 60090
USA

Emergency telephone number

Company Phone Number 847-215-6622

Emergency Telephone (INFOTRAC) 352-323-3500 (International)
800-535-5053 (North America)

Authorized European Representative MediMark® Europe SARL
11, rue Emile Zola – BP 2332
38033 Grenoble Cedex 2
France
Tel: +33 476 86 43 22
Fax: +33 476 17 19 82
Email: info@medimark-europe.com

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Eye Damage/Irritation	2A
Skin sensitization	1

Signal word Warning

Hazard statements H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.



Physical State Powder

Appearance Fine, white or pigmented

Odor Faint odor in bulk

Precautionary Statements – Prevention

P261 Avoid breathing dust, fumes, gas, mist, vapors or spray.
P264 Wash hands and exposed skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements – Response

P302+P352 IF ON SKIN: Wash with soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Precautionary Statements – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight - %
2-Propenoic acid, 2-methyl-, methyl ester, homopolymer	9011-14-7	80-90
Diethyl phthalate	84-66-2	10-20
Benzoyl Peroxide	94-36-0	1-5
Titanium Dioxide (CI77891)	13463-67-7	0-1

*Specific chemical weight has been withheld as a trade secret.

4. FIRST AID MEASURES**First aid measures**

Inhalation	Remove to fresh air. Get medical attention if discomfort persists.
Eye contact	Rinse immediately with plenty of water, including under the eyelids, for at least 15 minutes. If irritation persists, get medical advice / attention.
Ingestion	Do NOT induce vomiting. Drink plenty of water or milk immediately. If vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately and provide an estimate of when and how much material was ingested.
Skin Contact	Wash with soap and water. If irritation persists, call a physician. Take off contaminated clothing and wash before reuse.

Most important symptoms and effects, both acute and delayed

Symptoms Skin contact may aggravate an existing dermatitis. Direct contact with eyes may cause temporary irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Extinguishing Media**

Suitable: Water, carbon dioxide (CO₂), dry chemical

Unsuitable: Avoid extinguishing methods which may generate dust clouds.

Specific hazards arising from the chemical

For bulk size: Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust.

Protective equipment and precautions for firefighters

Self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Remove any contaminated clothing and wash thoroughly before reuse.

Methods and material for containment and clean-up

Method for containment Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material, sand or earth. May contaminate water supply.

Method for clean-up Sweep up to avoid slipping hazard. Keep airborne particulates at a minimum when cleaning up spills. Clean up in accordance with all applicable regulations. Wash all affected areas with plenty of warm water and soap.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use only in well-ventilated areas. Avoid contact with skin, eyes or clothing. Avoid breathing dust or fume. Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed to prevent water absorption and contamination. Store in a dry, cool and well-ventilated place away from direct sunlight or other sources of light or intense heat. Temperature not to exceed 35°C.

Packaging materials Keep in original container.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Propenoic acid, 2-methyl-, methyl ester, homopolymer 9011-14-7			
Diethyl phthalate 84-66-2	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³
Benzoyl peroxide 94-36-0	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³
Titanium Dioxide (CI77891) 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ (total dust)	

Appropriate engineering controls

Apply technical measures to comply with the occupational exposure limits. When working with large quantities of product, provide adequate ventilation (e.g. local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. Use good local exhaust at processing equipment, including buffers, sanders, grinders and polishers.

Individual protection measures, such as personal protective equipment

Eye / face protection

Depending on the use of this product, safety glasses or goggles may be worn. If necessary, refer to US OSHA 29 CFR SS1910.133, Canadian standards or the European Standard EN 166. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Skin and body protection	If anticipated that prolonged and repeated skin contact will occur during use of this product, wear gloves for routine industrial use. If necessary, refer to US OSHA 29 CFR SS1910.138 or the appropriate standards of Canada or the EC member states.
Respiratory protection	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per US OSHA requirement in 29 CFR SS 1910.134, or applicable US state regulations, or the appropriate standards of Canada, its provinces, EC member states or Australia. VENTILATION: Local exhaust at processing equipment.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Powder	Odor	Faint odor in bulk
Appearance	Fine		
Color	White or pigmented		
Property	Values		
Boiling point / boiling range	295°C		
Auto ignition temperature	80°C		
Flash point	303°C / 577°F		
Flammability limits in air			
Upper flammability limit	Not applicable		
Lower flammability limit	Not applicable		
Specific gravity	0.00		

10. STABILITY AND REACTIVITY

Reactivity	Not reactive under normal conditions
Chemical stability	Stable under recommended storage conditions
Possibility of hazardous reactions	None under normal processing
Hazardous polymerization	Does not occur.
Conditions to avoid	Heating above 240°C / 464°F
Incompatible materials	Strong oxidizing agents
Hazardous decomposition products	Methacrylate monomer, oxides of carbon when burned

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposures

Product information	This product has not been tested on animals to obtain toxicology data.
Inhalation	Not expected to be an inhalation hazard under normal conditions of intended use
Eye contact	Avoid contact with eyes.
Skin contact	Avoid contact with skin.
Ingestion	Do not taste or swallow.

Information on physical, chemical and toxicological effects

Symptoms	See Section 4.
-----------------	----------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Component Carcinogenicity	Titanium Dioxide (CI77891) 13463-67-7 % Weight : 0.1 to 1.0% NIOSH: Potential occupational carcinogen IARC: Possible human carcinogen OSHA: Listed
----------------------------------	---

12. ECOLOGICAL INFORMATION

Component Ecotoxicity

There is no specific data available for this product; however, very large releases may be harmful or fatal to overexposed aquatic life.

For Diethyl Phthalate:

Pimephales promeias	96 Hr: LC ₅₀	17 mg/L (flow-through)	Desmodesmus subspicatus	72 Hr EC ₅₀	23 mg/L
Pimephales promeias	96 Hr: LC ₅₀	16.8 mg/L (static)	Desmodesmus subspicatus	72 Hr EC ₅₀	23 mg/L
Lepomis macrochirus	96 Hr: LC ₅₀	16.7 mg/L (static)	Desmodesmus subspicatus	96 Hr EC ₅₀	21 mg/L
Onchorhynchus mykiss	96 Hr: LC ₅₀	12 mg/L (flow-through)	Desmodesmus subspicatus	96 Hr EC ₅₀	21 mg/L (static)
Daphnia magna	48 Hr: EC ₅₀	36-74 mg/L	Pseudokirchneriella subcapitata	96 Hr EC ₅₀	42-255 mg/L
Daphnia magna	48 Hr: EC ₅₀	86 mg/L (static)	Pseudokirchneriella subcapitata	96 Hr EC ₅₀	2.11-4.29 mg/L (static)

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Follow all local and national government regulations in disposing material or contaminated packaging.

Contaminated Packaging

For bulk only: Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards due to residual material associated with empty containers. Dispose of all empty containers properly in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

DOT

Not regulated

IATA

Not regulated

IMDG

Not regulated

15. REGULATORY INFORMATION

International Inventories

EINECS Listed

TSCA Listed

US Federal Regulations

SARA 302 – Extremely Hazardous – Not Listed

SARA 311 / 312 Hazard Categories – Not Listed

SARA 313 – Toxic Chemicals for Benzoyl peroxide 94-36-0 Listed

US State Regulations

California Proposition 65 – Warning. This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin: 13463-67-7 Titanium Dioxide (CI77891) 0.1 to 1.0%

16. OTHER INFORMATION

HMIS	Health Hazards	Flammability	Physical Hazards
	1	1	0

Effective Date 28-Sep-2018

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication.

The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet