SAFETY DATA SHEETS

This SDS packet was issued with item:

071397785

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071397769 071397777 071397793 071397801 071397819 071397827 071397835 071397850 071397868 071397876 071397884 071397892 071397900 071397918 071397926 071397934 071397942 071397959 071397975 071397983 071397991

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

071397710 071397728 071397736





according to UN GHS (ST/SG/AC.10/11/Rev.8)

VITA AKZENT LC

Revision date: 03.04.2019 Product code: 317 Page 1 of 9

1. Identification

Product identifier

VITA AKZENT LC

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

Special finishes Use as laboratory reagent

Details of the supplier of the safety data sheet

Company name: VITA Zahnfabrik H.Rauter GmbH & Co.KG

Street: Spitalgasse 3

Place: D-79713 Bad Säckingen

Post-office box: 1338

D-79704 Bad Säckingen

Telephone: +49(0)7761-562-0 Telefax: +49(0)7761-562-299

e-mail: info@vita-zahnfabrik.com

Contact person: regulatory affairs

e-mail: info@vita-zahnfabrik.com
Internet: www.vita-zahnfabrik.com
Responsible Department: Regulatory Affairs

Emergency phone number: +49-(0)761-19240

Further Information

medical device

2. Hazard(s) identification

Classification of the chemical

UN GHS (ST/SG/AC.10/11/Rev.8)

Hazard categories:

Flammable liquids: Flam. Liq. 2 Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitization: Skin Sens. 1

Specific target organ toxicity single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapor

Causes skin irritation

Causes serious eye damage

May cause an allergic skin reaction May cause respiratory irritation

Harmful to aquatic life with long lasting effects

Label elements

UN GHS (ST/SG/AC.10/11/Rev.8)

Hazard components for labelling

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

2-Propenoic acid, reaction products with pentaerythritol

Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinat

pentaerythritol tetraacrylate

pentaerythritol triacrylate

triethylene glycol dimethacrylate



according to UN GHS (ST/SG/AC.10/11/Rev.8)

VITA AKZENT LC

Revision date: 03.04.2019 Product code: 317 Page 2 of 9

Signal word: Danger

Pictograms:







Hazard statements

H225 Highly flammable liquid and vapor

H315 Causes skin irritation

H317 May cause an allergic skin reaction
H318 Causes serious eye damage
H335 May cause respiratory irritation

H412 Harmful to aquatic life with long lasting effects

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Hazards not otherwise classified

No information available.

3. Composition/information on ingredients

Mixtures



according to UN GHS (ST/SG/AC.10/11/Rev.8)

VITA AKZENT LC

Revision date: 03.04.2019 Product code: 317 Page 3 of 9

Hazardous components

CAS No	Components	Quantity
	Classification (UN GHS (ST/SG/AC.10/11/Rev.8))	
80-62-6	methyl methacrylate	30 - < 35 %
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335	
	Hexamethylene diisocyanate polymer with pentaerytriol reaction products with acrylic acid	25 - < 30 %
	Skin Irrit. 2; H315	
72869-86-4	7,7,9-Trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecan-1,16-diylbismethacrylat	5 - < 10 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335	
1245638-61- 2	2-Propenoic acid, reaction products with pentaerythritol	5 - < 10 %
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 2; H302 H315 H318 H317 H411	
84434-11-7	Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinat	1 - < 5 %
	Skin Sens. 1, Aquatic Chronic 2; H317 H411	
4986-89-4	pentaerythritol tetraacrylate	1 - < 5 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317	
3524-68-3	pentaerythritol triacrylate	1 - < 5 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317	
109-16-0	triethylene glycol dimethacrylate	1 - < 5 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335	
109-16-0	2,2'-ethylenedioxydiethyl dimethacrylate	1 - < 5 %
	Skin Sens. 1B; H317	
	Maleinsäureanhydrid, Telomer mit a-Methylstyrol, Dimer und Styrol, 3- (Dimethylamino)propylimid, Imid mit Polyethylenpolypropylenglykol 2-aminopropyl Me ether, quaternisiert mit 2-[(C10-16-alkyloxy)methyl]oxiran	< 1 %
	Aquatic Chronic 1; H410	
868-77-9	2-hydroxyethyl methacrylate	< 1 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317	

4. First-aid measures

Description of first aid measures

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Take off immediately all contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. When in doubt or if symptoms are observed, get medical advice.

After ingestion

Rinse mouth immediately and drink plenty of water. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. When in doubt or if symptoms are observed, get medical advice.

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed





according to UN GHS (ST/SG/AC.10/11/Rev.8)

VITA AKZENT LC

Revision date: 03.04.2019 Product code: 317 Page 4 of 9

Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Specific hazards arising from the chemical

Highly flammable. Vapors may form explosive mixtures with air.

Special protective equipment and precautions for fire-fighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Supress gases/vapors/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fume/vapor/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Reference to other sections

Safe handling: see section 7

Personal protection equipment (PPE): see section 8

Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fume/vapor/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.





according to UN GHS (ST/SG/AC.10/11/Rev.8)

VITA AKZENT LC

Revision date: 03.04.2019 Product code: 317 Page 5 of 9

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

8. Exposure controls/personal protection

Control parameters

Exposure limits

CAS No	Substance	ppm	mg/m³	f/cc	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	REL
80-62-6	Methyl methacrylate	100	410		TWA (8 h)	PEL
		100	410		TWA (8 h)	REL

Exposure controls









Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fume/vapor/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Recommended glove articles KCL Butyl Breakthrough time: 60 min Butyl caoutchouc (butyl rubber) / Breakthrough time: 8 min

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Provide adequate ventilation as well as local exhaustion at critical locations.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Liquid

Color:

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

101 °C

boiling range:

Flash point: 10 °C

Flammability

Solid/liquid: not applicable



according to UN GHS (ST/SG/AC.10/11/Rev.8)

V	IT	Δ /	١ĸ	ZE	M.	ТΙ	C
		~ /	- 1		IXI		. •

Revision date: 03.04.2019 Product code: 317 Page 6 of 9

not applicable Gas:

12,5 vol. % Upper explosion limits:

Self-ignition temperature

Lower explosion limits:

not applicable Solid: Gas: not applicable

not determined Decomposition temperature: not determined

Water solubility: The study does not need to be conducted

because the substance is known to be

insoluble in water.

2.1 vol. %

Solubility in other solvents

not determined

not determined Partition coefficient n-octanol/water: not determined Vapor pressure: Density (at 20 °C): 1,13 g/cm³ Relative vapour density: not determined

Other information

pH-Value:

Information with regard to physical hazard classes

Oxidizing properties Not oxidising.

Other safety characteristics

Solid content: not determined not determined Evaporation rate:

10. Stability and reactivity

Reactivity

Highly flammable.

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

No known hazardous reactions.

Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapors may form explosive mixtures with air.

Incompatible materials

No information available.

Hazardous decomposition products

No known hazardous decomposition products.

11. Toxicological information

Information on toxicological effects



according to UN GHS (ST/SG/AC.10/11/Rev.8)

VITA AKZENT LC

Revision date: 03.04.2019 Product code: 317 Page 7 of 9

Acute toxicity

CAS No	Components					
	Exposure route	Dose	Species	Source	Method	
80-62-6	methyl methacrylate					
	dermal	LD50 > 5000 mg/kg				
1245638-61- 2	2-Propenoic acid, reaction products with pentaerythritol					
	oral	ATE 500 mg/kg				
868-77-9	2-hydroxyethyl methacrylate					
	oral	LD50 5050 mg/kg	Rat			

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

12. Ecological information

Ecotoxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Components						
	Aquatic toxicity	Dose	[h] [d] Species	Source	Method		
868-77-9	2-hydroxyethyl methacrylate						
	Acute fish toxicity	LC50 227 mg/l	96 h Pimephales promelas				

Persistence and degradability

The product has not been tested.

Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Components	Log Pow
868-77-9	2-hydroxyethyl methacrylate	0,47

Mobility in soil

The product has not been tested.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste



according to UN GHS (ST/SG/AC.10/11/Rev.8)

VITA AKZENT LC

Revision date: 03.04.2019 Product code: 317 Page 8 of 9

according to applicable legislation.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

14. Transport information

Marine transport (IMDG)

UN 1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (methyl methacrylate; methyl

2-methylprop-2-enoate; methyl 2-methylpropenoate; urethanacrylat

oligomer)

Transport hazard class(es):

Packing group:

Hazard label:

3



Special Provisions: 274

Limited quantity: 1 L

Excepted quantity: E2

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: UN 1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (methyl methacrylate; methyl

2-methylprop-2-enoate; methyl 2-methylpropenoate; urethanacrylat

oligomer)

Transport hazard class(es):

Packing group:

Hazard label:

3

Hazard label:
3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3

1 L

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

Warning: Combustible liquid.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

15. Regulatory information

National regulatory information





according to UN GHS (ST/SG/AC.10/11/Rev.8)

VITA AKZENT LC

Revision date: 03.04.2019 Product code: 317 Page 9 of 9

Employment restrictions: Observe employment restrictions for young people.

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

16. Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Other data

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)