# **SAFETY DATA SHEETS**

# This SDS packet was issued with item:

071470285

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071470277 071470293 071470301



# Rodin<sup>TM</sup> Bond Safety Data Sheet

# 1. Identification

**Product name:** Rodin<sup>TM</sup> Bond

**Recommended use:**Dental Product: Adhesive **Restrictions on use:**Restricted to professional users

Supplier: Pac-Dent, Inc.

670 Endeavor Circle Brea, CA 92821 - U.S.A.

T 909-839-0888 (Customer Service)

Emergency number: 909-8390888

**Issue date:** 07/11/2023

# 2. Hazard(s) identification

# **Classification:**

Physical hazards	Health hazards
Flammable liquids Category 2	Skin corrosion/irritation Cat. 2, Eye irritation Cat. 2A, Skin sensitization Cat. 1, Specific Organ Toxicity
	(Single Exposure) Cat. 3, (Repeated Exposure) Cat. 1

# **GHS US labeling:**

Danger!







Hazard statements (GHS US)	Precautionary statements (GHS US)
H225 - Highly flammable liquid and vapor	P210 - Keep away from heat, hot surfaces, sparks, open
H315 - Causes skin irritation	flames and other ignition sources. No smoking.
H317 - May cause an allergic skin reaction	P233 - Keep container tightly closed.
H319 - Causes serious eye irritation	P240 - Ground/Bond container and receiving equipment.
	P241 - Use explosion-proof electrical, ventilating, lighting
	equipment.
	P242 - Use only non-sparking tools.
	P243 - Take precautionary measures against static
	discharge.
	P261 - Avoid breathing vapors.
	P264 - Wash hands thoroughly after handling.
	P272 - Contaminated work clothing must not be allowed
	out of the workplace.
	P280 - Wear eye protection, protective gloves.

07/11/2023 EN (English- US, Canada) 1 of 7

P303+P361+P353 - If on skin (or hair): Take off
immediately all contaminated clothing. Rinse skin with
water/shower.
P333+P313 - If skin irritation or rash occurs: Get medical
advice/attention.
P363 - Wash contaminated clothing before reuse.
P305+P351+P338 - IF IN EYES: Rinse cautiously with
water for several minutes. Remove contact lenses, if
present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical
advice/attention.
P370+P378 - In case of fire: Use carbon dioxide (CO2),
powder, alcohol-resistant foam, water spray to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents or container to hazardous or
special waste collection point, in accordance with local,
regional, national and/or international regulation

# 3: Composition/Information on ingredients

Component	CAS-No.	Amount (%)
Ethanol	64-17-5	10 - 30
2-hydroxyethyl methacrylate	868-77-9	10 – 30
2-hydroxy-1, 3-propanediyl bismethacrylate	1830-78-0	1-5
Alkali fluorosilicates(Na)	16893-85-9	0.1 - 1

<sup>\*</sup>Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

### 4. First-aid measures

**Inhalation**: Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms occur.

**Skin**: Wash skin with plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.

**Eyes**: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion**: Call a poison center or a doctor if you feel unwell.

**Symptoms/effects**: May cause moderate irritation to the eyes. May cause irritation to skin. May cause an allergic skin reaction.

Immediate medical attention and special treatment, if necessary: Treat symptomatically.

# 5. Fire-fighting measures

Suitable extinguishing media: Use dry chemical, CO2, water spray or alcohol-resistant foam.

Unsuitable extinguishing media: Do not use water jet.

**Fire hazard**: Highly flammable liquid and vapor. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Prolonged exposure to fire may cause containers to rupture/explode. Thermal decomposition generates: Carbon oxides (CO, CO2). Nitrogen oxides. Phosphorus oxides. Metallic oxides.

07/11/2023 EN (English- US, Canada) 2 of 7

**Special protective equipment and precautions for fire-fighters**: In case of fire: Stop leak if safe to do so. Use water spray or fog for cooling exposed containers. Do not allow run-off from firefighting to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Do not attempt to take action without suitable protective equipment.

#### 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** Remove ignition sources. Avoid contact with eyes, skin and clothing. Wear suitable protective clothing. Always wash hands after handling the product. Do not breathe vapors. Ventilate area.

Methods and material for containment and cleaning up: Stop leak if safe to do so. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Use non-sparking tools. Notify authorities if product enters sewers or public waters. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

# 7. Handling and storage

**Precautions for safe handling**: Avoid contact with eyes, skin and clothing. Wear personal protective equipment. Avoid breathing vapors. Ensure adequate ventilation. Wash hands with water and soap. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment.

**Storage conditions**: Store in dry, cool, well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed.

# 8. Exposure controls/personal protection

Exposure guidelines:	
Ethanol	1900 mg/m³ TWA OSHA PEL; 1000 ppm TWA OSHA PEL;
	1000 ppm STEL ACGIH TLV;
2-hydroxyethyl methacrylate	None established.
2-hydroxy-1, 3-propanediyl bismethacrylate	None established.
Alkali fluorosilicates(Na)	2.5 mg/m³ TWA OSHA PEL;
	2.5 mg/m³ TWA ACGIH TLV;

**Appropriate engineering controls**: Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits.

Environmental exposure controls: Avoid release to the environment.

07/11/2023 EN (English- US, Canada) 3 of 7

**Personal protective equipment:** 

Materials for protective clothing: Impervious clothing

Hand protection: Wear impervious gloves.

Eye protection: Use suitable eye protection. Chemical goggles

Skin and body protection: Wear suitable protective clothing

**Respiratory protection**: In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

## 9. Physical and chemical properties

Appearance: Yellow liquid.

Color

Physical state : Liquid Solubility : In water, material is partially

: Light yellow soluble.

Odor : Fruity Partition : No data available

Odor threshold : No data available coefficient noctanol/water pH : No data available (Log Pow)

Melting point : Not applicable Auto-ignition : No data available

Freezing point : No data available temperature

**Boiling point** : 78.24 °C (172.83 °F) (Ethanol) **Decomposition** : No data available

Flash point : 18 °C (64.4 °F) (Ethanol) temperature

Relative : No data available Viscosity, : No data available

evaporation rate kinematic

(butyl acetate=1) Viscosity, : No data available

Flammability : Not applicable. dynamic

(solid, gas) Explosion limits: No data available

Vapor pressure : No data available Explosive : No data available

Relative vapor : No data available properties

density at 20 °C

Oxidizing: No data available

Relative density : 1.25 properties

No additional information available

#### 10. Stability and reactivity

Reactivity: The product is non-reactive under normal conditions of use, storage and transport.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use.

Conditions to avoid: Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible materials**: Strong oxidizing agents.

**Hazardous decomposition products**: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. Toxicological information

**Inhalation**: May cause minor irritation to the respiratory tract and to other mucous membranes.

07/11/2023 EN (English- US, Canada) 4 of 7

Skin: May cause moderate irritation. May cause an allergic skin reaction.

Eyes: May cause moderate irritation, including burning sensation, tearing, redness or swelling.

Ingestion: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Chronic symptoms**: Prolonged absorption of fluorides may result in fluorosis. Symptoms include joint pain, changes in bone density (osteosclerosis), ossification of ligaments, limited mobility, teeth abnormalities and mottling of the dental enamel.

Carcinogenicity: Not classified

Ethanol: This component is not listed as a carcinogen or suspected carcinogen by IARC,

NTP, ACGIH, OSHA or the EU CLP.

2-hydroxyethyl methacrylate: This component is not listed as a carcinogen or suspected carcinogen by IARC,

NTP, ACGIH, OSHA or the EU CLP.

2-hydroxy-1, 3-propanediyl

This component is not listed as a carcinogen or suspected carcinogen by IARC,

bismethacrylate NTP, ACGIH, OSHA or the EU CLP.

This component is not listed as a carcinogen or suspected carcinogen by

Alkali fluorosilicates(Na): IARC, NTP, ACGIH, OSHA or the EU CLP.

Germ cell mutagenicity: Not classified

Reproductive toxicity:

Numerical measures of Not classified ATE US (oral): 3581.7 mg/kg

toxicity: Acute Toxicity

ATE US (dermal): 14580 mg/kg
ATE US (vapors): 145.8 mg/l

The following are the toxicity values for the components:

Ethanol: No Data Available

2-hydroxyethyl methacrylate:

2-hydroxy-1, 3-propanediyl

bismethacrylate:

Alkali fluorosilicates(Na): Causes skin irritation.

Skin corrosion/irritation

**Serious eve damage/irritation** Causes serious eye irritation.

**Respiratory or skin sensitization** May cause an allergic skin reaction.

STOT-single exposure Not classified STOT-repeated exposure Not classified

# 12. Ecological information

**Ecology - general**: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

**Ecotoxicity**:

Ethanol 14.2 g/L Fish LC50; 100 mg/L Daphnia EC50 2-hydroxyethyl methacrylate 100 mg/L Fish LC50; 380 mg/L Daphnia EC50

07/11/2023 EN (English- US, Canada) 5 of 7

Alkali fluorosilicates(Na) 35.4 mg/L Daphnia EC50

Persistence and degradability:No data availableBioaccumulative potential:No data availableMobility in soil:No data available

Other adverse effects: No data available

# 13. Disposal considerations

Regional legislation (waste): Dispose of in accordance with applicable federal, state, and local regulations.

Additional information: Flammable vapors may accumulate in the container.

# 14. Transport information

## **Department of Transportation (DOT)**

**Proper Shipping Name (DOT)** : Ethanol solutions

**UN-No.(DOT)** : UN1170

Class (DOT) : 3
Packing group (DOT) : II

Hazard labels (DOT) : Flammable liquid

Transport by sea

Proper Shipping Name (IMDG) : ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

UN-No. (IMDG) : 1170 Class (IMDG) : 3 Packing group (IMDG) : II

Air transport

**Proper Shipping Name (IATA)** : Ethanol solution

UN-No. (IATA) : 1170 Class (IATA) : 3 Packing group (IATA) : II

# 15. Regulatory information

**SARA Section 313 - Emission** 

Not subject to reporting requirements of the United States SARA Section 313

Reporting:

#### **CERCLA Section 103:**

This product is not subject to reporting under CERLCA. However, many states have more stringent reporting requirements. Report all spills in accordance with local, state, and federal regulations.

## **SARA 302:**

Not applicable

SARA Section 311/312 Hazard Classes: Refer to Section 2 for OSHA Hazard Classification.

07/11/2023 EN (English- US, Canada) 6 of 7

## **California Proposition 65:**

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

**TSCA:** All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### INTERNATIONAL INVENTORIES

**Australia AICS:** One or more ingredient(s) are not listed

Canada DSL: All the components are listed.

China IECSC:
One or more ingredient(s) are not listed
EU EINECS:
One or more ingredient(s) are not listed
Japan ENCS:
One or more ingredient(s) are not listed
Korea KECL:
One or more ingredient(s) are not listed
New Zealand:
One or more ingredient(s) are not listed
Philippines PICCS:
One or more ingredient(s) are not listed
Taiwan CSNN
One or more ingredient(s) are not listed

## 16. Other information

Revision date : 07/11/2023

NFPA		
NFPA health hazard:	2	
NFPA fire hazard:	3	
NFPA reactivity:	0	

## **NOTICE**

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date of preparation, however, Pac-Dent, Inc. makes no warranty with respect to the accuracy or suitability of the recommendations, and assumes no liability to any use thereof.

07/11/2023 EN (English- US, Canada) 7 of 7