SAFETY DATA SHEETS

This SDS packet was issued with item:

071495381

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071495209 071495217 071495225 071495233 071495241 071495258 071495266 071495274 071495282 071495290 071495308 071495316 071495324 071495332 071495340 071495357 071495373 071495399 071495407 071495415 071495423 071495431 071495449 071495456 071495464 071495480 071495498 071495506



Safety Data Sheet acc. to OSHA HCS

Version 3

Reviewed on 07/25/2018

1 Identification

· Product identifier

• Trade name: CERABIEN ZR : FC Paste Stain

• Article number: US824-FCPS

· Relevant identified uses of the substance or mixture and uses advised against

- No further relevant information available.
- · Application of the substance / the mixture Dental porcelain

· Details of the supplier of the safety data sheet

· Manufacturer: Kuraray Noritake Dental Inc. 300 Higashiyama, Miyoshi-cho, Miyoshi, Aichi, 470-0293 Japan · Contact information: Kuraray America, Inc. 33 Maiden Lane, 6th Floor, New York, NY 10038 U.S.A. Tel: 800-879-1676 Fax: 888-700-5200 Website: www.kuraraydental.com · Emergency telephone number: For chemical emergency spill, leak, fire, exposure or accident Call CHEMTREC day and night Within USA and Canada: 1-800-424-9300 CCN706984 or +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

· Classification of the substance or mixture

GH:

GHS08 Health hazard

Muta. 2	H341	Suspected of causing genetic defects.
Carc. 1A	H350	May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms GHS07, GHS08
- · Signal word Danger
- · Hazard-determining components of labeling:
- vanadium pentoxide
- nickel oxide
- Hazard statements H302 Harmful if swallowed.

(Contd. on page 2)



Safety Data Sheet acc. to OSHA HCS Version 3

Reviewed on 07/25/2018

Trade name: CERABIEN ZR : FC Paste Stain

	(Contd. of page 1)
H315 Causes sk	in irritation.
H319 Causes se	rious eye irritation.
	e an allergic skin reaction.
H341 Suspected	l of causing genetic defects.
H350 May caus	e cancer.
H361 Suspected	l of damaging fertility or the unborn child.
H372 Causes da	mage to organs through prolonged or repeated exposure.
· Precautionary	statements
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312	If swallowed: Call a poison center/doctor if you feel unwell.
P305+P351+P3	38 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
· Other hazards	

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

*

*

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:	
1313-99-1 nickel oxide	≤1%
Carc. 1A, H350; STOT RE 1, H372; Eye Irrit. 2A, H319; Skin Sens. 1, H317; Aquatic Chronic 4, H413	
1314-62-1 vanadium pentoxide	≤1%
Muta. 2, H341; Carc. 2, H351; Repr. 2, H361; STOT RE 1, H372; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335	
56-81-5 glycerol 1	15-35%
	5-15%
Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
Other ingredients:	

Potassium alumino silicate glass Pigments

4 First-aid measures

· Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

- 05



Safety Data Sheet acc. to OSHA HCS

Version 3

Reviewed on 07/25/2018

Trade name: CERABIEN ZR : FC Paste Stain

• **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

• Suitable extinguishing agents: Product is not flammable

• Special hazards arising from the substance or mixture No further relevant information available.

• Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures See Section 8.

· Environmental precautions: No special measures required.

· Methods and material for containment and cleaning up:

Pick up mechanically.

Ensure adequate ventilation.

Use appropriate Personal Protective Equipment (PPE).

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes. Do not swallow. Avoid generating dust. Do not breathe dust/fume/gas/mist/vapors/spray.

Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store at room temperature.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:		
1313-99-1 nickel oxide		
	Long-term value: 1 mg/m ³ as Ni	
REL (USA)	Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A	
TLV (USA)	Long-term value: 0.2 mg/m ³ as Ni; inhalable fraction	
	(Contd. on page 4)	

(Contd. of page 2)

I IS



Reviewed on 07/25/2018

Trade name: CERABIEN ZR : FC Paste Stain

	(Contd. of page
1314-62-1 vanadium pentoxide	
PEL (USA) Ceiling limit value: 0.5* (as V2O5,*respirable dust	
REL (USA) Ceiling limit value: 0.05*	
*15-min, except V metal	
TLV (USA) Long-term value: 0.05* n	
*as inhalable fraction	·····
Additional information: The lists that	t were valid during the creation were used as basis.
Exposure controls	
Personal protective equipment:	
	sures: Avoid contact with the eyes and skin.
Breathing equipment:	ion uso respiratory filter device. In 2002 of intensive or longer eveneur
use respiratory protective device that is	ion use respiratory filter device. In case of intensive or longer exposur
Protection of hands:	s independent of enculating an.
Protective gloves	
	ble and resistant to the product/ the substance/ the preparation.
	on to the glove material can be given for the product/ the preparation/
the chemical mixture.	
	sideration of the penetration times, rates of diffusion and the
degradation	
Material of gloves	
	es not only depend on the material, but also on further marks of qualit
	facturer. As the product is a preparation of several substances, the
	the coloulated in advance and has therefore to be checked prior to the
	t be calculated in advance and has therefore to be checked prior to the
application.	t be calculated in advance and has therefore to be checked prior to the
application. Penetration time of glove material	
application. Penetration time of glove material	t be calculated in advance and has therefore to be checked prior to the found out by the manufacturer of the protective gloves and has to be
application. Penetration time of glove material The exact break trough time has to be f observed.	
application. Penetration time of glove material The exact break trough time has to be f	
application. Penetration time of glove material The exact break trough time has to be f observed. Eye protection:	
application. Penetration time of glove material The exact break trough time has to be f observed.	
application. Penetration time of glove material The exact break trough time has to be f observed. Eye protection:	
application. Penetration time of glove material The exact break trough time has to be f observed. Eye protection:	
application. Penetration time of glove material The exact break trough time has to be for observed. Eye protection: Tightly sealed goggles	found out by the manufacturer of the protective gloves and has to be
application. Penetration time of glove material The exact break trough time has to be f observed. Eye protection:	found out by the manufacturer of the protective gloves and has to be
application. Penetration time of glove material The exact break trough time has to be f observed. Eye protection: Tightly sealed goggles Physical and chemical propert	found out by the manufacturer of the protective gloves and has to be
application. Penetration time of glove material The exact break trough time has to be for observed. Eye protection: Tightly sealed goggles	found out by the manufacturer of the protective gloves and has to be
application. Penetration time of glove material The exact break trough time has to be f observed. Eye protection: Tightly sealed goggles Physical and chemical propert Information on basic physical and ch	found out by the manufacturer of the protective gloves and has to be
application. Penetration time of glove material The exact break trough time has to be for observed. Eye protection: Tightly sealed goggles Physical and chemical propert Information on basic physical and che General Information Appearance: Form:	found out by the manufacturer of the protective gloves and has to be ies hemical properties Pasty
application. Penetration time of glove material The exact break trough time has to be for observed. Eye protection: Tightly sealed goggles Physical and chemical propert Information on basic physical and chemical Information Appearance:	found out by the manufacturer of the protective gloves and has to be ies hemical properties Pasty Colored
application. Penetration time of glove material The exact break trough time has to be for observed. Eye protection: Tightly sealed goggles Physical and chemical propert Information on basic physical and che General Information Appearance: Form: Color: Odor:	found out by the manufacturer of the protective gloves and has to be ies hemical properties Pasty Colored Odorless
application. Penetration time of glove material The exact break trough time has to be for observed. Eye protection: Tightly sealed goggles Physical and chemical propert Information on basic physical and che General Information Appearance: Form: Color:	found out by the manufacturer of the protective gloves and has to be ies hemical properties Pasty Colored
application. Penetration time of glove material The exact break trough time has to be for observed. Eye protection: Tightly sealed goggles Physical and chemical propert Information on basic physical and che General Information Appearance: Form: Color: Odor:	found out by the manufacturer of the protective gloves and has to be ies hemical properties Pasty Colored Odorless
application. Penetration time of glove material The exact break trough time has to be for observed. Eye protection: Tightly sealed goggles Physical and chemical propert Information on basic physical and che General Information Appearance: Form: Color: Odor: Odor threshold:	ies hemical properties Pasty Colored Odorless Not determined
application. Penetration time of glove material The exact break trough time has to be for observed. Eye protection: Tightly sealed goggles Physical and chemical propert Information on basic physical and che General Information Appearance: Form: Color: Odor: Odor threshold: pH-value:	found out by the manufacturer of the protective gloves and has to be ies hemical properties Pasty Colored Odorless Not determined



Version 3

Reviewed on 07/25/2018

Trade name: CERABIEN ZR : FC Paste Stain

		(Contd. of page 4
· Flash point:	177 °C (glycerol)	
· Flammability (solid, gaseous):	Product is not flammable.	
· Ignition temperature:	523 °C (glycerol)	
• Decomposition temperature:	Not determined	
• Auto igniting:	Not determined	
• Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	0.9 Vol % (glycerol)	
Upper:	Not determined	
· Oxidizing properties	Not determined	
· Vapor pressure:	0.1 hPa (20°C, glycerol)	
Density:		
Relative density	Not determined	
Vapor density	Not determined	
Evaporation rate	Not determined	
· Solubility in / Miscibility with		
Water:	Partly miscible.	
· Partition coefficient (n-octanol/wa	ter): Not determined	
· Viscosity:	Not determined	
Dynamic:	Not determined	
Kinematic:	Not determined	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: None

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

1314-62-1 vanadium pentoxide

Oral LD50 10 mg/kg (rat)

· Primary irritant effect:

- on the skin: Irritating effect
- on the eye: Causes serious eye irritation.
- · Sensitization: Sensitization possible through skin contact.

(Contd. on page 6)

US



Version 3

Reviewed on 07/25/2018

(Contd. of page 5)

1

2B

Κ

Trade name: CERABIEN ZR : FC Paste Stain

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· IARC (International Agency for Research on Cancer)

1313-99-1 nickel oxide

1314-62-1 vanadium pentoxide

· NTP (National Toxicology Program)

1313-99-1 nickel oxide

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

- Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Disposal must be made according to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADR, ADN, IMDG, IATA	Void	
· UN proper shipping name		
· DOT, ADR, ADN, IMDG, IATA	Void	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
Class	Void	
· Packing group		
· DOT, ADR, IMDG, IATA	Void	



Trade name: CERABIEN ZR : FC Paste Stain

		(Contd. of page 6)
· Environmental hazards:	Not applicable.	
· Special precautions for user	Not applicable.	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.		
UN "Model Regulation":	Void	

15 Regulatory information

Section 355 (extremely hazardous substances):	
1314-62-1 vanadium pentoxide	
Section 313 (Specific toxic chemical listings):	
1313-99-1 nickel oxide	
1314-62-1 vanadium pentoxide	
• SARA 311/312: See Section 2 for the information on physical and health hazards. • Proposition 65	
· Chemicals known to cause cancer:	
1313-99-1 nickel oxide	
1314-62-1 vanadium pentoxide	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· TLV (Threshold Limit Value established by ACGIH)	
1313-99-1 nickel oxide	A1
1314-62-1 vanadium pentoxide	A3
·NIOSH-Ca (National Institute for Occupational Safety and Health)	
1313-99-1 nickel oxide	

Precautionary statements



WARNING: This product can expose you to chemicals including vanadium oxide which is known to the State of California to cause cancer. For more information go to https://www.p65warnings.ca.gov/.

· National regulations:

• Additional classification according to Decree on Hazardous Materials: Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

(Contd. on page 8)

us



*

Reviewed on 07/25/2018

Trade name: CERABIEN ZR : FC Paste Stain

(Contd. of page 7)

16 Other information
This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
· NFPA ratings (scale 0 - 4)
Health = 2 Fire = 0 Reactivity = 0
· HMIS-ratings (scale 0 - 4)
HEALTH*2FIRE 0 REACTIVITYReactivity = 0
 Abbreviations and acronyms: Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Skin Sens. 1: Skin sensitisation – Category 1 Muta. 2: Germ cell mutagenicity – Category 2 Carc. 1A: Carcinogenicity – Category 1A Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4 * Data compared to the previous version altered.