SAFETY DATA SHEETS

This SDS packet was issued with item:

072343432

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

070841890 072343374 072343457 072343473

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

072343390 072343416 072343424 072343440 273036997

ZEST DENTAL SOLUTIONS

SAFETY DATA SHEET

1. Identification

Product identifier Prelude™ Adhesive

Other means of identification

Document number SDS-022-ZD Rev. A

Recommended use Adhesive.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Company name Danville Materials

Address 2875 Loker Avenue East

Carlsbad, CA 92010

Telephone1-800-827-7940ContactCustomer Service

E-mail danvillecs@zestdent.com

Website www.zestdent.com

Emergency telephone

number

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2Sensitization, skinCategory 1

800-451-8346 / 760-602-8703

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

OSHA defined hazards

Label elements

943643



Not classified.

Signal word Warning

Hazard statement Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an

allergic skin reaction. May cause respiratory irritation.

Precautionary statement

Version #: 01

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be

allowed out of the workplace. Wear protective gloves/eve protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison

center/doctor if you feel unwell. In case of fire: Use water fog, alcohol resistant foam, dry chemical

powder, carbon dioxide to extinguish.

Issue date: 19-April-2018

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Prelude™ Adhesive SDS US

Obtained by Global Safety Management, www.globalsafetynet.com, (877) 683-7460

Revision date: -

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Ethanol	64-17-5	15 - 35
2-Hydroxyethyl methacrylate	868-77-9	10 - 30
Bisphenol A glycidyl methacrylate	1565-94-2	10 - 30

Composition comments

The manufacturer has claimed one or more hazardous ingredients as trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on

All concentrations are in percent by weight.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

of ignition and flash back. During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Specific methods General fire hazards In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out.

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering them. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Prelude™ Adhesive SDS US

943643 Version #: 01 Revision date: -Issue date: 19-April-2018

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Persons susceptible to allergic reactions should not handle this product. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Follow rules for flammable liquids. Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	s for Air Contaminants (29 CFR 1910.1000) Type	Value	
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3 1000 ppm	
US. ACGIH Threshold Limi	t Values		
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Proprietary component III	TWA	2.5 mg/m3	
logical limit values	No biological exposure limits noted for the ingr	edient(s).	

Biol

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield. Wear a full-face respirator, if needed.

Skin protection

Wear appropriate chemical resistant gloves. Be aware that the liquid may penetrate the gloves. **Hand protection**

Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Wear NIOSH approved respirator

appropriate for airborne exposure at the point of use.

Prelude™ Adhesive SDS US **Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Light yellow.
Odor Not available.
Odor threshold Not available.

pH 2.2 (Approximately)Melting point/freezing point Not available.

Initial boiling point and boiling

range

Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials. Avoid heat, sparks, open flames and other ignition sources.

Protect against direct sunlight.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

Version #: 01

products

943643

Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition have not been characterized. Silicon oxide fumes.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Issue date: 19-April-2018

Eye contact Causes serious eye irritation.

Revision date: -

Ingestion May cause discomfort if swallowed.

Prelude™ Adhesive SDS US

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Test Results Components **Species**

2-Hydroxyethyl methacrylate (CAS 868-77-9)

Acute

Dermal

LD50 Rabbit > 3000 mg/kg

Oral

Rat LD50 > 4000 mg/kg

Ethanol (CAS 64-17-5)

Acute

Inhalation

Vapor

LC50 Mouse 39 g/m3, 4 Hours

Oral

LD50 Rat 7000 - 11000 mg/kg

Proprietary component I (CAS Proprietary)

Acute

Dermal

LD50 Rabbit 0.71 ml/kg

Inhalation

LC50 Rat 8.7 mg/l, 4 Hours

Oral

LD50 Rabbit 1100 mg/kg

> Rat 847 mg/kg

Causes skin irritation. Skin corrosion/irritation

Serious eve damage/eve

Causes serious eye irritation. irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Not classified. However: The product contains a small amount of substance that may damage the Reproductive toxicity

unborn child.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

Prelude™ Adhesive SDS US

Obtained by Global Safety Management, www.globalsafetynet.com, (877) 683-7460

943643 Version #: 01 Revision date: -Issue date: 19-April-2018

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results	
Ethanol (CAS 64-17-5)			
Aquatic				
Acute				
Crustacea	LC50	Ceriodaphnia dubia	5012 mg/l, 48 hours	
		Daphnia magna	454 mg/l, 11 days	
Fish	LC50	Pimephales promelas	13480 mg/l, 96 hours	
Chronic				
Crustacea	NOEC	Ceriodaphnia dubia	9.6 mg/l, 10 days	

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Hydroxyethyl methacrylate (CAS 868-77-9)

Ethanol (CAS 64-17-5)

Proprietary component I

2.62

Proprietary component II

5.77

Mobility in soil No data available for this product.

Other adverse effects The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic

organisms.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Ethanol solutions

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1170

UN proper shipping name

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III

Environmental hazards

Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 24, B1, IB3, T2, TP1

Packaging exceptions 4b, 150
Packaging non bulk 203
Packaging bulk 242

IATA

UN number UN1170

UN proper shipping name Ethanol solutions

Transport hazard class(es)

Class 3

Prelude™ Adhesive SDS US

943643 Version #: 01 Revision date: - Issue date: 19-April-2018 6 / 8

Subsidiary risk Label(s) 3
Packing group III
Environmental hazards No
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1170

UN proper shipping name ETHANOL SOLUTIONS

Transport hazard class(es)

Class 3
Subsidiary risk Packing group III
Environmental hazards

Marine pollutant No EmS F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Not established.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categories Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethanol (CAS 64-17-5) Low priority

Issue date: 19-April-2018

US state regulations

US. Massachusetts RTK - Substance List

Ethanol (CAS 64-17-5)

943643 Version #: 01 Revision date: -

Prelude[™] Adhesive SDS US

Proprietary component III (CAS Proprietary)

US. New Jersey Worker and Community Right-to-Know Act

Ethanol (CAS 64-17-5)

Proprietary component I (CAS Proprietary)
Proprietary component III (CAS Proprietary)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethanol (CAS 64-17-5)

US. Rhode Island RTK

Ethanol (CAS 64-17-5)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 19-April-2018

Revision date - 01

NFPA ratings



Disclaimer

Danville Materials cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Prelude™ Adhesive SDS US

Obtained by Global Safety Management, www.globalsafetynet.com, (877) 683-7460

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

ZEST DENTAL SOLUTIONS

SAFETY DATA SHEET

1. Identification

Product identifier Prelude™ Primer

Other means of identification

Document number SDS-020-ZD Rev. A

Recommended use Primer.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Company name Danville Materials

Address 2875 Loker Avenue East

Carlsbad, CA 92010

Telephone1-800-827-7940ContactCustomer Service

E-mail danvillecs@zestdent.com

Website www.zestdent.com

Emergency telephone

number

800-451-8346 / 760-602-8703

2. Hazard(s) identification

 Physical hazards
 Flammable liquids
 Category 3

 Health hazards
 Skin corrosion/irritation
 Category 2

 Serious eye damage/eye irritation
 Category 2

Not classified.

Sensitization, skin Category 1
Reproductive toxicity (the unborn child) (oral) Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

OSHA defined hazards

Label elements

Prelude™ Primer



Signal word Warning

Hazard statement Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an

allergic skin reaction. Suspected of damaging the unborn child by ingestion. May cause

respiratory irritation.

Precautionary statement

PreventionObtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep

container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face

protection.

Response If exposed or concerned: Get medical advice/attention. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Use water

SDS US

1/8

fog, alcohol resistant foam, dry chemical powder, carbon dioxide to extinguish.

943644 Version #: 01 Revision date: - Issue date: 19-April-2018

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Water	7732-18-5	30 - 50
2-Hydroxyethyl methacrylate	868-77-9	20 - 40
Ethanol	64-17-5	10 - 30

Composition comments

The manufacturer has claimed one or more hazardous ingredients as trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this CDC.

All concentrations are in percent by weight.

CENTER or doctor/physician if you feel unwell.

4. First-aid measures

Skin contact

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. If exposed or concerned: get medical attention/advice. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out.

Specific methods
General fire hazards

943644

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

Issue date: 19-April-2018

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Version #: 01

Revision date: -

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering them. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

2/8

Prelude™ Primer SDS US

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Persons susceptible to allergic reactions should not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Follow rules for flammable liquids. Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Value

8. Exposure controls/personal protection

Occupational exposure limits

Components

US. OSHA Table Z-1 Limits for Air Contaminants	(29 CFR 19	10.1000)
OO. OOHA TUDIO E I EIIIII TO AII OOHUUIIII TUITO	(=0 0: :\ :0	,

Type

	* •		
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
Proprietary component	TWA	5 mg/m3	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Proprietary component	TWA	5 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield. Wear a full-face respirator, if

needed.

Skin protection

Wear appropriate chemical resistant gloves. Be aware that the liquid may penetrate the gloves. Hand protection

Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

Skin protection

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Prelude™ Primer SDS US 943644 3/8 Version #: 01 Revision date: -Issue date: 19-April-2018

Obtained by Global Safety Management, www.globalsafetynet.com, (877) 683-7460

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Wear NIOSH approved respirator

appropriate for airborne exposure at the point of use.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical stateLiquid.FormClear liquid.ColorPink.

Odor Not available.
Odor threshold Not available.
pH 2 (Approximately)
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.
(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials. Avoid heat, sparks, open flames and other ignition sources.

Protect against direct sunlight.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition have not been characterized. Phosphorus oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Prelude™ Primer SDS US
943644 Version #: 01 Revision date: - Issue date: 19-April-2018 4 / 8

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Suspected of damaging the unborn child by ingestion.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic

effects.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species Test Results

2-Hydroxyethyl methacrylate (CAS 868-77-9)

<u>Acute</u>

Dermal

LD50 Rabbit > 3000 mg/kg

Oral

LD50 Rat > 4000 mg/kg

Ethanol (CAS 64-17-5)

Acute Inhalation

Vapor

LC50 Mouse 39 g/m3, 4 Hours

Oral

LD50 Rat 7000 - 11000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Reproductive toxicity Suspected of damaging the unborn child by ingestion.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Prelude™ Primer SDS US

943644 Version #: 01 Revision date: - Issue date: 19-April-2018

Components Species Test Results

Ethanol (CAS 64-17-5)

Aquatic

Acute

Crustacea LC50 Ceriodaphnia dubia 5012 mg/l, 48 hours

Daphnia magna 454 mg/l, 11 days

Fish LC50 Pimephales promelas 13480 mg/l, 96 hours

Chronic

Crustacea NOEC Ceriodaphnia dubia 9.6 mg/l, 10 days

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Hydroxyethyl methacrylate (CAS 868-77-9) 0.47 Ethanol (CAS 64-17-5) -0.31 Proprietary component 1.58

Mobility in soil No data available for this product.

Other adverse effects The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic

organisms.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <= 2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1170

UN proper shipping name Ethanol solutions

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III

Environmental hazards

Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 24, B1, IB3, T2, TP1

Packaging exceptions 4b, 150
Packaging non bulk 203
Packaging bulk 242

IATA

UN number UN1170

UN proper shipping name Ethanol solutions

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III
Environmental hazards No

Prelude™ Primer SDS US

ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1170

UN proper shipping name ETHANOL SOLUTIONS

Transport hazard class(es)

Class 3
Subsidiary risk Packing group III
Environmental hazards

Marine pollutant No F-E. S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Not established.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categories Skin corrosion or irritation

Yes

Serious eye damage or eye irritation Respiratory or skin sensitization

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethanol (CAS 64-17-5) Low priority

US state regulations

US. Massachusetts RTK - Substance List

Ethanol (CAS 64-17-5)

Proprietary component (CAS Proprietary)

US. New Jersey Worker and Community Right-to-Know Act

Ethanol (CAS 64-17-5)

Prelude™ Primer SDS US

Proprietary component (CAS Proprietary)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethanol (CAS 64-17-5)

Proprietary component (CAS Proprietary)

US. Rhode Island RTK

Ethanol (CAS 64-17-5)

Proprietary component (CAS Proprietary)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Inventory name

Issue date 19-April-2018

Revision date - 01

NFPA ratings



Disclaimer

Danville Materials cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Prelude™ Primer SDS US

On inventory (yes/no)*

No

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing