# This SDS packet was issued with item: 072798049

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

072797900 072797918 072797926 072797934 072798015

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

072798023 072798031



#### MATERIAL SAFETY DATA SHEET

## Product Identity: ROCKET HEAVY CLEAR ROCKET HEAVY RED ROCKET LIGHT ROCKET YELLOW

#### SECTION I.

#### Identification

#### Revision Date: NOVEMBER 2010

#### Manufacturer

Dental Ventures of America Inc. 1787 Pomona Road, Suite I Corona, CA. 92880 Emergency Telephone Number: (800) 424 - 9300 Product Information Number: (951) 270 - 0606

Chemical Name/Synonyms:Cyanoacrylate Adhesive (This product does not have a UN Number)Common Name:Cyanoacrylate Instant Adhesive	
DOT Hazard Classification:Cement, Liquid NOS NA 1133CAS Number:N/A - Mixture	
Formula/Molecular Weight:N/A - MixtureAppearance/Rocket Heavy Clear:Clear, Colorless Viscous LiquidOdor:Special StimuRocket Heavy Red:Pink Viscous LiquidOdor:Slightly Punge	
Rocket Heavy Red:Flink viscous LiquidOdor:Slightly FungRocket Light:Colorless LiquidOdor:Slightly PungBoiling Point/Rocket Heavy Clear:150 Degrees FSpecific Gravity: 1.07	,
Rocket Heavy Red:149 Degrees FSpecific Gravity: 1.07Rocket Light:150 Degrees FSpecific Gravity: 1.060	
Percent Volatiles:0 @ 70 Degrees FWater Miscibility:Negligible	

#### SECTION III.

#### Hazardous Ingredients/Identify Information

Listed below are the hazardous component (s) as defined in 49 CFR 172 and 29 CFR 1910, which are present in this product and all components which appear on the hazardous substance list of any state.

Rocket Heavy Clear: Rocket Heavy Red: Rocket Light:		Ethyl Cyanoacrylate: Ethyl Cyanoacrylate: Ethyl Cyanoacrylate:	0708	35850 35850 35850	80.00 +/- Skirtcom 80.00 +/- Skirtcom 90.0 by Weight
Caution:		Read Section VII of thi	s MSDS before using th	iis product.	
Exposure Limits:		TLV-2 PPM, Manufact	urers recommendation.		
NFPD CODES:	Health - 2	Flammability - 2	Reactivity - 1	Other - None	

SECTION IV.	First Aid Measures
Skin:	Immerse bonded surfaces in warm soapy water. Do not force separation.
Eyes:	Flush thoroughly with lukewarm or tepid water for at least 15 minutes. Call physician immediately.
Inhalation:	Move to fresh air. If symptoms persist, call a physician.
Mouth:	Saliva should lift the adhesive in 12 - 48 hours. Do not force removal. Do not swallow the adhesive when it loosens.
Lips:	Apply plenty of warm water. Use maximum wetting and pressure from saliva inside the mouth. Gently peel or roll the lips apart. Call a physician.

Dental Ventures of America, Inc.	Material Safety Data Shee ROCKET HEAVY O Product: ROCKET HEAVY R ROCKET LIGHT ROCKET YELLOW	CLEAR RED
All the following information pertain	ns to 'Rocket' Heavy Clear, Heavy Red, Light Clear and Yellow unless othe <i>Fire-Fighting Measures</i>	

Flash Point (MethodUsed): Recommended Extinguishing Media: Special Fire Fighting Procedures:	185 F (80 C) (TCC) Flammable Limits: LEL: NE UEL: NE Flush with large amounts of water or dry chemical extinguisher. Fumes may be irritating if not burning and require air supply with goggles while applying large amounts of water or dry chemical extinguisher. When fighting fire, wear full protective equipment, including self-contained breathing apparatus.
Unusual Fire and Explosion Hazards:	
SECTION VI.	Accidental Release Measures
Steps to Be Taken in Case Material is Released or Spilled:	Polymerize with water. Solid material may be scraped from surface.
SECTION VII.	Handling and Storage
	Handling and Storage pertains to 'Rocket' Heavy Clear, Heavy red, Light Clear and Yellow
All the following information	pertains to 'Rocket' Heavy Clear, Heavy red, Light Clear and Yellow Avoid contact with clothing as contact can cause burning. Avoid moisture, direct UV-Sunlight and do not store above 25 C (77 F). Keep container
All the following information Handling:	pertains to 'Rocket' Heavy Clear, Heavy red, Light Clear and Yellow Avoid contact with clothing as contact can cause burning.
All the following information Handling: Storage:	<ul> <li>pertains to 'Rocket' Heavy Clear, Heavy red, Light Clear and Yellow</li> <li>Avoid contact with clothing as contact can cause burning.</li> <li>Avoid moisture, direct UV-Sunlight and do not store above 25 C (77 F). Keep container tightly closed when not in use. Ideal storage: 5 - 10 C (41 F - 50 F).</li> <li>Avoid breathing vapor, contact with eyes and skin. Allow product to reach room</li> </ul>

SECTION VIII. Exposure Controls / Personal Protection

All the following information pertains to 'Rocket' Heavy Clear, Heavy red, Light Clear and Yellow

eyelid and/or eye. A large drop of material may cause a burn upon solidificatiInhalation:Vapors may cause irritation of nose and bronchial passages. Avoid prolongedOral Ingestion:It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and a	Warning: Cyanoacrylates bond skin rapidly and strongly. May also bond eyelid to eyelid and/or eye. A large drop of material may cause a burn upon solidification. Vapors may cause irritation of nose and bronchial passages. Avoid prolonged inhalation. It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and adheres		
in the mouth. The lips may be stuck together.			
Carcinogenicity: NTP: NO IARC Monographs: NO OSHA REGULATED: NO			
Other: These products have no known carcinogenicity, mutagenicity or teratogenicity effects. Further there are no know effects of chronic exposure or to target organs. No exposure limits have been established for this product as form	vn nulated.		
Personal Protective Equipment Recommended for Normal Conditions:			
Eye Protection:Safety glasses with side shields.Skin Protection:Polyethylene (non-sticking) gloves and rubber apron (no cotton or wool) to p	rotect		
Respirator Protection: N/A with local exhaust. A NIOSH-approved organic vapor canister may maintain vapor concentration below TLV. Mechanical (General) Large ar to 0.2 ppm.			
Work/Hygienic Practices: Soap and water helps remove adhesive from skin.			

Dental Ventures of America, Inc.

#### Material Safety Data Sheet, Pg. 3

Product:

#### ROCKET HEAVY CLEAR ROCKET HEAVY RED ROCKET LIGHT ROCKET YELLOW

All the following information pertains to 'Rocket' Heavy Clear, Heavy Red, Light Clear and Yellow unless otherwise specified.

SECTION IX.	Physical and Chemical Proper	rties	
Appearance/Rocket Heavy Clear:	Clear, Colorless Viscous Liquid	Odor:	Special Stimulative Odor
Rocket Heavy Red:	Pink Viscous Liquid	Odor:	Slightly Pungent
Rocket Light:	Colorless Liquid	Odor:	Slightly Pungent
Rocket Yellow	Transparent Yellow colored liquid	Odor:	Stimulative Odor
Boiling Point:	365 F	Specific Gra	avity (H2)=1): 1.05
Vapor Density:	nil-NE	Melting Poi	nt: NE
Vapor Pressure (mm Hg):	1 @ 20 C	Evaporation	n Rate (Butyl acetate=1):nil-NE
Solubility in Water:	Insoluble, material reacts to hardened	mass for non-ha	zardous waste.

SECTION X. Stability and Reactivity

Product is stable under normal conditions.Conditions to Avoid:Excessive heat above 176 F (81 C), moisture and alkalines. Stable up to 122 F (50 C).Incompatibility (Materials to Avoid):Polymerized by water, alcohol, amines, alkaline materials and direct UV.Hazardous Decomposition:Combustible by-products of carbon monoxide/dioxide.Hazardous Polymerization may not occur.

SECTION XI.	Toxicologi	cal Informati	on	
Route (s) of Entry:	Inhalation: Yes	Skin: No	Ingestion: LD50 = 12.2cc/kg (mice)	

#### SECTION XII. Ecological Information

Please see Sections I - XI.

SECTION XIII.

Disposal Considerations

These products, if disposed as shipped, are not a hazardous waste as specified in 40 CFR 261. Dispose of in an approved landfill in accordance with state and local regulations. Incinerate solid combustible waste or dump as chemical waste according to local, state and federal regulations.

#### SECTION XIV. Transport Information

Transport these products according to local, state, provincial and federal regulations. This product is not assigned a Packing Group.

#### SECTION XV. Regulatory Information

Substances listed as hazardous component (s) as defined in 49 CFR 172 and 29 CFR 1910, which are present in this product and all components which appear on the hazardous substance list of any state.

EPA SARA TITLE III HAZARD CLASS: Combustible liquid.

This product contains NO CHEMICALS subject to the reporting requirements of EPA SARA TITLE III Section 313 (40CFR372); or considered by State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as causing cancer or reproductive toxicity and for which warnings are now required.

The data herein relates to the product named and is based upon information that Dental Ventures of America, Inc. believes to be reliable and accurate. No warranty expressed or implied is intended. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. This information is offered solely for your consideration and interpretation.

msds revision rocket 11.90 ained by Global Safety Management, Inc. www.globalsafetynet.com (Tel: 1-813-435-5161)



### MATERIAL SAFETY DATA SHEET

Product Identity:

ROCKET ACCELERATOR - H

#### SECTION I.

Identification

**REVISION: NOVEMBER 2010** 

Manufacturer

Dental Ventures of America Inc. 1787 Pomona Rd. Suite I Corona, CA. 92880 Emergency Telephone Number: Infotrack (800) 535 - 5053 Product Information Number:

(951) 270 - 0606

SECTION II.	Composition/Information on Ingredients		
Rocket Accelerator - HCuringUN #1206Class3Packing GroupII	ng Accelerator/ Please refer to Section III.		
SECTION III.	Hazardous Ingredients/Identify Information		
Hazard Rating: 3			
Hazardous Components ( <u>Common Names, CAS Number)</u> Heptane (142-82-5)	OSHAACGIHOTHER LIMITS%r)PELTLVLIMITSOPTION400 ppm400 ppm70 - 90		
Acetone (67-64-1) Alkyl Toluidines (99-97-8)	750 ppm750 ppm1000 ppm10 - 20NENE5 - 10		
*This ingredient is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know.			
NFPD HAZARD CODES:	Health - 2 Flammability - 2 Reactivity - 1 Other - None		
SECTION IV.	First Aid Measures		
Eye Contact:	Immediately flush eye with copious amounts of water for 15 minutes. If persists, seek medical attention.	irritation	
Skin Contact:	Irritation upon direct contact. Remove contaminated clothing and wash affected areas with soap and water. Prolonged or repeated contact can cause burning & itching in sensitive individuals.		
Inhalation:	Remove to fresh air. Perform artificial respiration followed by oxygen if l has stopped. Get immediate medical attention.	oreathing	
Ingestion:	Do not induce vomiting. Get immediate medical attention.		
Note to Physician:	Gastric lavage using a cuffed endotrachael tube may be performed at phy	rsicians'	

msds 06.5 rocket accelerator h 1 - 3

discretion.

### Product: **ROCKET ACCELERATOR - H**

SECTION V.	Fire-Fighting Measures		
Flash Point (Method): Extinguishing Media: Special Fire Fighting Procedures: Unusual Fire and	-4 F (TCC) Flammable Limits: LEL: NE UEL: NE Dry chemical, foam or carbon dioxide. Firefighters should wear self-contained breathing apparatus. Remove all sources of ignition. Water fog or spray may be used to cool exposed containers & equipment. Do not spray water directly on fire - product will float & may be reignited on surface of water.		
Explosion Hazards:	Carbon oxides formed when burned. Highly flammable vapors, which are heavier than air,may accumulate in low areas and/or spread along ground away from handling site.		
SECTION VI.	Accidental Release Measures		
Steps To Take if Spilled:	Evacuate area of all unnecessary personnel. Wear respiratory protection and safety equipment and remove all possible sources of ignition. Soak up with inert absorbent. Place in container for disposal. Keep out of water sources and sewers.		
SECTION VII.	Handling and Storage		
Storage:	Do not store or handle product in the presence of heat, sparks,or open flame. Ground and bond container when transferring. Static discharge possible. In presence of flammable or combustible liquids, take action to minimize ignition		
Handling:	by grounding, inerting, etc. Store in a cool, dry area. Avoid direct contact with eyes, skin or clothing. Avoid vapors, mist, fumes or dust. Do not swallow. May be aspirated into lungs. Use and store in well ventilated area, keep container tightly closed when not in use, and away from heat sparks or flames. Ground all metal containers.		
SECTION VIII.	Exposure Controls / Personal Protection		
Personal Protection			
Ventilation Requirements: Personal Protective:	Local - must remove vapors directly from the point source to a safe location.Eye Protection:Chemical GogglesSkin Protection:Rubber GlovesRespirator Protection:Respirator with organic vapor cartridge.		
Exposure Controls	NA with adequate ventilation.		
Respiratory Protection (Specify Type)	A NIOSH approved vapor canister may be used to maintain vapor concen- tration below TLV.		
Ventilation:	Local Exhaust: To maintain concentration below TLV. Mechanical (General): As needed. Safety glasses/goggles with side shields, resistant gloves (Buna-N or Polyvinyl Alcohol) and apron to protect skin and clothing. Wash hands with soap and water after use. Launder contaminated clothing before reuse.		
Protective Clothing or Equipment:			
Work/Hygienic Practices:			
SECTION IX.	Physical and Chemical Properties		
Boiling Point: Vapor Pressure (mm Hg): Solubility in Water: Appearance & Odor: Specific Gravity (H20=1): Melting Point:	56 F (13 C)NEEvaporation Rate (Butyl Acetate=1):NegligibleVolatile (@ 70 F):100%Clear transparent liquid with mild odor0.7 Vapor Density (Air=1).NE		

SECTION X.	Stability and Reactivity
Stability: Incompatibility (Materials to Avoid) Hazardous Decomposition Products: Hazardous Polymerization:	Unstable XX Conditions to Avoid: Avoid heat, sparks & flames. Pure oxygen and strong oxidizing agents. Carbon oxides formed when burned. May Not Occur XX
SECTION XI.	Toxicological Information
Route(s) of Entry: Acute: Chronic:	Inhalation: Yes Skin: Yes Ingestion: Yes May cause mild irritation of eyes, skin and respiratory tract with prolonged exposure. Ingestion may cause weakness and gastrointestinal tract irritation. If swallowed, may be aspirated resulting in inflammation and possible fluid accumulation in the lungs. Possible irritation to mucous membranes resulting in symptoms of nausea, loss of
	appetite, lassitude, light-headedness, giddiness, dizziness and incoordination. Respiratory arrest, convulsions, semi-consciousness or unconsciousness may result from extreme exposure.
SECTION XII.	Ecological Information
Please refer to Sections II - XI.	
SECTION XIII.	Disposal Considerations
Waste Disposal:	This product, if disposed as shipped, meets EPA criteria of a hazardous waste as specified in 40 CFR 261 on the basis of its ignitability. Dispose of in a licensed hazardous waste facility in accordance with applicable laws.
SECTION XIV.	Transport Information
This product should be transported acco	ording to the local, state, provincial and federal regulations.
SECTION XV.	Regulatory Information
product and all components which appe Heptaine CASRN 14282 Acetone: CASRN Exposure Limits: PEL 1000 PPM, TWO	<ul> <li>as defined in 49 CFR 172 and 29 CFR 1910 which are present in the</li> <li>ear on the hazardous substance list of any state. Unknown</li> <li>25 80.0000 % Max. Exposure Limits: TWA 400 PPM, STEL 500 PPM Flammable</li> <li>67641 20.0000 % Max.</li> <li>O 750ppm STEL 1000 PPM, REP RTECS # AL3150000,</li> <li>302.4 LIST - RQ 5000#</li> </ul>

#### SECTION XVI.

Other

None.

The data herein relates to the product named and is based upon information that Dental Ventures of America, Inc. believes to be reliable and accurate. No warranty expressed or implied is intended. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. This information is offered solely for your consideration and interpretation.



### ROCKET HEAVY CLEAR, HEAVY RED, LIGHT AND YELLOW

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT DESCRIPTION: Rocket: Heavy Clear, Heavy Red Light and Yellow

Date Revised: November 2018

MANUFACTURER Dental Ventures of America, Inc. 1787 Pomona Rd., Suite C Corona, 92880, CA. Emergency Contact: Infotrack: 800.535.5053 Emergency Phone: 951.270.0606 Alternative Emergency Phone: 800.228.6696

USE OR APPLICATION: To join small parts in a dental laboratory setting.

USES ADVISED AGAINST: Industrial use only.

#### 2. HAZARD(S) IDENTIFICATION

#### GHS CLASSIFICATIONS

Health Eye Irritation, Category 2 Skin, Irritation, Category 2 Skin Sensitization, Category 1 Respiratory Tract Irritation, Category 3

#### GHS LABEL ELEMENTS



#### HAZARD STATEMENTS

- H 315: Causes skin irritation.
- H 319: Causes serious eye irritation.
- H335: May cause respiratory irritation.
- H317: May cause an allergic skin reaction.

#### PRECAUTIONARY STATEMENTS

2783BK66: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of reach of children.

- 46097G8KU: Contains Hydroquinone. May produce an allergic reaction.
- P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264: Wash skin and hands thoroughly after handling.
- P271: Use only outdoors or in a well-ventilated area.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.



### ROCKET HEAVY CLEAR, HEAVY RED, LIGHT AND YELLOW

**Response:** P305+P351+P338: IF IN EYES: Riinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P333+P313: If skin irritation occurs: Get medical advice/attention.
P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P312: Call POISON CENTER or doctor/physician if you feel unwell.
P362: Take off contaminated clothing and wash before reuse.

#### Storage

P403+P233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

#### Disposal

7944L501: Dispose of in a manner consistent with federal, state and local regulations

#### **EMERGENCY OVERVIEW:**

PHYSICAL APPEARANCE: Clear, colorless liquid

IMMEDIATE CONCERNS: R36/37/38: Irritating to eyes, respiratory system and skin. POTENTIAL HEALTH EFFECTS: EYES: R36: Irritating to eyes, SKIN: May cause skin irritation. Allergic reactions are possible. INGESTION: Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Not a toxic product. INHALATION: R37: Irritating to respiratory system. MEDICAL CONDITIONS AGGRAVATED: Not a likely route of exposure. ROUTES OF ENTRY: Inhalation & ingestion are major routes of entry.

CANCER STATEMENT: Not Applicable.

#### 3. COMPOSITION /INFORMATION ON INGREDIENTS

Under GHS-OSHA 4.11 the precise composition of this product is withheld as confidential business information (CBI). A more complete disclosure can be provided to a health, or safety professional when necessary.

#### SUBSTANCES or MIXTURE Mixture

NO. COMPONENT	CAS.NO	PERCENT/Wt.
ETHYL-2 CYANOACRYLATE Polymethyl methacrylate	7085-85-0 9011-14-7	60 - 100% 10 - 30%
Hydroquinone	123-31-9	0 - 1



### ROCKET HEAVY CLEAR, HEAVY RED, LIGHT AND YELLOW

#### 4. FIRST-AID MEASURES

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Wash with soap and water. Peel or roll skin apart.

**INHALATION:** Remove to fresh air. Prolonged or repeated elevated exposure may cause allergic reactions with asthma-like symptoms in sensitive individuals.

**INGESTION:** Peel or roll skin apart. Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Avoid swallowing solid adhesive after detachment. Not a toxic product.

#### SIGNS AND SYMPTOMS OF OVER EXPOSURE:

Causes eye irritation.

Moderate skin irritation.

Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will life adhesive in 1-2 days. Not a toxic product.

Prolonged or excessive inhalation may cause respiratory tract irritation.

Avoid exposure to vapor concentration in confined areas. Frequent or prolonged contact may irritate the skin and cause a skin rash.

#### 5. FIRE-FIGHTING MEASURES

**GENERAL HAZARD:** Combustible liquid and vapor. Product polymerized to solid by water.

**EXTINGUISHING MEDIA:** Use dry chemical extinguisher or flush with large amounts of water.

**FIRE FIGHTING EQUIPMENT:** As in any fire, wear self-contained breathing apparatus pressure-demand.(MSHA/ NIOSH approved or equivalent) and full protective gear.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustible by-products of carbon monoxide'dioxide.

#### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Polymerize with water. Solid material may be scraped from surface.

LARGE SPILL: Polymerize with water. Increase ventilation to area. Solid material may be scraped from surface.

**ENVIRONMENTAL PRECAUTIONS:** WATER SPILL: None known.



## SAFETY DATA SHEET ROCKET HEAVY CLEAR, HEAVY RED, LIGHT AND YELLOW

#### 7. HANDLING AND STORAGE

GENERAL PROCEDURES:	Use with adequate ventilation. Avoid contact with eyes. Skin and clothing.
HANDLING:	Avoid breathing(dust, vapor, mist, gas). Avoid contact with skin, eyes and clothing. Keep container closed when not in use.
STORAGE:	Store in cool place in original container and protect from sunlight. Keep away from sources of ignition.
STORAGE TEMPERATURE:	Ideal Storage: 41-50 f (5-10c)

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use only in a well ventilated area. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

#### PERSONAL PROTECTIVE EQUIPMENT

**Eyes and Face:** For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

**SKIN:** S36/37: Wear suitable protective clothing and gloves.

**RESPIRATORY:** Use only in a well-ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment.

**WORK HYGIENIC PRACTICES:** S24/25: Avoid contact with skin and eyes. Wash thoroughly after handling. Avoid contact with clothing as contact can cause burn.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with eyewash facility and a safety shower.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### PHYSICAL STATE: Liquid

<b>APPEARANCE:</b>	,	Clear, Colorless Viscous liquid	ODOR:	Special Stimulate
	Rocket Heavy Red:	Pink Viscous Liquid	ODOR:	0 7 0
	Rocket Light:	Colorless Liquid	ODOR:	Slightly Pungent
	Rocket Yellow:	Transparent Yellow Colored Liquid	ODOR:	Stimulated Odor
PERCENT VOLATILE:       <20 g/L       FLASH POINT AND METHOD: 85C (185F) CC Closed Cup				
VAPOR PRESSURE: 1mm Hg@20CVAPOR DENSITY: Not established.				
BOILING POINT:185C (365F)SOLUBILITY IN WATER: In soluble				
EVAPORATION	<b>RATE:</b> Not establishe	ed SPECIFIC GRAVITY: 1.06		
<b>VISCOSITY #1:</b> 400 to 600 Centipoise at 22C (72F) (VOC): <20.000 g/L				



### ROCKET HEAVY CLEAR, HEAVY RED, LIGHT AND YELLOW

#### **10. STABILITY AND REACTIVITY**

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

CONDITIONS TO AVOID: Avoid temperatures above 176F (80 C), moisture and alkalies.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition. Oxides of nitrogen and probably hydrogen cyanide are also possible.

INCOMPATIBLE MATERIALS: Polymerized by water, alcohol, amines, alkaline materials and direct UV.

#### 11. TOXICOLOGICAL INFORMATION

#### **ACUTE EFFECTS:**

Dermal LD50 >2000 mg/kgNotes: (Estimated)Oral LD50 > 5000 mg/kgNotes: (Estimated)Inhalation LC50 Vapors may be irritating. Recommended TWA 0.2ppm.Eye Effects: Bonds skin and eyes in seconds. Eye irritant.Skin Effects: Irritating to skin. May cause allergic skin reaction with prolonged contact.Sensitization: Possible skin sensitizer.

#### **12. ECOLOGICAL INFORMATION**

**GENERAL COMMENTS:** None known.

#### **13. DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:** Polymerize with water to a solid material. Dispose of as solid waste or trash in accordance with local government regulations of the region.

Please refer to Section 8 for Exposure Controls/Personal Protection.



## SAFETY DATA SHEET **ROCKET HEAVY CLEAR, HEAVY RED, LIGHT AND YELLOW**

#### **14. TRANSPORT INFORMATION**

UN Number: N/A UN Proper Shipping Name: Not restricted. TRANSPORT HAZARD CLASS(S) Not restricted PACKING GROUP NUMBER: Not restricted. ENVIRONMENTAL HAZARDS: Not restricted. GUIDANCE ON TRANSPORT IN BULK: Not restricted. CANADA TRANSPORT OF DANGEROUS GOODS: SHIPPING NAME: Not restricted.

#### **15. REGULATORY INFORMATION**

#### **UNITED STATES**

TSCA (TOXIC SUBSTANCE CONTROL ACT) TSCA STATUS: All ingredients in this mixture are in compliance with TSCA **CALIFORNIA PROPOSITION 65:** Consumer sizes of this product do not require a California Proposition 65 Warning based on potential exposure in normal consumer use.

#### **CANADA**

WHMIS HAZARD SYMBOL AND CLASSIFICATION

#### **16. OTHER INFORMATION**



Health: 1 Flammability: 2 Physical Hazard: 1 Personal protexction:

**DATE PREPARED:** November 2018 **SUPERSEDES MSDS: September 2017** 

#### MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Dental Ventures of America, Inc does not assume any liability for the accuracy or completeness of the information contained herein. Finial determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. 6



#### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT DESCRIPTION:** Curing Accelerator

Date Revised: November 2016

MANUFACTURER Dental Ventures of America, Inc. 1787 Pomona Rd., Suite C Corona, 92880, CA. Emergency Contact: Infotrack: 800.535.5053 Emergency Phone: 951.270.0606 Alternative Emergency Phone: 800.228.6696

**USE OR APPLICATION:** Used in conjunction with Rocket Glue for dental purposes.

USES ADVISED AGAINST: Use only as directed.

#### 2. HAZARD(S) IDENTIFICATION

#### **GHS CLASSIFICATIONS**

Health:

Acute Toxicity (Oral), Category 3 Acute Toxicity (Dermal) Category 3 Acute Toxicity (Inhalation), Category 3 Skin Irritation, Category 2 Eye Irritation, Category 2 Aspiration Hazard, Category 1 Specific Target Organ Toxicity (Repeated Exposure), Category 2 Specific Target Organ Toxicity (Single Exposure), Category 3

Physical:

Flammable Liquids, Category 2

SIGNAL WORD DANGER

#### **GHS LABEL ELEMENTS**



HAZARD STATEMENTSH225: Highly flammable liquid and vapor.H301: Toxic if swallowed.



#### HAZARD STATEMENTS, Cont.

- H304: May be fatal if swallowed and enters airways.
- H311: Toxic in contact with skin.
- H315: Causes skin irritation
- H319: Causes serious eye irritation
- H330: Fatal if inhaled.
- H373: May cause damage to organs through prolonged or repeated exposure.
- H350: May cause cancer.
- H351: Suspected of causing cancer.

#### PRECAUTIONARY STATEMENTS

#### **Prevention Statement(s)**

- P102: Keep out of reach of children
- P103: Read label before use
- P201: Obtain special instructions before use.
- P202: Do not handle until al safety precautions have been read and understood.
- P210: Keep away from heat/sparks/hot surfaces. No smoking.
- P273: Avoid release to the environment.
- P280: Wear protective gloves/protective clothing eye protection/face protection.
- P233: Keep container tightly closed.
- P240: Ground/bond container and receiving equipment.
- P241: Use explosion-proof electrical/ventilating/lighting equipment.
- P242: Use only non-sparking tools.
- P243: Take precautionary measures against static discharge.
- P264: Wash skin and hands thoroughly after handling.
- P270: Do not eat, drink or smoke when using this product.
- P271: Use only outdoors or in a well-ventilated area.
- P260: Do not breathe dust/fume/gas/mist/vapors/spray.
- P280: Wear protective gloves/protective clothing/eye and face protection.

#### **Response:**

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes, Remove contact lenses, if present and easy to do. Continue rinsing.
- P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340: IF INHALED: Remove to fresh air and keep at rest in position comfortable for breathing.
- P312: Call a POISON CENTER or doctor/physician if you feel unwell.

#### Storage:

- P403+P233: Store in a well-ventilated place. Keep container tightly closed.
- P403+P235: Store in a well-ventilated place. Keep cool.
- P405: Store locked up.

#### **Disposal:**

P501: Dispose of in a manner consistent with federal, state and local regulations.



#### 3. COMPOSITION /INFORMATION ON INGREDIENTS

Under GHS-OSHA 4.11 the precise composition of this product is withheld as confidential business information (CBI). A more complete disclosure can be provided to a health, or safety professional when necessary.

SUBSTANCES or MIXTURE Liquid

NO. COMPONENT	CAS.NO	PERCENT
Heptane	142-82-5	65-75
Acetone	67-64-1	15-25
N,N-DIMETHYL-P-TOLUIDINE	99-97-8	5-15

#### 4. FIRST-AID MEASURES

EYES: Flush eye with water for 15 minutes. Get medical attention.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms reoccur. Wash clothing before reuse.

**INHALATION:** Immediately remove patient to fresh air. If breathing has stopped, give artificial respira tion. Use oxygen as required. provided a qualified operator is available. Get medical attention immediately.

**INGESTION:** Do Not induce vomiting. Contact physician at once.

#### SIGNS AND SYMPTOMS OF OVER EXPOSURE:

EYES: Causes eye irritation.

SKIN: Remove contaminated clothing and wash affected areas with soap and water, Prolonged or repeated contact can cause dermatitis in sensitive individuals. Contact a physician if irritation persists.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

ACUTE EFFECTS: Eye, skin and respiratory irritant.

CHRONIC EFFECTS: Prolonged or repeated exposure may cause skin dermatitis, central nervous system depression and lung damange.

#### 5. FIRE-FIGHTING MEASURES

GENERAL HAZARD: Highly flammable

**EXTINGUISHING MEDIA:** Use dry chemical, foam or carbon dioxide.

HAZARDOUS COMBUSTION PRODUCTS: Combustible by-products of carbon monoxide and dioxide.

**FIRE FIGHTING PROCEDURES:** Isolate immediate fire hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Moive undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel.

**FIRE FIGHTING EQUIPMENT:** As in any fire, wear self-contained breathing apparatus pressuredemand, (MSHA/NIOSH APPROVED OR EQUIVALENT) and full protective gear.



#### SENSITIVE TO STATIC DISCHARGE:

Electrostatic charges may be generated during pumping. Ground all containers.

#### 6. ACCIDENTAL RELEASE MEASURES

#### METHODS AND MATERIALS FOR CONTAINMENT:

Small Spill: Ventilate area and remove sources of ignition. Confine and remove with inert absorbent. Large Spill: This material is water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

#### **CLEANUP PROCEDURES:**

Water Spill: Avoid runoff into storm sewers and ditches wich lead to waterways.

**Land Spill**: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent(clay, sand) materials and dispose of properly.

**Special Protective Equipment:** Use plastic/rubber gloves, chemical splash goggles or safety glasses with side shields.

#### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Avoid breathing of vapors. Use only in well ventilated areas. When handling, do not eat, drink or smoke.

HANDLING: Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

**STORAGE:** Keep away from heat, sparks and flame, sunlight and ignition sources. Do not place in direct sunlight or allow contamination with incompatible materials. Do not return any used material to storage container. Keep tightly capped. Storage Temperature: Ambient room temperature (70F/21C). **ELECTROSTATIC ACCUMULTION HAZARD**: Take measures to prevent the build-up of elctrostatic charge.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during use of this product.

**PERSONAL PROTECTIVE EQUIPMENT: EYES AND FACE:** For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact wear splash-proof goggles. **SKIN:** Wear chemical resistant gloves (Buna-N or Polyvinyl alcohol) and apron to protect skin and clothing.

**RESPIRATORY:** NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not know, or an circumstances where air purifying respirators may not provide adequate protection.

**WORK HYGIENIC PRACTICES:** Avoid direct contact and breathing vapor. Use with adequate ventilation. Wash hands with soap and water after use.



## ROCKET ACCELERATOR, Pg. 4

#### EXPOSURE GUIDELINES OSHA HAZARDOUS COMPONENTS (29cfr1910.1200

	EX	EXPOSURE LIMITS			
Chemical Name	OSHA PEL	ACGIH TLV	SupplierOEL		
	ppm mg/m3	ppm mg/m3	ppm mg/m3		
Heptane	TWA 500 2000 STEL	400 1640 500 2050			
Acetone	TWA 1000 2400 ppm(1) mg/m3(1)	500 ppm mg/m3	NL ppm NLmg/m3		
	STEL ppm mg/m3	750ppm mg/m3	NLppm NLmg/m3		

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid ODOR: Moderate odor APPEARANCE: Transparent, colorless liquid FLASHPOINT AND METHOD: 0C (Calculated) VAPOR PRESSURE: Not established VAPOR DENSITY: Not established BOILING POINT: 33 C (Calculated) SOLUBILITY IN WATER: Negligible EVAPORATION RATE: Not established SPECIFIC GRAVITY: 0.7 VISCOSITY #1: Not established (VOC): 574.000 g/L

#### **10. STABILITY AND REACTIVITY**

STABLE: Yes
HAZARDOUS POLYMERIZATION: Will not occur.
CONDITIONS TO AVOID: Heat, sparks and flame
INCOMPATIBLE MATERIALS: Pure oxygen and strong oxidizing agents
POSSIBILITY OF HAZARDOUS REACTIONS: Under normal conditions of storage and use, hazardous reactions will not occur.



#### **11. TOXICOLOGICAL INFORMATION**

#### ACUTE TOXICITY

Chemical Name	Oral LD 50 (rat)	
Heptane	No Data Available	
Acetone	5800 mg/kg	
N,N-dimethyl-p-toluidine 1650 mg/kg (rat)		
Further data is available upon request.		

Dermal LD 50 (rabbit)Inhalation LC50 (rat)No Data Available103000mg/L per 4 hr (rat)7426 mg/kg(guinea pig)50100mg/kg>2000 mg/kg (rat)498 mL/m3

#### 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** Prevent product from entering drains or sewers in cas of spill. ECOTOXICOLOGICAL INFORMATION: No data available. BIOACCUMULATION/ACCUMULATION: No data available.

#### **13. DISPOSAL CONSIDERATIONS**

#### WASTE DISPOSAL METHOD:

S56: Dispose of this material and its container to hazardous or special waste collection point.

Please refer to Section 8 for Exposure Controls/Personal Protection.

#### **14. TRANSPORT INFORMATION**

DOT (Department of Transportation, Air (ICAO/IATA), Vessel (IMO/IMDG)

UN Number: 1993

UN Proper Shipping Name: Flammable liquids N.O.S. (contains Heptane, Acetone, Dimethyl-p-toluidine-

TRANSPORT HAZARD CLASS(S) 3

PACKING GROUP NUMBER: II

**GUIDANCE ON TRANSPORT IN BULK: None given** 

SPECIAL PRECAUTIONS: None given.

AIR (ICAO/IATA) SHIPPING NAME: SEE ABOVE

VESSEL (IMO/IMDG): SHIPPING NAME: SEE ABOVE

Comments: The transport information provided in this section only applies to the material formulation;/ itself, and is not specific to any package/configuration. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container vlume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organizations to fllow all applicable laws, regulations and rules relating to the transportation of the material.



#### **15. REGULATORY INFORMATION**

UNITED STATES			
SARA TITLE III (SUPERFUND AMENDMENS AND REAUTHORIZATION ACT)			
FIRE: yes PRESSURE GENER	ATING: No REA	CTIVITY: No ACUTE: Yes CHRONIC: No	
CERCLA (COMPREHENSIVE REPONSE, COMPENSATION AND LIABILITY ACT)			
Chemical Name	Wt.%	CERCLA RQ	
Acetone	15-25	5,000	
TSCA (TOXIC SUBSTANCE CONTROL ACT)			
Chemical Name CAS			
Heptane		142-82-5	
N,N-DIMETHYL-P-TOLUIDINE		99-97-8	
TSCA STATUS: All ingredients in this mixture are in compliance with TSCA			

CALIFORNIA PROPOSITION 65 WARNING: This product contains chemicals known to the State of California to cause cancer, birthdefects, or other reproductive harm. (Dimethyl-p-toluidine, CAS 99-97-8), (Benzine contaminant in acetone, less than 0.003% CAS 71-43-2).

		,
Chemical Name	Wt.%	Listed
N,N-DIMETHYL-P-TOLUIDINE	5-15	Cancer

#### **16. OTHER INFORMATION**

DATE PREPARED: November 2016 SUPERSEDES MSDS: April 2015

#### HMIS RATING:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	0
PERSONAL PROTECTION	Η



#### MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Dental Ventures of America, Inc does not assume any liability for the accuracy or completeness of the information contained herein. Finial determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

SDS ROCKET ACCELERATOR 2016