SAFETY DATA SHEETS

This SDS packet was issued with item:

073262433

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

073262417 073262425



Printing date 04/20/2015

Version US-EN-Rev 1

Reviewed on 04/17/2015

1 Identification

· Product identifier

Trade name: G-BOND™

Relevant identified uses of the substance or mixture and uses advised against

Dental material

The product is intended for professional use.

To avoid risks for humans and environment obtain instructions.

- · Application of the substance / the mixture Dental bonding material
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC America Inc. 3737 W. 127th Street Alsip, IL 60803 USA

sds@gcamerica.com

- · Information department: Regulatory Affairs
- · Emergency telephone number:

During normal opening times (Mon.-Fri. 8:00 AM-5:00 PM CST): +1 (708) 597-0900 Transportation (CHEMTREC®) Emergency Telephone No. +1 (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Additional information:

The information provided is in regards to the toxicity and hazard rating(s) of the individual component(s) in the formulation. The associated risk(s) depends on the route(s) of exposure. The hazard rating system is based entirely on the existence of the risk(s) and does not take into account the likelihood of reduced risk(s) through proper usage and handling.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- Hazard-determining components of labeling: acetone

(Contd. on page 2)

Printing date 04/20/2015 Version US-EN-Rev 1 Reviewed on 04/17/2015

Trade name: G-BOND™

(Contd. of page 1)

urethane dimethacrylate (UDMA) dimethacrylate component** phosphoric acid ester monomer**

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Wear protective gloves / eye protection / face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Additional information:
- 17 % of the mixture consists of component(s) of unknown toxicity.
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *1 Fire = 3

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
67-64-1	acetone	25-50%
72869-86-4	urethane dimethacrylate (UDMA)	5-10%
	dimethacrylate component**	5-10%
	phosphoric acid ester monomer**	1-5%
	photoinitiator**	1-5%
	(Contd	on page 3)

- *,*

Printing date 04/20/2015 Version US-EN-Rev 1 Reviewed on 04/17/2015

Trade name: G-BOND™

(Contd. of page 2)

· Additional information:

If a substance is marked with **, then substance is a trade secret. This is allowed under OSHA's Hazard Communication Standard (HCS) as a trade secret and under GHS as Confidential Business Information (CBI).

4 First-aid measures

- · Description of first aid measures
- **General information:**

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

· After eve contact:

Protect unharmed eve.

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources

Avoid contact with the eyes and skin.

Wear protective clothing.

(Contd. on page 4)

Printing date 04/20/2015 Version US-EN-Rev 1 Reviewed on 04/17/2015

Trade name: G-BOND™

(Contd. of page 3)

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Observe instructions for use.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray on a naked flame or any incandescent material.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Observe instructions for use / storage.

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm

(Contd. on page 5)

Printing date 04/20/2015 Version US-EN-Rev 1 Reviewed on 04/17/2015

Trade name: G-BOND™

(Contd. of page 4)

 Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm

Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

- **Breathing equipment:** Suitable respiratory protective device recommended.
- · Protection of hands: Protective gloves
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses

9 Physical and chemical properties

Information on basic physical and chemical properties General Information Appearance:				
Form: Color: Odor: Odor threshold:	Liquid Light yellow Ester-like Not determined.			
· pH-value:	Not determined.			
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 55 °C (131 °F)			
· Flash point:	-10 °C (14 °F)			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	Undetermined.			

(Contd. on page 6)

Printing date 04/20/2015 Version US-EN-Rev 1 Reviewed on 04/17/2015

Trade name: G-BOND™

	(Contd. of page
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits:	
Lower:	2.6 Vol %
Upper:	13.0 Vol %
Vapor pressure:	Not determined.
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wa	ater): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	39.0 %
Water:	19.7 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable at ambient temperature.
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · **Incompatible materials:** No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification: No further relevant information available.
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.

(Contd. on page 7)

Printing date 04/20/2015 Version US-EN-Rev 1 Reviewed on 04/17/2015

Trade name: G-BOND™

(Contd. of page 6)

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
silicon dioxide	3	
butylated hydroxytoluene (BHT)	3	
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		

None of the ingredients is listed. • Carcinogenic categories' legend:

IARC Group 1: The agent is carcinogenic to humans.

IARC Group 2A: The agent is probably carcinogenic to humans.

IARC Group 2B: The agent is possibly carcinogenic to humans.

IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

IARC Group 4: The agent is probably not carcinogenic to humans.

NTP K: Known to be human carcinogen.

NTP R: Reasonably anticipated to be human carcinogen.

12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 8)

Printing date 04/20/2015 Version US-EN-Rev 1 Reviewed on 04/17/2015

Trade name: G-BOND™

· Recommended cleansing agent: Water, if necessary with cleansing agents.

(Contd. of page 7)

UN-Number DOT, ADR, IMDG, IATA	UN1090	
UN proper shipping name DOT ADR IMDG, IATA	Acetone solution 1090 Acetone solution ACETONE solution	
Transport hazard class(es)		
рот		
R AMMANE LOUD	O Elemental la l'ancida	
· Class · Label	3 Flammable liquids 3	
ADR	· ^Z	
3		
· Class · Label	3 (F1) Flammable liquids 3	
· Labei · IMDG, IATA		
3		
· Class · Label	3 Flammable liquids 3	
Packing group DOT, ADR, IMDG, IATA	II	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user Danger code (Kemler): EMS Number:	Warning: Flammable liquids 33 F-E,S-D	
Transport in bulk according to Annex	x II of Not applicable.	

Printing date 04/20/2015 Version US-EN-Rev 1 Reviewed on 04/17/2015

Trade name: G-BOND™

	(Contd. of pag
Transport/Additional information:	
· ADR	
Excepted quantities (EQ)	Code: E2
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
·IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN1090, Acetone solution, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · SARA (Superfund Amendments and Reauthorization Act)

Section 355 (extremely hazardous substances):	
None of the ingredient is listed.	
· Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
· TSCA (Toxic Substances Control Act):	
acetone	
urethane dimethacrylate (UDMA)	
dimethacrylate component**	
silicon dioxide	
photoinitiator**	
water, distilled	

· Carcinogenic categories

· EPA (Environmental Protection Agency)	
acetone	1
TLV (Threshold Limit Value established by ACGIH)	
acetone	A4
butylated hydroxytoluene (BHT)	A4
aluminum oxide	A4
· NIOSH-Ca (National Institute for Occupational Safety and Heal	th)
None of the ingredients is listed.	
· GHS label elements	

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

Printing date 04/20/2015 Version US-EN-Rev 1 Reviewed on 04/17/2015

Trade name: G-BOND™

(Contd. of page 9)

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

acetone

urethane dimethacrylate (UDMA)

dimethacrylate component**

phosphoric acid ester monomer**

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Wear protective gloves / eye protection / face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Department issuing SDS: Regulatory Affairs

Contact:

Regulatory Affairs

Telephone No. +1 (708) 597-0900

sds@gcamerica.com

· Date of preparation / last revision 04/20/2015 / -

Abbreviations and acronyms:

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

HCS: Hazard Communication Standard (USA)

MSDS: Material Safety Data Sheet

SDS: Safety Data Sheet

ECHA: European Chemicals Agency

OSHA: Occupational Safety and Health Administration (USA)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 11)

Printing date 04/20/2015 Version US-EN-Rev 1 Reviewed on 04/17/2015

Trade name: G-BOND™

(Contd. of page 10)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Sources

- Manufacturers' MSDSs/SDSs
- OSHA (https://www.osha.gov/dts/chemicalsampling/toc/chmcas.html)
- TOXNET (http://toxnet.nlm.nih.gov/)
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

· Notes:

CAS Registry Number is a Registered Trademark of the American Chemical Society. CHEMTREC® is a registered service mark of the American Chemistry Council, Inc.

* Data compared to the previous version altered. This version replaces all previous versions.

· Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.