SAFETY DATA SHEETS

This SDS packet was issued with item: 074585287

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071365550 074586327



Effective Date 23-Mar-2020

SAFETY DATA SHEET

Version 4

1. IDENTIFICATION

Product Identifier Product Name	FLEXACF	RYL SOFT LIQUID
Other means of identification SDS# UN/ID No Product Code	038 UN1993 1103, 110)4, 1106, 1107, 1108, 1109, 1123, 1134, 1156
Recommended use of the che	emical and	restrictions on use
Recommended Use		dental prosthesis
Details of the supplier of the s Supplier Address		tal Mfg. Co., Inc. ner Dr.
Emergency telephone numbe	<u>r</u>	
Company Phone Number Emergency Telephone (INFO)	(RAC)	+1-847-215-6622 +1-352-323-3500 (International) 800-535-5053 (North America)
Authorized European Represe	<u>entative</u>	MediMark® Europe Sarl 11 rue Emile Zola. BP 2332 38033 Grenoble Cedex 2 France Tel: +33 4 76 86 43 22 Fax: +33 4 76 17 19 82 Email: info@medimark-europe.com

2. HAZARDS IDENTIFICATION

Classification

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Serious eye damage / eye irritation	Category 2A
STOT Single exposure	Category 3
Hazardous to the aquatic environment- Acute hazard	Category 2

Signal word Warning

Hazard statements H226 Flammable liquid and vapor.

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.



Physical state Liquid

Odor Acrid

Precautionary Statements - Prevention

- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/ hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash hands thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements – Response

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use CO₂, dry chemical or foam for extinction.

Precautionary Statements – Storage	P403+P233	Store in a well-ventilated place. Keep container tightly closed.
	P403+P235	Store in a well-ventilated place. Keep cool.

Precautionary Statements – Disposal P501 Dispose of contents/container to an approved waste disposal plant.

Hazardous component(s) for labeling Contains n-Butyl methacrylate

3. COMPOSITION / INFORMATION ON INGREDIENTS

Classification of the substance or mixture

Chemical Name	CAS No	Weight - %	Trade Secret
Citric Plasticizer	Proprietary	<50	*
N-Butyl Methacrylate	97-88-1	<50	*
Trimethylolpropane Trimethacrylate	3290-92-4	<5	*
N, N-Dimethyl-p-Toluidine	99-97-8	<5	*

*Specific chemical weight has been withheld as a trade secret.

	4. FIRST AID MEASURES
First aid measures	
Inhalation	Remove victim to fresh air. Keep at rest in a position comfortable for breathing. Seek immediate medical attention if needed.
Eye contact Rinse immediately with plenty of water, including under the eyelids, for at least 15 minutes. If irritation p call a physician immediately.	
call a physician immediately. Ingestion If ingested, do not induce vomiting. Drink plenty of water or milk immediately. If vomiting, continue to offe water or milk. Never give anything by mouth to an unconscious person. Call a physician or poison contro center immediately and provide an estimate of when and how much material was ingested. Seek immedi medical attention.	
Skin Contact	Wash with soap and water. If irritation, redness or swelling persists, call a physician immediately. Take off contaminated clothing and wash before reuse.
Most important symptoms	s and effects, both acute and delayed
Symptoms	Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. May cause an allergic skin reaction.
Indication of any immedia Note to physicians	te medical attention and special treatment needed Treat symptomatically.
	5. FIRE-FIGHTING MEASURES
Sensitivity to Sta Protective equipment and p A self-contained breathing ap	
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions, prote Personal precautions	ective equipment and emergency procedures Before cleaning any spill or leak, individuals must wear personal protective equipment as required. Remove any contaminated clothing and wash thoroughly before reuse.
Environmental precautions	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Prevent product from entering drains. Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.
Methods and material for co	ontainment and clean-up
	Collect spillage. Do not adsorb onto sawdust or other combustible materials. Transfer to a container for disposal or recovery. Use only non-sparking tools.
	7. HANDLING AND STORAGE
Precautions for safe handli	ng Do not eat, drink, or smoke at the work place. Wash thoroughly after handling. Avoid breathing vapors. Use in a well-ventilated area. The vapor is heavier than air: beware of pits and confined spaces. Ground container and receiving equipment. Use explosion proof electrical equipment. Use only non-sparking tools. Take precautionary measure against static charge.
Flexacryl Soft Liquid 038 v.4	Page 3 of 1

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, open flame, hot surfaces – No smoking. Protect from sunlight. Methacrylate stored in bulk quantities must be kept in contact with air (oxygen). Keep at temperature not exceeding 30°C/86 °F. Monomer vapors are uninhabited and may form polymers in vent or flame arresters, resulting in blockage of vents.

Incompatible materials

Polymerization catalysts, such as peroxy or azo compounds, strong acids, alkalis and oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines			
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
n-Butyl Methacrylate	STEL: n/a	n/a	n/a
97-88-1	TWA: n/a		
ACGIH = American Conference of Goverr PEL = Permissible Exposure Levels / STE			
Appropriate engineering controls	Do not eat, drink or smoke at the work place. Provide adequate ventilation, including appropriate local extraction, to ensure that the occupational exposure limit is not exceeded. Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.		is not exceeded. Consideration
Engineering controls	Apply technical measures t	o comply with the occupational exp	osure limits.
Individual protection measures, su Eye / face protection	Depending on the use of th US OSHA 29CFR SS1910.	is product, safety glasses or goggle	es may be worn. If necessary, refer to f Canada or the EC member states. e in case of exposure to eyes.
Skin and body protection If anticipated that prolonged and repeated skin contact will occur during use of this product, v gloves for routine use. If necessary, refer to US OSHA 29CFR SS1910.138 or the appropriat standards of Canada or the EC member states. Wear suitable protective clothing.		SS1910.138 or the appropriate	
Respiratory protection No special respiratory protection is required under typical circumstances of use or handling necessary, use only respiratory protection authorized per US OSHA requirement in 29 CF 1910.134, or applicable US state regulations, or the appropriate standards of Canada, its provinces, or the EC member states. VENTILATION: Local exhaust at processing equipment		DSHA requirement in 29 CFR SS e standards of Canada, its	
General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly handling. Food, beverages and tobacco products should not be carried, stored, or consumption where this material is in use. Wash hands thoroughly before eating, drinking, or smoking		e carried, stored, or consumed	

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Acrid
Color	Clear to slightly yellow	Odor threshold	Not determined
Property	Values	Remarks / Method	
Hq	Not determined		
Melting point / freezing point	Not determined		
Boiling point / boiling range	Not determined		
Flash point	59°C/13 9 °F		
Evaporation rate	Not determined		
Flammability (solid, gas)	Not applicable		
Flammability limits in air			
Upper flammability limit	Not determined		
Lower flammability limit	Not determined		
Vapor pressure	Not determined		

Flexacryl Soft Liquid 038 v.4

Vapor density	Not determined
Specific gravity	0.978 g/mL
Water solubility	Not determined
Solubility in other solvents	Not determined
Autoignition temperature	Not determined

10. STABILITY AND REACTIVITY

<u>Reactivity</u> Will exothermically polymerize in the presence of initiators.

<u>Chemical stability</u> Stable in the presence of inhibitor.

Possibility of hazardous reactions

Hazardous polymerization Susceptible to polymerization initiated by prolonged storage or the presence of catalyst.

Conditions to avoid
Materials to avoidHeat and direct sunlight.Naterials to avoidPolymerization catalysts, such as peroxy or azo compounds, strong acids, alkalis and oxidizing agents.Incompatible materialsOxidizers
Reducing agent
Material has strong solvent properties and can soften paint and rubber.

Hazardous decomposition products

Does not decompose up to auto-ignition temperature.

11. TOXICOLOGICAL INFORMATION

Mixture ToxicityNo data availableComponent ToxicityNo data availableRoutes of Exposure – No data available

Component information

Chemical Name	ORAL LD50	DERMAL LD50	INHALATION LC50
N-Butyl Methacrylate 97-88-1	>2000 mg/kg	2000 mg/kg	4901 ppm (29 mg/l) 4 h
Trimethylolpropane Trimethacrylate 3290-92-4	>5000 mg/kg (rat)		-
N, N-Dimethyl-p-Toluidine 99-97-8	1650 mg/kg (rat)	>2000 mg/kg (rat)	498 mL/m ³ (rat)

Information on physical, chemical and toxicological effects

Inhalation	May cause respiratory irritation.
Eye contact	Causes severe eye irritation.
Skin contact	Causes skin irritation.
Ingestion	May be harmful if swallowed.
Delayed and immediate effect	s as well as chronic effects from short and long-term exposure
Sensitization	May cause allergic skin reaction.
Carcinogenicity	Not classifiable as a human carcinogen
STOT – single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT - repeated exposure	Not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component information N-Butyl methacrylate - Toxic to aquatic life.

Chemical Name	Algae / aquatic plants	Fish	Crustacea
N-Butyl Methacrylate 97-88-1	31.2 mg/l: 72 h selenastrum capricornutum mg/L EC50	11 mg/l: 96 h Pimephales promelas mg/L LC50 flow-through;	25.4 mg/l: 48 h Daphnia magna mg/L EC50
Trimethylolpropane Trimethacrylate 3290-92-4	-	-	-
N, N-Dimethyl-p- Toluidine 99-97-8	-	46-52 mg/l: 96 h Pimephales promelas mg/L LC50 flow-through	-

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Follow all local and national government regulations in disposing material or contaminated packaging. For U.S. - Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging

Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards due to residual material associated with empty containers. Dispose of all empty containers in accordance with local and national government regulations.

14. TRANSPORTATION INFORMATION

DOT

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (n-Butyl Methacrylate, stabilized /
	Plasticizer solution)
Hazard Class	3
Packing Group	

For domestic ground shipments, containers of less than 450 L capacity are not regulated by DOT.

IATA

UN / ID No	UN1993	
Proper shipping name	Flammable liquid, n.o.s. (n-Butyl Methacrylate, stabilized / Plasticizer solution)	
Hazard Class	3	
Packing Group		

IMDG

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (n-Butyl Methacrylate, stabilized /
	Plasticizer solution)
Hazard Class	3
Packing Group	

15. REGULATORY INFORMATION

International Inventories

TSCA DSL EINECS Listed United States Toxic Substances Control Act, Section 8(b) Inventory

Listed Canadian Domestic Substances List

Listed European Inventory of Existing Chemical Substances

EU Regulations	EC No. 1272/2008 (CLP) Classification, Labeling, Packaging
	Medical Devices Directive 93/42/EEC - Class I Medical Devices

<u>US Federal Regulations</u> SARA 302 – not listed, Extremely hazardous substance SARA 311 / 312 Hazard Categories - listed N-Butyl methacrylate 97-88-1 SARA 313 – not listed, N-Butyl methacrylate 97-88-1

<u>US State Regulations</u> California Proposition 65 – Warning. This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin: None

US State Right-to-Know Regulations Not established

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability
	Not determined	Not determined	Not determined
HMIS	Health Hazards	Flammability	Physical Hazards
	2	2	2

Effective Date 23-Mar-2020

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet