SAFETY DATA SHEETS

This SDS packet was issued with item: 075039607

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

075035811 075035829 075035837 075035845 075035852 075035860 075035878 075035886 075035894 075035902 075035910 075035928 075035936 075035944 075035951 075035969 075035977 075035985 075035993 075036009 075036017 075036025 075036033 075036041 075036058 075036066 075036074 075036082 075036090 075036108 075036116 075036124 075036132 075036140 075036157 075036165 075036173 075036181 075036199 075036207 075036215 075036223 075036231 075036249 075036256 075038955 075038963 075038971 075038989 075038997 075039003 075039011 075039029 075039037 075039045 075039052 075039060 075039078 075039086 075039044 075039102 075039110 075039128 075039136 075039144 075039151 075039169 075039177 075039185 075039193 075039201 075039219 075039227 075039235 075039243 075039250 075039268 075039276 075039284 075039292 075039300 075039318 075039326 075039334 075039342 075039359 075039367 075039375 075039284 075039292 075039409 075039417 075039425 075039334 075039454 075039557 075039367 075039375 075039482 075039391 075039508 075039516 075039524 075039532 075039540 075039557 075039565 075039573 075039581 075039599 075039508 075039516 075039524 075039532 075039557 075039565 075039573 075039581 075039599 075039508 075039623 075039631 075039542 075039557 075039664 075039672 075039680 075039680 075039588 075039588 075039573 075039588 075039573 075039588 075039573 075039588 075039599 075039508 075039623 075039631 075039548 075039555 075039664 075039672 075039680 075039688 075039598 075039714 075039722 075039730 075039748 075039755 075039763 075039771

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

075039912 075040365 075041066 075041595



Material Safety Data Sheet

Copyright, 2004, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M(TM) ESPE(TM) Imprint(TM) II Light Body Base MANUFACTURER: 3M DIVISION: 3M ESPE Dental Products

> ADDRESS: 3M Center St. Paul. MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 06/24/2004 Supercedes Date: 10/28/2002

Document Group: 18-1383-1

Product Use:

Limitations on Use: For use only by dental professionals Specific Use: Impression material

SECTION 2: INGREDIENTS

Ingredient VINYL POLYDIMETHYLSILOXANE QUARTZ SILICA SILANE TREATED SILICA CROSSLINKER (NJTSRN 26175-23140) <u>C.A.S. No.</u> 68083-19-2 14808-60-7 67762-90-7 Trade Secret <u>% by Wt</u> 35 - 45 35 - 45 5 - 10 5 - 10

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste Odor, Color, Grade: Odorless General Physical Form: Solid Immediate health, physical, and environmental hazards: are anticipated.

3.2 POTENTIAL HEALTH EFFECTS

No immediate health, physical or environmental hazards

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Inhalation:

No health effects are expected. This material contains quartz silica, which is a known carcinogen. No exposure to crystalline silica is anticipated during normal intended handling of the Imprint II paste or grinding of the cured impression. Therefore, the quartz in this material does not pose a cancer risk when the product is used as intended.

Ingestion:

Ingestion may cause:

Gastrointestinal Effects: Signs/symptoms may include stomach upset, nausea, vomiting and diarrhea.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: No need for first aid is anticipated.

If Swallowed: No need for first aid is anticipated.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature Flash Point Flammable Limits - LEL Flammable Limits - UEL No Data Available Not Applicable Not Applicable Not Applicable

5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Collect as much of the spilled material as possible. Clean up residue. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact. Avoid prolonged or repeated skin contact.

7.2 STORAGE

Not applicable.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Not applicable.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact. The following eye protection(s) are recommended: Safety Glasses with side shields.

8.2.2 Skin Protection

Avoid prolonged or repeated skin contact. Gloves not normally required.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Do not ingest.

8.3 EXPOSURE GUIDELINES

| | Ingredient | <u>Authority</u> | <u>Tvpe</u> | <u>Limit</u> | Additional Information |
|---|--|------------------|-------------------------|-----------------------|------------------------|
| ~ | SILANE TREATED SILICA OUARTZ SILICA | CMRG ACGIH | CEIL TWA, respirable | 5 mg/m3 0.05 mg/m3 | Table A2 |
| | QUARTZ SILICA | ACOIII | i w A, respirable | 0.05 11211.5 | Those The |

3M MATERIAL SAFETY DATA SHEET 3M(TM) ESPE(TM) Imprint(TM) II Light Body Base 06/24/2004

QUARTZ SILICA

OSHA

TWA, respirable

Table Z-1A

0.1 mg/m3

SOURCE OF EXPOSURE LIMIT DATA: ACGIH: American Conference of Governmental Industrial Hygienists CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| Specific Physical Form: | Paste |
|--------------------------|-------------------|
| Odor, Color, Grade: | Odorless |
| General Physical Form: | Solid |
| Autoignition temperature | No Data Available |
| Flash Point | Not Applicable |
| Flammable Limits - LEL | Not Applicable |
| Flammable Limits - UEL | Not Applicable |
| Boiling point | Not Applicable |
| Vapor Density | Not Applicable |
| Vapor Pressure | Not Applicable |
| Specific Gravity | No Data Available |
| pH | No Data Available |
| Melting point | No Data Available |
| Solubility in Water | Nil |
| Evaporation rate | Not Applicable |
| Percent volatile | No Data Available |
| Viscosity | No Data Available |

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance Carbon monoxide Carbon dioxide <u>Condition</u> During Combustion During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

3M MATERIAL SAFETY DATA SHEET 3M(TM) ESPE(TM) Imprint(TM) II Light Body Base 06/24/2004

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Cure (harden, set, or react) the product according to product instructions. Dispose of completely cured (or polymerized) wastes in a sanitary landfill. As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

LE-F000-5202-0

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 16: NFPA hazard classification heading was modified.

Copyright was modified.

Section 8: Exposure guidelines data source legend was modified.

Section 5: Fire fighting procedures information was modified.

Section 15: 311/312 hazard categories heading was modified.

Section 15: International regulations information was modified.

Section 15: State regulations information was modified.

Section 15: US federal regulations information was modified.

- Section 10: Hazardous polymerization heading was modified.
- Section 2: Ingredient table was modified.
- Section 16: NFPA explanation was modified.
- Section 15: Inventories information was modified.
- Section 12: Ecotoxicological information heading was modified.
- Section 12: Chemical fate information heading was modified.

Section 8: Exposure guidelines ingredient information was modified.

- Section 16: NFPA hazard classification for special hazards was modified.
- Section 12: Ecotoxicological phrase was modified.
- Section 12: Chemical Fate phrase was modified.

Section 2: Ingredient phrase was added.

3M MATERIAL SAFETY DATA SHEET 3M(TM) ESPE(TM) Imprint(TM) II Light Body Base 06/24/2004

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 18-1599-2 | Version Number: | 2.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 02/05/15 | Supercedes Date: | 09/06/02 |

Product identifier 3MTM ESPETM ImprintTM II Light Body

ID Number(s):

70-2010-3394-4, 70-2010-3395-1

Recommended use Dental Product, Impression material Restrictions on use For use only by dental professionals.

Supplier's details

| MANUFACTURER: | 3M |
|---------------|---------------------------------------|
| DIVISION: | 3M ESPE Dental Products |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, U |

 ADDRESS:
 3M Center, St. Paul, MN 55144-1000, USA

 Telephone:
 1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

18-1378-1, 18-1383-1

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy.

3MTM ESPETM ImprintTM II Light Body 02/05/15

In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright,2014,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 18-1383-1 | Version Number: | 6.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 10/20/14 | Supercedes Date: | 02/22/11 |

SECTION 1: Identification

1.1. Product identifier

 $3M^{\ensuremath{\text{TM}}}$ ESPE^{\ensuremath{\text{TM}}} Imprint^{\ensuremath{\text{TM}}} II Light Body Base

Product Identification Numbers LE-F000-5202-0

1.2. Recommended use and restrictions on use

Recommended use Dental Product, Impression material Restrictions on use For use only by dental professionals

| 1.3. Supplier's details | |
|-------------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | 3M ESPE Dental Products |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements Signal word Not applicable.

Symbols Not applicable.

Pictograms

Not applicable.

2.3. Hazards not otherwise classified None.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|-------------------------------------|---------------|------------------------|
| VINYL POLYDIMETHYLSILOXANE | 68083-19-2 | 35 - 45 Trade Secret * |
| QUARTZ SILICA | 14808-60-7 | 35 - 45 Trade Secret * |
| SILANE TREATED SILICA | 67762-90-7 | 5 - 10 Trade Secret * |
| CROSSLINKER (NJTSRN 26175-23140) | Trade Secret* | 5 - 10 Trade Secret * |
| POLYETHYLENE GLYCOL, SILOXANE- | 27306-78-1 | < 1 Trade Secret * |
| TERMINATED | | |
| GLYCOLS, POLYETHYLENE, ALLYL METHYL | 27252-80-8 | < 0.5 Trade Secret * |
| ETHER | | |

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|------------------|-------------------------|
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Observe precautions from other sections.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-----------------------|------------|--------|-------------------------------|---------------------|
| QUARTZ SILICA | 14808-60-7 | OSHA | TWA concentration(as total | |
| | | | dust):0.3 mg/m3;TWA | |
| | | | concentration(respirable):0.1 | |
| | | | mg/m3(2.4 millions of | |
| | | | particles/cu. ft.) | |
| QUARTZ SILICA | 14808-60-7 | ACGIH | TWA(respirable | A2: Suspected human |
| | | | fraction):0.025 mg/m3 | carcin. |
| SILANE TREATED SILICA | 67762-90-7 | CMRG | CEIL:5 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

Respiratory protection is not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| General Physical Form: | Solid |
|---|------------------------------------|
| Specific Physical Form: | Paste |
| Odor, Color, Grade: | Slight characteristic odor, yellow |
| Odor threshold | No Data Available |
| pH | No Data Available |
| Melting point | No Data Available |
| Boiling Point | Not Applicable |
| Flash Point | No flash point |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | Not Applicable |
| Flammable Limits(UEL) | Not Applicable |
| Vapor Pressure | Not Applicable |
| Vapor Density | Not Applicable |
| Density | No Data Available |
| Specific Gravity | No Data Available |
| Solubility in Water | Nil |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | Not Applicable |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Viscosity | No Data Available |
| Percent volatile | No Data Available |
| | |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance None known. Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use: Contains a chemical or chemicals which can cause cancer.

| Ingredient | C.A.S. No. | Class Description | Regulation |
|----------------------|------------|--------------------------------|---|
| SILICA, CRYS AIRRESP | 14808-60-7 | Known human carcinogen | National Toxicology Program Carcinogens |
| QUARTZ SILICA | 14808-60-7 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|-------------|---------|---|
| Overall product | Ingestion | | No data available; calculated ATE > 5,000 mg/kg |
| VINYL POLYDIMETHYLSILOXANE | Dermal | Rabbit | LD50 > 15,440 mg/kg |
| VINYL POLYDIMETHYLSILOXANE | Ingestion | Rat | LD50 > 15,440 mg/kg |
| QUARTZ SILICA | Dermal | | LD50 estimated to be $> 5,000 \text{ mg/kg}$ |
| QUARTZ SILICA | Ingestion | | LD50 estimated to be $> 5,000 \text{ mg/kg}$ |
| SILANE TREATED SILICA | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| SILANE TREATED SILICA | Inhalation- | Rat | LC50 > 0.691 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| SILANE TREATED SILICA | Ingestion | Rat | LD50 > 5,110 mg/kg |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Inhalation- | Rat | LC50 2 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Ingestion | Rat | LD50 > 2,000 mg/kg |
| TE – acute toxicity estimate | | | |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| VINYL POLYDIMETHYLSILOXANE | Rabbit | No significant irritation |
| QUARTZ SILICA | | No significant irritation |
| SILANE TREATED SILICA | Rabbit | No significant irritation |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| VINYL POLYDIMETHYLSILOXANE | Rabbit | Mild irritant |
| SILANE TREATED SILICA | Rabbit | No significant irritation |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Rabbit | Severe irritant |

Skin Sensitization

| Name | Species | Value |
|--|---------|-----------------|
| SILANE TREATED SILICA | Human | Not sensitizing |
| | and | |
| | animal | |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Guinea | Not sensitizing |
| | pig | |

Respiratory Sensitization

| | Name | Species Value |
|--|------|---------------|
|--|------|---------------|

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| QUARTZ SILICA | In Vitro | Some positive data exist, but the data are not |
| | | sufficient for classification |
| QUARTZ SILICA | In vivo | Some positive data exist, but the data are not |
| | | sufficient for classification |
| SILANE TREATED SILICA | In Vitro | Not mutagenic |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | In Vitro | Not mutagenic |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---------------|------------|---------|--------------|
| QUARTZ SILICA | Inhalation | Human | Carcinogenic |
| | | and | |
| | | animal | |

3MTM ESPETM ImprintTM II Light Body Base 10/20/14

| SILANE TREATED SILICA | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |] |
|-----------------------|------------------|-------|--|---|
|-----------------------|------------------|-------|--|---|

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---|-----------|--|---------|-----------------------------|------------------------------------|
| SILANE TREATED SILICA | Ingestion | Not toxic to female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| SILANE TREATED SILICA | Ingestion | Not toxic to male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| SILANE TREATED SILICA | Ingestion | Not toxic to development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Ingestion | Some positive reproductive/developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 450 mg/kg/day | premating & during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| | | 0 1 | | | | |
|------|-------|-----------------|-------|---------|-------------|----------|
| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure |
| | | | | | | Duration |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--------------------------|------------|-----------------------------------|--|---------|------------------------|--------------------------|
| QUARTZ SILICA | Inhalation | silicosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| SILANE TREATED SILICA | Inhalation | respiratory system silicosis | All data are negative | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

Name

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

Value

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial

waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document Group: | 18-1383-1 | Version Number: | 6.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 10/20/14 | Supercedes Date: | 02/22/11 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable

3MTM ESPETM ImprintTM II Light Body Base 10/20/14

for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright,2014,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 18-1378-1 | Version Number: | 6.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 10/20/14 | Supercedes Date: | 02/22/11 |

SECTION 1: Identification

1.1. Product identifier

 $3M^{\rm TM} \, ESPE^{\rm TM} \, Imprint^{\rm TM} \, II \, Light \; Body \; Catalyst$

Product Identification Numbers LE-F000-5201-2

1.2. Recommended use and restrictions on use

Recommended use Dental Product, Impression material Restrictions on use For use only by dental professionals

| 1.3. Supplier's details | |
|-------------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | 3M ESPE Dental Products |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements Signal word Not applicable.

Symbols Not applicable. Pictograms

Not applicable.

2.3. Hazards not otherwise classified None.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--------------------------------|------------|------------------------|
| VINYL POLYDIMETHYLSILOXANE | 68083-19-2 | 50 - 60 Trade Secret * |
| QUARTZ SILICA | 14808-60-7 | 35 - 45 Trade Secret * |
| SILANE TREATED SILICA | 67762-90-7 | 1 - 10 Trade Secret * |
| POLYETHYLENE GLYCOL, SILOXANE- | 27306-78-1 | < 0.5 Trade Secret * |
| TERMINATED | | |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide <u>Condition</u> During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Observe precautions from other sections.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-----------------------|------------|--------|-------------------------------|---------------------|
| QUARTZ SILICA | 14808-60-7 | OSHA | TWA concentration(as total | |
| | | | dust):0.3 mg/m3;TWA | |
| | | | concentration(respirable):0.1 | |
| | | | mg/m3(2.4 millions of | |
| | | | particles/cu. ft.) | |
| QUARTZ SILICA | 14808-60-7 | ACGIH | TWA(respirable | A2: Suspected human |
| | | | fraction):0.025 mg/m3 | carcin. |
| SILANE TREATED SILICA | 67762-90-7 | CMRG | CEIL:5 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| General Physical Form: | Solid |
|---|-----------------------------------|
| Specific Physical Form: | Paste |
| Odor, Color, Grade: | Slight characteristic odor, white |
| Odor threshold | No Data Available |
| рН | No Data Available |
| Melting point | No Data Available |
| Boiling Point | Not Applicable |
| Flash Point | No flash point |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | Not Applicable |
| Flammable Limits(UEL) | Not Applicable |
| Vapor Pressure | Not Applicable |
| Vapor Density | Not Applicable |
| Density | No Data Available |
| Specific Gravity | No Data Available |
| Solubility in Water | Nil |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | Not Applicable |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Percent volatile | No Data Available |
| | |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials None known.

10.6. Hazardous decomposition products Substance

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

Condition

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use: Contains a chemical or chemicals which can cause cancer.

| Ingredient | C.A.S. No. | Class Description | Regulation |
|----------------------|------------|--------------------------------|---|
| SILICA, CRYS AIRRESP | 14808-60-7 | Known human carcinogen | National Toxicology Program Carcinogens |
| QUARTZ SILICA | 14808-60-7 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|------|-------|---------|-------|
| | | | |

3MTM ESPETM ImprintTM II Light Body Catalyst 10/20/14

| Overall product | Ingestion | | No data available; calculated ATE > 5,000 mg/kg |
|--|-------------|--------|---|
| VINYL POLYDIMETHYLSILOXANE | Dermal | Rabbit | LD50 > 15,440 mg/kg |
| VINYL POLYDIMETHYLSILOXANE | Ingestion | Rat | LD50 > 15,440 mg/kg |
| QUARTZ SILICA | Dermal | | LD50 estimated to be $> 5,000 \text{ mg/kg}$ |
| QUARTZ SILICA | Ingestion | | LD50 estimated to be $> 5,000 \text{ mg/kg}$ |
| SILANE TREATED SILICA | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| SILANE TREATED SILICA | Inhalation- | Rat | LC50 > 0.691 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| SILANE TREATED SILICA | Ingestion | Rat | LD50 > 5,110 mg/kg |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Inhalation- | Rat | LC50 2 mg/l |
| | Dust/Mist | | - |
| | (4 hours) | | |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Ingestion | Rat | LD50 > 2,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| VINYL POLYDIMETHYLSILOXANE | Rabbit | No significant irritation |
| QUARTZ SILICA | | No significant irritation |
| SILANE TREATED SILICA | Rabbit | No significant irritation |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| VINYL POLYDIMETHYLSILOXANE | Rabbit | Mild irritant |
| SILANE TREATED SILICA | Rabbit | No significant irritation |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Rabbit | Severe irritant |

Skin Sensitization

| Name | Species | Value |
|--|---------|-----------------|
| SILANE TREATED SILICA | Human | Not sensitizing |
| | and | |
| | animal | |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Guinea | Not sensitizing |
| | pig | - |

Value

Species

Respiratory Sensitization Name

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| QUARTZ SILICA | In Vitro | Some positive data exist, but the data are not |
| | | sufficient for classification |
| QUARTZ SILICA | In vivo | Some positive data exist, but the data are not |
| | | sufficient for classification |
| SILANE TREATED SILICA | In Vitro | Not mutagenic |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | In Vitro | Not mutagenic |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|-----------------------|------------|---------|--|
| QUARTZ SILICA | Inhalation | Human | Carcinogenic |
| | | and | |
| | | animal | |
| SILANE TREATED SILICA | Not | Mouse | Some positive data exist, but the data are not |
| | Specified | | sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure |
|------|-------|-------|---------|-------------|----------|
| | | | | | |

3MTM ESPETM ImprintTM II Light Body Catalyst 10/20/14

| | | | | | Duration |
|---|-----------|--|-----|-----------------------------|------------------------------------|
| SILANE TREATED SILICA | Ingestion | Not toxic to female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| SILANE TREATED SILICA | Ingestion | Not toxic to male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| SILANE TREATED SILICA | Ingestion | Not toxic to development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |
| POLYETHYLENE GLYCOL, SILOXANE-TERMINATED | Ingestion | Some positive reproductive/developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 450 mg/kg/day | premating & during gestation |

Target Organ(s)

| Specific Target Organ Toxicity - single exposure | | | | | | |
|--|-------|-----------------|-------|---------|-------------|----------------------|
| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--------------------------|------------|-----------------------------------|--|---------|------------------------|-----------------------|
| QUARTZ SILICA | Inhalation | silicosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| SILANE TREATED SILICA | Inhalation | respiratory system silicosis | All data are negative | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

Name

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

Value

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <u>http://3M.com/Transportinfo</u> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document Group: | 18-1378-1 | Version Number: | 6.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 10/20/14 | Supercedes Date: | 02/22/11 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness

3MTM ESPETM ImprintTM II Light Body Catalyst 10/20/14

or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com