#### **SAFETY DATA SHEETS**

#### This SDS packet was issued with item:

075355938

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

075347810 075347828 075347836 075347844 075347851 075348578 075348586 075348594 075348602 075348610 075348628 075355490 075355706 075355714 075355730 075355748 075355755 075355763 075355805 075355813 075355839 075355847 075355854 075355862 075355904 075355912 075355920 075355946 075355953 075355961

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

075347802 075348370 075348388 075348396 075348404 075348412 075348420 075348438

## **SLEDGEHAMMER®**

#### **Self Cure Powder**

#### Section I - Product and Company Identification

SLEDGEHAMMER SELF CURE DENTAL ACRYLIC POWDER **Product Name:** 

Polymethylmethacrylate **Chemical Name:** 

Manufacturer: KEYSTONE RESEARCH & PHARMACEUTICAL Family: Acrylic Polymer

> 616 Hollywood Avenue Cherry Hill, NJ 08002

**Emergency Phone Numbers:** (800) 535 - 5053 Product Use: Dental Polymer Formula: Proprietary Formulation **Information Contacts:** (856) 663 - 4700

Product Number - 1000482, 1000483, 1000484, 1000485, 1000486, 1000487, 1000488, 1000489, 1000490, 1000507, 1000508, 1000509, 1000510, 1000511, 1000512, 1000513, 1000514, 1000515, 1000539, 1000540, 1000541, 1000547, 1000548, 1000549, 1001950, 1001952, 1001970, 1001971, 1000549, 1001970, 1001971, 1000549, 1001970, 1001971, 1000549, 1001970, 1001970, 1001971, 11001972, 1001973, 1001974, 1001975

#### Section II - Hazardous Ingredients

<b>Chemical Identity</b>	CAS Numbers	Exposure	Limits	Carcinogen	
		OSHA	ACGIH		
		TWA/STEL	TWA/STEL	IARC/NTP/OSHA	
Residual Monomer	N/R	N/R	N/R	N/E	
Diethyl Phthalate	84 - 66 - 2	5 mg/m3	5 mg/m3	N/E	
Benzoyl Peroxide	94 - 36 - 0	5 mg/m3	5 mg/m3	N/E	
Titanium Dioxide	13453 - 67 - 7	15 mg/m3	10 mg/m3	N/E	
N/E	- None Established	N/A - Not Appli	icable N/DA - N	No Data Available N/R - Not Reviewed	

#### Section III - Hazards Identification

#### **EMERGENCY OVERVIEW**

Free flowing powder

Considered a nuisance dust.

- Can cause eye/skin irritation.
- Polymer dust is combustible.
- Decomposition products include Methyl Methacrylate and Carbon Monoxide.

#### Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry Eyes or skin (No absorption); inhalation of dust.

Eye Higher concentration can irritate eyes. May cause eye irritation or damage

Skin Repeated or prolonged exposure may cause allergic skin rashes.

Ingestion Higher concentration can irritate respiratory system.

Possible temporary discomfort due to inhalation of dust concentration above the permissible exposure Inhalation

limit. Dust may cause irritation of the nose, throat, and lungs.

**Sub-Chronic Effects** 

Threshold Limit Value

Permissible Exposure

**Target Organs:** 

(Tlv):

Limit (Pel):

**Human Patch Test:** 

For Polymer: None Listed. For Decomposition Product, Methyl Methacrylate Monomer: Nose, Liver and Kidneys. For Diethyl Phthalate: None Listed. For Benzoyl Peroxide: None Listed. For Titanium Dioxide: None Listed. For Polymer: NE. For Decomposition Product, Methyl Methacrylate Monomer: 100ppm. For Diethyl Phthalate: 5ppm. For Benzoyl Peroxide: 5mg/m3. For Titanium Dioxide: 10 mg/m3

For Polymer: NE. For Decomposition Product, Methyl Methacrylate: 100 ppm. For Diethyll Phthalate: 5 ppm. For Benzoyl Peroxide: 5mg/m3. For Titanium Dioxide: 15 mg/m3

Approximate one-third of subjects developed mild redness at the site of application. Twenty percent showed

sensitivity when tested 10 days later.

Inhalation TClo, rat: 54 mg/m3/54 minutes, 6-15 days of pregnancy. Inhalation TClo.rat: 54 mg/m3/24 hours, 8 **Reproductive Effects:** weeks of pregnancy. Inhalation TClo, rat: 4480 mg/m3/2 hours, 6 -18 days of pregnancy. RTECS: OZ50750000,

TSCA Inventory; 1986

For Diethyl Phthalate:

TC50 Inhalation Human: 1000mg/m3. LD50 Intraperitoneal Mouse: 2749 mg/kg. LD50 Intraperitoneal Rat: 5058 mg/kg. LD50 Intravenous Rabbit: 100 mg/kg. LD50 Oral Guinea Pig: 8600 mg/kg. LD50 Oral Mouse: 6172 mg/kg. LD50 Oral Rat: 8600 mg/kg. LD lo Oral Rabbit: 1000mg/kg. LDlo Subcutaneous Guinea Pig: 3000 mg/kg. RTECS. T11050000, TSCA: 1986

For Benzoyl Peroxide:

LDlo Intraperitoneal Mouse: 250 mg/kg. LD50 Oral Rat: 7710 mg/kg.RTECS: DM8575000.TSCA: 1986.

For Titanium Dioxide:

LD50 Oral Rat: > 9000mg/kg. RTECS: TI08755079. TSCA: 1986.

Page 1 of 4

## **SLEDGEHAMMER®**

#### Self Cure Powder

#### Section III - Hazards Identification Continued

#### **Effects Of** Overexposure:

#### For Polymer:

OSHA classifies this material as Particulates, Not Otherwise Classified. Eyes, skin and Respiratory tract may be irritated by gross overexposure to Particulates, Not Otherwise Classified, no matter how they are generated. Avoid inhalation of dust. Keep dust out of eyes to prevent possible irritation.

#### For Decomposition Product:

Methyl Methacrylate Monomer; Liquid or high vapor concentration can irritate eyes, respiratory system and cause skin rashes. Prolonged exposure can lead to headaches, nausea, staggering gait, confusion, drowsiness and unconsciousness. Repeated and prolonged over exposure may cause permanent brain and nervous system damage, allergic skin rashes, eye corrosion and permanent injury, as well as changes in liver and kidney function or damage.

#### For Benzoyl Peroxide:

Prolonged and /or repeated skin contact may cause skin irritation, defatting, dermatitis and sensitization. May cause eye irritation or damage. Dust may cause irritation of the nose, throat and lungs. May produce muscular weakness

For Diethyl Phthalate: Direct contact with the liquid or exposure to its vapors or mists may cause burning, tearing, redness and swelling of the eyes. Prolonged or repeated skin exposure may cause redness, burning, drying, cracking and dermatitis. Persons with pre-existing skin disorders may be more susceptible to this material. Inhalation of excessive amounts may cause irritation of the nose, and throat, central nervous system depression such as drowsiness, dizziness, loss of coordination and fatigue. Persons with impaired lung function or asthma-like conditions may experience additional breathing difficulties. Ingestion of large amounts may cause irritation of the digestive tract and signs of nervous system depression.

#### For Titanium Dioxide:

May cause temporary drying effect or irritation of mucous membrane. Although non-corrosive, non-irritating and non-sensitizing, it may have a drying effect on the skin. In contact with the eye it is an inert foreign body. Harmless if swallowed, physiologically inert.

NOTE: Refer to Section 11, Toxicological Information for Details

#### Section IV - First Aid Measures

First Aid for Eye Flush with water for 15 minutes, including under eyelids. Get medical help if discomfort persists.

First Aid for Skin Wash with soap and water. Get medical help if discomfort persists. First Aid for Inhalation Remove to fresh air. Get medical help if discomfort persists. First Aid for Ingestion Rinse mouth out with water. Call doctor if amount was large.

#### Section V - Fire Fighting Measures

Flash Point		Flammable Limit	Auto-ignition Temperature
(°F/°C)		(vol%)	(vol%)
304 deg C ; 579 d	eg F	NA	NA
Extinguishing Media:	Water, Carbon Die	oxide, Dry Chemical	

Fire Fighting Instructions: Avoid extinguishing methods which may generate dust cloud. Water stream can disperse dust into air,

producing a fire hazard and possible explosion hazard if exposed to ignition source.

Unusual Hazards: Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately

those of coal dust. Firefighters should wear self-contained breathing apparatus.

#### Section VI - Accidental Release Measures

Spill or Release Procedures -Sweep up to avoid slipping hazard. Keep airborne particulates at a minimum when cleaning up spills.

#### Section VII - Handling and Storage

Storage

Hazard

Explosion

Handling Observe precautions found on the label. Wash face and hands thoroughly with soap and water after handling and before eating, drinking or smoking. Avoid prolonged or repeated contact with skin. Avoid contamination. Use only with adequate ventilation.

Store in cool, dry place away from heat, sparks, flame and direct sunlight. Close container after each use. Ground all metal containers when transferring. Use explosion-proof equipment Store away from combustibles and incompatible materials.

Polymer dust is combustible, explosive limits of the polymer particles suspended in air are approximately those of coal dust.

## **SLEDGEHAMMER®**

#### **Self Cure Powder**

#### Section VIII - Exposure Controls / Personal Protective Equipment

Engineering Controls

Use good local exhaust at processing equipment, including buffers, sanders, grinders and polishers. High temperature processing equipment should be well ventilated. Use explosion-proof equipment. Provide ventilation if necessary to control exposure levels below airborne exposure limits.

**Personal Protective Equipment** 

General Dust collectors are recommended for handling powder in bulk

Skin Protection Minimize contamination by following good industrial practice. Wearing nitrile, neoprene,

pvc, latex ot other impermeable gloves is recommended.

Respiratory Protection Avoid breathing dust and mist. Use dust mask.

#### Section IX - Physical and Chemical Properties

Appearance Original, Lt fiber pink or clear free powder	ed, Lt reddish	<b>Odor &amp; Odor Threshold</b> Faint odor in bulk	PH N/A	<b>Specific Gravity</b> N/E	Viscosity N/A	% Volatile	e 
Boiling Point/ Freezing Point	Decomposition Temperature		Vapor t Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)

N/A

N/A

N/A

N/A

Insoluble

#### Section X - Stability and Reactivity

572°F/300°C

Stability: Stable Incompatibility (Materials to Avoid): Strong oxidizing agents

N/A

Hazardous Decomposition Products: Methacrylate Monomer and Carbon Monoxide Hazardous Polymerization: Will not occur

Conditions to Avoid: Heating above 300° C

#### Section XI - Toxicological Information

Acute Oral Toxicity Acute Dermal Toxicity Acute Inhalation Toxicity Eye / Skin Irritation

LD50 Oral (Rat): 7990mg/kg

LD50 Dermal (Rabbit): 35,500 mg/kg

LC50 Inhalation (Rat: >12,500 to 16,500 ppm for 0.5 hrs

None

Sensitization N/DA

Mutagenicity N/DA

Sub-chronic Toxicity N/DA

#### Section XII - Ecological Information

**Ecotoxicological Information** 

Bluegills TLm24: 368 ppm

**Chemical Fate Information** 

Biodegradability N/DA Chemical Oxygen Demand N/DA

#### Section XIII - Disposal Concentrations

 This product contains a Diethyl Phthalate, contaminated product may be a RCRA/OSHA hazardous waste (40 CFR Part 261 and 29 CFR Part 1910). Incinerate material in accordance with Federal, State and Local regulations.

#### Section XIV - Transport Information

NA

#### Section XV - Regulatory Information

US Federal Regulations

Priority Pollutant

Clean Air Act: HAP
Clean Air Act: ODS
This product contains no hazardous air pollutants (HAP), as defined by the U. S. Clean Air Act.
This product neither contains, nor was manufactured with a Class I or Class II ozone depleting substances (ODS).

Clean Water Act: This product contains no chemicals listed under the U.S. Clean Water Act Priority Pollutant List.

## **SLEDGEHAMMER®**

#### **Self Cure Powder**

#### Section XV - Regulatory Information Continued

FDA: Food Packaging Status This product has not been cleared by the FDA for use in food packaging and/ or other applications as an

indirect food additive.

Occupational Safety and Health Act This product contains hazardous chemical under the OSHA Hazard Communication Standard. Its hazards

are: Immediate (acute ) health hazard; Fire hazard

**RCRA** This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261).

Dibutyl Phthalate; CAS NO: 84-74-2; RCRA Code: U088

SARA Title III: Section 302 This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances. SARA Title III: Section 304

This product contains chemicals regulated under Sec. 304 as extremely hazardous chemicals for

emergency release notification ("CERCLA" List). Dibutyl Phthalate; CAS NO: 84 74-2; RQ(Lbs): 1000 SARA Title III: Section 311-312: This product contains hazardous substance under the OSHA Hazard Communication Standard and is

> regulated under Section 311-312 (40 CFR 370). Its hazards are: Immediate (acute) health & fire hazard This product contains chemicals subject to the reporting requirements of Section 313 of Title III of the

Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. Benzoyl Peroxide: CAS

NO: 94 - 36 - 0

TSCA Section 8(b): Inventory: None

SARA Title III: Section 313:

State Regulations

CA Proposition 65 This product contains no substances known to the State of California to cause cancer and reproductive effects. MA Right-to-Know Law:

This product contains: Benzoyl Peroxide; CAS NO: 94-36-0 Dibutyl Phthalate; CAS NO: 84-74-2 which are listed

on the Massachusetts Hazardous Substance List.

This product contains: Benzoyl Peroxide; CAS NO: 94-36-0 Dibutyl Phthalate; CAS NO: 84-74-2 which are listed NJ Right-to-Know Law:

on the New Jersey Hazardous Substance List.

PA Right-to-Know Law: This product contains: Dibenzovl Peroxide; CAS NO: 94-36-0 Dibutyl Phthalate; CAS NO: 84-74-2 which are

listed on the Pennsylvania Environmental Hazardous Substance List.

International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List) All components of this product are listed on the Canadian DSL

EINECS: European Inventory: No information available

#### Section XVI - Other Information

NFPA: Health = NA/Flammability = NA/Reactivity = NA Hazard Rating System

HMIS: Health = 1/Flammability = 1/Reactivity = 0

Approval Date: June 2004 Revised August 14, 2008

Revised to change all appearances of Dialkyl Phthalate to Diethyl Phthalate in sections I, III and XIII and added product numbers to section I..

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800)535-5053.



## SAFETY DATA SHEET

#### Sledgehammer Self Cure Powder

#### **Section 1. Identification**

**GHS** product identifier

: Sledgehammer Self Cure Powder

Other means of identification

: Not available.

**Product code** 

: 1000507-1000515, 1000547-1000549, 1001969-1001972

**Product type** 

Powder.

**Product use** 

: Dental Products

Polymer

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Supplier's details

: Keystone Industries 616 Hollywood Ave. Cherry Hill, NJ 08002 (856) 663-4700

**Emergency telephone** number (with hours of operation)

: (800) 535-5053

## Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : COMBUSTIBLE DUSTS

CARCINOGENICITY - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 99%

**GHS label elements** 

**Hazard pictograms** 



Signal word

: Warning

**Hazard statements** 

May form combustible dust concentrations in air. Suspected of causing cancer.

**Precautionary statements** 

**Prevention** 

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing.

Response

: IF exposed or concerned: Get medical attention.

**Storage** 

: Store locked up.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label

elements

Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames

Hazards not otherwise

classified

and other ignition sources. No smoking. Prevent dust accumulation. : Fine dust clouds may form explosive mixtures with air. Handling and/or processing of

this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Date of issue/Date of revision : 5/14/2015 Date of previous issue : 4/21/2015 Version: 1 1/11

## Section 3. Composition/information on ingredients

Substance/mixture
Other means of identification

: Not available.

: Mixture

#### **CAS** number/other identifiers

**CAS number** : Not applicable.

May contain one or more of the following components in quantities considered hazardous:

Ingredient name	CAS number	EC number	%
titanium dioxide	13463-67-7	236-675-5	0.1 - 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

## Description of necessary first aid measures

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation** 

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** 

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact

: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.

Inhalation

: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.

Skin contact Ingestion

: No known significant effects or critical hazards.

: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact** 

: Adverse symptoms may include the following: irritation

redness

Date of issue/Date of revision : 5/14/2015 Date of previous issue : 4/21/2015 Version : 1 2/11

#### Section 4. First aid measures

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.

Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### See toxicological information (Section 11)

## Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

: Use dry chemical powder.

**Unsuitable extinguishing** 

media

: Do not use water jet.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: Fine dust clouds may form explosive mixtures with air.

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Date of issue/Date of revision : 5/14/2015 Date of previous issue : 4/21/2015 Version : 1 3/11

### Section 6. Accidental release measures

#### **Small spill**

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 200°C (392°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
itanium dioxide	ACGIH TLV (United States, 4/2014).
	TWA: 10 mg/m <sup>3</sup> 8 hours.
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Total dust
	OSHA PEL (United States, 2/2013).
	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust

Date of issue/Date of revision : 5/14/2015 Date of previous issue : 4/21/2015 Version : 1 4/11

## Section 8. Exposure controls/personal protection

## Appropriate engineering controls

# : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

## Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields. If operating conditions cause high dust concentrations to be produced, use dust goggles.

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

#### **Appearance**

Physical state : Solid. [Powder.]

Color : Colored

Odor : Faint odor. [Slight]
pH : Not applicable.

Melting point : Not available.

Boiling point : Not available.

Flash point : Closed cup: 304°C (579.2°F) [Tagliabue.]

Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure : Not available.
Vapor density : Not available.

Date of issue/Date of revision : 5/14/2015 Date of previous issue : 4/21/2015 Version : 1 5/11

## Section 9. Physical and chemical properties

Relative density : Not available.

**Solubility** : Insoluble in the following materials: cold water and hot water.

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: 200°C (392°F)Viscosity: Not available.

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid the creation of dust when handling and avoid all possible sources of ignition

(spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust

accumulation.

**Incompatible materials**: Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

## Section 11. Toxicological information

#### Information on toxicological effects

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-

Information on the likely routes of exposure

: Not available.

#### Potential acute health effects

**Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the eyes.

**Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

Date of issue/Date of revision : 5/14/2015 Date of previous issue : 4/21/2015 Version : 1 6/11

## **Section 11. Toxicological information**

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

irritation redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.

Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

General: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Not available.

## **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
titanium dioxide	-	352	low

## Section 12. Ecological information

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS#		Reference number
Diethyl phthalate; 1,2-Benzenedicarboxylic acid, diethyl ester	84-66-2	Listed	U088

## **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-	-
Packing group	-	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.	No.
Additional information	Reportable quantity 25000 lbs / 11350 kg Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable	-	-	-	-	-

Date of issue/Date of revision : 5/14/2015 Date of previous issue : 4/21/2015 Version : 1 8/11

Section 14. Transport information								

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according: Not available.

to Annex II of MARPOL 73/78 and the IBC Code

## Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: diethyl phthalate

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

: Not listed

**Clean Air Act Section 602** 

**Class I Substances** 

: Not listed

**Clean Air Act Section 602** 

Class II Substances

: Not listed

**DEA List I Chemicals** 

: Not listed

(Precursor Chemicals)

**DEA List II Chemicals** 

: Not listed

(Essential Chemicals)

**SARA 302/304** 

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

Classification : Not applicable.

#### **Composition/information on ingredients**

Name		hazard	Sudden release of pressure		(acute) health	Delayed (chronic) health hazard
titanium dioxide	0.1 - 1	No.	No.	No.	No.	Yes.

#### **State regulations**

Massachusetts : The following components are listed: DIETHYL PHTHALATE

New York : The following components are listed: Diethyl phthalate

New Jersey : The following components are listed: DIETHYL PHTHALATE; 1,

2-BENZENEDICARBOXYLIC ACID, DIETHYL ESTER; DEP; TITANIUM DIOXIDE;

**TITANIUM OXIDE (TiO2)** 

Date of issue/Date of revision : 5/14/2015 Date of previous issue : 4/21/2015 Version : 1 9/11

## Section 15. Regulatory information

**Pennsylvania** 

: The following components are listed: 1,2-BENZENEDICARBOXYLIC ACID, DIETHYL ESTER; TITANIUM OXIDE (TIO2)

#### California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	•	level	Maximum acceptable dosage level
titanium dioxide	Yes.	No.	No.	No.

**Canada inventory** 

**International regulations** 

International lists

: All components are listed or exempted.

: Australia inventory (AICS): All components are listed or exempted. China inventory (IECSC): All components are listed or exempted.

**Japan inventory**: All components are listed or exempted. **Korea inventory**: All components are listed or exempted. **Malaysia Inventory (EHS Register)**: Not determined.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

**Philippines inventory (PICCS)**: All components are listed or exempted. **Taiwan inventory (CSNN)**: All components are listed or exempted.

**Chemical Weapons** 

**Convention List Schedule** 

**I Chemicals** 

Chemical Weapons
Convention List Schedule

**II Chemicals** 

Chemical Weapons
Convention List Schedule

**III Chemicals** 


: Not listed

: Not listed

: Not listed

## Section 16. Other information

**Hazardous Material Information System (U.S.A.)** 



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (U.S.A.)** 



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Date of issue/Date of revision : 5/14/2015 Date of previous issue : 4/21/2015 Version : 1 10/11

#### Section 16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### **History**

Date of printing : 5/14/2015

Date of issue/Date of : 5/14/2015

revision

Date of previous issue : 4/21/2015

Version : 1

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships.

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

**UN = United Nations** 

References : Not available.

Indicates information that has changed from previously issued version.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Information contained within this SDS is only to be distributed as required by law.

Date of issue/Date of revision : 5/14/2015 Date of previous issue : 4/21/2015 Version : 1 11/11