# **SAFETY DATA SHEETS**

# This SDS packet was issued with item:

076320675

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

076320741

Page 1 of 7

**Revision: 1** 

1.1 Product identifier:

Product Names: Lithium-ion battery for Radii Plus / Radii Cal.

1.2 Relevant identified use:

Relevant use: Battery to be used with the Radii Plus and Radii Cal Dental Curing Light.

Further information:

Battery System: Lithium-ion (Li-ion) battery pack

Nominal voltage: 7.4V Rated Capacity: 1550mAh

Wh rating: 11.47 Wh

**Manufacturer / Supplier** 

SDI Limited SDI Inc

3-13 Brunsdon Street, Bayswater 729 N.Route 83, Suite 315 Victoria, 3153, Australia Bensenville 60106 IL, USA

<u>Telephone</u>: <u>Telephone</u>:

+61 3 8727 7111 (Business hours) 630 238 8300 (Business hours)

Southern Dental Industries Ltd

Block 8, St Johns Court

Swords Road

SDI Brasil Indústria e Comércio Ltda

Rua Dr. Virgílio de Carvalho Pinto, 612

Pinheiros, São Paulo, 05415-020

Santry, Dublin 9, Ireland Brasil

Telephone: Telephone:

+353 1 886 9577 (Business Hours) +55 11 3092 7100 (Business Hours)

Emergency contact number: +61 3 8727 7111

Email: ray.cahill@sdi.com.au (Technical Director, SDI Limited)

#### 2. Hazard Identification

Not classified as hazardous according to the Globally Harmonised System for classification and labelling of chemicals (GHS). No effect on skin contact, skin absorption, eye contact and inhalation under routine handling and use.

Potentially hazardous materials are sealed and contained in equipment. Equipment is packed in strong outer packaging to withstand normal handling and use. Exposure could occur if the equipment has been exposed to high temperatures (>125°C), battery or cells have been opened, crushed, dissembled or burned. Keep away from heat.

Obtained by Global Safety Management, www.globalsafetynet.com, (877) 683-7460

Page 2 of 7

Revision: 1

## 3. Composition / Information on ingredients

**Battery Cell** 

Components	Content (wt %)	CAS number
Lithium Cobalt Dioxide (LiCoO2)	Less than 38 wt %	12190-79-3
Lithium Hexafluorophosphate (LiPF6)	Less than 3 wt %	21324-40-3
Ethylene Carbonate (C3H4O3)	Less than 6 wt %	96-49-1
Chain carbonate ( - )	Less than 8 wt %	
Graphite (C)	Less than 20 wt %	7782-42-5
Lead (Pb)	Less than 0.1 wt % (1000ppm)	
Mercury (Hg)	Less than 0.0005 wt % (5ppm)	

Note: other 25% includes the below materials:

Al (positive Base Film, Cap, Can, Tab)

Cu (Negative film base) Ni (Tab, Terminal) Fe (Terminal)

Resin (PP, PE, PET) (Separator, Plastic, Parts, Insulator)

#### Circuit Module:

Hazardous ingredients	%	CAS number
Lead	< 0.1	7439-92-1
Mercury	0	7439-97-6
Chromium	0	7440-47-3
Cadmium	0	7440-43-9
Plastic case and Si2O	0	N/A

#### Plastic Parts and Paints:

Ingredients	%	CAS number
Polycarbonate	More than 81 wt%	25971-63-5
Flame retardant	Less than 12 wt%	
Elastomer	Less than 7 wt%	

### 4. First Aid Measures

Intact/undamaged cell(battery pack):

Inhalation, eye contact and skin contact: Not a health hazard.

Ingestion: If swallowed, obtain immediate medical attention.

If exposure to internal materials within cell(pack) due to damaged outer casing, the following actions are recommended:

Ingestion: Drink milk/water and induce vomiting. Seek immediate medical attention.

Skin: Wash skin thoroughly with soap and water and seek medical attention.

Eye: Rinse eyes with water for 15 minutes and seek medical attention.

Inhalation: Leave area immediately and seek medical attention.

Most important effects, acute and delayed:

Page 3 of 7

**Revision: 1** 

The most important known symptoms and effects are described in section 2 and/or in section 11.

Indication of any immediate medical attention and special treatment needed: no data available

# 5. Fire Fighting Measures

General Hazard: Cell is not flammable but internal organic material will burn if

the cell is incinerated.

Suitable extinguishing media: Carbon dioxide, foam, dry chemical extinguishing media or

water spray.

Unsuitable extinguishing media: No data available.

Specific hazards arising from the mixture: This product will burn under fire conditions. Combustion

products include but are not limited to hydrogen fluoride,

carbon monoxide and carbon dioxide.

If possible, remove cells from fire fighting area. If heated

above 125°C, cells can explode/vent.

Advice for firefighters: Use NIOSH/MSHA approved full-face self-contained breathing

apparatus (SCBA) with full protective gear.

#### 6. Accidental Release Measures

Personal precautions: Use personal protective equipment to avoid contact and exposure.

Remove all metal objects including jewellery, belts, etc before handling

battery.

Remove all sources of ignition. Ensure adequate ventilation.

For personal protection, see section 8.

Environmental precautions: Prevent any spillage from entering drains or waterways.

Method for Cleaning and containment of Spills: For small spills, use paper towel or dry cloth to absorb

electrolyte spill. For larger spills, clean up spill using an inert absorbent material such as dry sand or vermiculite. Place in appropriate container for disposal in accordance with local regulations. Clean up area with soap and water, and collect material for subsequent disposal. Do not allow to enter

drains or waterways.

Removal of ignition sources, provision of sufficient ventilation, control of dust: Not expected.

# 7. Handling and storage

Precautions for safe handling:

Do not damage, disassemble or open the battery. Keep away from heat and fire.

Conditions for safe storage, including any biocompatibilities:

Store in a cool, dry, well-ventilated place.

Page 4 of 7

**Revision: 1** 

The packed battery should not be exposed to high temperatures (>60°C or 140°F), opened, crushed, dissembled or burned.

Specific end use:

Apart from the use mentioned in section 1.2, there are no other uses for the

product.

# 8. Exposure controls and personal protection

Engineering controls: Keep away from heat and open flame. Store in a cool dry place.

Occupational Exposure Limits: We are not aware of any national exposure limit.

Exposure controls:

Respiratory protection: None required under normal conditions of use. SCBA required

in the event of a fire.

Hand protection: Gloves not required for handling of cells.

Eye / face protection: None required under normal conditions of use.

Foot protection: Steel toed shoes recommended for large container handling.

No personal protection is required for the normal handing or the battery. If ingredients within the battery are leaking follow first aid section of this document.

# 9. Physical and chemical properties

Properties such as pH, boiling point flash points are not applicable as the batteries are solid articles.

State: Solid

Odour: Not applicable Not applicable :Ha Not applicable Vapour pressure: Vapour density: Not applicable Boiling point: Not applicable Solubility in water: Insoluble Specific gravity: Not applicable Not applicable Density:

# 10. Stability and Reactivity

Stability: Stable under normal conditions.

Reactivity: Stable under normal conditions.

Conditions to avoid: Avoid exposure to heat and open flames, and corrosives. Do not crush,

puncture, incinerate, disassemble, or immerse in water.

Materials to avoid: Avoid exposure to heat, open flame, and corrosives.

Page 5 of 7

Revision: 1

Hazardous decomposition products: None under normal conditions. If cells are opened or damaged,

hydrogen fluoride and carbon monoxide may be released.

Hazardous reactivity (polymerization): Will not occur.

# 11. Toxicological information

Acute toxicity: This product does not elicit toxicological properties during routine

handling and use.

Contents of broken/leaking battery may be irritating/corrosive to

skin and eyes, and if ingested.

Serious eye damage/irritation: Contents of open battery can be eye irritant or corrosive.

Skin corrosion/irritation: Not expected under normal use. Contents of open battery can

be a skin irritant or corrosive.

Respiratory or skin sensitisation: Not a skin or respiratory sensitiser.

Inhalation: None expected.

Ingestion: Not expected under normal use. Ingestion of battery contents may

cause gastrointestinal tract burns, nausea and vomiting.

Germ cell mutagenicity: No data available

Carcinogenicity:

IARC: Not listed according to IARC.

(IARC: International Agency for Research on Cancer, by the World Health Organisation (WHO)).

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: May cause irritation/corrosion to eyes, skin,

gastrointestinal tract on contact with open battery contents.

Specific target organ toxicity – repeated exposure: None under normal conditions of use. May be skin

sensitisiser on contact with open battery contents.

Aspiration hazard: No data available

This product does not contain any kinds of the following substances and halogen-type flame retardants

including Chlorine and Bromide type harmful flame retardants which are listed in Appendix TCO documents and relevant

international ECO requirements:

Polybromated Biphenyls (PBB)
Polybromated Diphenylethers (PBDE)
Polychlorinated Biphenyls (PCB)
Polychlorinated Terphenyls (PCT)
Polychlorinated Paphthalene (PCN)

Chlorinated Paraffins (CFC) Polyvinyl Chloride (PVC) Carbon Tetrachloride

Page 6 of 7

Revision: 1

12. Ecological information

Self assessment: Slightly hazardous for water in the case of a broken/open

battery with leakage of the contents. The batteries do not contain mercury, cadmium or other heavy metals. Do not allow large quantities to reach sewage system and

waterways.

Ecotoxicity: No data available.

Persistence and biodegradeability: No data available.

Bioaccumulative potential: No data available.

Mobility in soil: No data available.

Results of PBT and VPvB assessment: PBT/VPvB assessment not available as chemical safety assessment not

required/not conducted.

Other adverse effects: No data available.

# 13. Disposal considerations

Do not dispose in fire. Disposal should be made with consideration to recycling options available in your area. Dispose at permitted waste treatment and/or disposal sites in accordance with local and national regulations.

Batteries do not contain hazardous materials according to EC Directives 91/157/EEC and 93/86/EEC.

\_\_\_\_\_

### 14. Transport information

#### IATA:

International Air Transport Association (IATA) Dangerous Goods Regulations (55<sup>th</sup> Edition) – Packing Instruction 965, 966 or 967 Section II is applied.

Lithium ion batteries supplied by SDI Limited are less than 100 Watt-hours and are in compliance with Section II PI 965, 966 or 967.

### IMDG:

Transport according to International Maritime Dangerous Goods (IMDG) Code Amendment 35-10, Special Provisions 188, 230, 310 & 957 for UN 3480 / 3481 Lithium Ion Battery, Packing Instruction P903 for lithium ion batteries.

There are no hazards in accordance with the UN recommendations tests (Manual of Tests and Criteria, Part III, sub-section 38.3, 1.2m Drop):

N	Items	Result	Remark
1	Altitude	Pass	
2	Thermal Shock	Pass	
3	Vibration	Pass	
4	Shock	Pass	
5	External Shock	Pass	
6	Impact	Pass	
7	Overcharge	Pass	
8	Forced Discharge	N/A	For cell
9	1.2m Drop Test	Pass	

Page 7 of 7

**Revision: 1** 

# 15. Regulatory information

Not classified as hazardous according to the Globally Harmonised System of Classification and Labelling of chemicals (GHS). The product is made from materials with no detectable mercury.

This battery is to be used in dental curing lights Radii Cal and Radii Plus regulated by:

TGA Medical Devices Directive 93/42/EEC FDA National regulations.

## 16. Other information

The information provided herein is given in good faith, but no warranty expressed or implied is made.

Prepared by: SDI Limited Phone Number:

3-13 Brunsdon Street, Bayswater

+61 3 8727 7111

Victoria, 3153, Australia

**Department issuing MSDS:** Research and Development

**Contact:** R&D Director

Page 1 of 8

**Revision: 3** 

## 1. Identification of the substance/mixture and of the Company/undertaking:

1.1 Product identifier:

Product Names: Lithium-ion battery in equipment – Radii Plus and Radii Cal

1.2 Relevant identified use:

Relevant use: Battery in Radii Plus and Radii Cal, to be used as dental curing

lights.

Further information:

Battery System: Lithium-ion (Li-ion) battery pack.

Nominal voltage: 7.4V Rated Capacity: 1550mAh Wh rating: 11.47 Wh

1.3 Details of the supplier of the Safety Data Sheet:

**Manufacturer / Supplier** 

SDI Limited SDI (North America) Inc. 3-13 Brunsdon Street, Bayswater Victoria, 3153, Australia Itasca, IL 60143, USA

<u>Telephone</u>: <u>Telephone</u>:

+61 3 8727 7111 (Business hours) +1 630 361 9200 (Business hours)

Southern Dental Industries Ltd

Block 8, St Johns Court

Surgeries Road

Southern Dental Industries Ltd

SDI Brasil Indústria e Comércio Ltda

Rua Dr. Virgílio de Carvalho Pinto, 612

Swords Road Pinheiros, São Paulo, 05415-020

Santry, Dublin 9, Ireland Brasil

+353 1 886 9577 (Business Hours) + 55 11 3092 7100 (Business Hours)

**Telephone:** 

**Emergency contact number:** +61 3 8727 7111

Email: <a href="mailto:ray.cahill@sdi.com.au">ray.cahill@sdi.com.au</a> (Technical Director, SDI Limited)

## 2. Hazard Identification

**Telephone:** 

Not classified as hazardous according to the Globally Harmonised System for classification and labelling of chemicals (GHS). No effect on skin contact, skin absorption, eye contact and inhalation under routine handling and use.

Potentially hazardous materials are sealed and contained in equipment. Equipment is packed in strong outer packaging to withstand normal handling and use. Exposure could occur if the equipment has been exposed to high temperatures (>125°C), battery or cells have been opened, crushed, dissembled or burned. Keep away from heat.

Obtained by Global Safety Management, 1-813-435-5161 - www.GSMSDS.com

Page 2 of 8

**Revision: 3** 

# 3. Composition / Information on ingredients

# Battery Cell:

Components	Content (wt %)	CAS number
Lithium Cobalt Dioxide (LiCoO2)	Less than 38 wt %	12190-79-3
Lithium Hexafluorophosphate (LiPF6)	Less than 3 wt %	21324-40-3
Ethylene Carbonate (C3H4O3)	Less than 6 wt %	96-49-1
Chain carbonate ( - )	Less than 8 wt %	
Graphite (C)	Less than 20 wt %	7782-42-5
Lead (Pb)	Less than 0.1 wt % (1000ppm)	
Mercury (Hg)	Less than 0.0005 wt % (5ppm)	

Note: other 25% includes the below materials:

- Al (positive Base Film, Cap, Can, Tab)
- Cu (Negative film base)
- Ni (Tab, Terminal)
- Fe (Terminal)
- Resin (PP, PE, PET) (Separator, Plastic, Parts, Insulator)

# Circuit Module:

Hazardous ingredients	%	CAS number
Lead	< 0.1	7439-92-1
Mercury	0	7439-97-6
Chromium	0	7440-47-3
Cadmium	0	7440-43-9
Plastic case and Si2O	0	N/A

# Plastic Parts and Paints:

Ingredients	%	CAS number
Polycarbonate	More than 81 wt%	25971-63-5
Flame retardant	Less than 12 wt%	
Elastomer	Less than 7 wt%	

Page 3 of 8

**Revision: 3** 

#### 4. First Aid Measures

Intact/undamaged cell (battery pack):

- Inhalation, eye contact and skin contact: Not a health hazard.

- Ingestion: If swallowed, obtain immediate medical attention.

If exposure to internal materials within cell (pack) due to damaged outer casing, the following actions are recommended:

- Ingestion: Drink milk/water and induce vomiting. Seek immediate medical attention.

- Skin: Wash skin thoroughly with soap and water and seek medical attention.

- Eye: Rinse eyes with water for 15 minutes and seek medical attention.

- Inhalation: Leave area immediately and seek medical attention.

Most important effects, acute and delayed:

The most important known symptoms and effects are described in section 2 and/or in section 11.

Indication of any immediate medical attention and special treatment needed: No data available.

# 5. Fire Fighting Measures

General Hazard: Cell is not flammable but internal organic material will

burn if the cell is incinerated.

Suitable extinguishing media: Carbon dioxide, foam, dry chemical extinguishing media

or water spray.

Unsuitable extinguishing media: No data available.

Specific hazards arising from the mixture: This product will burn under fire conditions. Combustion

products include but are not limited to hydrogen fluoride,

carbon monoxide and carbon dioxide.

If possible, remove cells from fire fighting area. If heated above 125°C, cells can explode/vent.

Advice for firefighters: Use NIOSH/MSHA approved full-face self-contained

breathing apparatus (SCBA) with full protective gear.

Page 4 of 8

**Revision: 3** 

### 6. Accidental Release Measures

Personal precautions: Use personal protective equipment to avoid contact & exposure.

Remove all metal objects including jewellery, belts, etc before

handling battery.

Remove all sources of ignition. Ensure adequate ventilation.

For personal protection, see section 8.

Environmental precautions: Prevent any spillage from entering drains or waterways.

Method for Cleaning

and containment of Spills: For small spills, use paper towel or dry cloth to absorb electrolyte

spill. For larger spills, clean up spill using an inert absorbent material such as dry sand or vermiculite. Place in appropriate container for disposal in accordance with local regulations. Clean up area with soap and water, and collect material for subsequent

disposal. Do not allow to enter drains or waterways.

Removal of ignition sources, provision of sufficient ventilation, control of dust: Not expected.

### 7. Handling and storage

<u>Precautions for safe handling:</u> Do not damage, disassemble or open the battery.

Keep away from heat and fire.

Conditions for safe storage, including any biocompatibilities:

Store in a cool, dry, well-ventilated place.

The packed battery should not be exposed to high temperatures (>60°C or 140°F), opened, crushed, dissembled or burned.

Specific end use: Apart from the use mentioned in section 1.2, there are no other

uses for the product.

# 8. Exposure controls and personal protection

Engineering controls: Keep away from heat and open flame.

Store in a cool dry place.

Occupational Exposure Limits: We are not aware of any national exposure limit.

Exposure controls:

Respiratory protection: None required under normal conditions of use. SCBA required in

the event of a fire.

Hand protection: Gloves not required for handling of cells.

Eye / face protection: None required under normal conditions of use.

Foot protection: Steel toed shoes recommended for large container handling.

No personal protection is required for the normal handing or the battery. If ingredients within the battery are leaking follow first aid section of this document.

Page 5 of 8

**Revision: 3** 

### 9. Physical and chemical properties

Properties such as pH, boiling point flash points are not applicable as the batteries are solid articles.

State: Solid

Odour: Not applicable
pH: Not applicable
Vapour pressure: Not applicable
Vapour density: Not applicable
Boiling point: Not applicable
Solubility in water: Insoluble
Specific gravity: Not applicable

Density: Not applicable

# 10. Stability and Reactivity

Stability: Stable under normal conditions.

Reactivity: Stable under normal conditions.

Conditions to avoid: Avoid exposure to heat and open flames, and corrosives. Do not

crush, puncture, incinerate, disassemble, or immerse in water.

Materials to avoid: Avoid exposure to heat, open flame, and corrosives.

Hazardous decomposition products: None under normal conditions. If cells are opened or

damaged, hydrogen fluoride and carbon monoxide may be

released.

Hazardous reactivity (polymerization): Will not occur.

### 11. Toxicological information

Acute toxicity: This product does not elicit toxicological properties during

routine handling and use.

Contents of broken/leaking battery may be irritating/corrosive to

skin and eyes, and if ingested.

Serious eye damage/irritation: Contents of open battery can be eye irritant or corrosive.

Skin corrosion/irritation: Not expected under normal use. Contents of open battery can

be a skin irritant or corrosive.

Respiratory or skin sensitisation: Not a skin or respiratory sensitiser.

Inhalation: None expected.

# Product: LITHIUM ION BATTERY IN EQUIPMENT (RADII PLUS, RADII CAL)

**Revision: 3** 

11. Toxicological information

Ingestion: Not expected under normal use. Ingestion of battery contents

may cause gastrointestinal tract burns, nausea and vomiting.

Germ cell mutagenicity: No data available.

Carcinogenicity: IARC: Not listed according to IARC.

(IARC: International Agency for Research on Cancer, by the

World Health Organisation (WHO)).

Reproductive toxicity: No data available.

Specific target organ toxicity – single exposure: May cause irritation/corrosion to eyes, skin,

gastrointestinal tract on contact with open

battery contents.

Specific target organ toxicity – repeated exposure: None under normal conditions of use. May be

skin sensitiser on contact with open battery

Page 6 of 8

contents.

No data available. Aspiration hazard:

This product does not contain any kinds of the following substances and halogen-type flame retardants including Chlorine and Bromide type harmful flame retardants which are listed in Appendix TCO documents and relevant international ECO requirements:

> Polybromated Biphenyls (PBB) Polybromated Diphenylethers (PBDE) Polychlorinated Biphenyls (PCB) Polychlorinated Terphenyls (PCT) Polychlorinated Paphthalene (PCN)

Chlorinated Paraffins (CFC) Polyvinyl Chloride (PVC) Carbon Tetrachloride

### 12. Ecological information

Self-assessment: Slightly hazardous for water in the case of a broken/open battery with

> leakage of the contents. The batteries do not contain mercury, cadmium or other heavy metals. Do not allow large quantities to reach sewage system

and waterways.

No data available. **Ecotoxicity:** 

Persistence and biodegradeability: No data available.

No data available. Bioaccumulative potential:

Mobility in soil: No data available.

Results of PBT and VPvB assessment: PBT/VPvB assessment not available as chemical safety assessment

not required/not conducted.

Other adverse effects: No data available.

Page 7 of 8

**Revision: 3** 

# 13. Disposal considerations

Do not dispose in fire. Disposal should be made with consideration to recycling options available in your area. Dispose at permitted waste treatment and/or disposal sites in accordance with local and national regulations.

Batteries do not contain hazardous materials according to EC Directives 91/157/EEC & 93/86/EEC.

## 14. Transport information

# IATA (56<sup>th</sup> Ed., 2015):

Proper shipping name: Lithium ion batteries contained in equipment

UN 3481 Class 9 EQ Code- E0

Packaging Instruction – P967 (Section II)

Special Provisions – A48, A99, A154, A164, A181, A185.

### IMDG (2014 Ed.)

Proper shipping name: Lithium ion batteries contained in equipment

UN 3481 Class 9 EO Code- E0

Packaging Instruction – P903, P908, P909, LP903, LP904

Special Provisions – 188, 230, 348, 360, 376, 377.

There are no hazards in accordance with the UN recommendations tests (Manual of Tests and Criteria, Part III, sub-section 38.3, 1.2m Drop):

N	Items	Result	Remark
1	Altitude	Pass	
2	Thermal Shock	Pass	
3	Vibration	Pass	
4	Shock	Pass	
5	External Shock	Pass	
6	Impact	Pass	
7	Overcharge	Pass	
8	Forced Discharge	N/A	For cell
9	1.2m Drop Test	Pass	

Page 8 of 8

**Revision: 3** 

# 15. Regulatory information

Not classified as hazardous according to the Globally Harmonised System of Classification and Labelling of chemicals (GHS). The product is made from materials with no detectable mercury.

This battery is to be used in dental curing lights Radii Cal and Radii Plus regulated by:

- TGA
- Medical Devices Directive 93/42/EEC
- FDA
- National regulations.

16. Other information

The information provided herein is given in good faith, but no warranty expressed or implied is made.

Prepared by: SDI Limited Phone Number:

3-13 Brunsdon Street, Bayswater +61 3 8727 7111 Victoria, 3153, Australia

Date of preparation/revision: 12 May 2015.

**Department issuing MSDS:** Research and Development

**Contact:** R&D Director