SAFETY DATA SHEETS

This SDS packet was issued with item:

074586426

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071365550 071365568 071365576 071365618 074585097 074585121 074586301 074586319 074586327 074586376 71365618

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

071386531 071386549 071386556 071390400 074585006 074585014 074585022 074585105 074585113 074585220 074585253 074585287 074585311 074585345 074585378 074585402 074585899 074585915 074585923 074585931 074585949 074586384 074586392 074586400 074586418 074586434 074586467 074586475 074592663



SAFETY DATA SHEET

Issue Date 26-Sept-2014 Revision Date 14-July-2015 Version 3

1. IDENTIFICATION

Product Identifier

Product Name FLEXACRYL SOFT LIQUID

Other means of identification

SDS# 038 UN/ID No UN1993

Product Code 1103, 1104, 1106, 1107, 1108, 1109, 1123, 1134, 1156

Recommended use of the chemical and restrictions on use

Recommended Use Fabrication of denture relines

Details of the supplier of the safety data sheet

Supplier Address Lang Dental Mfg. Co., Inc.

175 Messner Dr. Wheeling, IL 60090

USA

Emergency telephone number

Company Phone Number 847-215-6622

Emergency Telephone (INFOTRAC) 352-323-3500 (International)

800-535-5053 (North America)

Authorized European Representative MediMark® Europe SARL

11, rue Emile Zola – BP 2332 38033 Grenoble Cedex 2

France

Tel: +33 476 86 43 22 Fax: +33 476 17 19 82

Email: info@medimark-europe.com

2. HAZARDS IDENTIFICATION

Classification

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Serious eye damage / eye irritation	Category 2A
STOT Single exposure	Category 3
Hazardous to the aquatic environment- Acute hazard	Category 2

Signal word Warning

Hazard statements H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.



Appearance Colorless to slight yellow liquid Physical state Liquid Odor Acrid

Precautionary Statements - Prevention

P271 Use only outdoors or in a well-ventilated area.

P264 Wash face, hands and any exposed skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P272 Contaminated work clothing should not be allowed out of the workplace.

P261 Avoid breathing dust.

P210 Keep away from heat/sparks/open flames/hot surface. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.

Precautionary Statements - Response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P362 Take off contaminated clothing and wash it before reuse.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+P378 In case of fire: Use CO₂, dry chemical or foam for extinction.

Precautionary Statements - Storage P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal P501 Dispose of contents/container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC) May be harmful if swallowed

Other Information Harmful to aquatic life.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight - %	Trade Secret
Citric Plasticizer	Proprietary	<50	*
N-Butyl Methacrylate	97-88-1	<50	*
Trimethylolpropane Trimethacrylate	3290-92-4	<5	*
N, N-Dimethyl-p-Toluidine	99-97-8	<5	*

^{*}Specific chemical weight has been withheld as a trade secret.

Flexacryl Soft Liquid 038 v.3 Page 2 of 9

4. FIRST AID MEASURES

First aid measures

General advice If exposed or concerned, get medical advice or attention.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Keep patient warm and at

rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing

for at least 15 minutes. Call a physician immediately.

Ingestion Do NOT induce vomiting. Wash out mouth with water and give 200-300 mL (half pint) of water to drink. Get

medical attention. Never give anything by mouth to an unconscious person.

Skin Contact Wash off immediately with plenty of soap and water. Take off contaminated clothing. Wash contaminated

clothing before reuse. If skin irritation or rash occurs, get medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms May cause skin and eye irritation. Irritating to mouth, throat, and stomach if ingested. May cause irritation to

the mucous membranes and upper respiratory tract..

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable: Chemical foam, carbon dioxide (CO₂), dry chemical

Unsuitable: Not determined

Specific hazards arising from the chemical

Flammable. Vapors may travel to source of ignition and flash back. Fine mist or sprays may be flammable at temperatures below the flash point. May polymerize on heating. Sealed containers may rupture explosively if hot. Cool containers exposed to flames with water until well after the fire is out.

Hazardous Combustion Products: Carbon oxides

Sensitivity to Static Discharge: Yes

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Fight fire from a safe location.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Review Section 5 Fire-Fighting Measures and Section 7 Handling and Storage before proceeding

with clean up. Refer to protective measures listed in sections 7 and 8. Evacuate personnel to safe

areas. Ventilate affected area. Wear self-contained breathing apparatus (SCBA).

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and clean-up

Flexacryl Soft Liquid 038 v.3 Page 3 of 9

Method for containment Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Dike the

spilled material, where this is possible.

Method for clean-up

Take up with sand or other non-combustible absorbent material and place into containers for later

disposal. Clean up material as RCRA Hazardous Waste. Use non-sparking hand tools and

explosion-proof electrical equipment.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Do not breathe dust, fume, gas, mist, vapors, or spray. Avoid contact with skin, eyes, or clothing.

Wash thoroughly after handling. Keep containers closed when not in use. Ground container and transfer equipment to eliminate static electric sparks. Keep away from heat, sparks, open flame, and hot surfaces. NO SMOKING. Use non-sparking hand tools and explosion proof electrical equipment. Take precautionary measures against static discharges. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Contaminated clothing should not be allowed out

of the workplace.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct sunlight.

Store in accordance with National Fire Protection Association recommendations. Maintain air

space inside storage containers. Inhibitor requires air (oxygen) contact to function.

Incompatible materials Oxidizers and reducing agents

Material has strong solvent properties and can soften paint and rubber.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelinesConsideration should be given to the work procedures involved and the potential extent of

exposure as they may determine whether a higher level of protection is required. The following

information is given as general guidance.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Citric Plasticizer	TWA: 5 mg/m ³	TWA: 5 mg/m ³	IDLH: 4000 mg/m ³
	· ·	TWA: 5 mg/m ³ (vacated)	TWA: 5 mg/m ³

Appropriate engineering controls

Engineering controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye / face protection Wear approved safety goggles. Wear coverall chemical splash goggles and face shield when

possibility exists for eye and face contact due to splashing or spraying material.

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls as

appropriate to prevent skin contact. Nitrile rubber is better than PVC.

Respiratory protectionNone needed under normal use conditions. If the TLV is exceeded, use NIOSH approved organic

vapor respirator with a dust/mite pre-filter. Use positive pressure air supplied respirator if there is

any potential for an uncontrolled release, exposure is not known, or any other circumstances where air purifying respirators may not provide adequate protections.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid Odor Acrid

Appearance Colorless to slightly Odor threshold Not determined

yellow liquid

Color Clear to slightly yellow

<u>Property</u> <u>Values</u> <u>Remarks / Method</u>

pH Not determined
Melting point / freezing point
Boiling point / boiling range

Not determined
-25°C / -13°F
163-164°C / 325-

327°F

Flash point 59°C / 139°F
Evaporation rate Not determined
Flammability (solid, gas) n/a (liquid)

Flammability limits in air

Upper flammability limit Not established Lower flammability limit Not established

 Vapor pressure
 2 mm Hg
 @ 20°C

 Vapor density
 4.9
 @15.5°C (Air = 1)

Specific gravity 0.978
Water solubility 0.36 %

Water solubility 0.36 %
Solubility in other solvents Not determined

Partition coefficient 3.03

Autoignition temperature
Decomposition temperature
Kinematic viscosity
Dynamic viscosity
Explosive properties
Not determined

Other information

10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions

<u>Chemical stability</u> Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing

Hazardous polymerization Hazardous polymerization may occur. Monomer vapors are uninhibited and may form polymers in vent or flame arresters, resulting in blockage of vents. Conditions to avoid for hazard polymerization: excessive heat, storage in absence of inhibitor, inadvertent addition of catalyst

Conditions to avoid

Avoid all possible sources of ignition, contamination.

Incompatible materials

Oxidizers. Reducing agent.

Material has strong solvent properties and can soften paint and rubber.

<u>Hazardous decomposition products</u> If heated to decomposition, CO and CO₂ may be produced.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposures

Product information

Inhalation Harmful if inhaled.

Eye contact Causes severe eye irritation.

Skin contact Causes skin irritation. May be harmful in contact with skin.

Ingestion May be harmful if swallowed.

Component information

Chemical Name	ORAL LD50	DERMAL LD50	INHALATION LC50
Citric plasticizer	6300 mg/kg (rat)	>2000 mg/kg (rabbit)	>15.68 mg/L (rat) 4 h
N-Butyl Methacrylate 97-88-1	16 μg/kg (rat)	10181 mg/kg (rabbit)	4910 ppm (rat) 4 h
Trimethylolpropane Trimethacrylate 3290-92-4	=5660 /kg (rat)	= 16 mL/kg (rabbit)	-
N, N-Dimethyl-p-Toluidine 99-97-8	1650 mg/kg (rat)	-	1400 mg/m ³ (rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms May cause skin and eye irritation. May cause irritation to the mucous membranes and upper respiratory tract.

Irritating to mouth, throat, and stomach if ingested.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause allergic skin reaction.

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

Reproductive toxicity May damage fertility or the unborn child.

STOT – single exposure May cause respiratory irritation. May cause drowsiness or dizziness

STOT – repeated exposure May cause damage to organs through prolonged or repeated exposure.

<u>Numerical measures of toxicity – Product</u> Not determined

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)	4697	mg/kg
ATEmix (dermal)	2098	mg/kg
ATEmix (inhalation-dust/mist)	4998	mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life.

Chemical Name	Algae / aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Citric Plasticizer	0.4: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 1.2: 72 h Pseudokirchneriella subcapitata mg/L EC50	0.31 – 5.45: 96 h Pimephales promelas mg/L LC50 static 0.42 – 1.28: 96 h Lepomis macrochirus mg/L LC50 static 0.71 – 1.2: 96 h Pimephales promelas mg/L LC50 flow-through 1.24 – 5.3: 96 h Oncorhynchus mykiss mg/L LC50 static 1.38 – 1.74: 96 h Lepomis macrochirus mg/L LC50 flow-through > 1.24: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	EC50 = 10.9 mg/L 30 min EC50 = 10.9 mg/L 5 min EC50 = 11.1 mg/L 15 min EC50 = 2.2 mg/L 24 h	2.99 48 h Daphnia magna mg/L EC50 Static 3.4: 48 h Daphnia magna mg/L EC50
N-Butyl Methacrylate 97-88-1	57: 96 h Pseudokirchneriella subcapitata mg/L EC50	11:96 h Pimephales promelas mg/L LC50 flow-through	EC50 = 37 mg/L 5 min EC50 = 49 mg/L 15 min EC50 = 55 mg/L 5 min EC50 > 253.6 mg/L 18 h	32:48 h Daphnia magna mg/L EC50
Trimethylolpropane Trimethacrylate 3290-92-4	-	144: 96 h Oncorhynchus mykiss LC50 160: 96 h Pimephales promelas mg/L LC50 112: 96 h Lepomis macrochirus mg/L LC50	-	-
N,N-Dimethyl-p- Toluidine 99-97-8	-	42-50.5: 96 h Pimephales promelas mg/L LC50 flow-through	-	-

Persistence and degradability Material is readily biodegradable. 88% in 28 days

<u>Bioaccumulation</u> This product has moderate potential for bioaccumulation.

<u>Mobility</u> This product is predicted to have moderate mobility in soil.

Chemical Name	Partition coefficient
Citric Plasticizer	5.38
N-Butyl Methacrylate	2.26

Other adverse effects This product is substantially removed in biological treatment process BOD 28 day / DOC = 32.8%.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesFollow all local and national government regulations in disposing material or contaminated

packaging.

For U.S. - Dispose of in accordance with federal, state and local regulations. Do not flush to surface or sanitary sewer system Dispose of by incineration or in accordance with local regulations.

Do not incinerate closed containers.

Contaminated PackagingDispose of all empty containers in accordance with local and national government regulations.

Flexacryl Soft Liquid 038 v.3

Chemical Name	RCRA	RCRA – Basis for Listing	RCRA – D Series Wastes	RCRA – U Series Wastes
Citric Plasticizer	U069	Included in waste stream;	-	U069
		F039		

14. TRANSPORTATION INFORMATION

DOT

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (n-Butyl Methacrylate, stabilized / Plasticizer solution)
Hazard Class	3
Packing Group	

<u>IATA</u>

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (n-Butyl Methacrylate, stabilized / Plasticizer solution)
Hazard Class	3
Packing Group	

IMDG

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (n-Butyl Methacrylate, stabilized / Plasticizer solution)
Hazard Class	3
Packing Group	III

15. REGULATORY INFORMATION

International Inventories

DSL Listed Canadian Domestic Substances List

EINECS Listed European Inventory of Existing Chemical Substances

EU Regulations EC No. 1272/2008 (CLP) Classification, Labeling, Packaging

Medical Devices Directive 93/42/EEC - Class I Medical Devices

US Federal Regulations

Chemical Name	CAS	Weight %	SARA 313 Threshold Values %
Citric Plasticizer	Proprietary	<50	1.0

SARA 311 / 312 Hazard Categories

Chemical Name	CWA – Reportable	CWA – Toxic	CWA – Priority	CWA – Hazardous
	Quantities	Pollutants	Pollutants	Substances
Citric Plasticizer	10 lb.	X	Χ	Χ

Chemical Name	Hazardous Substances RQs	CERCLA / SARA RQ	Reportable Quantity (RQ) Final
Citric Plasticizer	10 lb.	-	10 lb. / 4.54 kg

Flexacryl Soft Liquid 038 v.3 Page 8 of 9

US State Regulations

Chemical Name	California Proposition 65
Citric Plasticizer	Developmental Female Reproductive Male Reproductive

US State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Citric Plasticizer	X	X	X
N-Butyl Methacrylate	Х	X	Х

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability
	Not determined	Not determined	Not determined
HMIS	Health Hazards	Flammability	Physical Hazards
	2	2	2

Issue Date 26-Sept-2014 **Revision Date** 14-July-2015

Revision Note Section 2 – Revise classification categories, revise some Hazard Statements and Precautionary Statements,

remove pictogram

Information to be updated in due course Hazard pictograms listed in this SDS to be added to product label

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



SAFETY DATA SHEET

Issue Date 26-Sept-2014 Revision Date Version 1

1. IDENTIFICATION

Product Identifier

Product Name FLEXACRYL POWDER

Other means of identification

SDS# 001

Product Code 0920, 0923, 0930, 0934, 0950, 0956, 0970, 0980, 1123, 1134, 1156

Recommended use of the chemical and restrictions on use

Recommended Use Fabrication of denture relines

Details of the supplier of the safety data sheet

Supplier Address

Lang Dental Mfg. Co., Inc. 175 Messner Dr. Wheeling, IL 60090

USA

Emergency telephone number

Company Phone Number 847-215-6622

Emergency Telephone (INFOTRAC) 352-323-3500 (International)

800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Skin sensitization Category 1

Signal word

Warning

Hazard statements

May cause an allergic skin reaction



Physical State Powder Appearance Fine, white or pink Odor Faint odor in bulk

Precautionary Statements - Prevention

Avoid breathing dust, fumes, gas, mist, vapors or spray.

Flexacryl Powder 001 Page 1 of 6

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves.

Precautionary Statements - Response

If on skin, wash with plenty of soap and water.

If skin irritation or rash occurs, get medical advice / attention.

Wash contaminated clothing before reuse.

Precautionary Statements - Disposal

Dispose of contents / container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

Not applicable

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight - %	Trade Secret
Polymer	9003-42-3	< 99	*
Benzoyl peroxide	94-36-0	<2	*

^{*}Specific chemical weight has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

Inhalation Remove to fresh air. Keep at rest in a position comfortable for breathing, Get medical attention if discomfort

persists.

Eye contact Rinse immediately with plenty of water, including under the eyelids, for at least 15 minutes. If irritation persists,

get medical advice / attention.

Ingestion Do NOT induce vomiting. Drink plenty of water or milk immediately. If vomiting, continue to offer water or milk.

Never give anything by mouth to an unconscious person. Call a physician or poison control center

immediately and provide an estimate of when and how much material was ingested.

Skin ContactWash with soap and water. If irritation persists, call a physician. Take off contaminated clothing and wash

before reuse.

Most important symptoms and effects, both acute and delayed

Symptoms Eyes, skin and respiratory tract may be irritated by gross overexposure to particulates. Eyes may be red, itchy,

irritated or watering from overexposure. Ingestion of large amounts may be irritating if product is swallowed.

May cause nausea, headache, vomiting or diarrhea.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable: Water, carbon dioxide (CO₂), dry chemical

Unsuitable: Avoid extinguishing methods which may generate dust clouds. Water stream can disperse dust in air producing a fire

hazard and possible explosion hazard if exposed to ignition source.

Specific hazards arising from the chemical

Flexacryl Powder 001 Page 2 of 6

For bulk size: Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust.

Protective equipment and precautions for firefighters

Self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

thoroughly before reuse.

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and clean-up

Method for containment Prevent further leakage or spillage if safe to do so.

Method for clean-up Sweep up to avoid slipping hazard. Keep airborne particulates at a minimum when cleaning up

spills. Clean up in accordance with all applicable regulations. Wash all affected areas with plenty of

warm water and soap.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use only in well-ventilated areas. Avoid contact with skin, eyes or clothing. Avoid breathing dust or

fume. Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly

after handling. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed to prevent water absorption and contamination. Store in a dry, cool

and well-ventilated place away from direct sunlight or other sources of light or intense heat.

Preferable storage temperature not to exceed 35°C.

Packaging materials Keep in original container.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Benzoyl peroxide	TWA: 5 mg/m ³	TWA: 5 mg/m ³	IDLH: 1500 mg/m ³
94-36-0	_	TWA: 5 mg/m ³ (vacated)	TWA: 5 mg/m ³

Appropriate engineering controls

Apply technical measures to comply with the occupational exposure limits. When working with

large quantities of product, provide adequate ventilation (e.g. local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. Use good local exhaust at processing equipment, including buffers, sanders, grinders and polishers.

Individual protection measures, such as personal protective equipment

Flexacryl Powder 001 Page 3 of 6

Eye / face protection Depending on the use of this product, safety glasses or goggles may be worn. If necessary, refer to

US OSHA 29 CFR SS1910.133, Canadian standards or the European Standard EN 166. Ensure

that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Skin and body protection If anticipated that prolonged and repeated skin contact will occur during use of this product, wear

gloves for routine industrial use. If necessary, refer to US OSHA 29 CFR SS1910.138 or the

appropriate standards of Canada or the EC member states.

Respiratory protection No special respiratory protection is required under typical circumstances of use or handling. If

necessary, use only respiratory protection authorized per US OSHA requirement in 29 CFR SS 1910.134, or applicable US state regulations, or the appropriate standards of Canada, its

provinces, EC member states or Australia. VENTILATION: Local exhaust at processing equipment.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical statePowderOdorFaint odor in bulkAppearanceFineOdor thresholdNot determined

Color White or pink

<u>Property</u> <u>Values</u> <u>Remarks / Method</u>

pH Not determined

Melting point / freezing point

Boiling point / boiling range

Flash point

Evaporation rate

Flammability (solid, gas)

Not determined

Not applicable

Not applicable

Non-flammable

Flammability limits in air

Oxidizing properties

Upper flammability limit Not applicable Not applicable Lower flammability limit Vapor pressure Not applicable Vapor density Not applicable Specific gravity Not determined Water solubility Insoluble in water Solubility in other solvents Not determined Partition coefficient Not determined Autoignition temperature Not determined **Decomposition temperature** Not determined Kinematic viscosity Not determined Dynamic viscosity Not determined Not determined **Explosive properties**

10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions

<u>Chemical stability</u> Stable under recommended storage conditions

Not determined

<u>Possibility of hazardous reactions</u> None under normal processing

Hazardous polymerization Does not occur.

<u>Conditions to avoid</u> Heating above 240°C / 464°F

Flexacryl Powder 001 Page 4 of 6

<u>Incompatible materials</u> Strong oxidizing agents

<u>Hazardous decomposition products</u> Methacrylate monomer, oxides of carbon when burned

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposures

Product information This product has not been tested on animals to obtain toxicology data.

Inhalation Persons with impaired lung function or asthma-like conditions may experience additional breathing difficulties.

Eye contact Avoid contact with eyes.

Skin contact May be irritating to skin in some sensitive individuals, especially after prolonged or repeated contact.

Ingestion Large amounts may cause nausea, headache, vomiting or diarrhea.

Component information

Chemical Name	ORAL LD50	DERMAL LD50	INHALATION LC50
Benzoyl peroxide 94-36-0	6400 mg/kg (rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms See Section 4.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Not classifiable as a human carcinogen (IARC group 3)

<u>Numerical measures of toxicity – Product</u> Not determined

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral) 6250 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity There is no specific data available for this product; however, very large releases may be harmful or fatal to overexposed

aquatic life.

Persistence and degradability Not determined

<u>Bioaccumulation</u> Not determined

<u>Mobility</u> Not determined

Other adverse effects Not determined

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and regulations.

Flexacryl Powder 001 Page 5 of 6

Chemical Name	California Hazardous Waste Status
Benzoyl peroxide 94-36-0	6400 mg/kg (rat)

Contaminated Packaging

For bulk only: Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards due to residual material associated with empty containers. Dispose of all empty containers properly in accordance with federal, state and local regulations.

Chemical Name	California Hazardous Waste Status
Benzoyl peroxide	Toxic, Ignitable, Reactive
94-36-0	

14. TRANSPORTATION INFORMATION

DOT Not regulated

<u>IATA</u> Not regulated

<u>IMDG</u> Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA For use in FDA regulated products only United States Toxic Substances Control Act, Section 8(b) Inventory

DSL Listed Canadian Domestic Substances

US Federal Regulations

Chemical Name	CAS	Weight %	SARA 313 - Threshold Values %
Benzoyl peroxide	94-36-0	1	1.0

US State Regulations

US State Right-to-know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Benzoyl peroxide	X	X	X
94-36-0			

16. OTHER INFORMATION

HMIS	Health Hazards	Flammability	Physical Hazards
	1	1	0

Issue Date

26-Sept-2014

Revision Date Revision Note

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Flexacryl Powder 001 Page 6 of 6



SAFETY DATA SHEET

Issue Date 26-Sept-2014 Revision Date 14-July-2015 Version 3

1. IDENTIFICATION

Product Identifier

Product Name FLEXACRYL HARD LIQUID

Other means of identification

SDS# 037 UN/ID No UN1993

Product Code 0903, 0904, 0906, 0907, 0908, 0923, 0934, 0956

Recommended use of the chemical and restrictions on use

Recommended Use Fabrication of denture relines

Details of the supplier of the safety data sheet

Supplier Address Lang Dental Mfg. Co., Inc.

175 Messner Dr. Wheeling, IL 60090

USA

Emergency telephone number

Company Phone Number 847-215-6622

Emergency Telephone (INFOTRAC) 352-323-3500 (International)

800-535-5053 (North America)

Authorized European Representative MediMark® Europe SARL

11, rue Emile Zola – BP 2332 38033 Grenoble Cedex 2

France

Tel: +33 476 86 43 22 Fax: +33 476 17 19 82

Email: info@medimark-europe.com

2. HAZARDS IDENTIFICATION

Classification

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Serious eye damage / eye irritation	Category 2A
STOT Single exposure	Category 3
Hazardous to the aquatic environment- Acute hazard	Category 2

Signal word Warning

Hazard statements H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Flexacryl Hard Liquid 037 v.3



Appearance Colorless to slightly yellow Physical state Liquid Odor Acrid

Precautionary Statements - Prevention

P271 Use only outdoors or in a well-ventilated area.

P264 Wash face, hands and any exposed skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P272 Contaminated work clothing should not be allowed out of the workplace.

P261 Avoid breathing dust.

P210 Keep away from heat/sparks/open flames/hot surface. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.

Precautionary Statements - Response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P362 Take off contaminated clothing and wash it before reuse.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+P378 In case of fire: Use CO₂, dry chemical or foam for extinction.

Precautionary Statements - Storage P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal P501 Dispose of contents/container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC) May be harmful if swallowed.

Other Information Harmful to aquatic life.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight - %	Trade Secret
N-Butyl Methacrylate	97-88-1	<94	*
Trimethylolpropane	3290-92-4	<10	*
Trimethacrylate			
N, N-Dimethyl-p-Toluidine	99-97-8	<2	*

^{*}Specific chemical weight has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Keep patient warm and at

rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing

for at least 15 minutes. Call a physician immediately.

Ingestion Do NOT induce vomiting. Wash out mouth with water and give 200-300 mL (half pint) of water to drink. Get

medical attention. Never give anything by mouth to an unconscious person.

Skin Contact Wash off immediately with plenty of soap and water. Take off contaminated clothing. Wash contaminated

clothing before reuse. If skin irritation or rash occurs, get medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms May cause skin and eye irritation. May cause irritation to the mucous membranes and upper respiratory tract.

Irritating to mouth, throat and stomach if ingested.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable: Chemical foam, carbon dioxide (CO₂), dry chemical

Unsuitable: Not determined.

Specific hazards arising from the chemical

Vapors may travel to source of ignition and flash back. Fine mist or sprays may be flammable at temperatures below the flash point. Sealed containers may rupture explosively if hot. Cool containers exposed to flames with water until well after the fire is out.

Hazardous Combustion Products: Carbon oxides

Sensitivity to Static Discharge: Yes

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Fight fire from a safe location.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Refer to protective measures listed in Sections 7 and 8. Review Fire Fighting Measures and

Handling (Personnel) sections before proceeding with clean-up. Ventilate affected area. Wear self-

contained breathing apparatus (SCBA). Evacuate personnel to safe area.

Environmental precautions Do not allow into any sewer, on the ground or any body of water.

Methods and material for containment and clean-up

Method for containment ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Dike far ahead of liquid spill for later disposal.

Flexacryl Hard Liquid 037 v.3 Page 3 of 8

Method for clean-up

Take up with sand, earth or other non-combustible absorbent material. Clean-up material as a

RCRA Hazardous Waste. Use non-sparking hand tools and explosion-proof electrical equipment.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Do not breathe dust, fume, gas, mist, vapor or spray. Avoid contact with skin, eyes or clothing.

Wash thoroughly after handling. Keep containers closed when not in use. Ground container and transfer equipment to eliminate static electric sparks. Keep away from heat, spark, open flame and hot surfaces. NO SMOKING. Use only in well-ventilated areas. Use personal protection

not surfaces. NO SMOKING. Use only in well-ventilated areas. Use personal protection recommended in Section 8. Contaminated work clothing should not be allowed out of the workplace. Use non-sparking hand tools and explosion-proof electrical equipment. Take

precautionary measures against static discharge.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct sunlight.

Store in accordance with National Fire Protection Association recommendations. Maintain air

space inside storage containers. Inhibitor requires air (oxygen) contact to function.

Incompatible materials Oxidizers, reducing agent

Material has strong solvent properties and can soften paint and rubber.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines The following information is given as general guidance.

Appropriate engineering controls

Engineering controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye / face protection Wear approved safety goggles.

Skin and body protection Wear impervious protective clothing, including: booths, gloves, lab coat, apron or coveralls, as

appropriate, to prevent skin contact. Nitrile rubber is better than PVC.

Respiratory protectionUse NIOSH approved air-purifying respirator if the potential to exceed established exposure limits

exists. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure is not known or any other circumstances where air purifying respirators may not

Page 4 of 8

provide adequate protections.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical stateLiquidOdorAcridAppearanceLiquidOdor thresholdNot determined

Color Clear to slightly yellow

<u>Property</u> <u>Values</u> <u>Remarks / Method</u>

pH Not determined
Melting point / freezing point Not determined
Boiling point / boiling range 163-164°C / 325-327° F

Flash point 51°C / 124°F
Evaporation rate Not determined Flammability (solid, gas) n/a (liquid)

Flammability limits in air

Upper flammability limit 8.0% Lower flammability limit 2.0%

 Vapor pressure
 28mm Hg
 @ 20°C

 Vapor density
 4.9
 @15.5°C (Air = 1)

Specific gravity 0.910 Water solubility 0.36%

Solubility in other solvents Not determined Partition coefficient Not determined 296°C / 564.8°F **Autoignition temperature Decomposition temperature** Not determined Kinematic viscosity Not determined Dynamic viscosity Not determined **Explosive properties** Not determined Oxidizing properties Not determined

Other information

10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions

Chemical stability Stable under recommended storage conditions

<u>Possibility of hazardous reactions</u> None under normal processing

Hazardous polymerization Hazardous polymerization may occur. Monomer vapors are uninhibited and may form polymers in vent

or flame arresters, resulting in blockage of vents. Conditions to avoid for hazardous polymerization:

excessive heat, storage in absence of inhibitor, inadvertent addition of catalyst.

Conditions to avoid Heat

All possible sources of ignition

Contamination

Incompatible materials Oxidizers

Reducing agent

Material has strong solvent properties and can soften paint and rubber.

<u>Hazardous decomposition products</u> Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposures

Product information

Inhalation Harmful if inhaled.

Eye contact Causes severe eye irritation.
Skin contact Causes skin irritation.
Ingestion May be harmful if swallowed.

Flexacryl Hard Liquid 037 v.3 Page 5 of 8

Component information

Chemical Name	ORAL LD50	DERMAL LD50	INHALATION LC50
N-Butyl Methacrylate 97-88-1	16 g/kg (rat)	10181 mg/kg (rabbit)	4910 ppm (rat) 4 h
Trimethylolpropane Trimethacrylate 3290-92-4	=5660 /kg (rat)	= 16 mL/kg (rabbit)	-
N, N-Dimethyl-p-Toluidine 99-97-8	1650 mg/kg (rat)	-	1400 mg/m³ (rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms May cause skin and eye irritation. May cause irritation to the mucous membranes and upper respiratory tract.

Irritating to mouth, throat and stomach if ingested.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause allergic skin reaction.

Carcinogenicity Not classifiable as a human carcinogen

STOT – single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT – repeated exposure May cause damage to organs through prolonged or repeated exposure.

Not determined

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)	3864	mg/kg
ATEmix (dermal)	10834	mg/kg
ATEmix (inhalation-dust/mist)	5225	mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life.

Chemical Name	Algae / aquatic plants	Fish	Toxicity to microorganisms	Crustacea
N-Butyl Methacrylate 97-88-1	57: 96 h Psuedokirchneriella subcapitata mg/L EC50	11: 96 h Pimephales promelas mg/L LC50 flow-through;	EC50 = 37 mg/L 5 min EC50 = 49 mg/L 15 min EC50 = 55 mg/L 30 min EC50 > 253.6 mg/L 18 h	32: 48 h Daphnia magna mg/L EC50
Trimethylolpropane Trimethacrylate 3290-92-4	-	144: 96 h Oncorhynchus mykiss LC50 160: 96 h Pimephales promelas mg/L LC50 112: 96 h Lepomis macrochirus mg/L LC50	-	-
N,N-Dimethyl-p- Toluidine 99-97-8	-	42-50.5: 96 h Pimphales promelas mg/L LC50 flow-through	-	-

Flexacryl Hard Liquid 037 v.3 Page 6 of 8

Persistence and degradability Material is readily biodegradable. 88% in 28 days

<u>Bioaccumulation</u> This product has moderate potential for bioaccumulation.

<u>Mobility</u> The product is predicted to have moderate mobility in soil.

Chemical Name	Partition coefficient
N-Butyl Methacrylate	2.26

Other adverse effects

This product is substantially removed in biological treatment processes BOD 28 day/DOC=32.8%

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesFollow all local and national government regulations in disposing material or contaminated

packaging.

For U.S. - Dispose of in accordance with federal, state and local regulations. Do not flush to surface or sanitary sewer system Dispose of by incineration or in accordance with local regulations.

Do not incinerate closed containers.

Contaminated PackagingDispose of all empty containers in accordance with local and national government regulations.

14. TRANSPORTATION INFORMATION

Note Based on package size, product may be eligible for limited quantity exception

<u>DOT</u>

UN / ID No	UN1993
Proper shipping name	N-Butyl Methacrylate, stabilized / Trimethylolpropane Trimethacrylate
	solution
Hazard Class	3
Packing Group	III

<u>IATA</u>

UN / ID No	UN1993
Proper shipping name	N-Butyl Methacrylate, stabilized / Trimethylolpropane Trimethacrylate
Tropor chipping hame	solution
Hazard Class	3
Packing Group	

<u>IMDG</u>

UN / ID No	UN1993
Proper shipping name	N-Butyl Methacrylate, stabilized / Trimethylolpropane Trimethacrylate solution
Hazard Class	3
Packing Group	III

Flexacryl Hard Liquid 037 v.3 Page 7 of 8

15. REGULATORY INFORMATION

International Inventories

DSL Listed Canadian Domestic Substances List

EINECS Listed European Inventory of Existing Chemical Substances

EU Regulations EC No. 1272/2008 (CLP) Classification, Labeling, Packaging

Medical Devices Directive 93/42/EEC - Class I Medical Devices

US Federal Regulations

SARA 311 / 312 Hazard Categories

US State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Butyl methacrylate	X	X	X
97-88-1			

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability
	Not determined	Not determined	Not determined
HMIS	Health Hazards	Flammability	Physical Hazards
	2	2	2

Issue Date 26-Sept-2014 **Revision Date** 14-July-2015

Revision Note Section 2 – revise classification categories, revise some Hazard Statements and Precautionary Statements,

remove pictogram

Information to be updated in due course Hazard pictograms listed in this SDS to be added to product label.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Flexacryl Hard Liquid 037 v.3 Page 8 of 8