

SAFETY DATA SHEETS

This SDS packet was issued with item:

077181258

N/A

according to Regulation (EC) No 1907/2006

Adhesive AC

Revision date: 21.04.2015

Print date: 17.05.2016

Page 1 of 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Adhesive AC

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

for dental use only

1.3. Details of the supplier of the safety data sheet

Company name:	Coltène/Whaledent AG
Street:	Feldwiesenstrasse 20
Place:	CH-9450 Altstätten
Telephone:	+41 (71) 75 75 300
Telefax:	+41 (71) 75 75 301
e-mail:	info.ch@coltene.com
Internet:	www.coltene.com
Responsible Department:	Regulatory Affairs msds@coltene.com

1.4. Emergency telephone number: +41 (0) 44 251 51 51 - Tox Info Suisse (24 h)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

ethyl acetate

Signal word: Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

according to Regulation (EC) No 1907/2006

Adhesive AC

Revision date: 21.04.2015

Print date: 17.05.2016

Page 2 of 6

P337+P313

If eye irritation persists: Get medical advice/attention.

Special labelling of certain mixtures

EUH066

Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
141-78-6	ethyl acetate			> 95 %
	205-500-4	607-022-00-5		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Seek medical advice.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water spray. Foam. Extinguishing powder. Carbon dioxide (CO₂). Sand.**Unsuitable extinguishing media**

High power water jet.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Wipe up with absorbent material (eg. cloth, fleece). Clear contaminated areas thoroughly.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

according to Regulation (EC) No 1907/2006

Adhesive AC

Revision date: 21.04.2015

Print date: 17.05.2016

Page 3 of 6

Advice on safe handling

Avoid contact with skin and eyes.
for professional use only Keep out of the reach of children.
Observe instructions for use.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material.
Keep away from sources of ignition. - No smoking.

Further information on handling

After use replace the closing cap immediately.
Observe instructions for use.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed and in a well-ventilated place.

Further information on storage conditions

Recommended storage temperature: 15 - 23 °C

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

8.2. Exposure controls**Protective and hygiene measures**

When using do not eat, drink or smoke.

Eye/face protection

Framed glasses.

Hand protection

Single-use gloves.

Skin protection

Lab apron.

Respiratory protection

Provide adequate ventilation.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid
Colour: light yellow
Odour: characteristic

Test method

pH-Value: neutral

Changes in the physical state

Initial boiling point and boiling range: 80 °C

Flash point: > -4 °C

Lower explosion limits: 2 vol. %

according to Regulation (EC) No 1907/2006

Adhesive AC

Revision date: 21.04.2015

Print date: 17.05.2016

Page 4 of 6

Upper explosion limits:	11.5 vol. %
Ignition temperature:	> 460 °C
Vapour pressure:	100 hPa
Density:	0.9 g/cm³
Water solubility:	80 g/L

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

heat.

10.5. Incompatible materials

Oxidizing agents.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

LD50: > 5000mg/kg (Rat)

Irritation and corrosivity

Causes serious eye damage.

STOT-single exposure

Kann Schläfrigkeit und Benommenheit verursachen. (Ethylacetat.)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information**12.1. Toxicity**

LC50: 333 g/l 48h - Oncorhynchus mykiss

12.4. Mobility in soil

No data available

Further information

According to the criteria of the EC-classification and labelling "dangerous for the environment" (93/21/EEC) the material/product is not to be classified as dangerous to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

SECTION 14: Transport information**Land transport (ADR/RID)**

<u>14.1. UN number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3
Classification code:	F1

according to Regulation (EC) No 1907/2006

Adhesive AC

Revision date: 21.04.2015

Print date: 17.05.2016

Page 5 of 6

Limited quantity: LQ6

Hazard No: 33

Other applicable information (land transport)

Special provisions: 274

E3

: 1

D/E

Special provisions: 274 601 640C

E2

: 2

Special provisions: 640C

Marine transport (IMDG)**14.1. UN number:** UN 1133**14.2. UN proper shipping name:** Adhesives**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3

Marine pollutant: •

Limited quantity: 5 L

EmS: F-E, S-D

Other applicable information (marine transport)

Special provisions: 274, 330, 944

Special provisions: 944

Air transport (ICAO)**14.1. UN number:** UN 1133**14.2. UN proper shipping name:** Adhesives**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3

Limited quantity Passenger: 1 L

IATA-packing instructions - Passenger: 305

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 307

IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E2

: Y305

60 L

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information****Additional information**

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

according to Regulation (EC) No 1907/2006

Adhesive AC

Revision date: 21.04.2015

Print date: 17.05.2016

Page 6 of 6

H336

May cause drowsiness or dizziness.

EUH066

Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)