SAFETY DATA SHEETS

This SDS packet was issued with item:

070447177

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071805316

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

070446948 070446955 070447433 071704550 071803352 071803360 071803626 071805324 071805332 071837202



Dentsply (Australia)

Chemwatch: **4993-91** Version No: **4.1.1.1**

Material Safety Data Sheet according to NOHSC and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 01/01/2013
Print Date: 14/10/2014
Initial Date: Not Available
S.Local.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Dentsply Prime & Bond NT
Chemical Name	Not Applicable
Synonyms	Prime & Bond NT
Proper shipping name	ACETONE
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

For dental use only.

Details of the manufacturer/importer

Registered company name	Dentsply (Australia)
Address	11-21 Gilby Road Mount Waverley 3149 VIC Australia
Telephone	+61 3 9538 8240
Fax	+61 3 9538 8260
Website	www.dentsply.com.au
Email	Not Available

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	1300 552 929 (Mon-Fri 9am-5pm)
Other emergency telephone numbers	1300 552 929 (Mon-Fri 9am-5pm)

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	3		
Toxicity	1		0 = Minimum
Body Contact	2		1 = Low
Reactivity	1		2 = Moderate 3 = High
Chronic	0		4 = Extreme

Poisons Schedule

S5

Page 2 of 10 Dentsply Prime & Bond NT

Issue Date: **01/01/2013**Print Date: **14/10/2014**

Risk Phrases ^[1]

R36/37/38	Irritating to eyes, respiratory system and skin.
R67	Vapours may cause drowsiness and dizziness.
R66	Repeated exposure may cause skin dryness and cracking.
R11	Highly flammable.

Legend:

1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI





Relevant risk statements are found in section 2

Indication(s)	of
dang	er

F, Xi

SAFETY ADVICE	
S09	Keep container in a well ventilated place.
S16	Keep away from sources of ignition. No smoking.
S23	Do not breathe gas/fumes/vapour/spray.
S24	Avoid contact with skin.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
S29	Do not empty into drains.
S33	Take precautionary measures against static discharges.
S37	Wear suitable gloves.
S39	Wear eye/face protection.
S40	To clean the floor and all objects contaminated by this material, use water and detergent.
S41	In case of fire and/or explosion, DO NOT BREATHE FUMES.
S43	In case of fire use
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well ventilated areas.
S56	Dispose of this material and its container at hazardous or special waste collection point.
S64	If swallowed, rinse mouth with water (only if the person is conscious).

Other hazards

Inhalation, skin contact and/or ingestion may produce health damage*.
Possible respiratory and skin sensitizer*.
HARMFUL-May cause lung damage if swallowed.
Cumulative effects may result following exposure*.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
67-64-1	>60	acetone
Not Available	30	methacrylate, typically
80-62-6	NotSpec.	methyl methacrylate

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact

If this product comes in contact with the eyes:

▶ Wash out immediately with fresh running water.

	 Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to acetone:

- Symptoms of acetone exposure approximate ethanol intoxication.
- About 20% is expired by the lungs and the rest is metabolised. Alveolar air half-life is about 4 hours following two hour inhalation at levels near the Exposure Standard; in overdose, saturable metabolism and limited clearance, prolong the elimination half-life to 25-30 hours.
- There are no known antidotes and treatment should involve the usual methods of decontamination followed by supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

Management:

Measurement of serum and urine acetone concentrations may be useful to monitor the severity of ingestion or inhalation.

Inhalation Management:

- Maintain a clear airway, give humidified oxygen and ventilate if necessary.
- If respiratory irritation occurs, assess respiratory function and, if necessary, perform chest X-rays to check for chemical pneumonitis.
- Consider the use of steroids to reduce the inflammatory response.
- ▶ Treat pulmonary oedema with PEEP or CPAP ventilation.

Dermal Management:

- Remove any remaining contaminated clothing, place in double sealed, clear bags, label and store in secure area away from patients and staff.
- Irrigate with copious amounts of water.
- An emollient may be required.

Eye Management:

- Irrigate thoroughly with running water or saline for 15 minutes.
- Stain with fluorescein and refer to an ophthalmologist if there is any uptake of the stain.

Oral Management:

- ▶ No GASTRIC LAVAGE OR EMETIC
- Encourage oral fluids.

Systemic Management:

- Monitor blood glucose and arterial pH.
- Ventilate if respiratory depression occurs.
- If patient unconscious, monitor renal function.
- Symptomatic and supportive care.

The Chemical Incident Management Handbook:

Guy's and St. Thomas' Hospital Trust, 2000

BIOLOGICAL EXPOSURE INDEX

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

 Determinant
 Sampling Time
 Index
 Comments

 Acetone in urine
 End of shift
 50 mg/L
 NS

NS: Non-specific determinant; also observed after exposure to other material

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Alcohol stable foam
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water course.

Fire/Explosion Hazard

- ▶ Hot organic vapours or mist are capable of sudden spontaneous combustion when mixed with air even at temperatures below their published autoignition temperatures.
- ▶ The temperature of ignition decreases with increasing vapour volume and vapour/air contact times and is influenced by pressure change.
- ▶ Ignition may occur under elevated-temperature process conditions especially in processes performed under vacuum subjected to sudden ingress of air or in processes performed at elevated pressure, where sudden escape of vapours or mists to the atmosphere occurs.
- Liquid and vapour are highly flammable.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills

- ▶ Remove all ignition sources.
- ▶ Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- ▶ Control personal contact with the substance, by using protective equipment.

Major Spills

- ▶ Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- ▶ May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- ▶ Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

Other information

- Store in original containers in approved flame-proof area.
- ▶ No smoking, naked lights, heat or ignition sources.
- ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- · Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- ▶ For low viscosity materials (i): Drums and jerry cans must be of the non-removable head type.

Storage incompatibility

Avoid reaction with oxidising agents

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure	acetone	Acetone	1185 mg/m3 / 500	2375 mg/m3 / 1000	Not	Not
Standards			ppm	ppm	Available	Available

Continued...

Australia Exposure	methyl	Methyl	208 mg/m3 / 50	416 mg/m3 / 100	Not	Not
Standards	methacrylate	methacrylate	ppm	ppm	Available	Available

EMERGENCY LIMITS

Ingredient	TEEL-0	TEEL-1	TEEL-2	TEEL-3
Dentsply Prime & Bond NT	Not Available	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
acetone	20,000 ppm	2,500 [LEL] ppm
methacrylate, typically	Not Available	Not Available
methyl methacrylate	4,000 ppm	1,000 ppm

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Personal protection











Eye and face protection

- Chemical goggles.
- Full face shield may be required for supplementary but never for primary protection of eyes.
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

Hands/feet protection

NOTE:

- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- ► Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

Body protection

See Other protection below

Other protection

- Overalls.
- ▶ PVC Apron.
- ▶ PVC protective suit may be required if exposure severe.
- Eyewash unit.

Thermal hazards

Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection:

Dentsply Prime & Bond NT

Material	СРІ
BUTYL	А
BUTYL/NEOPRENE	A
PE/EVAL/PE	А
PVDC/PE/PVDC	A
SARANEX-23 2-PLY	В
TEFLON	В
CPE	С
HYPALON	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	Air-line*	AX-2	AX-PAPR-2 ^
up to 10 x ES	-	AX-3	-
10+ x ES	-	Air-line**	-

* - Continuous Flow; ** - Continuous-flow or positive pressure demand ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low

Continued...

Chemwatch: 4993-91 Page 6 of 10 Issue Date: 01/01/2013 Version No: 4.1.1.1 Print Date: 14/10/2014

Dentsply Prime & Bond NT

NEOPRENE	С
NITRILE	С
NITRILE+PVC	С
PVA	С
PVC	С
SARANEX-23	С
VITON/NEOPRENE	С

boiling point organic compounds(below 65 degC)

* CPI - Chemwatch Performance Index

A: Best Selection

- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Yellow, highly flammable liquid with a characteristic odour; does not mix with water.				
Physical state	Liquid	Relative density (Water = 1)	Not Available		
Odour	Not Available	Partition coefficient n-octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	465		
pH (as supplied)	Not Available	Decomposition temperature	Not Available		
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available		
Initial boiling point and boiling range (°C)	55	Molecular weight (g/mol)	Not Applicable		
Flash point (°C)	<0	Taste	Not Available		
Evaporation rate	Not Available	Explosive properties	Not Available		
Flammability	Flammable.	Oxidising properties	Not Available		
Upper Explosive Limit (%)	13.0	Surface Tension (dyn/cm or mN/m)	Not Available		
Lower Explosive Limit (%)	2.6	Volatile Component (%vol)	64.6		
Vapour pressure (kPa)	233 hPa	Gas group	Not Available		
Solubility in water (g/L)	Immiscible	pH as a solution(1%)	Not Available		
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available		

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7

Chemwatch: **4993-91**Version No: **4.1.1.1**

Dentsply Prime & Bond NT

Issue Date: **01/01/2013**Print Date: **14/10/2014**

Hazardous decomposition products

See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information	on	toxico	logical	effects

Information on toxico	logical effects
Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis.
Еуе	Evidence exists, or practical experience predicts, that the material may cause severe eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Eye contact may cause significant inflammation with pain. Corneal injury may occur; permanent impairment of vision may result unless treatment is prompt and adequate. Repeated or prolonged exposure to irritants may cause inflammation characterised by a temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.
Chronic	Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant.

Dentsply Prime &	TOXICITY	IRRITATION
Bond NT	Not Available	Not Available
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 20000 mg/kg	Eye (human): 500 ppm - irritant
acetone	Inhalation (rat) LC50: 50100 mg/m3/8 hr	Eye (rabbit): 20mg/24hr -moderate
	Oral (rat) LD50: 5800 mg/kg	Eye (rabbit): 3.95 mg - SEVERE
		Skin (rabbit): 500 mg/24hr - mild
		Skin (rabbit):395mg (open) - mild
	Not Available	Not Available
methyl methacrylate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >5000 mg/kg	Eye (rabbit): 150 mg
	Dermal (rabbit) LD50: 35500 mg/kg *	Skin (rabbit): 10000 mg/kg (open)
	Inhalation (rat) LC50: 3750 ppm *	
	Oral (rat) LD50: 7872 mg/kg	
	Not Available	Not Available

Not available. Refer to individual constituents.

Chemwatch: 4993-91 Page 8 of 10 Issue Date: 01/01/2013 Version No: 4.1.1.1 Print Date: 14/10/2014

Dentsply Prime & Bond NT

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the **ACETONE** epidermis. for acetone: The acute toxicity of acetone is low.

METHYL METHACRYLATE The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. Inhalation (human) TCLo: 60 mg/m3(15 ppm) [* Manuf. Rohm Haas]

Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	✓	Reproductivity	0
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

✓ – Data required to make classification available Legend:

🗶 – Data available but does not fill the criteria for classification

Not Available to make classification

CMR STATUS

Not Applicable

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
acetone	LOW (Half-life = 14 days)	MEDIUM (Half-life = 116.25 days)
methyl methacrylate	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
acetone	LOW (BCF = 3.162)
methyl methacrylate	LOW (BCF = 2.305)

Mobility in soil

Ingredient	Mobility
acetone	HIGH (KOC = 1.981)
methyl methacrylate	LOW (KOC = 10.14)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Page 9 of 10 Issue Date: 01/01/2013 Version No: 4.1.1.1 Print Date: 14/10/2014 **Dentsply Prime & Bond NT**

Marine Pollutant HAZCHEM •2YE

Land transport (ADG)

UN number	1090	
Packing group	Ш	
UN proper shipping name	ACETONE	
Environmental hazard	No relevant data	
Transport hazard class(es)	Class 3 Subrisk Not Applicable	
Special precautions for user	Special provisions Not Applicable Limited quantity 1 L	

Air transport (ICAO-IATA / DGR)

• •	,			
UN number	1090			
Packing group	II .			
UN proper shipping name	Acetone			
Environmental hazard	No relevant data	No relevant data		
	ICAO/IATA Class	ss 3		
Transport hazard class(es)	ICAO / IATA Subrisk	Not Applicable		
0.000(00)	ERG Code	зн		
	Special provisions		Not Applicable	
	Cargo Only Packing Instructions		364	
	Cargo Only Maximum Qty / Pack		60 L	
Special precautions for user	Passenger and Cargo Packing Instructions		353	
101 4001	Passenger and Cargo Maximum Qty / Pack		5 L	
	Passenger and Cargo Limited Quantity Packing Instructions		Y341	
	Passenger and Cargo Limited Maximum Qty / Pack		1L	

Sea transport (IMDG-Code / GGVSee)

UN number	1090	
Packing group	II .	
UN proper shipping name	ACETONE	
Environmental hazard	No relevant data	
Transport hazard class(es)	IMDG Class 3 IMDG Subrisk Not Applicable	
Special precautions for user	EMS Number F-E , S-D Special provisions Not Applicable Limited Quantities 1 L	

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid	methyl methacrylate	Υ

 Chemwatch: 4993-91
 Page 10 of 10
 Issue Date: 01/01/2013

 Version No: 4.1.1.1
 Print Date: 14/10/2014
 Print Date: 14/10/2014

Dentsply Prime & Bond NT

Substances Carried in
Bulk

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

acetone(67-6/ found c following regul	on the	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"
nethacrylate(80 is found c following regul	on the	"Australia Exposure Standards", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Inventory of Chemical Substances (AICS)", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "Australia Hazardous Substances Information System - Consolidated Lists"

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Printing date 14.02.2017 Version number 7 Revision: 14.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Prime & Bond NT
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture Adhesive
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

DENTSPLY DeTrey GmbH

De-Trey-Str. 1 D-78467 Konstanz

GERMANY

Tel.: +49-(0)7531-583-0 *Fax*: +49-(0)7531-583-104

email: KonstanzDEU.info-sdb@dentsplysirona.com

- · Further information obtainable from:
- Departement Research & Development for technical information
- Departement Marketing & Sales for distribution of the safety data sheets
- 1.4 Emergency telephone number: +49-(0)7531-583-0 8:00 17:00 (GMT + 1:00)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

acetone

Di(ethylene glycol) dimethacrylate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

(Contd. on page 2)

Printing date 14.02.2017 Version number 7 Revision: 14.02.2017

Trade name: Prime & Bond NT

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

As this product is a medical device in the meaning of Directive 93/42/EEC and intended for use by the end consumer and is applied in an invasive manner or body contact, it is exempt from the labelling requirements according to regulation 1272/2008.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1	acetone	50-100%
EINECS: 200-662-2	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 105883-40-7	Urethane Dimethacrylate Resin	10-25%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 87699-25-0	Dipentaerythritol pentaacrylate phosphate	2.5-<10%
	Aquatic Chronic 2, H411; 🗘 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 2358-84-1	Di(ethylene glycol) dimethacrylate	2.5-<10%
	♦ Skin Sens. 1, H317	
CAS: 3290-92-4	propylidynetrimethyl trimethacrylate	0.25-<2.5%
	🕸 Aquatic Chronic 2, H411	1
CAS: 128-37-0	2,6-di-tert-butyl-p-cresol	0.25-<2.5%
EINECS: 204-881-4	🕸 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Immediately remove any clothing soiled by the product.
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Immediately wash with water and soap and rinse thoroughly.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Information for doctor No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

-GB

(Contd. on page 3)

Printing date 14.02.2017 Version number 7 Revision: 14.02.2017

Trade name: Prime & Bond NT

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with full jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Observe normal care for working with chemicals.

Prevent formation of aerosols.

Ensure good ventilation/exhaustion at the workplace.

- · Handling Product is intended for dental use only.
- · Information about fire and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 14.02.2017 Version number 7 Revision: 14.02.2017

Trade name: Prime & Bond NT

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

· Regulatory information WEL: EH40/2011

· DNELs

CAS: 128-37-0 2,6-di-tert-butyl-p-cresol

Inhalative DNEL Werte 3.5 mg/m³ bw/day (rat)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Natural rubber, NR

Recommended thickness of the material: ≥ 0.75 mm

Permeation: Level ≥ 2

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles.

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

(Contd. on page 5)

Printing date 14.02.2017 Version number 7 Revision: 14.02.2017

Trade name: Prime & Bond NT

	(Contd. of page
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	undetermined :: 60°C
Flash point:	-19 °C (c.c. Abel)
Flammability (solid, gaseous)	Not applicable.
Ignition temperature:	465 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	2.6 Vol %
Upper:	12.8 Vol %
Vapour pressure at 20 °C:	233 hPa
Density at 20 °C:	0.9 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Partly miscible
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Solvent content:	
Organic solvents:	67.0 %
Solids content:	3.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- $\cdot \textbf{\textit{Acute toxicity}} \ \textit{Based on available data, the classification criteria are not met.}$

(Contd. on page 6)

-GB

Printing date 14.02.2017 Version number 7 Revision: 14.02.2017

Trade name: Prime & Bond NT

	(Contd. of page 5)	
alues rele	vant for classification:	
4-1 aceton	e	
LD50	5800 mg/kg (rat)	
LD50	20000 mg/kg (rabbit)	
LC50/4 h	76 mg/l (rat)	
CAS: 3290-92-4 propylidynetrimethyl trimethacrylate		
LD50	>2000 mg/kg (rat)	
CAS: 128-37-0 2,6-di-tert-butyl-p-cresol		
LD50	2930 mg/kg (rat)	
LD50	> 2000 mg/kg (rabbit)	
	4-1 aceton LD50 LD50 LC50/4 h 1-92-4 prop LD50 37-0 2,6-d LD50	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

Repeated or prolonged contact with the not polymerized product may cause sensitization for acrylates / methacrylates.

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:			
CAS: 67-6	CAS: 67-64-1 acetone		
LC50/96h	5540 mg/l (Fish acute toxicity study)		
EC50/48h	6100 mg/L (daphnia magna)		
CAS: 3290	92-4 propylidynetrimethyl trimethacrylate		
LC50/96h	2 mg/l (Fish acute toxicity study)		
EC50/48h	>9.22 mg/L (daphnia magna)		
CAS: 128-	CAS: 128-37-0 2,6-di-tert-butyl-p-cresol		
LC50/48h	>0.57 mg/l (daphnia magna)		
LC50/96h	>0.42 mg/l (Fish acute toxicity study)		
EC50/72h	>0.42 mg/l (Algea, gowth inhibition test)		

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

(Contd. on page 7)

Printing date 14.02.2017 Version number 7 Revision: 14.02.2017

Trade name: Prime & Bond NT

(Contd. of page 6)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.
- \cdot 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
18 01 06*	chemicals consisting of or containing hazardous substances	
HP 3	Flammable	
HP 4	Irritant - skin irritation and eye damage	
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP 13	Sensitising	
HP 14	Ecotoxic	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1090
· 14.2 UN proper shipping name	1000 / 07770 / 1
· ADR · IMDG, IATA	1090 ACETONE mixture ACETONE, MIXTURE
· 14.3 Transport hazard class(es)	
· ADR	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3

-GB

(Contd. on page 8)

Printing date 14.02.2017 Version number 7 Revision: 14.02.2017

Trade name: Prime & Bond NT

	(Contd. of pa
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F- E , S - D
Stowage Category	E
14.7 Transport in bulk according to Ani	nex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
- IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1090 ACETONE MIXTURE, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The attached safety data sheet covers the dangers and measures to be taken when large quantities of material are released, for example due to accidents during transport or storage by the dealer.

For quantities of material typically used in clinical practice, information necessary for safe use and storage of the product is given in the DFU.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 9)

Printing date 14.02.2017 Version number 7 Revision: 14.02.2017

Trade name: Prime & Bond NT

H411 Toxic to aquatic life with long lasting effects.

(Contd. of page 8)

- · Department issuing SDS: Research & Development
- · Contact: HotLine for urgent technical support: +49-7531-583-350
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.

GB