This SDS packet was issued with item:

077640089

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

077340425 077640147 077640154 077640162 077640188

according to Regulation (EC) No. 453/2010

Dental Use



Date Issued: 09/06/2012

SDS No: 7-001.13 **Date Revised:** 03/18/2015

Revision No: 14

Ultra-Etch®

SECTION 1: Identification of the substance/preparation and of the company/undertaking

1.1. Product identifier

Product code : UX/10947
Product name : Ultra-Etch®

Product description: Phosphoric Acid dental etchant

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Professional Dental Acid Etching Solution

1.3. Details of the supplier of the safety data sheet

Manufacturer

Ultradent Products, Inc. 505 W. 10200 S.

South Jordan, UT 84095

Distributor

Ultradent Products GmbH Am Westhover Berg 30 51149 Cologne Germany Email: infoDE@ultradent.com

Emergency Phone: +49(0)2203-35-92-0

1.4. Emergency telephone number

CHEMTREC (NORTH AMERICA) :(800) 424 - 9300

(INTERNATIONAL) :+1(703) 527 - 3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 1999/45/EC

: The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Danger symbols : C
R phrases : R34

Classification according to Regulation (EC) No 1272/2008 [CLP]

Health : Skin Corrosion, Category 1B

2.2. Label elements

This mixture contains Phosphoric Acid. This material is considered hazardous as defined by the OSHA Hazard Communication Standard (29 CFR 1819.1200)

Classification according to Directive 1999/45/EC

Hazard pictogram(s) : C



Corrosiv

R&S statement(s) : R34: Causes burns.

according to Regulation (EC) No. 453/2010
Dental Use



Date Issued : 09/06/2012

SDS No: 7-001.13 **Date Revised:** 03/18/2015

Revision No: 14

Ultra-Etch®

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard pictogram(s)

Corrosive

Signal Word : WARNING

Hazard statement(s) : H314: Causes severe skin burns and eye damage.

Precautionary statement(s)

Prevention: P280: Wear protective gloves/protective clothing/eye protection/face

protection.

Response : P305+P351+P338: IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P302+P352: IF ON SKIN: Wash with plenty of soap and water. P332+P313: If skin irritation occurs: Get medical advice/attention.

P301: IF SWALLOWED:

P310: Immediately call a POISON CENTER or doctor/physician.

P331: Do NOT induce vomiting.

Storage : P273: Avoid release to the environment.

Disposal: P501: Dispose of in compliance with governmental regulation. (EC

1975L0442-20/11/2003)

2.3. Other hazards

Immediate concerns : Corrosive. Will cause eye burns and permanent tissue damage.

SECTION 3: Composition / information on ingredients

3.1. Substances

Not Applicable

3.2. Mixtures

Chemical Name	CAS	EINECS No.	Wt.%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No 1272/2008 [CLP]
Phosphoric Acid	7664-38-2	231-633-2	< 45	C; R34	Skin Corr.,Cat. 1B; H314

For full text of H-statements and R-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

according to Regulation (EC) No. 453/2010
Dental Use



Date Issued : 09/06/2012 **SDS No :** 7-001.13

Date Revised: 03/18/2015

Revision No: 14

Ultra-Etch®

Following eyes: Immediately flush with plenty of water. After initial flushing, remove

any contact lenses and continue flushing for at least 15 minutes. Have

eyes examined and tested by medical personnel.

Following skin: Wash with soap and water. Get medical attention if irritation develops

or persists.

Following ingestion: If swallowed, rinse mouth with water, Do NOT Induce Vomiting. Give

victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious

person.

Following inhalation: No specific treatment is necessary since this material is not likely to be

hazardous by inhalation. If exposed to excessive levels of dusts or fumes, remove to fresh air and get medical attention if cough or other

symptoms develop.

4.2. Most important symptoms and effects, both acute and delayed

Eyes : Causes severe eye burns.

Skin : Corrosive, causes skin burning.

Ingestion: Harmful if swallowed.

Inhalation: None expected for this product.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician : Corrosive

SECTION 5: Fire fighting measures

5.1. Extinguishing media

Extinguishing media : Please see Fire Fighting Equipment under Section 5.3.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products: Not Determined
Explosion hazards: Not Determined
Fire explosion: Not Determined
Sensitive to static discharge: Not Determined
Sensitivity to impact: Not Determined

5.3. Advice for firefighters

Fire fighting procedures : General: Evacuate all personnel; use protective equipment for fire-

fighting. Use self-contained breathing apparatus when the product is

involved in fire.

Fire fighting equipment: Non-combustible.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General procedures: Refer to Section 8 for Personal Protective Equipment.

6.2. Environmental precautions

according to Regulation (EC) No. 453/2010

Dental Use



Date Issued : 09/06/2012 **SDS No :** 7-001.13

Date Revised: 03/18/2015

Revision No: 14

Ultra-Etch®

Water spill: Do not allow to enter sewers or drains that may lead to waterways.

6.3. Methods and material for containment and cleaning up

Small spill : Clean up spills immediately, observing precautions in Protective

Equipment section.

Large spill : Absorb with inert, damp non-combustible material, then flush area

with water.

6.4. Reference to other sections

Reference to other sections: Not Applicable

SECTION 7: Handling and storage

7.1. Precautions for safe handling

General procedures: Avoid contact with eyes, skin and clothing.

Handling : Use suitable protective equipment.

Storage: See product labeling.

7.2. Conditions for safe storage, including any incompatibilities

Shelf life : See product labeling

7.3. Specific end use(s)

Specific end use(s): Professional Dental Acid Etching Solution

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

Control parameters : Not Determined

8.2. Exposure controls

Eye/face protection: Wear eye protection

Skin protection: Wear suitable protective clothing and gloves.

Respiratory protection : Good general ventilation should be sufficient to control airborne levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gel
Colour : Blue

Odour : Odorless or no characteristic odor

pH : < 1

Solubility in water: Partially soluble in water.

9.2. Other information

Percent volatile : Not Determined

SECTION 10: Stability and reactivity

according to Regulation (EC) No. 453/2010
Dental Use



Date Issued : 09/06/2012 **SDS No :** 7-001.13

Date Revised: 03/18/2015

Revision No: 14

Ultra-Etch®

10.1. Reactivity

Reactivity: Stable

10.2. Chemical stability

Chemical stability : Stable when stored and handled under recommended conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization: None

10.4. Conditions to avoid

Conditions to avoid : Avoid strong bases, Metals. Excess heat, exposure to moist air or

water.

10.5. Incompatible materials

Incompatible materials: Strong caustics, most metals.

10.6. Hazardous decomposition products

Hazardous decomposition

products

: Phosphine, oxides of phosphorous, hydrogen gas

Additional information: Reacts with bases to form phosphate salts and is corrosive (especially

when hot) to many metals and alloys. Liberates explosive hydrogen gas when reacting with chlorides and stainless steel, and reacts violently with sodium tetrahydroborate. Forms flammable gases with sulfides, mercaptans, cyanides, and aldehydes. Also forms toxic fumes with cyanides, sulfides, fluorides, organic peroxides, and halogenated

organics.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute

Notes: Device is a strong acid and is extremely toxic. It is to be used only as

directed with PPE, and only by licensed dental professionals.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity : Not Determined

Aquatic toxicity (acute)

96-hour LC₅₀ : Not Determined
48-hour EC₅₀ : Not Determined
96-hour EC₅₀ : Not Determined

12.2. Persistence and degradability

Persistence and degradability: Not Determined

12.3. Bioaccumulative potential

Bioaccumulative potential : Not Determined

according to Regulation (EC) No. 453/2010
Dental Use



Date Issued : 09/06/2012 **SDS No :** 7-001.13

Date Revised: 03/18/2015

Revision No: 14

Ultra-Etch®

12.4. Mobility in soil

Mobility in soil : Not Determined

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

: Not Determined

12.6. Other adverse effects

Environmental data : Not defined

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal method: Dispose of in compliance with governmental regulation. (EC

1975L0442-20/11/2003)

SECTION 14: Transport information

14.1. UN number

UN number : 1760

14.2. UN proper shipping name

UN proper shipping name : Corrosive liquid, n.o.s. (Phosphoric acid mixture)

14.3. Transport hazard class(es)

Primary hazard class/division : 8
Hazard classification : 8

14.4. Packing group

Packing group : III

14.5. Environmental hazards

Marine pollutant #1 : N/A

14.6. Special precautions for user

ADR - road : N/A
RID - rail : N/A
IMDG - sea : N/A
IATA - air : N/A

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk: N/A

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

RoHS: Please refer to Medical Devices Directive 93/42/EEC

15.2. Chemical safety assessment

Chemical safety assessment: See Section 11

according to Regulation (EC) No. 453/2010
Dental Use



Date Issued : 09/06/2012 **SDS No :** 7-001.13

Date Revised : 03/18/2015

Revision No: 14

Ultra-Etch®

SECTION 16: Other information

Relevant R-phrases and/or Hstatements (number and full

text)

Prepared by

Revision summary

General statements

Manufacturer disclaimer

: R34: Causes burns.

Skin Corr., Cat. 1B: Skin Corrosion, Category 1B H314: Causes severe skin burns and eye damage.

: Anu Kattoju

: This SDS replaces the 02/25/2015 SDS. Revised: **Section 1**: . **Section 2**: . **Section 8**: PERSONAL PROTECTIVE EQUIPMENT - SKIN. **Section 10**: HAZARDOUS POLYMERIZATION.

: N/A= Not Applicable

: FOR DENTAL USE ONLY: Use as directed. The information and recommendations are taken from sources (raw material SDS(s) and manufacturer's knowledge) believed to be accurate; however,the manufacturer, makes no warranty with respect to the accuracy of the information or the suitability of the recommendation and assumes no liability to any user thereof. Each user should review these recommendations in the specific context of the intended use and

determine whether they are appropriate.



Printing date 26.10.2018 Revision: 03.10.2018

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Ultra-Etch® & Opal® Etch

· Article number: 10947

· Index number: SDS 7-001.17

· Relevant identified uses of the substance or mixture and uses advised against

Professional Dental Acid Etching Solution

· Application of the substance / the mixture Professional Dental Acid Etching Solution

Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Ultradent Products Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

onlineordersupport@utradent.com

EC Responsible Person Ultradent Products GmbH Am Westhover Berg 30 51149 Cologne Germany

Email: infoDe@ultradent.com

Emergency Phone: +49(0)2203-35-92-0

· Further information obtainable from: Customer Service

· Emergency telephone number:

CHEMTREC (NORTH AMERICA) : (800) 424-9300 (INTERNATIONAL) : +(703) 527-3887

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.



Acute Tox. 4 H332 Harmful if inhaled.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The Regulation EC 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP) shall not apply to a medical device in the finished state used in direct physical contact with the human body according to Art. 1.5 (d). Therefore, the product is exempted from the CLP labeling requirements, and no SDS is required by Regulation 1907/2006, Art. 2 (6c), REACH. Therefore, all given data, classification, and information on this SDS are provided solely on a voluntary basis.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.10.2018 Revision: 03.10.2018

Trade name: Ultra-Etch® & Opal® Etch

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

Phosphoric Acid Polyethylene Glycol

· Hazard statements

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 7664-38-2	Phosphoric Acid	< 40%
EINECS: 231-633-2	Acute Tox. 1, H330; Acute Corr.1, H290; Skin Corr. 1B, H314; Acute Tox. 4, H302	
CAS: 25322-68-3	Polyethylene Glycol	< 10%
NLP: 500-038-2	♦ Acute Tox. 2, H330	
	Dimethicone	< 1%
	♦ Repr. 2, H361f; STOT RE 2, H373	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

GB2

Printing date 26.10.2018 Revision: 03.10.2018

Trade name: Ultra-Etch® & Opal® Etch

(Contd. of page 2)

4 First aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: This product is a viscous gel, therefore chance of inhalation is not possible.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If swallowed in large quantities seek medical attention.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters:
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 4)

Printing date 26.10.2018 Revision: 03.10.2018

Trade name: Ultra-Etch® & Opal® Etch

(Contd. of page 3)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

See product labelling.

Keep container tightly sealed.

· Specific end use(s) Professional Dental Acid Etching Solution

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

7664-38-2 Phosphoric Acid

WEL (Great Britain) Short-term value: 2 mg/m³ Long-term value: 1 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work..

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

Printing date 26.10.2018 Revision: 03.10.2018

Trade name: Ultra-Etch® & Opal® Etch

(Contd. of page 4)

Physical and chemical properties	
Information on basic physical and chen General Information	nical properties
Appearance:	
Form:	Gel
Colour:	Blue
Odour:	Odourless
Odour threshold:	Not determined.
pH-value at 20°C:	<1
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	2: 100 °C
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	1.3 g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Water:	< 60 %
VOC (EC)	0.00 %
Solids content:	<20.0 %
Other information	Refractive Index 34-37 Brix

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.

(Contd. on page 6)

Printing date 26.10.2018 Revision: 03.10.2018

Trade name: Ultra-Etch® & Opal® Etch

(Contd. of page 5)

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

· LD/LC50	· LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)			
Oral	LD50	4,358 mg/kg (rat)	
Inhalative	LC50/4 h	<0.88 mg/l	
7664-38-2	Phosphoric Acid		
Oral	LD50	1,530 mg/kg (rat)	
Dermal	LD50	2,740 mg/kg (rabbit)	
Inhalative	LC50/4 h	0.42225 mg/l (rabbit)	
25322-68	3 Polyethylene Glycol		
Oral	LD50	19,600 mg/kg (Guinea pig)	
		17,300 mg/kg (mouse)	
		>10,000 mg/kg (rat)	
	LC50 Fish	>100 mg/l (Fish)	
Dermal	LD50	>20,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	1.65 mg/l (rat)	
	LC50(Daphnia magna)	>10,000 mg/l (Water Flea) (Toxicity to aquatic invertebrates)	

- Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes severe skin burns and eye damage.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 7)

Printing date 26.10.2018 Revision: 03.10.2018

Trade name: Ultra-Etch® & Opal® Etch

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Europ	ean waste catalogue
HP 6	Acute Toxicity
HP 8	Corrosive

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
ADR, IMDG, IATA	UN1805
UN proper shipping name	
ADR	1805 PHOSPHORIC ACID, SOLUTION mixture
IMDG, IATA	PHOSPHORIC ACID, SOLUTION mixture
Transport hazard class(es)	
ADR, IMDG, IATA	
Class	8 Corrosive substances.
Ciass Label	8
Packing group	O
ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances.
Danger code (Kemler):	80
EMS Number:	F- A , S - B
Segregation groups	Acids

Printing date 26.10.2018 Revision: 03.10.2018

Trade name: Ultra-Etch® & Opal® Etch

	(Contd. of page
· Stowage Category	A
· Transport in bulk according to Annex II of	Marpol
and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1805 PHOSPHORIC ACID, SOLUTION MIXTURE, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product: None

Contained substance: None.

Substances in Candidate List (Art. 59 REACH): None.

Substances subject to authorisarion (Annex XIV REACH): None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None

Substances subject to the Rotterdam Convention: None.

Substances subject to the Stockholm Convention: None.

Healthcare controls: Information not available.

- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Chemical safety assessment:

Device is a strong acid and is extremely toxic. It is to be used only as directed with PPE, and only by licensed dental professionals.

Printing date 26.10.2018 Revision: 03.10.2018

Trade name: Ultra-Etch® & Opal® Etch

(Contd. of page 8)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H330 Fatal if inhaled.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing SDS: Regulatory Affairs

· Contact: Customer Service

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Met. Corr.1: Corrosive to metals - Category 1

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 1: Acute toxicity - Category 1

Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

GB2