SAFETY DATA SHEETS

This SDS packet was issued with item:

072343382

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

070701268 072343416 072343424 072343432 072343440 072343465 273036997

ZEST DENTAL

SAFETY DATA SHEET

1. Identification

Product identifier Prelude™ Adhesive

Other means of identification

Document number SDS-022-ZD Rev. A

Recommended use Adhesive. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Danville Materials Company name

2875 Loker Avenue East **Address**

Carlsbad, CA 92010

1-800-827-7940 Telephone Contact **Customer Service**

E-mail danvillecs@zestdent.com

Website www.zestdent.com

Emergency telephone

number

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3 **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2

800-451-8346 / 760-602-8703

Sensitization, skin Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

OSHA defined hazards

Label elements

943643



Not classified.

Signal word Warning

Hazard statement Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an

allergic skin reaction. May cause respiratory irritation.

Precautionary statement

Version #: 01

Revision date: -

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be

allowed out of the workplace. Wear protective gloves/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Response

If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison

center/doctor if you feel unwell. In case of fire: Use water fog, alcohol resistant foam, dry chemical

1/8

powder, carbon dioxide to extinguish.

Issue date: 19-April-2018

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Prelude™ Adhesive SDS US Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Ethanol	64-17-5	15 - 35
2-Hydroxyethyl methacrylate	868-77-9	10 - 30
Bisphenol A glycidyl methacrylate	1565-94-2	10 - 30

Composition comments

The manufacturer has claimed one or more hazardous ingredients as trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on

All concentrations are in percent by weight.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Specific methods General fire hazards In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out.

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering them. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Prelude™ Adhesive SDS US 2/8

943643 Version #: 01 Revision date: -Issue date: 19-April-2018

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Persons susceptible to allergic reactions should not handle this product. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Follow rules for flammable liquids. Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Value

2.5 mg/m3

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for	or Air Contaminants (29	CFR 1910.1000)
Components	Type	

Componente	.) 60	T UI UI	
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3	_
		1000 ppm	
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	

Biological limit values

Proprietary component III

No biological exposure limits noted for the ingredient(s).

TWA

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield. Wear a full-face respirator, if needed

Heeut

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Be aware that the liquid may penetrate the gloves.

Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Wear NIOSH approved respirator

appropriate for airborne exposure at the point of use.

Prelude™ Adhesive SDS US

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Light yellow.
Odor Not available.
Odor threshold Not available.

pH 2.2 (Approximately)

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials. Avoid heat, sparks, open flames and other ignition sources.

Protect against direct sunlight.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

Version #: 01

products

943643

Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic

compounds whose composition have not been characterized. Silicon oxide fumes.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Issue date: 19-April-2018

Eye contact Causes serious eye irritation.

Revision date: -

Ingestion May cause discomfort if swallowed.

Prelude™ Adhesive SDS US

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species Test Results

2-Hydroxyethyl methacrylate (CAS 868-77-9)

<u>Acute</u>

Dermal

LD50 Rabbit > 3000 mg/kg

Oral

LD50 Rat > 4000 mg/kg

Ethanol (CAS 64-17-5)

Acute

Inhalation

Vapor

LC50 Mouse 39 g/m3, 4 Hours

Oral

LD50 Rat 7000 - 11000 mg/kg

Proprietary component I (CAS Proprietary)

Acute

Dermal

LD50 Rabbit 0.71 ml/kg

Inhalation

LC50 Rat 8.7 mg/l, 4 Hours

Oral

LD50 Rabbit 1100 mg/kg

Rat 847 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Reproductive toxicity Not classified. However: The product contains a small amount of substance that may damage the

unborn child.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

Prelude™ Adhesive SDS US

943643 Version #: 01 Revision date: - Issue date: 19-April-2018

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results	
Ethanol (CAS 64-17-5)			
Aquatic				
Acute				
Crustacea	LC50	Ceriodaphnia dubia	5012 mg/l, 48 hours	
		Daphnia magna	454 mg/l, 11 days	
Fish	LC50	Pimephales promelas	13480 mg/l, 96 hours	
Chronic				
Crustacea	NOEC	Ceriodaphnia dubia	9.6 mg/l, 10 days	

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Hydroxyethyl methacrylate (CAS 868-77-9) 0.47 Ethanol (CAS 64-17-5) -0.31 Proprietary component I 2.62 Proprietary component II 5.77

Mobility in soil No data available for this product.

The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic Other adverse effects

organisms.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Ethanol solutions

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1170

UN proper shipping name

Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) Ш Packing group

Environmental hazards

No Marine pollutant

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Issue date: 19-April-2018

24, B1, IB3, T2, TP1 Special provisions

4b, 150 Packaging exceptions Packaging non bulk 203 Packaging bulk 242

IATA

UN1170 **UN** number

UN proper shipping name Ethanol solutions

Revision date: -

Transport hazard class(es)

Version #: 01

Class 3

Prelude™ Adhesive SDS US 943643

Subsidiary risk Label(s) 3 Packing group Ш **Environmental hazards** No **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1170

UN proper shipping name **ETHANOL SOLUTIONS**

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant No F-E, S-D **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

Not established.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation categories

Serious eye damage or eye irritation Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethanol (CAS 64-17-5) Low priority

Issue date: 19-April-2018

US state regulations

US. Massachusetts RTK - Substance List

Ethanol (CAS 64-17-5)

SDS US Prelude™ Adhesive 943643 Version #: 01 Revision date: -

Proprietary component III (CAS Proprietary)

US. New Jersey Worker and Community Right-to-Know Act

Ethanol (CAS 64-17-5)

Proprietary component I (CAS Proprietary)
Proprietary component III (CAS Proprietary)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethanol (CAS 64-17-5)

US. Rhode Island RTK

Ethanol (CAS 64-17-5)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 19-April-2018

Revision date - 01

NFPA ratings



Disclaimer

Danville Materials cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Prelude™ Adhesive SDS US

943643 Version #: 01 Revision date: - Issue date: 19-April-2018

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).