

SAFETY DATA SHEETS

This SDS packet was issued with item:

072760791

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

070425462 070441162 072760775 072760858 072760882 072760890

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

070469593 070639989 072759116 072759124 072759132 072759140 072759900 072759934 072760189 072760759
072760767 072760783 072760866 072760874 072760924 072760932 072760940 072760957 072760965 072760999
072761005 072761013 078562617 273044119 273044121 273045762

DENTSPLY International

Safety Data Sheet

Safety Data Sheet (conforms to with Regulation (EC) 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 2015/830), US 29CFR1910.1200, Canada Hazardous Products Regulation

Date Issued: 28 May 2004
Document Number: 151
Date Revised: 28 June 2017
Revision Number: 6

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier:

Trade Name (as labeled): Lucitone® Liquid
Part/Item Number: 684309, 684315

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against:

Recommended Use: Fabrication of Dentures
Restrictions on Use: For Professional Use Only

1.3 Details of the Supplier of the Safety Data Sheet:

Manufacturer/Supplier Name: Dentsply Sirona Prosthetics
Manufacturer/Supplier Address: 570 West College Ave.
York, PA 17401
Manufacturer/Supplier Telephone Number: 717-845-7511 (Product Information)
Email address: Prosthetics_MSDS@Dentsplysirona.com

1.4 Emergency Telephone Number:

Emergency Contact Telephone Number: 800-424-9300 Chemtrec

2. HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture:

GHS Classification:		
Health	Environmental	Physical
Skin Irritant Category 2 (H315) Skin Sensitization Category 1 (H317) Specific Target Organ Toxicity- Single Exposure Category 3 (H335)	Not Hazardous	Flammable Liquid Category 2 (H225)

2.2 Label Elements:



Signal Word: Danger

Contains: Methyl Methacrylate, Ethylene Glycol Dimethacrylate

Hazard Phrases	Precautionary Phrases
H225 Highly flammable liquid and vapor. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.	P210 Keep away from heat, sparks, open flames, and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground or bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating, and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mist, vapors or spray. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves, protective clothing, and eye protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P333+P313 If skin irritation or rash occurs: Get medical attention. P363 Wash contaminated clothing before reuse. P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. P312 Call a POISON CENTER or doctor if you feel unwell. P370+P378 In case of fire: Use carbon dioxide, foam, water spray or water fog for extinction. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents and container in accordance with local and national regulations.

2.3 Other Hazards: None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixture:

Hazardous Components	C.A.S. #	EINECS # / REACH Registration #	Classification	WT %
Methyl Methacrylate	80-62-6	201-297-1 /	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	90-99
Ethylene Glycol Dimethacrylate	97-90-5	202-617-2 /	Skin Sens. 1, H317 STOT SE 3, H335	1-10

The exact concentration is being withheld as a trade secret.

Refer to Section 16 for the full text of the GHS Classifications.

4. FIRST AID MEASURES

4.1 Description of First Aid Measures:

Eye	Flush victim's eyes with large quantities of water, while holding the eyelids apart. Get medical attention if irritation develops or persists.
Skin	Wash skin thoroughly with soap and water. Get medical attention if irritation or rash develops. Remove and launder clothing before re-use.
Inhalation	Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention if breathing is difficult or irritation persists.
Ingestion	If small quantities are swallowed, rinse out mouth with water. Do not induce vomiting unless directed to do so by a medical professional. Get medical attention if symptoms develop or if you feel unwell.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed:

May cause eye, skin, and respiratory tract irritation. Prolonged or repeated contact may cause allergic skin reaction (skin rash). Inhalation of vapors may cause dizziness, headache, and other central nervous system effects.

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed:

Immediate medical attention should not be required.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing Media:

Use carbon dioxide, foam, water spray or water fog. Water may be ineffective unless used as a fine spray or fog.

5.2 Special Hazards Arising from the Substance or Mixture:

Highly flammable liquid and vapor. Vapors are heavier than air and may travel to ignition source and flash back. Heat of fire may cause an exothermic auto polymerization reaction. Emits toxic fumes under fire conditions. Closed containers may explode due to pressure build up when exposed to extreme heat. Decomposition may release carbon monoxide, carbon dioxide, methyl methacrylate, and irritating smoke and fumes.

5.3 Advice for Fire-Fighters:

Fire Fighting Procedures/Precautions for Fire Fighters:	Fight fire from a safe distance of protected location. Use water to cool fire-exposed containers. Firefighters should wear full emergency equipment and approved positive pressure self-contained breathing apparatus. Do not enter fire area without proper protection.
--	--

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures:

Evacuate spill area and keep unprotected personnel away. Remove all ignition sources such as open flames, spark producing equipment, pilot lights, etc. Use non-sparking tools and equipment. Avoid breathing vapors or mists. Ventilate area with explosion proof equipment. Avoid contact with skin, eyes or clothing. Wear appropriate protective clothing as described in Section 8.

6.2 Environmental Precautions:

Report releases as required by local and national authorities.

6.3 Methods and Material for Containment and Cleaning up:

Contain and collect using an inert absorbent material and place in appropriate containers for disposal. Clean spill site with water. Use non-sparking tools.

6.4 Reference to Other Sections:

Refer to Section 8 for Personal Protective Equipment and Section 13 for Disposal information.

7. HANDLING AND STORAGE

7.1 Precautions for Safe Handling:

Avoid contact with skin, eyes or clothing. Wear protective clothing and equipment as described in Section 8. Avoid breathing mists or vapors. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Use with non-sparking tools and explosion proof equipment. Electrically bond and ground containers for transfer. Do not expose to direct sunlight. Keep containers closed when not in use.

Do not reuse containers. Empty containers retain product residues and can be hazardous. Follow all SDS precautions when handling empty containers.

7.2 Conditions for Safe Storage, Including Any Incompatibilities: Store in a cool, dry, well-ventilated location away from oxidizers and other incompatible materials. Do not store in direct sunlight. Prevent moisture contact. Protect from physical damage. Keep container tightly closed when not in use.

7.3 Specific End Use (s): For professional use only.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters:**Occupational Exposure Limits:**

Methyl Methacrylate	50 ppm TWA, 100 ppm STEL ACGIH TLV (Sens)
	100 ppm TWA OSHA PEL
	50 ppm TWA, 100 ppm STEL DFG MAK
	50 ppm TWA, 100 ppm STEL Belgium
	50 ppm TWA, 100 ppm STEL UK WEL
	50 ppm TWA, 100 ppm STEL EU OEL

Ethylene Glycol Dimethacrylate	None Established
--------------------------------	------------------

Biological Exposure Limits: None Established

8.2 Exposure Controls:

Appropriate Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits. Use explosion proof electrical equipment and wiring where required.

Individual Protection Measures (PPE):

Specific Eye/face Protection: Chemical safety glasses are recommended where splashing is possible.

Specific Skin Protection: Wear nitrile rubber or other impervious gloves to prevent skin contact. Wear impervious clothing if needed to prevent any contact with this product, such as gloves, apron, boots, or whole body suit.

Specific Respiratory Protection: None required with adequate ventilation. If the occupational exposure limits are exceeded, an approved respirator with applicable cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with applicable regulations and good industrial hygiene practice.

Specific Thermal Hazards: None required

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical and Chemical Properties:

Appearance:	Clear liquid	Explosive limits:	LEL: 2.1% UEL: 12.5%
Odor:	Acrylic odor	Vapor pressure (mmHg):	29 mmHg @ 68°F (20°C)
Odor threshold:	0.21 ppm (methyl methacrylate)	Vapor density:	3.45
pH:	Not available	Relative density:	0.94
Melting/freezing point:	-54°F (-48°C)	Solubility(ies):	1.5%
Initial boiling point and boiling range:	Not available	Partition coefficient: n-octanol/water:	Not available
Flash point:	55°F (13°C) TOC	Auto-ignition temperature:	815°F (435°C)
Evaporation rate:	3.1 (Bac=1)	Decomposition temperature:	Not available
Flammability (solid, gas):	Not applicable	Viscosity:	Not available
Explosive Properties:	Vapors are explosive above the LEL	Oxidizing Properties:	None

9.2 Other Information: None available.

10. STABILITY AND REACTIVITY

10.1 Reactivity: May auto polymerize.

10.2 Chemical Stability: Product may become unstable if heated.

10.3 Possibility of Hazardous Reactions: Polymerization can occur. Reaction with oxidizers may cause fire.
10.4 Conditions to Avoid: Conditions leading to polymerization are excessive heat, oxygen-free atmosphere inhibitor depletion (due to excessive aging), direct sunlight, and contamination with polymerization catalysts.
10.5 Incompatible materials: Avoid contact with oxidizing agents, reducing agents, acids, and bases.
10.6 Hazardous Decomposition Products: Thermal decomposition may release carbon monoxide, carbon dioxide, methyl methacrylate, and irritating smoke and fumes.

11. TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects:

<p>Potential Health Effects:</p> <p><u>Eyes:</u> Liquid and vapor may cause moderate irritation (tears, blurred vision and redness).</p> <p><u>Skin:</u> May cause moderate skin irritation. May cause allergic skin reaction (skin sensitization).</p> <p><u>Ingestion:</u> Ingestion can cause gastrointestinal irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.</p> <p><u>Inhalation:</u> May cause respiratory tract irritation with coughing, mucous production and shortness of breath. High concentration is irritating to the respiratory tract and may cause dizziness, headache and anesthetic effects.</p>
<p>Chronic Health Effects: Prolonged or repeated overexposure may cause skin irritation or sensitization in some individuals, as well as kidney, lung, liver, and heart damage.</p>
<p>Irritation: Methyl Methacrylate: Moderately to slightly irritating to rabbit skin. Slightly to non-irritating to rabbit eyes. Ethylene Glycol Dimethacrylate: Not irritating to rabbit eyes</p>
<p>Corrosivity: No data available. This product is not expected to be corrosive.</p>
<p>Sensitization: Methyl Methacrylate: Sensitizing in a Mouse local lymphnode assay. Ethylene Glycol Dimethacrylate: Found to be an extremely weak sensitizer in the Mouse local lymphnode assay.</p>
<p>Carcinogenicity: Methyl methacrylate: The results of a 2-year inhalation studies conducted for NTP showed no evidence of carcinogenicity of methyl methacrylate for male rats exposed at 500 or 1,000 ppm and female rats exposed at 250, 500 or 1,000 ppm. In another study, no increase was seen in the number or type of tumors in either rats or hamsters from a chronic inhalation study. No carcinogenic activity was also reported in a chronic oral study. However, acute oral exposure studies and structure-activity relationship comparisons with other acrylates suggest that the introduction of a methyl group to the acrylate moiety (e.g., EC to MMA) negates carcinogenic activity. None of the components of this product are listed as carcinogens by OSHA, IARC, NTP, ACGIH or the EU CLP.</p>
<p>Mutagenicity: Methyl Methacrylate: Negative in AMES test, positive and negative in in-vitro studies. Negative in vivo studies.</p>
<p>Aspiration Hazard: Not an aspiration hazard</p>
<p>Acute Toxicity Data:</p> <p>Methyl Methacrylate: Oral rat LD50- 7800 mg/kg; Inhalation rat LC50- 29.8 mg/L/ 4hr (7093 ppm/4 hr); Skin rabbit LD50->5000 mg/kg</p> <p>Ethylene Glycol Dimethacrylate: Oral rat LD50: 3300 mg/kg; Oral mouse LD50: 2 g/kg</p>
<p>Reproductive Toxicity Data: Methyl Methacrylate: In a study in rats, there were no developmental effects, although there were decreases in maternal body weight following inhalation of concentrations up to 8,315 mg/m³. There was no reduction in fertility in a dominant lethal assay in mice exposed to this compound at concentrations up to 36,900 mg/m³ and no adverse effects on reproductive organs in repeated dose studies conducted to date.</p>
<p>Specific Target Organ Toxicity Single Exposure (STOT-SE): Methyl Methacrylate: In an inhalation study with dogs, a 2000 ppm dose showed a drop in arterial blood pressure and GI motor activities. The lethal oral dose for methyl methacrylate is 6 to 9 g/kg in lab animals. Poisoned animals exhibit respiratory depression, and coma; also irritation of skin, eyes and respiratory tract.</p>

Specific Target Organ Toxicity Repeated Exposure (STOT-RE): Methyl Methacrylate: Impairment of locomotor activity and learning and behavioral effects on the brain were observed in rats exposed orally to 500 mg/kg bw/day for 21 days.

12. ECOLOGICAL INFORMATION

12.1 Toxicity:

Methyl Methacrylate: 96h LC50 Fathead minnow- 130 mg/L; 48h EC50 Algae- 170 mg/L

Ethylene Glycol Dimethacrylate: 96 hr LC50 Zebrafish- 15.95 mg/L; 48 hr EC50 Daphnia magna- 44.9 mg/L

12.2 Persistence and Degradability: Methyl methacrylate is readily biodegradable - 88% after 28 days. Ethylene Glycol Dimethacrylate: 69% after 28 days- readily biodegradable (but failing 10 day window) in screening tests.

12.3 Bio-accumulative Potential: The potential for bioaccumulate is expected to be low for methyl methacrylate.

12.4 Mobility in Soil: Methyl methacrylate is expected to have very high to high mobility in soil.

12.5 Results of PBT and vPvB Assessment: Not applicable

12.6 Other Adverse Effects: None

13. DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods:

Waste Treatment Recommendations: Dispose in accordance with national and local regulations.

14. TRANSPORT INFORMATION

	14.1 UN Number	14.2 UN Proper Shipping Name	14.3 Hazard Class(s)	14.4 Packing Group	14.5 Environmental Hazards
DOT	UN1247	Methyl Methacrylate Monomer, Inhibited	3	II	Not applicable
ADR/RID	UN1247	Methyl Methacrylate Monomer, Inhibited	3	II	Not applicable
IMDG	UN1247	Methyl Methacrylate Monomer, Inhibited	3	II	Not applicable
IATA/ICAO	UN1247	Methyl Methacrylate Monomer, Inhibited	3	II	Not applicable

14.6 Special Precautions for User: Not applicable.

14.7 Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.

15. REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture:

U.S. Federal Regulations

Comprehensive Environmental Response and Liability Act of 1980 (CERCLA): Releases above the RQ of 1,010 lbs. (based on the RQ for methyl methacrylate of 1,000 lbs present at 90-99%) must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Toxic Substances Control Act (TSCA): This product is a medical device and not subject to chemical notification.

Clean Water Act (CWA): This material is not regulated under the Clean Water Act.

Clean Air Act (CAA): Methyl methacrylate is regulated under the Clean Air Act.

Superfund Amendments and Reauthorization Act (SARA) Title III Information:

SARA Section 311/312 (40 CFR 370) Hazard Categories: Classified under OSHA Hazcom 2012 GHS as per Section 2 of this SDS.

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372):

Components	C.A.S. #	WT %
Methyl Methacrylate	80-62-6	90-99%

State Regulations

California: This product contains the following substances known to the state of California to cause cancer and/or reproductive toxicity: None known.

International Regulations

Canadian Environmental Protection Act: This product is a medical device and not subject to chemical notification requirements.

European Inventory of Existing Chemicals (EINECS): This product is a medical device and not subject to chemical notification requirements.

EU REACH: This product is a medical device and not subject to chemical notification requirements.

Australian Inventory of Chemical Substances: This product is a medical device and not subject to chemical notification requirements.

China Inventory of Existing Chemicals and Chemical Substances: This product is a medical device and not subject to chemical notification requirements.

Japanese Existing and New Chemical Substances: This product is a medical device and not subject to chemical notification requirements.

Korean Existing Chemicals List: This product is a medical device and not subject to chemical notification requirements.

Philippine Inventory of Chemicals and Chemical Substances: This product is a medical device and not subject to chemical notification requirements.

15.2 Chemical Safety Assessment: None required.

16. OTHER INFORMATION

HMIS Hazard Rating:

Health – 2 Flammability – 3 Physical Hazard – 2

Full text of Classification abbreviations used in Section 2 and 3:

Flam. Liq. 2 Flammable Liquid Category 2

Skin Irrit. 2 Skin Irritant Category 2

Skin Sens. 1 Skin Sensitization Category 1

STOT SE 3 Specific Target Organ Toxicity Single Exposure Category 3

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Supersedes: 5 May 2014

Date Updated: 28 June 2017

Revision Summary: 3 Year update. Changes to all sections.

Data Sources: US NLM ChemID Plus and HSDB, Substance SDS for components, ECHA REACH Registration Website, Country websites for occupational exposure limits.

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199 Denture Base Powder****Lucitone 199 Repair Powder****Lucitone Fas-Por +, Powder****Lucitone Clear Dental Resin Powder****Lucitone Clear Pour Acrylic Powder****Lucitone Intensive Colors**

Version: 1.13 / GB
Revision date: 25.10.2018
Issue date: 14.02.2003
replaces version: 1.12
Page: 1 / 9

Material no. 0D905930
Specification 142125
VA-Nr 01804105

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name
Lucitone 199 Denture Base Powder
Lucitone 199 Repair Powder
Lucitone Fas-Por +, Powder
Lucitone Clear Dental Resin Powder
Lucitone Clear Pour Acrylic Powder
Lucitone Intensive Colors

REACH Registration No.: if available listed in Chapter. 3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant applications identified For dental use only.

1.3. Details of the supplier of the safety data sheet

Company DeguDent GmbH
Postfach 1364
D-63403 Hanau

Telephone +49 (0)6181/59-5767
Telefax +49 (0)6181/59-5879
Email address SDB.Degudent-DE@dentsplysirona.com

1.4. Emergency telephone number

Emergency information +49 (0)6181/59-50 (This telephone number is available during office hours only.)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not a hazardous mixture according to Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling as per (EU) 1272/2008

Statutory basis Labelling not required according to EU-CLP Ordinance (1272/2008).

2.3. Other hazards

Mechanical irritation of skin and mucous linings of eyes and respiratory tract may occur., Danger of dust explosion.

A PBT/vPvB evaluation is not available, since a chemical safety evaluation is not required / has not been carried out.

SECTION 3: Composition/information on ingredients

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199 Denture Base Powder****Lucitone 199 Repair Powder****Lucitone Fas-Por +, Powder****Lucitone Clear Dental Resin Powder****Lucitone Clear Pour Acrylic Powder****Lucitone Intensive Colors**

Version: 1.13 / GB
Revision date: 25.10.2018
Issue date: 14.02.2003
replaces version: 1.12
Page: 2 / 9

Material no. 0D905930
Specification 142125
VA-Nr 01804105

**3.1. Substances**

-

3.2. Mixtures

Information on ingredients / Hazardous components as per EU-CLP Regulation (EC) No. 1272/2008

• Poly(methyl methacrylate)	95% - 100%
CAS-No. 9011-14-7	

Texts of H phrases, see in Chapter 16

SECTION 4: First aid measures**4.1. Description of first aid measures**

Remove contaminated or saturated clothing.

Inhalation

In case product dust is released:

Move victims into fresh air.

In case of persistent discomfort

Obtain medical attention.

Skin contact

Wash off with soap and plenty of water.

Eye contact

Possible discomfort is due to foreign substance effect.

Rinse thoroughly with plenty of water keeping eyelid open.

In case of persistent discomfort

Consult an ophthalmologist.

Ingestion

Rinse mouth.

After absorbing large amounts of substance:

Consult a physician.

4.2. Most important symptoms and effects, both acute and delayed**Symptoms**

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

After absorbing large amounts of substance:

Acceleration of gastrointestinal passage

If skin sensitisation has developed and a causal relationship has been confirmed, further exposure should not be allowed

SECTION 5: Firefighting measures**5.1. Extinguishing media**

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199 Denture Base Powder****Lucitone 199 Repair Powder****Lucitone Fas-Por +, Powder****Lucitone Clear Dental Resin Powder****Lucitone Clear Pour Acrylic Powder****Lucitone Intensive Colors**

Version: **1.13 / GB**
Revision date: **25.10.2018**
Issue date: **14.02.2003**
replaces version: **1.12**
Page: **3 / 9**

Material no. **0D905930**
Specification **142125**
VA-Nr **01804105**



Suitable extinguishing media: mist
Foam
quenching powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media: High volume water jet

5.2. Special hazards arising from the substance or mixture

May be released in case of fire: carbon monoxide, carbon dioxide, organic products of decomposition.

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

No particular measures required.

6.2. Environmental precautions

Do not allow entrance in sewage water, soil stretches of water, groundwater, drainage systems.

6.3. Methods and material for containment and cleaning up

Pick up mechanically and collect in a suitable container. Avoid formation of dust.

Sweep up to prevent slipping hazard.

Clean up promptly by scoop or vacuum.

Additional advice

Danger of slipping due to leaking or spilt product.

Ensure explosion proofness. Dispose of contaminated material as a waste in a correct manner.

6.4. Reference to other sections

Disposal considerations; see section 13.

Wear personal protective equipment; see section 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid dust formation.

7.2. Conditions for safe storage, including any incompatibilities**Advice on protection against fire and explosion**

Danger of dust explosion.

Caution - electrostatic charge may occur.

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Storage

Keep in a dry place.

German storage class

13 - Non Combustible Solids

7.3. Specific end use(s)

We are unaware of any specific end uses which go beyond the data reported in Section 1.

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199 Denture Base Powder****Lucitone 199 Repair Powder****Lucitone Fas-Por +, Powder****Lucitone Clear Dental Resin Powder****Lucitone Clear Pour Acrylic Powder****Lucitone Intensive Colors**

Version: 1.13 / GB
Revision date: 25.10.2018
Issue date: 14.02.2003
replaces version: 1.12
Page: 4 / 9

Material no. 0D905930
Specification 142125
VA-Nr 01804105

**8.1. Control parameters****• exposure limit for dust**

CAS-No.		
Control parameters	10 mg/m3	(EH40 WEL)
type of exposure	Inhalable fraction.	
Control parameters	4 mg/m3	(EH40 WEL)
type of exposure	Respirable fraction.	

8.2. Exposure controls**Engineering measures**

In case product dust is released:, Local ventilation.

Personal protective equipment**Respiratory protection**

If workplace exposure limit is exceeded apply Dust mask with P2 particle filter.

Hand protection

Wear protective gloves made of the following materials:.

Glove material butyl-rubber

Material thickness 0.5 mm

Break through time 60 min

The suitability for a specific workplace should be discussed with the producers of the protective gloves.,

The exact break through time can be obtained from the protective glove producer and this has to be observed.

Preventive skin protection, Use barrier cream regularly.

Eye/face protection

Safety glasses with side-shields, If dust occurs: basket-shaped glasses

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice., Do not eat, drink, smoke, or sniff while at work. Wash your hands and/or face before breaks and before termination of work., If workplace exposure limits are exceeded and/or larger amounts are released (leakage, spilling, dust) the indicated respiratory protection should be used.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

Form powder
Colour depending on staining result

Odour characteristic

Odour threshold: no data available

pH not applicable
(solid)

Melting point/range > 210 °C

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199 Denture Base Powder****Lucitone 199 Repair Powder****Lucitone Fas-Por +, Powder****Lucitone Clear Dental Resin Powder****Lucitone Clear Pour Acrylic Powder****Lucitone Intensive Colors**

Version: 1.13 / GB
Revision date: 25.10.2018
Issue date: 14.02.2003
replaces version: 1.12
Page: 5 / 9

Material no. 0D905930
Specification 142125
VA-Nr 01804105



Flash point	not applicable (solid)
Evaporation rate	not applicable, (solid)
Flammability (solid, gas)	no data available
Lower explosion limit	no data available
Upper explosion limit	no data available
Vapour pressure	not applicable (solid)
Density	no data available
Water solubility	insoluble
Partition coefficient: n-octanol/water	not applicable
Autoinflammability	Not capable of spontaneous combustion or heating.
Thermal decomposition	250 °C
Viscosity, dynamic	not applicable (solid)
Explosiveness	Dusts might form explosive mixtures with air.
Oxidizing properties	no data available

9.2. Other information

Bulk density	325 - 375 kg/m ³	(20 °C)
Other information	No further physicochemical data were determined.	

SECTION 10: Stability and reactivity**10.1. Reactivity**

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No hazardous reactions are known if properly handled and stored.

10.4. Conditions to avoid

None known

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199 Denture Base Powder****Lucitone 199 Repair Powder****Lucitone Fas-Por +, Powder****Lucitone Clear Dental Resin Powder****Lucitone Clear Pour Acrylic Powder****Lucitone Intensive Colors**

Version: 1.13 / GB
Revision date: 25.10.2018
Issue date: 14.02.2003
replaces version: 1.12
Page: 6 / 9

Material no. 0D905930
Specification 142125
VA-Nr 01804105

**10.6. Hazardous decomposition products**

decomposition products if heated above 250°C

irritative gases/vapours, Carbon monoxide, Carbon dioxide (CO₂), organic products of decomposition**SECTION 11: Toxicological information****11.1. Information on toxicological effects***No results of animal experiments with the product available.*

Acute oral toxicity no data available

Acute inhalation toxicity no data available

Acute dermal toxicity no data available

Skin irritation no data available

Eye irritation no data available

Sensitization no data available

Assessment of STOT single exposure no data available

Assessment of STOT repeat exposure no data available

Risk of aspiration toxicity not applicable

Mutagenicity assessment no data available

Carcinogenicity No data available

Toxicity to reproduction No data available

Human experience Mechanical irritation of skin and mucous linings of eyes and respiratory tract may occur.

Toxicology Assessment

Acute effects An Expert Judgment stated that no classification is necessary based on present knowledge.

SECTION 12: Ecological information**12.1. Toxicity***Ecotoxicological tests with this preparation are not available.***12.2. Persistence and degradability**

Biodegradability No data available

12.3. Bioaccumulative potential

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199 Denture Base Powder****Lucitone 199 Repair Powder****Lucitone Fas-Por +, Powder****Lucitone Clear Dental Resin Powder****Lucitone Clear Pour Acrylic Powder****Lucitone Intensive Colors**

Version: 1.13 / GB
Revision date: 25.10.2018
Issue date: 14.02.2003
replaces version: 1.12
Page: 7 / 9

Material no. 0D905930
Specification 142125
VA-Nr 01804105

**12.4. Mobility in soil**

Mobility

Is absorbed by the soil and is not mobile.
The product is a high-molecular-weight, water insoluble, solid polymer.

12.5. Results of PBT and vPvB assessment

A PBT/vPvB evaluation is not available, since a chemical safety evaluation is not required / has not been carried out.

12.6. Other adverse effects

Further Information

The product is a solid, insoluble in water, chemically inert and virtually not biologically degradable.
No negative effects known.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Product**

Disposal according to local authority regulations.

Uncleaned packaging

Disposal according to local authority regulations.

SECTION 14: Transport information**Not dangerous according to transport regulations.**

14.1. UN number: --
14.2. UN proper shipping name: --
14.3. Transport hazard class(es): --
14.4. Packing group: --
14.5. Environmental hazards: --
14.6. Special precautions for user: No

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National legislation****15.2. Chemical safety assessment**

Chemical safety assessment No Chemical Safety Report as per Articles 2(8), 2(9) or 14 of the REACH Regulation is required for this product.

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199 Denture Base Powder****Lucitone 199 Repair Powder****Lucitone Fas-Por +, Powder****Lucitone Clear Dental Resin Powder****Lucitone Clear Pour Acrylic Powder****Lucitone Intensive Colors**

Version: 1.13 / GB
 Revision date: 25.10.2018
 Issue date: 14.02.2003
 replaces version: 1.12
 Page: 8 / 9

Material no. 0D905930
 Specification 142125
 VA-Nr 01804105

**SECTION 16: Other information**

Classification and applied procedure to derive the classification of mixtures according to EU Regulation (EC) No. 1272/2008 (CLP)

Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Legend

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ASTM	American Society for Testing and Materials
ATP	Adaptation to Technical Progress
BCF	Bioconcentration factor
BetrSichV	German Ordinance on Industrial Safety and Health
c.c.	closed cup
CAS	Chemical Abstract Services
CESIO	European Committee of Organic Surfactants and their Intermediates
ChemG	German Chemicals Act
CMR	carcinogenic-mutagenic-toxic for reproduction
DIN	German Institute for Standardization
DMEL	Derived minimum effect level
DNEL	Derived no effect level
EINECS	European Inventory of Existing Commercial Chemical Substances
EC50	half maximal effective concentration
GefStoffV	German Ordinance on Hazardous Substances
GGVSEB	German ordinance for road, rail and inland waterway transportation of dangerous goods
GGVSee	German ordinance for sea transportation of dangerous goods
GLP	Good Laboratory Practice
GMO	Genetic Modified Organism
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
ISO	International Organization For Standardization
LOAEL	Lowest observed adverse effect level
LOEL	Lowest observed effect level
NOAEL	No observed adverse effect level
NOEC	no observed effect concentration
NOFI	no observed effect level

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199 Denture Base Powder****Lucitone 199 Repair Powder****Lucitone Fas-Por +, Powder****Lucitone Clear Dental Resin Powder****Lucitone Clear Pour Acrylic Powder****Lucitone Intensive Colors**

Version: 1.13 / GB
Revision date: 25.10.2018
Issue date: 14.02.2003
replaces version: 1.12
Page: 9 / 9

Material no. 0D905930
Specification 142125
VA-Nr 01804105



OECD	Organisation for Economic Cooperation and Development
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative, toxic
PEC	Predicted effect concentration
PNEC	Predicted no effect concentration
REACH	REACH registration
RID	Convention concerning International Carriage by Rail
STOT	Specific Target Organ Toxicity
SVHC	Substances of Very High Concern
TA	Technical Instructions
TPR	Third Party Representative (Art. 4)
TRGS	Technical Rules for Hazardous Substances
VCI	German chemical industry association
vPvB	very persistent, very bioaccumulative
VOC	volatile organic compounds
VwVwS	German Administrative Regulation on the Classification of Substances Hazardous to Waters into Water Hazard Classes
WGK	Water Hazard Class
WHO	World Health Organization