SAFETY DATA SHEETS

This SDS packet was issued with item:

075908207

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

075908157 075908165 075908181 075908199

MATERIAL SAFETY DATA SHEET: SEAL-RITE, SEAL-RITE LV

<u>IDENTITY</u>

Trade Name:

Code:

Seal-Rite Pit and Fissure Sealant

SEAL, SEAL-3, RITE,

Seal-Rite Low Viscosity Pit and Fissure Sealant

SEAL-LV, SEAL-LV3, RITE-LV

Chemical Description: Glass filler materials in methacrylate resins.

Product Use: Visible light-cure pit and fissure dental sealant.

SECTION I

Pulpdent Corporation

Phone Numbers

80 Oakland Street

24 Hour Emergency: 1-800-535-5053

Watertown, MA 02472 USA

Customer Service: 1-800-343-4342/1-617-926-6666

Date prepared: September 1, 2008

SECTION II - HAZARDOUS INGREDIENTS

IngredientsCAS NumberPercentPEL / TLVUncured Methacrylate resins------66.0Not establishedAmorphous silica112945-52-55.0 $6 \text{ mg/m}^3 / 10 \text{ mg/m}^3$ Sodium fluoride7981-49-42.0 $2.5 \text{ mg/m}^3 \text{ (as F)}$

DOT HAZARD CLASSIFICATION:

Not regulated

WHMIS CLASSIFICATION:

D-2, Possible Irritation, Possible Sensitization

NFPA HMIS RATING: HEALTH: 1

FLAMMABILITY: 0

REACTIVITY: 1

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

Specific Gravity: SEAL 1.550, SEAL-LV 1.290

Vapor Pressure: <1 mm Hg

Vapor Density: 1

Solubility in water: Nil

Odor Threshold: Not available

Appearance and Odor: Off-white, thickened liquid with faint characteristic odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not established

Flammable limits: Not established

Extinguishing Media: Carbon dioxide, dry chemical, alcohol foam, or water fog; water spray to keep fire-

exposed containers cool.

Special Fire Fighting Procedures: A self-contained breathing apparatus should be worn by fire fighting personnel. Cool exposed containers with water spray to prevent polymerization under fire conditions.

Hazardous Combustion Products: Hazardous polymerization with heat build up and release of carbon monoxide, carbon dioxide and oxides of nitrogen may occur under fire conditions.

SECTION V - REACTIVITY DATA

Stability: Stable

Conditions to avoid: Temperature > 27°C / 80°F; intense light.

Incompatibility: Reducing and oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, oxides of nitrogen.

Hazardous Polymerization: None under normal conditions of use. Conditions to avoid: Temperature > 27°C / 80°F; intense light.

1 of 2

MATERIAL SAFETY DATA SHEET: SEAL-RITE, SEAL-RITE LV

SECTION VI - HEALTH HAZARD DATA

Summary of Acute Hazards: Minimal health hazard under normal conditions of use.

Route of Exposure

Signs & Symptoms

Inhalation

May be irritating to mucous membranes

Eye Contact

May be irritating Not applicable

Skin Absorption Skin Contact

Primary route of exposure, may cause irritation.

Ingestion

May be irritating to mucous membranes.

Summary of Chronic Hazards: Sensitization with prolonged or repeated contact.

.

Carcinogenicity

None known

_

Teratogenicity, Mutagenicity, Reproductive Toxicity: None known.

Emergency First Aid Procedures:

Inhalation

Move to fresh air. Administer artificial respiration, if required,

and seek medical attention.

Eye contact

Flush eyes with running water for 15+ minutes. Seek

medical attention.

Ingestion

Consult physician immediately.

Skin contact

Wash skin with soap and running water.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING & USE

Handling / Storage Precautions: Store tightly capped in original container at cool room temperature. Avoid temperature extremes (>27°C/80°F, <15°C/60°F), intense light, moisture and contaminants. Remove applicator tip and recap immediately after use.

Release or Spill: Wipe up material with paper or cloth towels and collect for disposal.

Waste Disposal Method: Follow all government regulations.

Other Precautions: Wash hands after use.

SECTION VIII - CONTROL MEASURES

Respiratory Protection: None required under anticipated conditions of normal use.

Ventilation: No special ventilation required under anticipated conditions of normal use.

Protective Gloves: Recommended.

Eye Protection: Safety glasses are recommended.

Other Protective Clothing or Equipment: Emergency eye wash fountain should be close by and maintained.

Work/Hygienic Practices: Avoid prolonged contact with skin. Wash hands after use.

The information presented herein is believed to be factual as it has been derived from the works of persons believed to be qualified experts. However, nothing contained in this information is to be taken as a warranty or representation for which Pulpdent Corporation bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.

Pulpdent Corporation Revision Date: May 28, 2019

Safety Data Sheet

Trade Name: SEAL-RITE™ PIT AND FISSURE SEALANT

1.0	Commercial Product Name and Supplier					
1.1	Commercial product name / designation	Seal-Rite Pit and Fis.	sure Sealant			
		Seal-Rite Low Viscos	sity Pit and Fissure Sealar	nt		
1.2	Application / Use	Dental material for use by dental professional only.				
1.2.2	SIC	851 Human health ad	ctivity			
1.2.3	Use Category	55				
1.3	Manufacturer Pulpdent Corporation 80 Oakland Street, P.O. Box 780 Watertown, MA 02472 USA	Telephone: 1 617 92 Email: Pulpdent@pul	6-6666 / Fax:1 617 926-6 lpdent.com	262		
1.4	Emergency Telephone Number	1-800-535-5053 (24 Hour / USA)				
1.5	Authorized European Representative	Advena Ltd. Pure Offices, Plato Close Warwick, CV34 6WE United Kingdom				
2.0	Hazards Identification					
2.1	Classification	Irritant.				
2.1.1	Classification according to Regulation (EC) No 1272/2008 [CLP]	Hazard Class Eye irritation STOT SE Skin irritation Skin sensitization	Hazard Category 2 3 2 1	Hazard Statement H319 H335 H315 H317		
2.1.2	Classification according to Directive 67/548/EEC	Irritant; Xi; R 36/37	/38 – 43 (See SECTION 16	for full text of risk phrases		
2.2	GHS Label Elements Hazard Pictograms					
	<u >					
	Signal Word: WARNING Restricted to use by dental professional only.					
	Hazard Statements H319: Eye irritation. 2. May cause eye irritation. H335: STOT SE. 3. May cause respiratory irritation. H315: Skin irritation. 2. May cause skin irritation. H317: Sensitization. 1. May cause an allergic skir					
	Precautionary Statements P261: Avoid breathing vapor					

P261: Avoid breathing vapor.

P280: Wear protective gloves and eye protection

P305+P351: If in eyes, rinse cautiously with water for several minutes.

P337+P313: If eye irritation persists, get medical advice/attention.

P302+P352: If on skin, wash with plenty of soap and water.

P333+P313: If irritation or rash occurs, get medical advice/attention.

P410+P411: Protect from sunlight. Store at temperature not exceeding 27°C / 80°F.

Pulpdent Corporation Revision Date: May 28, 2019

Safety Data Sheet

Trade Name: **SEAL-RITE™ PIT AND FISSURE SEALANT**

3.0	Composition					
3.1	Chemical charac	terization of the preparation:	Methacrylate ester monomers in a light-cured, glass-filled paste.			
3.2	Hazardous ingredients					
	CAS Number	Name of the Ingredient	Concentration	Classification per 67/548/EEC	Classification per Regulation (EC) No.1272/2008 (CLP)	
	Proprietary	Uncured methacrylate ester monomers	55-65%	Xi (Irritant), R36/37/38, R43	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315 Skin sensitization, 1, H317	
	112945-52-5	Amorphous silica	5 %	Xi (Irritant), R36/37/38	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315	
4.0	First Aid Measur	es				
4.1	General Information	no	May be irritating to eyes, respiratory system and skin. Prolonged or repeated contact with methacrylate may cause sensitization. Show this safety data sheet to medical personnel. Get medical attention in case of uncertainty.			
4.2	Inhalation		Move to fresh air. If necessary, administer oxygen and/or artificial respiration and seek medical attention.			
4.3	Skin Contact		Take off contaminated clothing. Wash skin thoroughly with soap and water.			
4.4	Eye Contact		Keep eyelids apart and flush with running water for 15+ minutes. Get medical attention.			
4.5	Ingestion Rinse mouth with water. Do not induce vomiting. Get immediate me attention. May be irritating to mucous membranes. Never give anythin mouth to an unconscious person.					
4.6	Precautions for first responders Ventilate the area. Wear eye and skin protection.			on.		
4.7	Information for p	hysicians				
	Symptoms		Irritation or redness in eyes, throat or on skin.			
	Hazards		May be irritating to eyes, respiratory system and skin. May cause sensitization by skin contact.			
	Treatment		As above under First Aid.			
5.0	Fire Fighting M	easures				
5.1	Suitable extinguishing media		Carbon dioxide, dry chemical, alcohol foam, or water fog. Water spray may be used to keep fire exposed containers cool.			
5.2	Extinguishing media to avoid		Do not use direct water stream			
5.3	Special exposure	Special exposure hazards in a fire		Heat may cause polymerization with rapid release of energy.		
5.4	·		Self-contained breathing apparatus.			
6.0	Accidental Release Measures					
6.1	Personal precau	Personal precautions. Ventilate area. Wear safety glasses, gloves and lab coat.			nd lab coat.	
6.2	Environmental p	recautions	Contain spilled material. Follow all government regulations.			

Pulpdent Corporation Revision Date: May 28, 2019

Safety Data Sheet

Trade Name: **SEAL-RITE™ PIT AND FISSURE SEALANT**

6.3	Method for clean up	Absorb/wipe up spill with paper towels or cloths. Collect for disposal in a covered container. Wash area of spill with alcohol or soap and water.	
7.0	Handling and Storage		
7.1	Handling	For use only by dental professionals trained in its use. Follow good hygiene practices. Remove applicator tip from syringe and cap container immediately after use. Keep light-cured materials shaded from intense light sources.	
7.2	Storage	Store product tightly capped in original container at cool room temperature (<25°C). Avoid direct, strong light, ignition sources, temperature extremes (>27°C/80°F, <5°C/40°F). Shelf life for unopened product is two years from date of manufacture, provided that the material has been stored properly.	
7.3	Specific uses	Dental material	
8.0	Exposure Controls / Personal Protection	on	
8.1	Exposure limit values	PEL: Not established. TLV: Not established.	
8.2	Exposure controls		
8.2.1	Occupational exposure controls	No special equipment required under normal conditions of use.	
8.2.1.1	Respiratory protection	Good general ventilation is sufficient to control any airborne vapors.	
8.2.1.2	Hand protection	No special requirements other than the usual surgical gloves.	
8.2.1.3	Eye protection	No special requirements other than the usual safety glasses	
8.2.1.4	Skin protection	Good personal hygiene and safety practices; wearing a lab coat.	
8.2.1.5	Other controls	Emergency eye wash fountain. Wash hands after use.	
8.2.2	Environmental exposure controls	Cure material before disposing. To the best of our knowledge, cured material is inert. Follow all government regulations.	
9.0	Physical and Chemical Properties		
9.1	Appearance / Color		
9.1.1	Color / Physical state	Off-white paste	
9.1.2	Odor	Faint, characteristic	
9.2	Important health, safety and environmental information		
9.2.1	рН	Not determined	
9.2.2	Boiling point	Not determined	
9.2.3	Flash point	Not determined	
9.2.4	Flammability (solid, gas)	Not applicable	
9.2.5	Explosive properties	Not applicable	
9.2.6	Oxidizing properties	Not determined	
9.2.7	Vapor pressure	< 1 mm Hg / 133 Pa / Id: B	
9.2.8	Specific gravity	Seal-Rite: 1.550; Seal-Rite LV: 1.290	
9.2.9	Solubility in water	Nil	
9.2.10	Partition coefficient	Not determined	

Safety Data Sheet

Trade Name: SEAL-RITE™ PIT AND FISSURE SEALANT 9.2.11 Viscosity Not determined > 1 9.2.12 Vapor density 9.2.13 Evaporation rate Not determined 10.0 Stability and reactivity 10.1 Temperature extremes (>27°C/80°F, <5°C/40°F), light. Conditions to avoid 10.2 Materials to avoid Reducing and oxidizing agents, peroxides, amines. 10.3 Under fire conditions and with amounts far greater than that supplied Hazardous decomposition products in this product, hazardous polymerization may occur with heat buildup and release of carbon monoxide, carbon dioxide, oxides of nitrogen. 10.4 Further information Direct light will polymerize light-cured material. 11.0 **Toxicological information** 11.1 Not toxic. Minimal health hazard in the quantities present in this Acute toxicity product and under normal conditions of use. 11.2 May be irritating to eyes, mucous membranes or skin on contact or Irritation and corrosiveness with prolonged exposure. 11.3 Sensitization May be sensitizing. Prolonged or frequent skin contact may cause allergic skin reactions in some susceptible individuals. 11.4 Sub-acute, sub-chronic and prolonged Prolonged/frequent skin contact may cause allergic skin reactions in toxicity susceptible individuals. Prolonged exposure to large amounts of this material may cause eye and respiratory irritation. 11.5 Carcinogenicity, Mutagenicity, None known. Reproductive Toxicity 11.6 Empirical data None available. 11.7 Clinical experience Seal-Rite and Seal-Rite-LV have been used safely and effectively by dentists in the US and internationally for more than 15 years with no reports of adverse events. 12.0 **Ecological Information** 12.1 Ecotoxicity To the best of our knowledge, polymerized material is inert. No other information is available. 13.0 **Disposal Considerations** 13.1 Regulations Polymerize before disposal. Follow all local and national government regulations in disposing material or contaminated packaging. 14.0 **Transport Information** 14.1 Restrictions None. Not regulated by IATA. 15.0 **Regulatory Information** 15.1 EU Class IIa medical devices under MDD 93/42/EEC. 15.2 **US FDA** Class II medical devices 15.3 Health Canada Class III medical devices

16.0	Other information				
16.1	List of relevant R phrases	R36/37/38: Irritating to eyes, respiratory system and skin. R43: Sensitizing by skin contact			
16.2	Hazard Statements	H319: Eye irritation. Hazard category 2. H335: Specific Target Organ Toxicity - Single exposure; hazard category. 3. Respiratory tract irritation. H315: Skin irritation. Hazard category 2. H317: Skin Sensitization. Hazard category 1.			
16.3	Precautionary Statements	P261: Avoid breathing vapor. P280: Wear protective gloves and eye protection P305+P351: If in eyes, rinse cautiously with water for several minutes. P337+P313: If eye irritation persists, get medical advice/attention. P302+P352: If on skin, wash with plenty of soap and water. P333+P313: If irritation or rash occurs, get medical advice/attention. P410+P411: Protect from sunlight. Store at temperature not exceeding 27°C / 80°F.			
16.4	Restrictions on use	Pulpdent products are to be sold to and used by dental professionals only.			
16.5	Further information	The information presented herein is believed to be factual as it has been derived from the works of persons believed to be qualified experts. However, nothing contained in this information is to be taken as a warranty or representation for which Pulpdent Corporation bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.			
16.6	Sources of key data	National Institute for Occupational Safety (NIOSH) US Occupational Safety and Health Administration (OSHA) Eur-Lex European Union Law: Regulation (EC) No. 1272/2008 (CLP) and Regulation (EC) No. 1907/2006 (REACH). Guidance on the compilation of safety data sheets. Version 1.1; December 2011. European Chemicals Agency			
16.7	Information which has been added, deleted or revised.	This Safety Data Sheet has been revised to meet the requirements of GHS SDS format and Regulations (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH). Specifically Sections 2.1, 2.2, 3.2, 16.2, 16.3 have been modified.			

Revision Date: May 28, 2019