# **SAFETY DATA SHEETS**

# This SDS packet was issued with item:

071393248

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071393230 071393255 071393263



Page 1/9

Tel.: +49 (0)800 4372522

### Safety Data Sheet acc. to OSHA HCS

Printing date 07/05/2021 Reviewed on 07/05/2021

## 1 Identification

- · Product identifier
  - · Trade name: Venus Bulk Flow ONE

- · Application of the substance / the mixture Dental filling material
- · Details of the supplier of the safety data sheet
  - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

· Information department:

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545 e-mail: customer.servicehkna@kulzer-dental.com

Emergency telephone number:

Emergency CONTACT (24-Hour-Number) ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

## 2 Hazard(s) identification

Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child. Repr. 1B

· Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate

2-ethylhexyl 4-(dimethylamino)benzoate

Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

Precautionary statements

Avoid release to the environment.

Wear protective gloves / eye protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)



Page 2/9

### Safety Data Sheet acc. to OSHA HCS

Printing date 07/05/2021 Reviewed on 07/05/2021

# Trade name: Venus Bulk Flow ONE

(Contd. of page 1)

· Classification system

· NFPA ratings for USA (scale 0-4)



· HMIS-Ratings (Scale 0-4)



Health = 2 Fire = 0

Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

Description: -

· Dangero	us components:	
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	10-25%
	Skin Sens. 1B, H317	
13760-80-0	ytterbium trifluoride	≥10-<20%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
109-16-0	triethylen glycol dimethacrylate	≥0.1-<1%
	Skin Sens. 1B, H317	
21245-02-3	2-ethylhexyl 4-(dimethylamino)benzoate	≥0.1-<1%
	Repr. 1B, H360	

<sup>·</sup> Additional information For the wording of the listed hazard phrases refer to section 16.

#### 4 First-aid measures

- · Description of first aid measures
  - After inhalation Supply fresh air; consult doctor in case of complaints.
  - After skin contact If skin irritation continues, consult a doctor.
  - After eve contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- Information for doctor
  - · Most important symptoms and effects, both acute and delayed Allergic reactions
  - Indication of any immediate medical attention and special treatment needed No further relevant information available.



Page 3/9

# Safety Data Sheet acc. to OSHA HCS

Printing date 07/05/2021 Reviewed on 07/05/2021

## Trade name: Venus Bulk Flow ONE

(Contd. of page 2)

# 5 Fire-fighting measures

- · Extinguishing media
  - · Suitable extinguishing agents
    - CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
  - · Protective equipment: No special measures required.
- · Additional information -

## 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- Methods and material for containment and cleaning up: Pick up mechanically.
- · Reference to other sections
  - See Section 7 for information on safe handling
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

· PAC-1:		
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane 1,16-diyl bismethacrylate	e- 120 mg/m³
13760-80-0	ytterbium trifluoride	30 mg/m <sup>3</sup>
1343-98-2	silicic acid	18 mg/m³
109-16-0	triethylen glycol dimethacrylate	33 mg/m³
13463-67-7	Titanium dioxide	30 mg/m <sup>3</sup>
579-07-7	1-phenylpropane-1,2-dione	0.4 mg/m <sup>3</sup>
80-62-6	methyl methacrylate	17 ppm
2530-85-0	3-trimethoxysilylpropyl methacrylate	71 mg/m³
64-19-7	acetic acid	5 ppm
· PAC-2:		•
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	1,300 mg/m <sup>3</sup>
13760-80-0	ytterbium trifluoride	330 mg/m³
1343-98-2	silicic acid	95 mg/m³
109-16-0	triethylen glycol dimethacrylate	360 mg/m³
13463-67-7	Titanium dioxide	330 mg/m³
579-07-7	1-phenylpropane-1,2-dione	4.5 mg/m³
80-62-6	methyl methacrylate	120 ppm
2530-85-0	3-trimethoxysilylpropyl methacrylate	780 mg/m³
64-19-7	acetic acid	35 ppm
· PAC-3:		
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane- 1,16-diyl bismethacrylate	7,900 mg/m <sup>3</sup>
		Contd. on pag



Page 4/9

### Safety Data Sheet acc. to OSHA HCS

Printing date 07/05/2021 Reviewed on 07/05/2021

# Trade name: Venus Bulk Flow ONE

		(Contd. of page 3)
	ytterbium trifluoride	2,000 mg/m³
1343-98-2	silicic acid	570 mg/m³
109-16-0	triethylen glycol dimethacrylate	2,100 mg/m³
13463-67-7	Titanium dioxide	2,000 mg/m³
	1-phenylpropane-1,2-dione	27 mg/m³
	methyl methacrylate	570 ppm
	3-trimethoxysilylpropyl methacrylate	4,700 mg/m³
64-19-7	acetic acid	250 ppm

# 7 Handling and storage

- Handling
  - Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
  - Storage
    - Requirements to be met by storerooms and receptacles: No special requirements.
    - Information about storage in one common storage facility: Not required.
    - Further information about storage conditions: Store in dry conditions.
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Control parameters
  - Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Not required.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
  - Personal protective equipment
    - General protective and hygienic measures
      - Wash hands before breaks and at the end of work.
    - · Breathing equipment: Not necessary if room is well-ventilated.
    - Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.

recommended

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Page 5/9

# Safety Data Sheet acc. to OSHA HCS

Printing date 07/05/2021 Reviewed on 07/05/2021

# Trade name: Venus Bulk Flow ONE

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

· Eye protection: Tightly sealed goggles.

Body protection: Light weight protective clothing

#### 9 Physical and chemical properties · Information on basic physical and chemical properties General Information Appearance: Form: Pasty Color: Whitish · Odor: Odorless · Odor threshold: Not determined. Not determined. · pH-value: · Change in condition undetermined Melting point/Melting range: Boiling point/Boiling range: undetermined Not applicable · Flash point: · Flammability (solid, gaseous) Not applicable. Decomposition temperature: Not determined. · Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Not determined. **Explosion limits:** Lower: Not determined. · Upper: Not determined. · Vapor pressure: Not determined. · Density at 20 °C (68 °F): 1.9 g/cm3 (15.8555 lbs/gal) Relative density Not determined. Not determined. · Vapor density · Evaporation rate Not determined. · Solubility in / Miscibility with · Water: Not miscible or difficult to mix · Partition coefficient (n-octanol/water): Not determined. Viscosity: dynamic: Not determined. Not determined. · kinematic: · Other information No further relevant information available.

US



Page 6/9

# Safety Data Sheet acc. to OSHA HCS

Printing date 07/05/2021 Reviewed on 07/05/2021

Trade name: Venus Bulk Flow ONE

(Contd. of page 5)

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: none
- · Additional information: -

## 11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

41637-38-1 (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyloxy-2,1-ethanediyl) bismethacrylate

Oral LD50 >2000 mg/kg (rat) (OECD 423)

Dermal LD50 >2000 mg/kg (rat) (OECD 402)

72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate

Oral LD50 >5000 mg/kg (rat) (OECD 401)
Dermal LD50 >2000 mg/kg (rat) (OECD 402)

109-16-0 triethylen glycol dimethacrylate

Oral LD50 8300 mg/kg (rat)

Dermal LD50 >2000 mg/kg (mouse)

21245-02-3 2-ethylhexyl 4-(dimethylamino)benzoate

Oral LD50 14900 mg/kg (rat)

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
  - · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

13760-80-0 ytterbium trifluoride

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Reproductive toxicity

21245-02-3 2-ethylhexyl 4-(dimethylamino)benzoate

Oral NOAEL (Fruchtbarkeit) 50 mg/kg/d /64 d (rat) (OECD 421)

## 12 Ecological information

· Toxicity

· Aquatic toxicity:

41637-38-1 (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyloxy-2,1-ethanediyl) bismethacrylate

EC50/72h >100 mg/l (algae) (OECD 201)

(Contd. on page 7)



Page 7/9

# Safety Data Sheet acc. to OSHA HCS

Printing date 07/05/2021 Reviewed on 07/05/2021

# Trade name: Venus Bulk Flow ONE

_		(Contd. of page 6)
	EC50/48h	>100 mg/l (daphnia) (OECD 202)
	LC50/96h	>100 mg/l (fish) (OECD 203)
	NOEC 28d	14.3 mg/l (bacteria)
	72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-di bismethacrylate	
	EC50/48h	>1.2 mg/l (daphnia) (OECD 202)
	LC50/96h	10.1 mg/l (fish) (OECD 203)
	ErC50 / 72 h	>0.68 mg/l (algae) (OECD 201)
	NOEC / 72h	0.21 mg/l (algae) (OECD 201)
	109-16-0 triethylen glycol dimethacrylate	
	EC50/21d	51.9 mg/L (daphnia) (OECD 211)
	LC50/96h	16.4 mg/l (fish) (OECD 203)
	NOEC / 21d	32 mg/l (daphnia) (OECD 211)
	ErC50 / 72 h	>100 mg/l (algae) (OECD 201)
	NOEC / 72h	18.6 mg/l (algae) (OECD 201)
	EbC50 / 72h	72.8 mg/l (algae) (OECD 201)
Ī	· Persistence	and degradability
		7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate
	biodegradabi	lity 22 % /28d (nd) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)
	109-16-0 trie	thylen glycol dimethacrylate
	biodegradabi	lity 85 % /28d (nd) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)

- Behavior in environmental systems:
  - · Bioaccumulative potential No further relevant information available.
  - · Mobility in soil No further relevant information available.
- · Additional ecological information:
  - General notes: Avoid transfer into the environment.
- · Results of PBT and vPvB assessment
  - · PBT: Not applicable.
  - · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packagings:
  - Recommendation:

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

119



Page 8/9

#### Safety Data Sheet acc. to OSHA HCS

Printing date 07/05/2021 Reviewed on 07/05/2021

Trade name: Venus Bulk Flow ONE

(Contd. of page 7)

UN-Number		
· DOT, ADR, IMDG, IATA	Void	
	VOIG	
UN proper shipping name · DOT, ADR, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA		
· Class	Void	
Packing group DOT, ADR, IMDG, IATA	Void	
Environmental hazards:  · Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:	-	
UN "Model Regulation":	Void	

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

SARA Section 313 (specific toxic chemical listings)

80-62-6 methyl methacrylate

· Hazardous Air Pollutants

80-62-6 methyl methacrylate

Proposition 65

**Prop 65 - Chemicals known to cause cancer**The listing is for titanium dioxide as "airborne, unbound particles of respirable size".
Titanium dioxide of this product (< 0,1 %) is within a product matrix.

13463-67-7 Titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

EPA (Environmental Protection Agency)

80-62-6 methyl methacrylate

E, NL

(Contd. on page 9)



Page 9/9

#### Safety Data Sheet acc. to OSHA HCS

Printing date 07/05/2021 Reviewed on 07/05/2021

## Trade name: Venus Bulk Flow ONE

(Contd. of page 8)

· TLV (Threshold Limit Value)

13760-80-0 ytterbium trifluoride

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 Titanium dioxide

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H360 May damage fertility or the unborn child.

Date of preparation / last revision 07/05/2021 / -

## Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement

Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

VPVB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.