

SAFETY DATA SHEETS

This SDS packet was issued with item:

075218326

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

075219456 075219464 075219472 075219480 075219498

Printing date 05/07/2012

Reviewed on 04/01/2012

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** ALLOY PRIMER
- **Article number:** US054
- **Application of the substance / the preparation** Adhesive, dental metal
- **Details of the supplier of the safety data sheet**
- **Manufacturer:**
Kuraray Noritake Dental Inc.
1621 Sakazu, Kurashiki, Okayama 710-0801,
Japan
- **Contact information:**
Kuraray America, Inc.
33 Maiden Lane, 6th Floor, New York,
NY 10038 U.S.A.
Tel: 800-879-1676
Fax: 888-700-5200
Website: www.kuraraydental.com

2 Composition/information on ingredients

- **Chemical characterization:** Single Component
- **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

67-64-1	acetone	 H225;  H319; H336	>90%
---------	---------	---	------

- **Other ingredients:**
6-(4-Vinylbenzyl-N-propyl)amino-1,3,5-triazine-2,4-dithione
10-Methacryloyloxydecyl dihydrogen phosphate

3 Hazards identification

- **Classification of the substance or mixture**



GHS02 Flame

H225 Highly flammable liquid and vapour.



GHS07

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Irritant

Irritating to eyes.



Highly flammable

Highly flammable.

Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

(Contd. on page 2)

USA

Printing date 05/07/2012

Reviewed on 04/01/2012

Trade name: ALLOY PRIMER

(Contd. of page 1)

· **Label elements**· **GHS label elements**

The product is classified and labelled according to the Globally Harmonized System (GHS).

· **Hazard pictograms** GHS02, GHS07· **Signal word** Danger· **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

4 First aid measures· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Generally the product does not irritate the skin.· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Do not induce vomiting; immediately call for medical help.

If symptoms persist consult doctor.

5 Firefighting measures· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** No further relevant information available.· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

— USA —

(Contd. on page 3)

Printing date 05/07/2012

Reviewed on 04/01/2012

Trade name: ALLOY PRIMER

(Contd. of page 2)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location (2-25°C).

- **Information about storage in one common storage facility:**

Store away from oxidizing agents.

Store away from reducing agents.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL 2400 mg/m³, 1000 ppm

REL 590 mg/m³, 250 ppm

TLV Short-term value: 1782 mg/m³, 750 ppm

Long-term value: 1188 mg/m³, 500 ppm

BEI

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

- **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 4)

USA

Printing date 05/07/2012

Reviewed on 04/01/2012

Trade name: ALLOY PRIMER

(Contd. of page 3)

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

9 Physical and chemical properties**· General Information****· Appearance:**

Form:	Liquid
Color:	Transparent
Odor:	Acetone-like

· **pH-value:** Not applicable

· Change in condition

Melting point/Melting range:	94.7 °C (acetone)
Boiling point/Boiling range:	55°C (131 °F) (acetone)

· **Flash point:** -19°C (-2 °F) (acetone)

· **Ignition temperature:** 465.0°C (869 °F) (acetone)

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	2.6 Vol % (acetone)
Upper:	13.0 Vol % (acetone)

· **Vapor pressure at 20°C (68 °F):** 233.0 hPa (175 mm Hg) (acetone)

· **Density:** 0.79 g/cm³ (acetone)

· **Vapour density** 2.0 g/cm³ (acetone, air=1)

· Solubility in / Miscibility with

Water: Partly miscible.

· **Segregation coefficient (n-octanol/water):** -0.24 (acetone)

· **VOC content:** 99.0 %

· **Other information** No further relevant information available.

USA

(Contd. on page 5)

Printing date 05/07/2012

Reviewed on 04/01/2012

Trade name: ALLOY PRIMER

(Contd. of page 4)

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

12 Ecological information

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|----------------------------------|------------------------|
| · UN-Number | |
| · DOT | UN1090 |
| · ADR, IMDG, IATA | 1090 |
| · UN proper shipping name | |
| · ADR | 1090 ACETONE, solution |

(Contd. on page 6)

USA

Printing date 05/07/2012

Reviewed on 04/01/2012

Trade name: ALLOY PRIMER

(Contd. of page 5)

· IMDG, IATA	ACETONE, solution
· Transport hazard class(es)	
· DOT, IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· ADR	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN1090; ACETONE, solution; 3; II

15 Regulatory information

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 7)

USA

Printing date 05/07/2012

Reviewed on 04/01/2012

Trade name: ALLOY PRIMER

(Contd. of page 6)

· **Cancerogenity categories**· **EPA (Environmental Protection Agency)**

67-64-1 acetone

I

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1 acetone

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **GHS label elements** Not determined**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Version:** 4· **Relevant phrases**

Not applicable

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

USA

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/28/2017

Version 5

Reviewed on 07/28/2017

1 Identification

- **Product identifier**
- **Trade name:** ALLOY PRIMER
- **Article number:** US054
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Adhesive, dental metal
- **Details of the supplier of the safety data sheet**
- **Manufacturer:**
Kuraray Noritake Dental Inc.
1621 Sakazu, Kurashiki, Okayama 710-0801,
Japan
- **Contact information:**
Kuraray America, Inc.
33 Maiden Lane, 6th Floor, New York,
NY 10038 U.S.A.
Tel: 800-879-1676
Fax: 888-700-5200
Website: www.kuraraydental.com
- **Emergency telephone number:**
For chemical emergency spill, leak, fire, exposure or accident
Call CHEMTREC day and night
Within USA and Canada: 1-800-424-9300 CCN706984 or
+1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Danger
- **Hazard-determining components of labeling:**
acetone
- **Hazard statements**
H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P280 Wear protective gloves / eye protection / face protection.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2017

Version 5

Reviewed on 07/28/2017

Trade name: ALLOY PRIMER

(Contd. of page 1)

- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances** None
- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

67-64-1	acetone	 Flam. Liq. 2, H225;  Eye Irrit. 2A, H319; STOT SE 3, H336	>90%
---------	---------	--	------

· **Other ingredients:**

6-(4-Vinylbenzyl-N-propyl)amino-1,3,5-triazine-2,4-dithione
 10-Methacryloyloxydecyl dihydrogen phosphate

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Do not induce vomiting; immediately call for medical help.
If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

US

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/28/2017

Version 5

Reviewed on 07/28/2017

Trade name: ALLOY PRIMER

(Contd. of page 2)

6 Accidental release measures**· Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage**· Handling:****· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and receptacles:** Store in a cool location (2-25 °C).**· Information about storage in one common storage facility:**

Store away from oxidizing agents.

Store away from reducing agents.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.**8 Exposure controls/personal protection****· Additional information about design of technical systems:** No further data; see item 7.**· Control parameters****· Components with limit values that require monitoring at the workplace:****67-64-1 acetone**PEL 2400 mg/m³, 1000 ppmREL 590 mg/m³, 250 ppmTLV Short-term value: 1782 mg/m³, 750 ppmLong-term value: 1188 mg/m³, 500 ppm

BEI

· Additional information: The lists that were valid during the creation were used as basis.**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

(Contd. on page 4)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/28/2017

Version 5

Reviewed on 07/28/2017

Trade name: ALLOY PRIMER

(Contd. of page 3)

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

· **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**

Neoprene gloves

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR

Neoprene gloves

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Color:

Transparent

· **Odor:**

Acetone-like

· **pH-value:**

Not determined

· **Change in condition**

Melting point/Melting range:

-94.7 °C (acetone)

Boiling point/Boiling range:

55 °C (acetone)

· **Flash point:**

-19 °C (acetone)

· **Ignition temperature:**

465.0 °C (acetone)

· **Decomposition temperature:**

Not determined

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:

2.6 Vol % (acetone)

Upper:

13.0 Vol % (acetone)

· **Oxidizing properties**

Not determined

· **Vapor pressure at 20 °C:**

233.0 hPa (acetone)

· **Density:**

0.79 g/cm³ (acetone)

· **Relative density**

Not determined

· **Vapor density**

2.0 g/cm³ (acetone, air=1)

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2017

Version 5

Reviewed on 07/28/2017

Trade name: ALLOY PRIMER

(Contd. of page 4)

· Evaporation rate	Not determined
· Solubility in / Miscibility with Water:	Partly miscible.
· Partition coefficient (n-octanol/water):	-0.24 (acetone)
· Viscosity:	Not determined
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2017

Version 5

Reviewed on 07/28/2017

Trade name: ALLOY PRIMER

(Contd. of page 5)

- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|----------------------------|
| · UN-Number | UN1090 |
| · DOT | 1090 |
| · ADR, IMDG, IATA | 1090 |
| · UN proper shipping name | 1090 ACETONE, solution |
| · ADR | ACETONE, solution |
| · IMDG, IATA | ACETONE, solution |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · ADR, IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | II |
| · DOT, ADR, IMDG, IATA | II |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| · Danger code (Kemler): | 33 |
| · EMS Number: | F-E,S-D |

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2017

Version 5

Reviewed on 07/28/2017

Trade name: ALLOY PRIMER

(Contd. of page 6)

- | | |
|---|----------------------------------|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | UN1090; ACETONE, solution; 3; II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

67-64-1 acetone

I

· TLV (Threshold Limit Value established by ACGIH)

67-64-1 acetone

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

Not determined

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· NFPA ratings (scale 0 - 4)



Health = 1

Fire = 3

Reactivity = 0

(Contd. on page 8)

US

Printing date 07/28/2017

Version 5

Reviewed on 07/28/2017

Trade name: ALLOY PRIMER

(Contd. of page 7)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1
FIRE	3
REACTIVITY	0

Health = 1

Fire = 3

Reactivity = 0

· **Abbreviations and acronyms:**

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

US