

SAFETY DATA SHEETS

This SDS packet was issued with item:

076709638

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

076709570

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

071182781 076709588 076709653

Material Safety Data Sheet

U.S. Department of Labor

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Hazard Rating

4= Extreme Toxicity = 2
3= High Fire = 3
2= Moderate Reactivity = 0
1= Slight
0= Insignificant Personal Protection = B
** See Sect IV



IDENTITY (As Used on Label and List) Stone Die & Plaster Hardener-Resin or Thinner	DOT Hazard Class Flammable Liquid, nos UN 1993, Class 3, PG II ORM-D consumer commodity	Code: 02-xxxx
--	---	-------------------------

Section I - Contact

Manufacturer's Name: George Taub Products & Fusion Co. Inc.	Emergency Telephone Number: Chemtrec: 800-424-9300, 703-527-3887
Address (Number, Street, City, State, and ZIP Code): 277 New York Ave Jersey City, N.J. 07307	Telephone Number for Information: 201-798-5353
	Date Prepared: 06/13/11
	Signature of Preparer (optional):

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)):	CAS REG. NO.:	OSHA PEL:	ACGIH TLV:	% (optional):
2-Butanone	78-93-3	200 ppm	200 ppm	> 80
Methyl methacrylate	80-62-6	100 ppm	100 ppm	< 1
Non-Hazardous Components: Resin co-polymer (proprietary)				

Section III - Physical/Chemical Characteristics

Boiling Point: 175.3 F	Melting Point: -122.8 F	Evaporation Rate (Butyl Acetate = 1): > 1.0	Viscosity: > 30 sec. Zahn # 1 cup
Vapor Pressure (mm Hg): 80 mm Hg @ 20 C	Vapor Density (AIR = 1): > 1.0	Specific Gravity (H ₂ O = 1): 0.95 - 1.0	% Volatile (by weight): > 80
Solubility in Water: Partially for resin, moderately for thinner			
Appearance and Odor: Clear, light yellow or colorless liquid, with low viscosity. Pungent, sweet odor.			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used): 24.8 F (-4 C) Tag closed cup	Flammable Limits:	LEL: 1.8	UEL: 11.5
Extinguishing Media: ☐ Foam ☒ "Alcohol" Foam ☒ CO ₂ ☒ Dry Chemical ☐ Water Spray ☐ Other			
Special Fire Fighting Procedures: Wear MSHA/NIOSH approved pressure demand, self-contained breathing apparatus with full protective equipment. Cool fire-exposed containers with water spray. High pressure solid stream of water will spread the fire.			
Unusual Fire and Explosion Hazards: Solvent vapors can travel to an ignition source and flash back. Explosive mixtures can form with air. Hazardous decomposition products: carbon monoxide.			

Section V - Reactivity Data

Stability: ☒ Stable ☐ Unstable	Conditions to Avoid: Avoid contacts with ignition sources (e.g. sparks, open flame, heated surfaces)
Incompatibility (Materials to Avoid): Strong oxidizing agents, strong acids and strong bases	
Hazardous Decomposition or Byproducts: Oxides of carbon. May yield acrylic monomers.	
Hazardous Polymerization: ☐ May Occur ☒ Will Not Occur	Conditions to Avoid: Not applicable

Section VI - Health Hazard Data

Route(s) of Entry: ☒ Inhalation ☒ Skin ☒ Eyes ☒ Ingestion

Health Hazards (Acute and Chronic):

If inhaled or ingested may cause drowsiness, dizziness, headache, nausea, vomiting, diarrhea, gastrointestinal irritation, central nervous system effects, slow respiration, unconsciousness, pulmonary edema, pneumonitis, coma and death. May cause sensitization by skin contact and moderate skin irritation including irritation of nose and throat. Direct eye contact can cause severe irritation temporary damage and possibly conjunctivitis.

Carcinogenicity: ☐ NTP ☐ IARC Monographs ☐ OSHA Regulated Not classifiable

Signs and Symptoms of Exposure:

Drowsiness, dizziness, nausea, vomiting, diarrhea, headache, allergic skin reaction, abdominal pain.

Medical Conditions - Generally Aggravated by Exposure: None known.

Emergency and First Aid Procedures:

Inhalation: Move to fresh air. Give artificial respiration if breathing has stopped. Shortness of breath - give oxygen. Get prompt medical attention. Skin Contact: Wash off with soap and plenty of water. Remove and wash contaminated clothing. Eye Contact: Rinse immediately with plenty of water for minimum of 15 min. Get prompt medical attention. Ingestion: Do not induce vomiting. Drink 1-2 glass of water. Get prompt medical attention

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled:

Personal Precautions: Appropriate protective equipment must be worn for handling spill, see Section 8. If exposed to material, see Section 6. Environmental Precautions: Warning - Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

Waste Disposal Method:

Spill Clean up: Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery, use caution. Soak up with inert absorbent material (Paper towel, sand, silica gel, sawdust). Avoid breathing vapor. Wear MSHA/NIOSH approved respirator. Note: Spills on porous surfaces can contaminate ground water. Normal Disposal: Waste Classification: Methyl Ethyl Ketone (78-93-3), 40 CFR 261.20-.24. For discard, this is classified as a hazardous waste with the characteristic of ignitability and toxicity. RCRA #D001. Reportable quantity is 100 lbs.(40 CFR 302) Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations. (See 40 CFR 268). For small quantity spills, allow solvent in paper towel to evaporate in well ventilated areas or outdoors (preferred). Contaminated packaging: Empty containers should be taken for local recycling or waste disposal.

Precautions to Be Taken in Handling and Storing:

Use of proper ventilation required. Use non-sparking tools and grounding cables when transferring. Wash after handling. Storage: Avoid temperature extremes during storage. Store out of sunlight and in cool place. Keep containers tightly capped. Clean neck of resin container free of resin buildup to maintain proper seal. Store containers in approved area for flammables. Avoid ignition sources, e.g handpiece motor, bunsen burner.

Other Precautions:

CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Emptied containers contain residue. Follow all MSDS and labels.

Section VIII - Control Measures

Respiratory Protection (Specify Type): None required if airborne concentrations maintained below the exposure limit.

Ventilation: ☒ Local Exhaust ☐ Mechanical (*General*) ☐ Special ☐ Other

Use explosion-proof local exhaust ventilation with min. capture velocity of 100 ft/min at point of vapor evolution.

Protective Gloves: Chemical-resistant only **Eye Protection:** Chemical-resistant goggles

Other Protective Clothing or Equipment: Chemical-resistant apron or other impervious cloth

Work/Hygienic Practices: Eyewash, shower

Section IX - Regulatory Information

This product is considered hazardous under OSHA Hazard Communication. Standard (29CFR 1910.1200).

This product is a 'controlled product' under Canadian Workplace Hazardous Materials Information System (WHMIS) SARA TITLE III: Sect 313 (40CFR372) above de minimus concentrations (Methyl methacrylate (80-62-6), Methyl Ethyl Ketone (78-93-3)). CERCLA (40CFR302.4) regulated components: MMA (RQ 1000 lbs), MEK (RQ 5000 lbs).

Disclaimer: While the information and recommendations set forth herein are believed to be accurate as of the date hereof, George Taub Products makes no warranty with respect thereto and disclaims all liability from reliance thereon.

Safety Data Sheet

Stone Die & Plaster Hardener Resin

SDS Revision Date: 05/21/2021

1. Identification

1.1. Product identifier

Product Identity

Stone Die & Plaster Hardener Resin

Alternate Names

Stone Die & Plaster Hardener Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

See Technical Data Sheet.

Application Method

See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name

George Taub Products & Fusion Co., Inc.
277 New York Ave
Jersey City, NJ 07307

Emergency

CHEMTREC (USA)

(800) 424-9300

24 hour Emergency Telephone No.

201-798-5353

Customer Service: George Taub Products & Fusion Co., Inc.

Chemtrec: 800-424-9300, 703-527-3887

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225

Highly Flammable liquid and vapor.

Eye Irrit. 2;H319

Causes serious eye irritation.

Skin Sens. 1;H317

May cause an allergic skin reaction.

STOT SE 3;H336

May cause drowsiness or dizziness.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H225 Highly flammable liquid and vapor.

Safety Data Sheet

Stone Die & Plaster Hardener Resin

SDS Revision Date: 05/21/2021

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P313 Get medical advice / attention.

P321 Specific treatment (see information on this label).

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

Safety Data Sheet

Stone Die & Plaster Hardener Resin

SDS Revision Date: 05/21/2021

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Butanone CAS Number: 0000078-93-3	75 - 100	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Methyl methacrylate CAS Number: 0000080-62-6	0.10 - 1.0	Flam. Liq. 2;H225 STOT SE 3;H335 Skin Irrit. 2;H315 Skin Sens. 1;H317	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	Drowsiness, dizziness, nausea, vomiting, diarrhea, headache, allergic skin reaction, abdominal pain, Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.
Inhalation	May cause drowsiness or dizziness.
Eyes	Causes serious eye irritation.
Skin	May cause an allergic skin reaction.

Safety Data Sheet

Stone Die & Plaster Hardener Resin

SDS Revision Date: 05/21/2021

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

Do not use: water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of carbon. May yield acrylic monomers.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Special Fire Fighting Procedures: Wear MSHA/NIOSH approved pressure demand, self-contained breathing apparatus with full protective equipment. Cool fire-exposed containers with water spray. High pressure solid stream of water will spread the fire.

Unusual Fire and Explosion Hazards: Solvent vapors can travel to an ignition source and flash back. Explosive mixtures can form with air. Hazardous decomposition products: carbon monoxide.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Personal Precautions: Appropriate protective equipment must be worn for handling spill, see Section 8. If exposed to material, see Section 6.

Environmental Precautions: Warning - Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

Waste Disposal Method:

Spill Clean up: Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery, use caution. Soak up with inert absorbent material (Paper towel, sand, silica gel, sawdust). Avoid breathing vapor. Wear MSHA/NIOSH approved respirator. Note: Spills on porous surfaces can contaminate ground water.

Safety Data Sheet

Stone Die & Plaster Hardener Resin

SDS Revision Date: 05/21/2021

NORMAL DISPOSAL:

Waste Classification: Methyl Ethyl Ketone (78-93-3), 40 CFR 261.20- 24. For discard, this is classified as a hazardous waste with the characteristic of ignitability and toxicity. RCRA #D001. Reportable quantity is 100 lbs.(40 CFR 302) Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations. (See 40 CFR 268). For small quantity spills, allow solvent in paper towel to evaporate in well ventilated areas or outdoors (preferred).

CONTAMINATED PACKAGING: Empty containers should be taken for local recycling or waste disposal.

7. Handling and storage

7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Water, acids, alkalis, chlorinated solvents.

Precautions to Be Taken in Handling and Storing: Limit storage of flammable material to approved areas. Keep properly ventilated. Ground all containers when transferring material. Store bottles away from heat. Keep away from open flame of Bunsen burner or furnace. Keep containers tightly sealed. Periodically clean neck of bottle of resinous build up (clean inside of cap) to maintain proper seal. Do not smoke when using. Avoid storing near acids, chlorinated solvents. Add thinner as needed, to keep proper thinness of material.

Other Precautions: Storage Temp: Min: 4.4C/40F; Max: 49C/120F; Cool Ambient Temperature preferred.

STEL: 125 ppm MEK. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Emptied containers contain residue.

Follow all SDS and labels. Keep away from spark.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000078-93-3	Butanone	OSHA	TWA 200 ppm (590 mg/m3)
		ACGIH	TWA: 50 ppm STEL: 100 ppm
		NIOSH	TWA 200 ppm (590 mg/m3) ST 300 ppm (885 mg/m3)
		Supplier	No Established Limit
0000080-62-6	Methyl methacrylate	OSHA	TWA 100 ppm (410 mg/m3)
		ACGIH	TWA: 50 ppm STEL: 100 ppm S

Safety Data Sheet

Stone Die & Plaster Hardener Resin

SDS Revision Date: 05/21/2021

		NIOSH	TWA 100 ppm (410 mg/m3)
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000078-93-3	Butanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000080-62-6	Methyl methacrylate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

8.2. Exposure controls

Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes

Chemical-resistant goggles

Skin

Use chemical-resistant apron or other impervious clothing, and rubber boots if necessary, to avoid contaminating regular clothing and shoes and to prevent skin contact. General ventilation.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance

Clear, light yellow or colorless Liquid

Odor

Pungent, sweet odor

Odor threshold

Not determined

pH

Not Measured

Melting point / freezing point

-122.8 F

Initial boiling point and boiling range

175.3 F

Flash Point

24.8 F/-4 C (TCC)

Evaporation rate (Ether = 1)

> 1.0 (Butyl Acetate = 1)

Flammability (solid, gas)

Not Applicable

Upper/lower flammability or explosive limits

Lower Explosive Limit: 1.8

Upper Explosive Limit: 11.5

Safety Data Sheet

Stone Die & Plaster Hardener Resin

SDS Revision Date: 05/21/2021

Vapor pressure (Pa)	80 mm Hg @ 20C
Vapor Density	> 1.0 (Air = 1)
Specific Gravity	0.95 - 1.0 (H2O = 1)
Solubility in Water	Partially for resin, moderately for thinner
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	> 30 sec (Zahn # 1 cup)
% Volatile	> 80%

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid excessive heat, open flames and all ignition sources.

10.5. Incompatible materials

Avoid contact with strong oxidizers, strong acids and strong bases.

10.6. Hazardous decomposition products

Oxides of carbon. May yield acrylic monomers.

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50,	Inhalation Dust/Mist LC50,	Inhalation Gas LC50,
------------	---------------------	---------------------	---------------------------	-------------------------------	-------------------------

Safety Data Sheet

Stone Die & Plaster Hardener Resin

SDS Revision Date: 05/21/2021

			mg/L/4hr	mg/L/4hr	ppm
Butanone - (78-93-3)	2,737.00, Rat - Category: 5	6,480.00, Rabbit - Category: NA	32.00, Mouse - Category: NA	No data available	No data available
Methyl methacrylate - (80-62-6)	5,000.00, Rat - Category: 5	5,000.00, Rabbit - Category: 5	29.80, Rat - Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Butanone - (78-93-3)	400.00, Cyprinodon variegatus	520.00, Daphnia magna	500.00 (96 hr), Skeletonema costatum
Methyl methacrylate - (80-62-6)	79.00, Oncorhynchus mykiss	69.00, Daphnia magna	170.00 (96 hr), Selenastrum capricornutum

Safety Data Sheet

Stone Die & Plaster Hardener Resin

SDS Revision Date: 05/21/2021

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1993	UN1993	UN1993
14.2. UN proper shipping name	UN1993, Flammable liquids, n.o.s. 3, II	Flammable liquids, n.o.s.	Flammable liquids, n.o.s.
14.3. Transport hazard class(es)	DOT Hazard Class: 3	IMDG: 3 Sub Class: Not Applicable	Air Class: 3
14.4. Packing group	II	II	II
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user	No further information		

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS Classification	WHMIS 2015 compliant
US EPA Tier II Hazards	Fire: Yes Sudden Release of Pressure: No

Safety Data Sheet

Stone Die & Plaster Hardener Resin

SDS Revision Date: 05/21/2021

Reactive: No
Immediate (Acute): Yes
Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs (lbs):

Butanone (5,000.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Butanone

Pennsylvania RTK Substances (>1%):

Butanone

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness and dizziness.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

End of Document